

Appendix 02

All results were generated from following R codes. All the functions used in this script can be found at <https://github.com/upulcooray/Social-participation/tree/main/R>

```
library(targets)
library(upulR) # personal R package for creating Table-1

library(future)
library(future.callr)

# Define custom functions and other global objects -----
source("R/functions.R")
source("R/helper_functions.R")

base_cov <- c("Age", "Sex", "L0_inc", "Y0_any", "L0_den", "L0_mari", "L0_srh")
l1_cov <- c("L1_inc", "L1_den", "L1_mari", "L1_srh")
expo <- c("A0_teeth", "A1_teeth")
out <- "Y2"

d0 <- NULL

d1 <- function(data, trt) {
  (data[[trt]]==1)*data[[trt]]+ (data[[trt]]!=1)* 1
}

d2 <- function(data, trt) {
  (data[[trt]]==2)*data[[trt]]+ (data[[trt]]!=2)* 2
}

d3 <- function(data, trt) {
  (data[[trt]]==3)*data[[trt]]+ (data[[trt]]!=3)* 3
}

d4 <- function(data, trt) {
  (data[[trt]]==4)*data[[trt]]+ (data[[trt]]!=4)* 4
}
```

```

# Set target-specific options such as packages-----
tar_option_set(packages = c("tidyverse", "haven",
                             "Gmisc", "htmlTable",
                             "flextable", "EValue",
                             "lmtpr", "mice", "upulR"))

plan(callr)

# Starting the list of targets-----
list(
  tar_target(df_file,
             "data/selected",
             format = "file")
  ,
  # Working data -----
  tar_target(working_df,
             readRDS(file=df_file))
  ,
  # create a dataset for descriptive analysis-----
  tar_target(descriptive_data,
             get_descriptive_data(working_df))
  ,
  tar_target(imp_data,
             get_mice_data(descriptive_data ,
                           mice_cars= c(expo[1],base_cov),
                           imp_only_vars= c(expo[2],l1_cov, out),
                           m=5))
  ,

  # plot distribution of missing covariates -----
  tar_target(mis_by_outcome2,
             plot_missing(descriptive_data,
                           by_var = "Y2",
                           x_lab = "Social participation in 2016 (Outcome)") %>%
             ggplot2::ggsave(filename = "figures/missing_outcome.svg",

```

```

                                width = 12,height = 10 ),
format= "file")

,
tar_target(mis_by_exposure2,
  plot_missing(descriptive_data,
    by_var = "AO_teeth",
    x_lab = "Number of teeth at baseline") %>%
  ggplot2::ggsave(filename = "figures/missing_exposure.svg",
    width = 12,height = 10 ),
  format= "file")

,
# Flow of participants (Add connecting arrows using Inkscape)
tar_target(sample_flowchart2,
  flow_chart_imp(df= descriptive_data ,
    expo,out,base_cov,l1_cov))

,

# Table 1 -----
tar_target(tab1_data2,
  get_tab1_data(descriptive_data),
  format= "rds")

,

tar_target(table_1_2,
  upulR::create_table1(df = tab1_data2,
    headvar = out,
    rowvars = c(expo[1],base_cov),
    headvar_na_level = "Censored",
    file_name = "tables/table_1",
    header = "Social participation in 2016"))

,

tar_target(dropouts_comparison2,
  get_dropout_comparison(df=tab1_data2,
    rowvars= c(expo[1],base_cov)))

,

# get a tmle ready data set-----
# dummify all categorical variables/ all variables as numeric

tar_target(tmle_data2,

```

```

    get_tmle_data(imp_data),
    format= "rds")
,

# Set-up TMLE -----
tar_target(a, expo) # time varying exposure (2010 & 2013)
,

tar_target(y, out) # Outcome (2016)
,
# Time-invariant covariates
tar_target(w, colnames(tmle_data2 %>% select(Age,Sex,contains("Y0"))))

,
# time-varying covariates
tar_target(tv, list(colnames(tmle_data2 %>% select(contains("L0"))),
                    colnames(tmle_data2 %>% select(contains("L1")))))
,

tar_target(cens, c("c1", "c2"))
,

tar_target(sl_lib, c("SL.glm", "SL.xgboost", "SL.nnet"))
,

tar_target(params,
  list(trt = a,
       outcome = y ,
       baseline = w ,
       time_vary=tv,
       outcome_type = "binomial",
       cens = cens,
       k=0
       # ,
       # learners_outcome = sl_lib,
       # learners_trt = sl_lib
  ))
,

# Run TMLE -----

tar_target(tmle_res_m1_noSL,
  lapply(paste0("d",0:4) ,

```

```

        function (x) do.call(run_lmtp,
                             c(params, list(data= tmle_data2 %>% filter(.imp==1),
                                             shift= eval(as.symbol(x)))))
    )))
,
tar_target(tmle_res_m1_SL,
           lapply(paste0("d",0:4) ,
                  function (x) do.call(run_lmtp,
                                         c(params, list(data= tmle_data2 %>% filter(.imp==1),
                                                         learners_outcome = sl_lib,
                                                         learners_trt = sl_lib,
                                                         shift= eval(as.symbol(x)))))
                  )))
,
tar_target(tmle_res_m2_noSL,
           lapply(paste0("d",0:4) ,
                  function (x) do.call(run_lmtp,
                                         c(params, list(data= tmle_data2 %>% filter(.imp==2),
                                                         shift= eval(as.symbol(x)))))
                  )))
,
tar_target(tmle_res_m2_SL,
           lapply(paste0("d",0:4) ,
                  function (x) do.call(run_lmtp,
                                         c(params, list(data= tmle_data2 %>% filter(.imp==2),
                                                         learners_outcome = sl_lib,
                                                         learners_trt = sl_lib,
                                                         shift= eval(as.symbol(x)))))
                  )))
,
tar_target(tmle_res_m3_noSL,
           lapply(paste0("d",0:4) ,
                  function (x) do.call(run_lmtp,
                                         c(params, list(data= tmle_data2 %>% filter(.imp==3),
                                                         shift= eval(as.symbol(x)))))
                  )))
,
tar_target(tmle_res_m3_SL,
           lapply(paste0("d",0:4) ,
                  function (x) do.call(run_lmtp,
                                         c(params, list(data= tmle_data2 %>% filter(.imp==3),
                                                         learners_outcome = sl_lib,

```

```

                                learners_trt = sl_lib,
                                shift= eval(as.symbol(x)))
                                )))
,
tar_target(tmle_res_m4_noSL,
            lapply(paste0("d",0:4) ,
                    function (x) do.call(run_lmtp,
                                           c(params, list(data= tmle_data2 %>% filter(.imp==4),
                                                             shift= eval(as.symbol(x))))
                                )))
,
tar_target(tmle_res_m4_SL,
            lapply(paste0("d",0:4) ,
                    function (x) do.call(run_lmtp,
                                           c(params, list(data= tmle_data2 %>% filter(.imp==4),
                                                             learners_outcome = sl_lib,
                                                             learners_trt = sl_lib,
                                                             shift= eval(as.symbol(x))))
                                )))
,
tar_target(tmle_res_m5_noSL,
            lapply(paste0("d",0:4) ,
                    function (x) do.call(run_lmtp,
                                           c(params, list(data= tmle_data2 %>% filter(.imp==5),
                                                             shift= eval(as.symbol(x))))
                                )))
,
tar_target(tmle_res_m5_SL,
            lapply(paste0("d",0:4) ,
                    function (x) do.call(run_lmtp,
                                           c(params, list(data= tmle_data2 %>% filter(.imp==5),
                                                             learners_outcome = sl_lib,
                                                             learners_trt = sl_lib,
                                                             shift= eval(as.symbol(x))))
                                )))
,

# contrast & pool ref=d0, est= "sl" -----

tar_target(res_d0_sl,
            get_pooled_results(tmle_res_m1_SL,
                               tmle_res_m2_SL,
                               tmle_res_m3_SL,

```

```

        tmle_res_m4_SL,
        tmle_res_m5_SL,
        est= "sl",
        ref_d = 0L))

,

# contrast @ pool ref=d1, est= "sl" -----

tar_target(res_d1_sl,
            get_pooled_results(tmle_res_m1_SL,
                                tmle_res_m2_SL,
                                tmle_res_m3_SL,
                                tmle_res_m4_SL,
                                tmle_res_m5_SL,
                                est= "sl",
                                ref_d = 1L))

,

# contrast @ pool ref=d0, est= "glm" -----

tar_target(res_d0_glm,
            get_pooled_results(tmle_res_m1_noSL,
                                tmle_res_m2_noSL,
                                tmle_res_m3_noSL,
                                tmle_res_m4_noSL,
                                tmle_res_m5_noSL,
                                est= "glm",
                                ref_d = 0L))

,

# contrast @ pool ref=d1, est= "glm" -----

tar_target(res_d1_glm,
            get_pooled_results(tmle_res_m1_noSL,
                                tmle_res_m2_noSL,
                                tmle_res_m3_noSL,
                                tmle_res_m4_noSL,
                                tmle_res_m5_noSL,
                                est= "glm",
                                ref_d = 1L))

,

```

```

# combine pooled results -----

tar_target(pooled_estimates,
            rbind(res_d0_sl,res_d1_sl,
                  res_d0_glm,res_d1_glm))
,

tar_target(table_2,
            get_table2(pooled_estimates),
            format= "file")
,

tar_target(figure_2,
            get_figure2(pooled_estimates),
            format = "file")

)

```

The R session information (including the OS info, R version and all packages used):

```
sessionInfo()
```

```

R version 4.1.2 (2021-11-01)
Platform: x86_64-pc-linux-gnu (64-bit)
Running under: Ubuntu 21.10

```

```
Matrix products: default
```

```
BLAS: /usr/lib/x86_64-linux-gnu/blas/libblas.so.3.9.0
```

```
LAPACK: /usr/lib/x86_64-linux-gnu/lapack/liblapack.so.3.9.0
```

```
locale:
```

```

[1] LC_CTYPE=en_US.UTF-8      LC_NUMERIC=C               LC_TIME=en_US.UTF-8
[4] LC_COLLATE=en_US.UTF-8    LC_MONETARY=ja_JP.UTF-8    LC_MESSAGES=en_US.UTF-8
[7] LC_PAPER=ja_JP.UTF-8      LC_NAME=C                  LC_ADDRESS=C
[10] LC_TELEPHONE=C            LC_MEASUREMENT=en_US.UTF-8 LC_IDENTIFICATION=C

```

```
attached base packages:
```

```
[1] stats      graphics  grDevices  utils      datasets  methods   base
```


other attached packages:

```
[1] future.callr_0.7.0 future_1.24.0      upulR_0.1.0      stringr_1.4.0
[5] targets_0.10.0      devtools_2.4.3      usethis_2.1.5
```

loaded via a namespace (and not attached):

```
[1] colorspace_2.0-2      ellipsis_0.3.2      visdat_0.5.3      lmtpl_1.0.0
[5] rprojroot_2.0.2      ggstance_0.3.5      flextable_0.6.10  htmlTable_2.4.0
[9] base64enc_0.1-3      fs_1.5.2            rstudioapi_0.13   mice_3.14.0
[13] listenv_0.8.0        remotes_2.4.2      fansi_1.0.2      lubridate_1.8.0
[17] xml2_1.3.3          codetools_0.2-18   splines_4.1.2     cachem_1.0.6
[21] knitr_1.37          pkgload_1.2.4      Formula_1.2-4     nanianr_0.6.1
[25] broom_0.7.11        cluster_2.1.2      png_0.1-7         compiler_4.1.2
[29] backports_1.4.1     assertthat_0.2.1   Matrix_1.4-0      fastmap_1.1.0
[33] survey_4.1-1        cli_3.2.0          htmltools_0.5.2   prettyunits_1.1.1
[37] tools_4.1.2         igraph_1.2.11      gtable_0.3.0      glue_1.6.2
[41] dplyr_1.0.7         tinytex_0.36       Rcpp_1.0.8        SuperLearner_2.0-28
[45] vctrs_0.3.8         progressr_0.10.0   iterators_1.0.13  xfun_0.30
[49] globals_0.14.0      ps_1.6.0           brio_1.1.3        testthat_3.1.2
[53] lifecycle_1.0.1     XML_3.99-0.9       scales_1.1.1      parallel_4.1.2
[57] RColorBrewer_1.1-2  yaml_2.3.5         memoise_2.0.1     gridExtra_2.3
[61] ggplot2_3.3.5       gdtools_0.2.3      rpart_4.1-15      glueformula_0.1.0
[65] gam_1.20            latticeExtra_0.6-29 stringi_1.7.6      highr_0.9
[69] desc_1.4.1          fastDummies_1.6.3  foreach_1.5.1     checkmate_2.0.0
[73] pkgbuild_1.3.1      zip_2.2.0          rlang_1.0.2       pkgconfig_2.0.3
[77] systemfonts_1.0.3  evaluate_0.15      lattice_0.20-45   purrr_0.3.4
[81] htmlwidgets_1.5.4  processx_3.5.2     tidyselect_1.1.1  parallelly_1.30.0
[85] magrittr_2.0.2      R6_2.5.1           generics_0.1.1    nnls_1.4
[89] Hmisc_4.6-0        base64url_1.4      DBI_1.1.2         pillar_1.7.0
[93] foreign_0.8-82      withr_2.5.0        Gmisc_3.0.0       forestplot_2.0.1
[97] survival_3.2-13    abind_1.4-5        nnet_7.3-17       tibble_3.1.6
[101] crayon_1.5.0        uuid_1.0-3         utf8_1.2.2        rmarkdown_2.11
[105] officer_0.4.1       jpeg_0.1-9         arsenal_3.6.3     grid_4.1.2
[109] data.table_1.14.2   callr_3.7.0        forcats_0.5.1     digest_0.6.29
[113] tidyr_1.1.4         munsell_0.5.0      mitools_2.4       sessioninfo_1.2.2
```