

Module 12 - Questions

- 1) Which of the following belongs to a function?
 - a) `#include <iostream>`
 - b) `using namespace std;`
 - c) `int process_data(int, int);`
 - d) `#define x 30`
- 2) When a variable from one function is passed to another function, what is it known as?
 - a) Argument.
 - b) Parameter.
 - c) Header.
 - d) Template.
- 3) For the function header, `void func1(int x1, int x2)`, what should be the return type of the following function?
 - a) -1
 - b) 0
 - c) 1
 - d) None of the above.

- 4) If `a = 3` and `b = 5`, what does the following function returns?

```
int func1(int a, int b)
{
    if ((a == 3) && !(b == 5))
        return -1;
    return ((a-5+b)*2);
}
```

- a) -1
 - b) 3
 - c) 6
 - d) None of the above.
- 5) What is the following variable `x` known as?

```
#include <iostream>
using namespace std;
int x;
int main()
```

- a) Local variable.
 - b) Global variable.
 - c) Static local variable.
 - d) Reference variable.

- 6) What does the following function return after being called 5 times?

```
int func1()  
{  
    int x = 1;  
    x += 2;  
    return x;  
}
```

- a) 1
- b) 3
- c) 7
- d) 11

- 7) What does the following function return after being called 3 times?

```
int func1()  
{  
    static int x = 1;  
    x += 3;  
    return x;  
}
```

- a) 1
- b) 4
- c) 7
- d) 10

- 8) If `x = 11` in the main function and passed to `func1` as a reference variable, what does `func1` return?

```
void func1(int &y)  
{  
    y++;  
}
```

- a) 0
- b) 1
- c) 12
- d) None of the above

- 9) If `x = 16` in the main function, what will `x` be when it is passed to `func1` as a reference variable?

```
void func1(int &y)  
{  
    y *= 2;  
}
```

- a) 0
- b) 16
- c) 32
- d) None of the above.

10) Given that a function has four prototypes with the same name, as mentioned below, which of the following overloaded function will be selected for processing `func1(pi, 8)`?

```
void func1(int, int);      // Option 1
void func1(int, float);    // Option 2
void func1(float, int);    // Option 3
void func1(float, float);  // Option 4
```

- a) Option 1
- b) Option 2
- c) Option 3
- d) Option 4

Answers:

1. (c) 2. (a) 3. (d) 4. (c) 5. (b) 6. (b) 7. (d) 8. (d) 9. (c) 10. (c)