

Module 13 - Questions

- 1) Which of the following keywords are needed to initialise a local array variable, `x[SZ]` to 0?

- a) `#include <iostream>`
- b) `using namespace std;`
- c) `for (int i = 0; i < SZ; i++) {x[i] = 0;}`
- d) `return 0;`

- 2) Which of the following statement best describes why the following code illegal?

```
int x[3];  
for (int i = 0; i < 5; i++) {x[i] = 1;}
```

- a) It gives compilation errors.
- b) The number of iterations in the `for` loop is larger than size of the array `x`.
- c) No compilation error, but the number of iterations in the `for` loop is larger than the size of the array `x`.
- d) There are no errors.

- 3) What action does the following code performs?

```
x[i--];
```

- a) Pre-decrement the array index.
- b) Post-decrement the array index.
- c) Pre-decrement the array content indexed by `i`.
- d) Post-decrement the array content indexed by `i`.

- 4) What is the size of the array below?

```
int x[9] = {2,4,5,6,6};
```

- a) 3
- b) 5
- c) 7
- d) 9

- 5) What is the content of `x[1][2]`?

```
int x[3][3] = { {3, 2, 4},  
                {9, 8, 5},  
                {6, 1, 7} };
```

- a) 5
- b) 1
- c) 8
- d) 7

6) Which of the following is a correct declaration for accepting a 2D array into a function func1?

- a) void func1(int x[][COLS], int COLS);
- b) void func1(int x[][ROWS], int ROWS);
- c) void func1(int x[][COLS], int ROWS);
- d) void func1(int x[ROWS][], int ROWS);

7) What is the content of names[2][3]?

```
char names[3][10] = {"John", "Laura", "Jack"};
```

- a) n
- b) u
- c) r
- d) k

8) What does names[3] represent?

```
char names[3][10] = {"Python", "MATLAB", "C++", "Verilog"};
```

- a) Python
- b) MATLAB
- c) C++
- d) Verilog

Answers:

1. (c) 2. (c) 3. (b) 4. (d) 5. (a) 6. (c) 7. (d) 8. (d)