

WESTERN SYDNEY
UNIVERSITY



Module 2

Using Additional Function Arguments

User Defined Input

- Until this point, we have “hard coded” the values of variables
- The input function allows us to prompt the user to enter a value
- Syntax of input():

```
outputVar = input('message')
```

MATLAB R2016b - academic use

Search Documentation

FILE NAVIGATE BREAKPOINTS RUN

Current Folder: \\ad.uws.edu.au\dfshare\HomesK-W\$\30010651\My Documents\MATLAB

Editor - \\ad.uws.edu.au\dfshare\HomesK-W\$\30010651\My D... T

```

1 - x=input('Enter a number')
2 - y=input('Enter a number: ')

```

Workspace

Name	Value
x	10
y	1.2323

Command Window

```

>> inp_ex1
Enter a number10
x =
    10
Enter a number: 1.2323
y =
    1.2323
fx >>

```

script Ln 2 Col 21

Data Types for Input

- Scalars
- Matrices
 - enter inside square brackets
- Character strings
 - enter string value inside single quotes (for example, user needs to type `'John'` – WITH the single quotations)
 - Or... specify string input with `'s'` (more reliable) so user does not need to include single quotes with their input

```
name = input('Enter first name: ', 's')
```

```
1 - a=input('Enter a row vector: ')
2 - b=input('Enter a matrix: ')
3 - c=input('Enter first name: ')
4 - d=input('Enter a sentence: ')
```

Command Window

```
>> inp_ex2
Enter a row vector: [1 2 3 4]
a =
     1     2     3     4
Enter a matrix: [1 2 3;4 5 6]
b =
     1     2     3
     4     5     6
Enter first name: 'John'
c =
John
Enter a sentence: 'It is time to have a coffee.'
d =
It is time to have a coffee.
```

fx >>

```
1 - a=input('Enter a name: ','s')
2 - b=input('Enter full name: ','s')
```

Command Window

```
>> inp_ex3
Enter a name: John
a =
John
Enter full name: John Doe
b =
John Doe
>> inp_ex3
Enter a name: 'John'
a =
'John'
Enter full name: 'John Doe'
b =
'John Doe'
```

No need to enter ' '

Optional to enter ' '

fx >> |