



Lab2 ARM Assembly I

實驗二 ARM Assembly I

1. Lab objectives 實驗目的

Familiar with basic ARMv7 assembly language.

In this Lab ,we will learn topics below.

- How to use conditional branch to finish the loop.
- How to use logic and arithmetic instructions.
- How to use registers and basic function parameter passing.
- How to access memory and array.

熟悉基本ARMv7組合語言語法使用。

在這次實驗中需要同學了解

- 如何利用條件跳躍指令完成程式迴圈的操作
- 算數與邏輯操作指令使用
- 暫存器(Register)使用與基本函式參數傳遞
- 記憶體與陣列存取

2. Theory 實驗原理

Please check the part of course materials of assembly language.

請參考上課Assembly部分講義。

3. Steps 實驗步驟

3.1. Hamming distance

計算兩個數長度為half-word(2bytes)的漢明距離，並將結果存放至result變數中。

Please calculate the Hamming distance of 2 half-word (2 bytes) numbers, and store the result into the variable “result”.

```
.data
    result: .byte 0
.text
.global main
.equ X, 0x55AA
.equ Y, 0xAA55
```



```
hamm:
    //TODO
    bx lr
main:
    movs R0, #X //This code will cause assemble error. Why? And how
to fix.
    movs R1, #Y
    ldr R2, =result
    bl hamm
L: b L
```

Note: 漢明距離主要是利用XOR計算兩數bit間差異個數，計算方式可參考下列連結。

Note: Hamming distance is basically using the XOR function to calculate the different number of “bits” of two numbers. Please check the following link for more information.

Reference: https://en.wikipedia.org/wiki/Hamming_distance

3.2. Fibonacci serial

宣告一數值N ($1 \leq N \leq 100$), 計算Fib(N)並將回傳值存放至R4暫存器

Declare a number N ($1 \leq N \leq 100$) and calculate the Fibonacci serial Fib(N). Store the result into register R4.

```
.text
.global main
.equ N, 20

fib:
    //TODO
    bx lr
main:
    movs R0, #N
    bl fib
L: b L
```

Note: 回傳值格式為signed integer, 若Fib[N]結果 overflow的話回傳-2, 當N數值出過範圍時fib回傳-1, 計算方式可參考下列連結

Note: The returned value should be in signed integer format. If the result of Fib(N) overflows, you should return -2. If the value of N is outside the accepted range, you should return -1. Check the following link for more details of the calculation.

Reference: https://it.wikipedia.org/wiki/Successione_di_Fibonacci

3.3. Bubble sort

利用組合語言完成長度為8byte的8bit泡沫排序法。

Please implement the Bubble sort algorithm for the 8 bytes data array with each element in 8bits by assembly.

實作要求：完成do_sort函式，其中陣列起始記憶體位置作為輸入參數R0，程式結束後需觀察arr1與arr2記憶體內容是否有排序完成。

Implementation Requirement: Fill-in the do_sort function. The start address of the



array is store in the R0 register. Observe the result of arr1 and arr2 in the memory viewer after calling the do_sort functions. The two arrays should be sorted.

```
.data
    arr1: .byte 0x19, 0x34, 0x14, 0x32, 0x52, 0x23, 0x61, 0x29
    arr2: .byte 0x18, 0x17, 0x33, 0x16, 0xFA, 0x20, 0x55, 0xAC
.text
    .global main
do_sort:
    //TODO
    bx lr
main:
    ldr r0, =arr1
    bl do_sort
    ldr r0, =arr2
    bl do_sort
L: b L
```

Note: 注意記憶體存取需使用byte alignment指令，例如：STRB, LDRB

Note: The memory access may require the instructions that support byte-alignment, such as STRB, LDRB.