

Veriopt Theories

September 17, 2022

Contents

1	Canonicalization Optimizations	1
1.1	AbsNode Phase	2
1.2	AddNode Phase	7
1.3	AndNode Phase	10
1.4	BinaryNode Phase	14
1.5	ConditionalNode Phase	15
1.6	MulNode Phase	18
1.7	Experimental AndNode Phase	25
1.8	NotNode Phase	39
1.9	OrNode Phase	40
1.10	ShiftNode Phase	44
1.11	SignedDivNode Phase	45
1.12	SignedRemNode Phase	45
1.13	SubNode Phase	46
1.14	XorNode Phase	51
1.15	NegateNode Phase	53
1.16	AddNode	56
1.17	NegateNode	57

1 Canonicalization Optimizations

```
theory Common
imports
  OptimizationDSL.Canonicalization
  Semantics.IRTreeEvalThms
begin

lemma size-pos[size-simps]: 0 < size y
by (induction y; auto?)

lemma size-non-add[size-simps]: size (BinaryExpr op a b) = size a + (size b) * 2
by (induction op; auto)
```

lemma *size-non-const*[*size-simps*]:
 $\neg \text{is-ConstantExpr } y \implies 1 < \text{size } y$
using *size-pos* **apply** (*induction y; auto*)
apply (*metis Suc-lessI mult-eq-1-iff mult-pos-pos n-not-Suc-n numeral-2-eq-2*
pos2)
by (*metis add-strict-increasing less-Suc0 linorder-not-less mult-2-right not-add-less2*)

lemmas *arith*[*size-simps*] = *Suc-leI add-strict-increasing*

definition *well-formed-equal* :: *Value* \Rightarrow *Value* \Rightarrow *bool*
(infix ≈ 50) **where**
well-formed-equal $v_1 \ v_2 = (v_1 \neq \text{UndefVal} \longrightarrow v_1 = v_2)$

lemma *well-formed-equal-defn* [*simp*]:
well-formed-equal $v_1 \ v_2 = (v_1 \neq \text{UndefVal} \longrightarrow v_1 = v_2)$
unfolding *well-formed-equal-def* **by** *simp*

end

1.1 AbsNode Phase

theory *AbsPhase*
imports
Common
begin

phase *AbsNode*
terminating *size*
begin

lemma *abs-pos*:
fixes $v :: ('a :: \text{len word})$
assumes $0 \leq_s v$
shows (*if* $v <_s 0$ *then* $- v$ *else* v) = v
by (*simp add: assms signed.leD*)

lemma *abs-neg*:
fixes $v :: ('a :: \text{len word})$
assumes $v <_s 0$
assumes $-(2 \wedge (\text{Nat.size } v - 1)) <_s v$
shows (*if* $v <_s 0$ *then* $- v$ *else* v) = $- v \wedge 0 <_s -v$
by (*smt (verit, ccfv-SIG) assms(1) assms(2) signed-take-bit-int-greater-eq-minus-exp*

signed-take-bit-int-greater-eq-self-iff sint-0 sint-word-ariths(4) word-sless-alt)

```

lemma abs-max-neg:
  fixes  $v :: ('a :: \text{len word})$ 
  assumes  $v <_s 0$ 
  assumes  $-(2^{\wedge}(\text{Nat.size } v - 1)) = v$ 
  shows  $-v = v$ 
  using assms
  by (metis One-nat-def add.inverse-neutral double-eq-zero-iff mult-minus-right size-word.rep-eq)

```

```

lemma final-abs:
  fixes  $v :: ('a :: \text{len word})$ 
  assumes take-bit  $(\text{Nat.size } v) \ v = v$ 
  assumes  $-(2^{\wedge}(\text{Nat.size } v - 1)) \neq v$ 
  shows  $0 \leq_s (\text{if } v <_s 0 \text{ then } -v \text{ else } v)$ 

```

```

proof (cases  $v <_s 0$ )
  case True
  then show ?thesis
  proof (cases  $v = -(2^{\wedge}(\text{Nat.size } v - 1))$ )
    case True
    then show ?thesis using abs-max-neg
    using assms by presburger
  next
  case False
  then have  $-(2^{\wedge}(\text{Nat.size } v - 1)) <_s v$ 
  unfolding word-sless-def using signed-take-bit-int-greater-self-iff
  by (smt (verit, best) One-nat-def diff-less double-eq-zero-iff len-gt-0 lessI
less-irrefl
mult-minus-right neg-equal-0-iff-equal signed.rep-eq signed-of-int
signed-take-bit-int-greater-eq-self-iff signed-word-eqI sint-0 sint-range-size
sint-sbintrunc' sint-word-ariths(4) size-word.rep-eq unsigned-0 word-2p-lem

word-sless.rep-eq word-sless-def)
  then show ?thesis
  using abs-neg abs-pos signed.nless-le by auto
qed
next
  case False
  then show ?thesis using abs-pos by auto
qed

```

```

lemma wf-abs: is-IntVal  $x \implies \text{intval-abs } x \neq \text{UndefVal}$ 
  using intval-abs.simps unfolding new-int.simps
  using is-IntVal-def by force

```

```

fun bin-abs :: ' $a :: \text{len word} \Rightarrow 'a :: \text{len word}$  where
  bin-abs  $v = (\text{if } (v <_s 0) \text{ then } (- v) \text{ else } v)$ 

```

```

lemma val-abs-zero:
  intval-abs (new-int b 0) = new-int b 0
  by simp

lemma less-eq-zero:
  assumes val-to-bool (val[(IntVal b 0) < (IntVal b v)])
  shows int-signed-value b v > 0
  using assms unfolding intval-less-than.simps(1) apply simp
  by (metis bool-to-val.elims val-to-bool.simps(1))

lemma val-abs-pos:
  assumes val-to-bool(val[(new-int b 0) < (new-int b v)])
  shows intval-abs (new-int b v) = (new-int b v)
  using assms using less-eq-zero unfolding intval-abs.simps new-int.simps
  by force

lemma val-abs-neg:
  assumes val-to-bool(val[(new-int b v) < (new-int b 0)])
  shows intval-abs (new-int b v) = intval-negate (new-int b v)
  using assms using less-eq-zero unfolding intval-abs.simps new-int.simps
  by force

lemma val-bool-unwrap:
  val-to-bool (bool-to-val v) = v
  by (metis bool-to-val.elims one-neq-zero val-to-bool.simps(1))

lemma take-bit-unwrap:
  b = 64  $\implies$  take-bit b (v1::64 word) = v1
  by (metis size64 size-word.rep-eq take-bit-length-eq)

lemma bit-less-eq-def:
  fixes v1 v2 :: 64 word
  assumes b ≤ 64
  shows sint (signed-take-bit (b − Suc (0::nat)) (take-bit b v1))
    < sint (signed-take-bit (b − Suc (0::nat)) (take-bit b v2))  $\longleftrightarrow$ 
    signed-take-bit (63::nat) (Word.rep v1) < signed-take-bit (63::nat) (Word.rep
v2)
  using assms sorry

lemma less-eq-def:
  shows val-to-bool(val[(new-int b v1) < (new-int b v2)])  $\longleftrightarrow$  v1 <s v2
  unfolding new-int.simps intval-less-than.simps bool-to-val-bin.simps bool-to-val.simps
int-signed-value.simps apply (simp add: val-bool-unwrap)
  apply auto unfolding word-sless-def apply auto
  unfolding signed-def apply auto using bit-less-eq-def
  apply (metis bot-nat-0.extremum take-bit-0)

```

```

by (metis bit-less-eq-def bot-nat-0.extremum take-bit-0)

lemma val-abs-always-pos:
  assumes intval-abs (new-int b v) = (new-int b v')
  shows  $0 \leq_s v'$ 
  using assms
proof (cases v = 0)
  case True
  then have v' = 0
    using val-abs-zero assms
    by (smt (verit, ccfv-threshold) Suc-diff-1 bit-less-eq-def bot-nat-0.extremum
diff-is-0-eq len-gt-0 len-of-numeral-defs(2) order-le-less signed-eq-0-iff take-bit-0 take-bit-signed-take-bit
take-bit-unwrap)
  then show ?thesis by simp
next
  case neq0: False
  then show ?thesis
proof (cases val-to-bool(val[(new-int b 0) < (new-int b v)]))
  case True
  then show ?thesis using less-eq-def
    using assms val-abs-pos
    by (smt (verit, ccfv-SIG) One-nat-def Suc-leI bit.compl-one bit-less-eq-def
cancel-comm-monoid-add-class.diff-cancel diff-zero len-gt-0 len-of-numeral-defs(2)
mask-0 mask-1 one-le-numeral one-neq-zero signed-word-eqI take-bit-dist-subL take-bit-minus-one-eq-mask
take-bit-not-eq-mask-diff take-bit-signed-take-bit zero-le-numeral)
  next
  case False
  then have val-to-bool(val[(new-int b v) < (new-int b 0)])
    using neq0 less-eq-def
    by (metis signed.neqE)
  then show ?thesis using val-abs-neg less-eq-def unfolding new-int.simps
intval-negate.simps
    by (metis signed.nless-le take-bit-0)
qed

qed

```

```

lemma intval-abs-elim:
  assumes intval-abs x  $\neq$  UndefVal
  shows  $\exists t v . x = \text{IntVal } t v \wedge \text{intval-abs } x = \text{new-int } t \text{ (if int-signed-value } t v < 0 \text{ then } -v \text{ else } v)$ 
  using assms
  by (meson intval-abs.elims)

```

```

lemma wf-abs-new-int:
  assumes intval-abs (IntVal t v)  $\neq$  UndefVal
  shows intval-abs (IntVal t v) = new-int t v  $\vee$  intval-abs (IntVal t v) = new-int
t (-v)

```

```

using assms
using intval-abs.simps(1) by presburger

lemma mono-undef-abs:
  assumes intval-abs (intval-abs x)  $\neq$  UndefVal
  shows intval-abs x  $\neq$  UndefVal
  using assms
  by force

lemma val-abs-idem:
  assumes intval-abs(intval-abs(x))  $\neq$  UndefVal
  shows intval-abs(intval-abs(x)) = intval-abs x
  using assms
proof -
  obtain b v where in-def: intval-abs x = new-int b v
    using assms intval-abs-elim mono-undef-abs by blast
  then show ?thesis
proof (cases val-to-bool(val[(new-int b v) < (new-int b 0)]))
  case True
  then have nested: (intval-abs (intval-abs x)) = new-int b (-v)
    using val-abs-neg intval-negate.simps in-def
    by simp
  then have x = new-int b (-v)
    using in-def True unfolding new-int.simps
  by (smt (verit, best) intval-abs.simps(1) less-eq-def less-eq-zero less-numeral-extra(1)

      mask-1 mask-eq-take-bit-minus-one neg-one.elims neg-one-signed new-int.simps

      one-le-numeral one-neq-zero signed.neqE signed.not-less take-bit-of-0
  val-abs-always-pos)
  then show ?thesis using val-abs-always-pos
    using True in-def less-eq-def signed.leD
    using signed.nless-le by blast
next
  case False
  then show ?thesis
    using in-def by force
qed
qed

lemma val-abs-negate:
  assumes intval-abs (intval-negate x)  $\neq$  UndefVal
  shows intval-abs (intval-negate x) = intval-abs x
  using assms apply (cases x; auto)
  apply (metis less-eq-def new-int.simps signed.dual-order.strict-iff-not signed.less-linear

      take-bit-0)
  by (smt (verit, ccfv-threshold) add.inverse-neutral intval-abs.simps(1) less-eq-def

```

```

less-eq-zero
  less-numeral-extra(1) mask-1 mask-eq-take-bit-minus-one neg-one.elims neg-one-signed

new-int.simps one-le-numeral one-neq-zero signed.order.order-iff-strict take-bit-of-0

val-abs-always-pos)

```

Optimisations

```

optimization AbsIdempotence:  $\text{abs}(\text{abs}(x)) \mapsto \text{abs}(x)$ 
  apply auto
  by (metis UnaryExpr unary-eval.simps(1) val-abs-idem)

```

```

optimization AbsNegate:  $\text{abs}(-x) \mapsto \text{abs}(x)$ 
  apply auto using val-abs-negate
  by (metis unary-eval.simps(1) unfold-unary)

```

end

end

1.2 AddNode Phase

theory AddPhase

imports

Common

begin

phase AddNode

terminating size

begin

lemma binadd-commute:

assumes bin-eval BinAdd $x \ y \neq \text{UndefVal}$

shows bin-eval BinAdd $x \ y = \text{bin-eval BinAdd } y \ x$

using assms intval-add-sym **by** simp

```

optimization AddShiftConstantRight:  $((\text{const } v) + y) \mapsto y + (\text{const } v)$  when
 $\neg(\text{is-ConstantExpr } y)$ 

```

using size-non-const **apply** fastforce

unfolding le-expr-def

apply (rule impI)

subgoal premises 1

apply (rule allI impI)+

subgoal premises 2 **for** $m \ p \ va$

apply (rule BinaryExprE[OF 2])

subgoal premises 3 **for** $x \ ya$

```

    apply (rule BinaryExpr)
    using 3 apply simp
    using 3 apply simp
    using 3 binadd-commute apply auto
  done
done
done
done

```

optimization *AddShiftConstantRight2*: $((\text{const } v) + y) \mapsto y + (\text{const } v)$ when $\neg(\text{is-ConstantExpr } y)$

```

  unfolding le-expr-def
  apply (auto simp: intval-add-sym)

  using size-non-const by fastforce

```

lemma *is-neutral-0* [simp]:

```

  assumes 1: intval-add (IntVal b x) (IntVal b 0)  $\neq$  UndefVal
  shows intval-add (IntVal b x) (IntVal b 0) = (new-int b x)
  using 1 by auto

```

optimization *AddNeutral*: $(e + (\text{const } (\text{IntVal } 32 \ 0))) \mapsto e$

```

  unfolding le-expr-def apply auto
  using is-neutral-0 eval-unused-bits-zero
  by (smt (verit) add-cancel-left-right intval-add.elims val-to-bool.simps(1))

```

ML-val $\langle @\{term \ \langle x = y \rangle\} \rangle$

lemma *NeutralLeftSubVal*:

```

  assumes e1 = new-int b ival
  shows val[(e1 - e2) + e2]  $\approx$  e1
  apply simp using assms by (cases e1; cases e2; auto)

```

optimization *RedundantSubAdd*: $((e_1 - e_2) + e_2) \mapsto e_1$

```

  apply auto using eval-unused-bits-zero NeutralLeftSubVal
  unfolding well-formed-equal-defn
  by (smt (verit) evalDet intval-sub.elims new-int.elims)

```

lemma *allE2*: $(\forall x y. P \ x \ y) \implies (P \ a \ b \implies R) \implies R$

```

  by simp

```


lemma *just-goal2*:
assumes $1: (\forall a\ b. (\text{intval-add } (\text{intval-sub } a\ b)\ b \neq \text{UndefVal} \wedge a \neq \text{UndefVal})$
 \longrightarrow
 $\text{intval-add } (\text{intval-sub } a\ b)\ b = a)$
shows $(\text{BinaryExpr BinAdd } (\text{BinaryExpr BinSub } e_1\ e_2)\ e_2) \geq e_1$
unfolding *le-expr-def unfold-binary bin-eval.simps*
by (*metis 1 evalDet evaltree-not-undef*)

optimization *RedundantSubAdd2*: $e_2 + (e_1 - e_2) \mapsto e_1$
by (*smt (verit, del-insts) BinaryExpr BinaryExprE RedundantSubAdd(1) bi-nadd-commute le-expr-def rewrite-preservation.simps(1)*)

lemma *AddToSubHelperLowLevel*:
shows $\text{intval-add } (\text{intval-negate } e)\ y = \text{intval-sub } y\ e$ (**is** $?x = ?y$)
by (*induction y; induction e; auto*)

optimization *AddToSub*: $-e + y \mapsto y - e$
using *AddToSubHelperLowLevel* **by** *auto*

print-phases

lemma *val-redundant-add-sub*:
assumes $a = \text{new-int } bb\ ival$
assumes $\text{val}[b + a] \neq \text{UndefVal}$
shows $\text{val}[(b + a) - b] = a$
using *assms apply (cases a; cases b; auto)*
by *presburger*

lemma *val-add-right-negate-to-sub*:
assumes $\text{val}[x + e] \neq \text{UndefVal}$
shows $\text{val}[x + (-e)] = \text{val}[x - e]$
using *assms by (cases x; cases e; auto)*

lemma *exp-add-left-negate-to-sub*:
 $\text{exp}[-e + y] \geq \text{exp}[y - e]$

```

apply (cases e; cases y; auto)
using AddToSubHelperLowLevel by auto+

Optimisations

optimization RedundantAddSub:  $(b + a) - b \mapsto a$ 
  apply auto using val-redundant-add-sub eval-unused-bits-zero
  by (smt (verit) evalDet intval-add.elims new-int.elims)

optimization AddRightNegateToSub:  $x + -e \mapsto x - e$ 
  using AddToSubHelperLowLevel intval-add-sym by auto

optimization AddLeftNegateToSub:  $-e + y \mapsto y - e$ 
  using exp-add-left-negate-to-sub by blast

```

end

end

1.3 AndNode Phase

```

theory AndPhase
  imports
    Common
    Proofs.StampEvalThms
  begin

  phase AndNode
    terminating size
  begin

  lemma bin-and-nots:
     $(\sim x \ \& \ \sim y) = (\sim (x \mid y))$ 
    by simp

  lemma bin-and-neutral:
     $(x \ \& \ \sim False) = x$ 
    by simp

  lemma val-and-equal:
    assumes  $x = \text{new-int } b \ v$ 
    and  $\text{val}[x \ \& \ x] \neq \text{UndefVal}$ 
    shows  $\text{val}[x \ \& \ x] = x$ 

```

```

using assms by (cases x; auto)

lemma val-and-nots:
  val[ $\sim x \ \& \ \sim y$ ] = val[ $\sim(x \mid y)$ ]
  apply (cases x; cases y; auto) by (simp add: take-bit-not-take-bit)

lemma val-and-neutral:
  assumes x = new-int b v
  and    val[x &  $\sim(\text{new-int } b' \ 0)$ ]  $\neq$  UndefVal
  shows  val[x &  $\sim(\text{new-int } b' \ 0)$ ] = x
  using assms apply (cases x; auto) apply (simp add: take-bit-eq-mask)
  by presburger

lemma val-and-zero:
  assumes x = new-int b v
  shows  val[x & (IntVal b 0)] = IntVal b 0
  using assms by (cases x; auto)

lemma exp-and-equal:
  exp[x & x]  $\geq$  exp[x]
  apply auto using val-and-equal eval-unused-bits-zero
  by (smt (verit) evalDet intval-and.elims new-int.elims)

lemma exp-and-nots:
  exp[ $\sim x \ \& \ \sim y$ ]  $\geq$  exp[ $\sim(x \mid y)$ ]
  apply (cases x; cases y; auto) using val-and-nots
  by fastforce

lemma exp-sign-extend:
  assumes e = (1 << In) - 1
  shows  BinaryExpr BinAnd (UnaryExpr (UnarySignExtend In Out) x)
    (ConstantExpr (new-int b e))
     $\geq$  (UnaryExpr (UnaryZeroExtend In Out) x)

  apply auto
  subgoal premises p for m p va
  proof -
    obtain va where va: [m,p]  $\vdash$  x  $\mapsto$  va
    using p(2) by auto
    then have va  $\neq$  UndefVal
    by (simp add: evaltree-not-undef)
    then have 1: intval-and (intval-sign-extend In Out va) (IntVal b (take-bit b
e))  $\neq$  UndefVal
    using evalDet p(1) p(2) va by blast
    then have 2: intval-sign-extend In Out va  $\neq$  UndefVal

```

```

    by auto
  then have 21: (0::nat) < b
    by (simp add: p(4))
  then have 3: b  $\sqsubseteq$  (64::nat)
    by (simp add: p(5))
  then have 4: - ((2::int) ^ b div (2::int))  $\sqsubseteq$  sint (signed-take-bit (b - Suc
(0::nat)) (take-bit b e))
    by (simp add: p(6))
  then have 5: sint (signed-take-bit (b - Suc (0::nat)) (take-bit b e)) < (2::int)
^ b div (2::int)
    by (simp add: p(7))
  then have 6: [m,p]  $\vdash$  UnaryExpr (UnaryZeroExtend In Out)
    x  $\mapsto$  intval-and (intval-sign-extend In Out va) (IntVal b (take-bit b e))
  apply (cases va; simp)
  apply (simp add:  $\langle$ va::Value $\rangle \neq$  UndefVal $\rangle$ ) defer
  subgoal premises p for x3
  proof -
    have va = ObjRef x3
    using p(1) by auto
    then have sint (signed-take-bit (b - Suc (0::nat)) (take-bit b e)) <
(2::int) ^ b div (2::int)
      by (simp add: 5)
    then show ?thesis
      using 2 intval-sign-extend.simps(3) p(1) by blast
  qed

  subgoal premises p for x4
  proof -
    have sg1: va = ObjStr x4
    using 2 p(1) by auto
    then have sint (signed-take-bit (b - Suc (0::nat)) (take-bit b e)) <
(2::int) ^ b div (2::int)
      by (simp add: 5)
    then show ?thesis
      using 1 sg1 by auto
  qed

  subgoal premises p for x21 x22
  proof -
    have sgg1: va = IntVal x21 x22
    by (simp add: p(1))
    then have sgg2: sint (signed-take-bit (b - Suc (0::nat)) (take-bit b e))
< (2::int) ^ b div (2::int)
      by (simp add: 5)
    then show ?thesis
      sorry
  qed
done

```

```

    then show ?thesis
    by (metis evalDet p(2) va)
qed
done

```

```

lemma val-and-commute[simp]:
  val[x & y] = val[y & x]
  apply (cases x; cases y; auto)
  by (simp add: word-bw-comms(1))

```

Optimisations

```

optimization AndEqual: x & x ⟶ x
using exp-and-equal by blast

```

```

optimization AndShiftConstantRight: ((const x) & y) ⟶ y & (const x)
                                         when ¬(is-ConstantExpr y)
using val-and-commute apply auto
using size-non-const by auto

```

```

optimization AndNots: (~x) & (~y) ⟶ ~(x | y)
defer using exp-and-nots
apply presburger sorry

```

```

optimization AndSignExtend: BinaryExpr BinAnd (UnaryExpr (UnarySignExtend
In Out) x)

```

```

      (const (new-int b e))
    ⟶ (UnaryExpr (UnaryZeroExtend In Out) x)
      when (e = (1 << In) - 1)

```

```

using exp-sign-extend by simp

```

```

optimization AndNeutral: (x & ~(const (IntVal b 0))) ⟶ x
  when (wf-stamp x ∧ stamp-expr x = IntegerStamp b lo hi)
  apply auto using val-and-neutral
by (smt (verit) Value.sel(1) eval-unused-bits-zero intval-and.elims intval-word.simps

    new-int.simps new-int-bin.simps take-bit-eq-mask)

```

end

```

context stamp-mask

```

begin

lemma *AndRightFallthrough*: $((\text{and } (\text{not } (\downarrow x)) (\uparrow y)) = 0) \longrightarrow \text{exp}[x \ \& \ y] \geq \text{exp}[y]$
apply *simp* **apply** (*rule impI*; (*rule allI*)+)
apply (*rule impI*)
subgoal *premises p* **for** *m p v*
proof –
 obtain *xv* **where** *xv*: $[m, p] \vdash x \mapsto xv$
 using *p(2)* **by** *blast*
 obtain *yv* **where** *yv*: $[m, p] \vdash y \mapsto yv$
 using *p(2)* **by** *blast*
 have $v = \text{val}[xv \ \& \ yv]$
 using *p(2)* *xv yv*
 by (*metis BinaryExprE bin-eval.simps(4) evalDet*)
 then **have** $v = yv$
 using *p(1)* *not-down-up-mask-and-zero-implies-zero*
 by (*smt (verit) eval-unused-bits-zero intval-and.elims new-int.elims new-int-bin.elims*
p(2) unfold-binary xv yv)
 then **show** *?thesis* **using** *yv* **by** *simp*
qed
done

lemma *AndLeftFallthrough*: $((\text{and } (\text{not } (\downarrow y)) (\uparrow x)) = 0) \longrightarrow \text{exp}[x \ \& \ y] \geq \text{exp}[x]$
apply *simp* **apply** (*rule impI*; (*rule allI*)+)
apply (*rule impI*)
subgoal *premises p* **for** *m p v*
proof –
 obtain *xv* **where** *xv*: $[m, p] \vdash x \mapsto xv$
 using *p(2)* **by** *blast*
 obtain *yv* **where** *yv*: $[m, p] \vdash y \mapsto yv$
 using *p(2)* **by** *blast*
 have $v = \text{val}[xv \ \& \ yv]$
 using *p(2)* *xv yv*
 by (*metis BinaryExprE bin-eval.simps(4) evalDet*)
 then **have** $v = xv$
 using *p(1)* *not-down-up-mask-and-zero-implies-zero*
 by (*smt (verit) and.commute eval-unused-bits-zero intval-and.elims new-int.simps*
new-int-bin.simps p(2) unfold-binary xv yv)
 then **show** *?thesis* **using** *xv* **by** *simp*
qed
done

end

end

1.4 BinaryNode Phase

```

theory BinaryNode
  imports
    Common
begin

phase BinaryNode
  terminating size
begin

optimization BinaryFoldConstant: BinaryExpr op (const v1) (const v2) ⟶ ConstantExpr (bin-eval op v1 v2)
  unfolding le-expr-def
  apply (rule allI impI)+
  subgoal premises bin for m p v
  print-facts
  apply (rule BinaryExprE[OF bin])
  subgoal premises prems for x y
  print-facts

  proof –
    have x: x = v1 using prems by auto
    have y: y = v2 using prems by auto
    have xy: v = bin-eval op x y using prems x y by simp
    have int:  $\exists b\ vv. v = \text{new-int } b\ vv$  using bin-eval-new-int prems by fast
    show ?thesis
      unfolding prems x y xy
      apply (rule ConstantExpr)
      apply (rule validDefIntConst)
      using prems x y xy int sorry
    qed
  done
done

print-facts

end

end

```

1.5 ConditionalNode Phase

```

theory ConditionalPhase
  imports
    Common
    Proofs.StampEvalThms
begin

```

phase *ConditionalNode*
terminating *size*
begin

lemma *negates*: $\exists v\ b.\ e = \text{IntVal } b\ v \wedge b > 0 \implies \text{val-to-bool } (\text{val}[e]) \longleftrightarrow \neg(\text{val-to-bool } (\text{val}[\neg e]))$
unfolding *intval-logic-negation.simps*
by (*metis* (*mono-tags*, *lifting*) *intval-logic-negation.simps*(1) *logic-negate-def new-int.simps of-bool-eq*(2) *one-neq-zero take-bit-of-0 take-bit-of-1 val-to-bool.simps*(1))

lemma *negation-condition-intval*:
assumes $e = \text{IntVal } b\ ie$
assumes $0 < b$
shows $\text{val}[(\neg e) \ ?\ x : y] = \text{val}[e \ ?\ y : x]$
using *assms* **by** (*cases* *e*; *auto simp: negates logic-negate-def*)

optimization *NegateConditionFlipBranches*: $((\neg e) \ ?\ x : y) \mapsto (e \ ?\ y : x)$ *when* $(\text{wf-stamp } e \wedge \text{stamp-expr } e = \text{IntegerStamp } b\ lo\ hi \wedge b > 0)$
apply *simp using negation-condition-intval*
by (*smt* (*verit*, *ccfv-SIG*) *ConditionalExpr ConditionalExprE UnaryExprE negates unary-eval.simps*(4) *valid-value-elim*(3) *wf-stamp-def*)

optimization *DefaultTrueBranch*: $(\text{true} \ ?\ x : y) \mapsto x$.

optimization *DefaultFalseBranch*: $(\text{false} \ ?\ x : y) \mapsto y$.

optimization *ConditionalEqualBranches*: $(e \ ?\ x : x) \mapsto x$.

optimization *condition-bounds-x*: $((u < v) \ ?\ x : y) \mapsto x$
when $(\text{stamp-under } (\text{stamp-expr } u) (\text{stamp-expr } v) \wedge \text{wf-stamp } u \wedge \text{wf-stamp } v)$
apply *simp apply* (*rule impI*) **apply** (*rule allI*)**+** **apply** (*rule impI*)
using *stamp-under-defn*
by *force*

optimization *condition-bounds-y*: $((u < v) \ ?\ x : y) \mapsto y$
when $(\text{stamp-under } (\text{stamp-expr } v) (\text{stamp-expr } u) \wedge \text{wf-stamp } u \wedge \text{wf-stamp } v)$
apply *simp apply* (*rule impI*) **apply** (*rule allI*)**+** **apply** (*rule impI*)
using *stamp-under-defn-inverse*
by *force*

lemma *val-optimise-integer-test*:
assumes $\exists v.\ x = \text{IntVal } 32\ v$
shows $\text{val}[(x \ \&\ (\text{IntVal } 32\ 1)) \ \text{eq } (\text{IntVal } 32\ 0)] \ ?\ (\text{IntVal } 32\ 0) : (\text{IntVal } 32\ 1)] =$
 $\text{val}[x \ \&\ \text{IntVal } 32\ 1]$

using *assms* **apply** *auto*
apply (*metis* (*full-types*) *bool-to-val.simps*(2) *val-to-bool.simps*(1))
by (*metis* (*mono-tags*, *lifting*) *and-one-eq* *bool-to-val.simps*(1) *even-iff-mod-2-eq-zero*
odd-iff-mod-2-eq-one *val-to-bool.simps*(1))

optimization *ConditionalEliminateKnownLess*: $((x < y) ? x : y) \mapsto x$
 $\text{when } (\text{stamp-under } (\text{stamp-expr } x) (\text{stamp-expr } y)$
 $\wedge \text{wf-stamp } x \wedge \text{wf-stamp } y)$
using *stamp-under-defn* **by** *auto*

optimization *ConditionalEqualIsRHS*: $((x \text{ eq } y) ? x : y) \mapsto y$
apply *auto*
by (*smt* (*verit*) *Value.inject*(1) *bool-to-val.simps*(2) *bool-to-val-bin.simps* *evalDet*
intval-equals.elims *val-to-bool.elims*(1))

optimization *normalizeX*: $((x \text{ eq } \text{const } (\text{IntVal } 32 \ 0)) ?$
 $(\text{const } (\text{IntVal } 32 \ 0)) : (\text{const } (\text{IntVal } 32 \ 1))) \mapsto x$
 $\text{when } (x = \text{ConstantExpr } (\text{IntVal } 32 \ 0) \mid (x = \text{ConstantExpr}$
 $(\text{IntVal } 32 \ 1)))$.

optimization *normalizeX2*: $((x \text{ eq } (\text{const } (\text{IntVal } 32 \ 1))) ?$
 $(\text{const } (\text{IntVal } 32 \ 1)) : (\text{const } (\text{IntVal } 32 \ 0))) \mapsto x$
 $\text{when } (x = \text{ConstantExpr } (\text{IntVal } 32 \ 0) \mid (x =$
 $\text{ConstantExpr } (\text{IntVal } 32 \ 1)))$.

optimization *flipX*: $((x \text{ eq } (\text{const } (\text{IntVal } 32 \ 0))) ?$
 $(\text{const } (\text{IntVal } 32 \ 1)) : (\text{const } (\text{IntVal } 32 \ 0))) \mapsto$
 $x \oplus (\text{const } (\text{IntVal } 32 \ 1))$
 $\text{when } (x = \text{ConstantExpr } (\text{IntVal } 32 \ 0) \mid (x = \text{ConstantExpr}$
 $(\text{IntVal } 32 \ 1)))$.

optimization *flipX2*: $((x \text{ eq } (\text{const } (\text{IntVal } 32 \ 1))) ?$
 $(\text{const } (\text{IntVal } 32 \ 0)) : (\text{const } (\text{IntVal } 32 \ 1))) \mapsto$
 $x \oplus (\text{const } (\text{IntVal } 32 \ 1))$
 $\text{when } (x = \text{ConstantExpr } (\text{IntVal } 32 \ 0) \mid (x = \text{ConstantExpr}$
 $(\text{IntVal } 32 \ 1)))$.

lemma *stamp-of-default*:
assumes *stamp-expr* $x = \text{default-stamp}$
assumes *wf-stamp* x
shows $([m, p] \vdash x \mapsto v) \longrightarrow (\exists vv. v = \text{IntVal } 32 \ vv)$
using *assms*
by (*metis* *default-stamp* *valid-value-elim*(3) *wf-stamp-def*)

optimization *OptimiseIntegerTest*:

```

  (((x & (const (IntVal 32 1))) eq (const (IntVal 32 0))) ?
   (const (IntVal 32 0)) : (const (IntVal 32 1)))  $\mapsto$ 
   x & (const (IntVal 32 1))
   when (stamp-expr x = default-stamp  $\wedge$  wf-stamp x)
  apply simp apply (rule impI; (rule allI)+; rule impI)
  subgoal premises eval for m p v
proof -
  obtain xv where xv: [m, p]  $\vdash$  x  $\mapsto$  xv
  using eval by fast
  then have x32:  $\exists v. xv = \text{IntVal } 32 \ v$ 
  using stamp-of-default eval by auto
  obtain lhs where lhs: [m, p]  $\vdash$  exp[(((x & (const (IntVal 32 1))) eq (const (IntVal
32 0))) ?
   (const (IntVal 32 0)) : (const (IntVal 32 1))))]  $\mapsto$  lhs
  using eval(2) by auto
  then have lhsV: lhs = val[((xv & (IntVal 32 1)) eq (IntVal 32 0)) ? (IntVal 32
0) : (IntVal 32 1)]
  using xv evaltree.BinaryExpr evaltree.ConstantExpr evaltree.ConditionalExpr
  by (smt (verit) ConditionalExprE ConstantExprE bin-eval.simps(11) bin-eval.simps(4)
evalDet intval-conditional.simps unfold-binary)
  obtain rhs where rhs: [m, p]  $\vdash$  exp[x & (const (IntVal 32 1))]  $\mapsto$  rhs
  using eval(2) by blast
  then have rhsV: rhs = val[xv & IntVal 32 1]
  by (metis BinaryExprE ConstantExprE bin-eval.simps(4) evalDet xv)
  have lhs = rhs using val-optimize-integer-test x32
  using lhsV rhsV by presburger
  then show ?thesis
  by (metis eval(2) evalDet lhs rhs)
qed
done

```

optimization *opt-optimize-integer-test-2*:

```

  (((x & (const (IntVal 32 1))) eq (const (IntVal 32 0))) ?
   (const (IntVal 32 0)) : (const (IntVal 32 1)))  $\mapsto$ 
   x
   when (x = ConstantExpr (IntVal 32 0) | (x = ConstantExpr (IntVal
32 1))) .

```

end

end

1.6 MulNode Phase

theory *MulPhase*

imports

Common

Proofs.StampEvalThms

begin

phase *MulNode*

terminating *size*

begin

lemma *bin-eliminate-redundant-negative*:

$uminus (x :: 'a::len word) * uminus (y :: 'a::len word) = x * y$

by *simp*

lemma *bin-multiply-identity*:

$(x :: 'a::len word) * 1 = x$

by *simp*

lemma *bin-multiply-eliminate*:

$(x :: 'a::len word) * 0 = 0$

by *simp*

lemma *bin-multiply-negative*:

$(x :: 'a::len word) * uminus 1 = uminus x$

by *simp*

lemma *bin-multiply-power-2*:

$(x :: 'a::len word) * (2^j) = x << j$

by *simp*

lemma *take-bit64*[*simp*]:

fixes $w :: int64$

shows *take-bit 64 w = w*

proof –

have $Nat.size\ w = 64$

by (*simp add: size64*)

then show *?thesis*

by (*metis lt2p-lem mask-eq-iff take-bit-eq-mask verit-comp-simplify1 (2) wsst-TYs(3)*)

qed

lemma *testt*:

fixes $a :: nat$

fixes $b\ c :: 64\ word$

shows *take-bit a (take-bit a (b) * take-bit a (c)) =*

*take-bit a (b * c)*
by (*smt (verit, ccfv-SIG) take-bit-mult take-bit-of-int unsigned-take-bit-eq word-mult-def*)

lemma *val-eliminate-redundant-negative*:
assumes $\text{val}[-x * -y] \neq \text{UndefVal}$
shows $\text{val}[-x * -y] = \text{val}[x * y]$
using *assms apply (cases x; cases y; auto)*
using *testt by auto*

lemma *val-multiply-neutral*:
assumes $x = \text{new-int } b \ v$
shows $\text{val}[x * (\text{IntVal } b \ 1)] = \text{val}[x]$
using *assms by force*

lemma *val-multiply-zero*:
assumes $x = \text{new-int } b \ v$
shows $\text{val}[x * (\text{IntVal } b \ 0)] = \text{IntVal } b \ 0$
using *assms by simp*

lemma *val-multiply-negative*:
assumes $x = \text{new-int } b \ v$
shows $\text{val}[x * \text{intval-negate } (\text{IntVal } b \ 1)] = \text{intval-negate } x$
using *assms*
by (*smt (verit) Value.disc(1) Value.inject(1) add.inverse-neutral intval-negate.simps(1)*)

is-IntVal-def mask-0 mask-eq-take-bit-minus-one new-int.elims of-bool-eq(2)
take-bit-dist-neg
take-bit-of-1 val-eliminate-redundant-negative val-multiply-neutral val-multiply-zero
verit-minus-simplify(4) zero-neq-one

lemma *val-MulPower2*:
fixes $i :: 64 \text{ word}$
assumes $y = \text{IntVal } 64 \ (2 \wedge \text{unat}(i))$
and $0 < i$
and $i < 64$
and $\text{val}[x * y] \neq \text{UndefVal}$
shows $\text{val}[x * y] = \text{val}[x << \text{IntVal } 64 \ i]$
using *assms apply (cases x; cases y; auto)*
subgoal premises p for x2
proof –
have $63 :: \text{int64} = \text{mask } 6$
by *eval*
then have $(2 :: \text{int}) \wedge 6 = 64$
by *eval*
then have $\text{uint } i < (2 :: \text{int}) \wedge 6$

```

    by (metis linorder-not-less lt2p-lem of-int-numeral p(4) size64 word-2p-lem
word-of-int-2p wsst-TYs(3))
  then have and i (mask 6) = i
    using mask-eq-iff by blast
  then show  $x2 \ll \text{unat } i = x2 \ll \text{unat } (\text{and } i \text{ (63::64 word)})$ 
    unfolding 63
    by force
qed
by presburger

```

lemma *val-MulPower2Add1*:

```

  fixes i :: 64 word
  assumes y = IntVal 64 ((2 ^ unat(i)) + 1)
  and 0 < i
  and i < 64
  and val-to-bool(val[IntVal 64 0 < x])
  and val-to-bool(val[IntVal 64 0 < y])
  shows val[x * y] = val[(x << IntVal 64 i) + x]
  using assms apply (cases x; cases y; auto)
  subgoal premises p for x2
  proof -
    have 63: (63 :: int64) = mask 6
      by eval
    then have (2::int) ^ 6 = 64
      by eval
    then have and i (mask 6) = i
      using mask-eq-iff by (simp add: less-mask-eq p(6))
    then have  $x2 * ((2::64 \text{ word}) \wedge \text{unat } i + (1::64 \text{ word})) = (x2 * ((2::64 \text{ word}) \wedge \text{unat } i)) + x2$ 
      by (simp add: distrib-left)
    then show  $x2 * ((2::64 \text{ word}) \wedge \text{unat } i + (1::64 \text{ word})) = x2 \ll \text{unat } (\text{and } i \text{ (63::64 word)}) + x2$ 
      by (simp add: 63 <and (i::64 word) (mask (6::nat)) = i>)
    qed
  using val-to-bool.simps(2) by presburger

```

lemma *val-MulPower2Sub1*:

```

  fixes i :: 64 word
  assumes y = IntVal 64 ((2 ^ unat(i)) - 1)
  and 0 < i
  and i < 64
  and val-to-bool(val[IntVal 64 0 < x])
  and val-to-bool(val[IntVal 64 0 < y])
  shows val[x * y] = val[(x << IntVal 64 i) - x]
  using assms apply (cases x; cases y; auto)
  subgoal premises p for x2

```

```

proof –
  have 63: (63 :: int64) = mask 6
    by eval
  then have (2::int) ^ 6 = 64
    by eval
  then have and i (mask 6) = i
    using mask-eq-iff by (simp add: less-mask-eq p(6))
  then have x2 * ((2::64 word) ^ unat i – (1::64 word)) = (x2 * ((2::64 word)
    ^ unat i)) – x2
    by (simp add: right-diff-distrib)
  then show x2 * ((2::64 word) ^ unat i – (1::64 word)) = x2 << unat (and i
    (63::64 word)) – x2
    by (simp add: 63 <and (i::64 word) (mask (6::nat)) = i)
  qed
using val-to-bool.simps(2) by presburger

```

lemma *val-distribute-multiplication*:

```

assumes x = new-int 64 xx ∧ q = new-int 64 qq ∧ a = new-int 64 aa
shows val[x * (q + a)] = val[(x * q) + (x * a)]
apply (cases x; cases q; cases a; auto) using distrib-left assms by auto

```

lemma *val-MulPower2AddPower2*:

```

fixes i j :: 64 word
assumes y = IntVal 64 ((2 ^ unat(i)) + (2 ^ unat(j)))
and 0 < i
and 0 < j
and i < 64
and j < 64
and x = new-int 64 xx
shows val[x * y] = val[(x << IntVal 64 i) + (x << IntVal 64 j)]
using assms
proof –
  have 63: (63 :: int64) = mask 6
    by eval
  then have (2::int) ^ 6 = 64
    by eval
  then have n: IntVal 64 ((2 ^ unat(i)) + (2 ^ unat(j))) =
    val[(IntVal 64 (2 ^ unat(i))) + (IntVal 64 (2 ^ unat(j)))]

    using assms by (cases i; cases j; auto)
  then have 1: val[x * ((IntVal 64 (2 ^ unat(i))) + (IntVal 64 (2 ^ unat(j))))]
    =
    val[(x * IntVal 64 (2 ^ unat(i))) + (x * IntVal 64 (2 ^ unat(j)))]

    using assms val-distribute-multiplication val-MulPower2 by simp
  then have 2: val[(x * IntVal 64 (2 ^ unat(i)))] = val[x << IntVal 64 i]

```

```

    using assms val-MulPower2
    using Value.distinct(1) intval-mul.simps(1) new-int.simps new-int-bin.simps
    by (smt (verit))
  then show ?thesis
    using 1 Value.distinct(1) assms(1) assms(3) assms(5) assms(6) intval-mul.simps(1)
n new-int.simps new-int-bin.elims val-MulPower2
    by (smt (verit, del-insts))
qed

```

thm-oracles *val-MulPower2AddPower2*

```

lemma exp-multiply-zero-64:
   $\text{exp}[x * (\text{const } (\text{IntVal } 64\ 0))] \geq \text{ConstantExpr } (\text{IntVal } 64\ 0)$ 
  using val-multiply-zero apply auto
  using Value.inject(1) constantAsStamp.simps(1) int-signed-value-bounds intval-mul.elims

  mult-zero-right new-int.simps new-int-bin.simps nle-le numeral-eq-Suc take-bit-of-0

  unfold-const valid-stamp.simps(1) valid-value.simps(1) zero-less-Suc
  by (smt (verit))

```

```

lemma exp-multiply-neutral:
   $\text{exp}[x * (\text{const } (\text{IntVal } b\ 1))] \geq x$ 
  using val-multiply-neutral apply auto
  by (smt (verit) Value.inject(1) eval-unused-bits-zero intval-mul.elims mult.right-neutral

  new-int.elims new-int-bin.elims)

```

thm-oracles *exp-multiply-neutral*

```

lemma exp-MulPower2:
  fixes  $i :: 64\ \text{word}$ 
  assumes  $y = \text{ConstantExpr } (\text{IntVal } 64\ (2^{\text{unat}(i)}))$ 
  and  $0 < i$ 
  and  $i < 64$ 
  and  $\text{exp}[x > (\text{const } \text{IntVal } b\ 0)]$ 
  and  $\text{exp}[y > (\text{const } \text{IntVal } b\ 0)]$ 
  shows  $\text{exp}[x * y] \geq \text{exp}[x << \text{ConstantExpr } (\text{IntVal } 64\ i)]$ 
  using assms apply simp using val-MulPower2
  by (metis ConstantExprE equiv-exprs-def unfold-binary)

```

Optimisations

```

optimization EliminateRedundantNegative:  $-x * -y \mapsto x * y$ 
  apply auto using val-eliminate-redundant-negative bin-eval.simps(2)
  by (metis BinaryExpr)

```

```

optimization MulNeutral:  $x * \text{ConstantExpr } (\text{IntVal } b\ 1) \mapsto x$ 
  using exp-multiply-neutral by blast

```

optimization *MulEliminator*: $x * \text{ConstantExpr } (\text{IntVal } b \ 0) \mapsto \text{const } (\text{IntVal } b \ 0)$
apply *auto* **using** *val-multiply-zero*
using *Value.inject(1) constantAsStamp.simps(1) int-signed-value-bounds intval-mul.elims*
mult-zero-right new-int.simps new-int-bin.simps take-bit-of-0 unfold-const
valid-stamp.simps(1) valid-value.simps(1)
by (*smt (verit)*)

optimization *MulNegate*: $x * -(\text{const } (\text{IntVal } b \ 1)) \mapsto -x$
defer
apply *auto* **using** *val-multiply-negative*
apply (*smt (verit) Value.distinct(1) Value.sel(1) add.inverse-inverse intval-mul.elims*
intval-negate.simps(1) mask-eq-take-bit-minus-one new-int.simps new-int-bin.simps
take-bit-dist-neg unary-eval.simps(2) unfold-unary
val-eliminate-redundant-negative)
sorry

fun *isNonZero* :: *Stamp* \Rightarrow *bool* **where**
isNonZero (IntegerStamp b lo hi) = (lo > 0) |
isNonZero - = False

lemma *isNonZero-defn*:
assumes *isNonZero (stamp-expr x)*
assumes *wf-stamp x*
shows ($[m, p] \vdash x \mapsto v \longrightarrow (\exists vv \ b. (v = \text{IntVal } b \ vv \wedge \text{val-to-bool val}[(\text{IntVal } b \ 0) < v]))$)
apply (*rule impI*) **subgoal premises** *eval*
proof –
obtain *b lo hi* **where** *xstamp: stamp-expr x = IntegerStamp b lo hi*
using *assms*
by (*meson isNonZero.elims(2)*)
then obtain *vv* **where** *vdef: v = IntVal b vv*
by (*metis assms(2) eval valid-int wf-stamp-def*)
have *lo > 0*
using *assms(1) xstamp* **by** *force*
then have *signed-above: int-signed-value b vv > 0*
using *assms unfolding wf-stamp-def*
using *eval vdef xstamp* **by** *fastforce*
have *take-bit b vv = vv*
using *eval eval-unused-bits-zero vdef* **by** *auto*
then have *vv > 0*
using *signed-above*
by (*metis bit-take-bit-iff int-signed-value.simps not-less-zero signed-eq-0-iff signed-take-bit-eq-if-positive*
take-bit-0 take-bit-of-0 verit-comp-simplify1(1) word-gt-0)
then show *?thesis*


```

    using vdef using signed-above
    by simp
qed
done

optimization MulPower2:  $x * y \mapsto x << \text{const } (\text{IntVal } 64 \ i)$ 
    when  $(i > 0 \wedge$ 
     $64 > i \wedge$ 
     $y = \text{exp}[\text{const } (\text{IntVal } 64 \ (2 \wedge \text{unat}(i)))]$ )

    defer
    apply simp apply (rule impI; (rule allI)+; rule impI)
    subgoal premises eval for m p v
    proof -
    obtain xv where xv:  $[m, p] \vdash x \mapsto xv$ 
    using eval(2) by blast
    then obtain xvv where xvv:  $xv = \text{IntVal } 64 \ xvv$ 
    using eval
    using ConstantExprE bin-eval.simps(2) evalDet intval-bits.simps intval-mul.elims
    new-int-bin.simps unfold-binary
    by (smt (verit))
    obtain yv where yv:  $[m, p] \vdash y \mapsto yv$ 
    using eval(1) eval(2) by blast
    then have lhs:  $[m, p] \vdash \text{exp}[x * y] \mapsto \text{val}[xv * yv]$ 
    by (metis bin-eval.simps(2) eval(1) eval(2) evalDet unfold-binary xv)
    have  $[m, p] \vdash \text{exp}[\text{const } (\text{IntVal } 64 \ i)] \mapsto \text{val}[(\text{IntVal } 64 \ i)]$ 
    by (smt (verit, ccfv-SIG) ConstantExpr constantAsStamp.simps(1) eval-bits-1-64
    take-bit64 validStampIntConst valid-value.simps(1) xv xvv)
    then have rhs:  $[m, p] \vdash \text{exp}[x << \text{const } (\text{IntVal } 64 \ i)] \mapsto \text{val}[xv << (\text{IntVal } 64 \ i)]$ 
    using xv xvv using evaltree.BinaryExpr
    by (metis Value.simps(5) bin-eval.simps(8) intval-left-shift.simps(1) new-int.simps)
    have  $\text{val}[xv * yv] = \text{val}[xv << (\text{IntVal } 64 \ i)]$ 
    using val-MulPower2
    by (metis ConstantExprE eval(1) evaltree-not-undef lhs yv)
    then show ?thesis
    by (metis eval(1) eval(2) evalDet lhs rhs)
    qed
    sorry

```

end

end

1.7 Experimental AndNode Phase

```

theory NewAnd
imports

```

Common
Graph.Long

begin

lemma *bin-distribute-and-over-or*:
 $\text{bin}[z \ \& \ (x \mid y)] = \text{bin}[(z \ \& \ x) \mid (z \ \& \ y)]$
by (*smt* (*verit*, *best*) *bit-and-iff* *bit-eqI* *bit-or-iff*)

lemma *intval-distribute-and-over-or*:
 $\text{val}[z \ \& \ (x \mid y)] = \text{val}[(z \ \& \ x) \mid (z \ \& \ y)]$
apply (*cases* *x*; *cases* *y*; *cases* *z*; *auto*)
using *bin-distribute-and-over-or* **by** *blast+*

lemma *exp-distribute-and-over-or*:
 $\text{exp}[z \ \& \ (x \mid y)] \geq \text{exp}[(z \ \& \ x) \mid (z \ \& \ y)]$
apply *simp* **using** *intval-distribute-and-over-or*
using *BinaryExpr* *bin-eval.simps*(4,5)
using *intval-or.simps*(1) **unfolding** *new-int-bin.simps* *new-int.simps* **apply** *auto*
by (*metis* *bin-eval.simps*(4) *bin-eval.simps*(5) *intval-or.simps*(2) *intval-or.simps*(5))

lemma *intval-and-commute*:
 $\text{val}[x \ \& \ y] = \text{val}[y \ \& \ x]$
by (*cases* *x*; *cases* *y*; *auto* *simp*: *and.commute*)

lemma *intval-or-commute*:
 $\text{val}[x \mid y] = \text{val}[y \mid x]$
by (*cases* *x*; *cases* *y*; *auto* *simp*: *or.commute*)

lemma *intval-xor-commute*:
 $\text{val}[x \oplus y] = \text{val}[y \oplus x]$
by (*cases* *x*; *cases* *y*; *auto* *simp*: *xor.commute*)

lemma *exp-and-commute*:
 $\text{exp}[x \ \& \ z] \geq \text{exp}[z \ \& \ x]$
apply *simp* **using** *intval-and-commute* **by** *auto*

lemma *exp-or-commute*:
 $\text{exp}[x \mid y] \geq \text{exp}[y \mid x]$
apply *simp* **using** *intval-or-commute* **by** *auto*

lemma *exp-xor-commute*:
 $\text{exp}[x \oplus y] \geq \text{exp}[y \oplus x]$
apply *simp* **using** *intval-xor-commute* **by** *auto*

lemma *bin-eliminate-y*:
assumes $\text{bin}[y \ \& \ z] = 0$
shows $\text{bin}[(x \mid y) \ \& \ z] = \text{bin}[x \ \& \ z]$

```

using assms
by (simp add: and.commute bin-distribute-and-over-or)

lemma intval-eliminate-y:
  assumes  $\text{val}[y \ \& \ z] = \text{IntVal } b \ 0$ 
  shows  $\text{val}[(x \mid y) \ \& \ z] = \text{val}[x \ \& \ z]$ 
  using assms bin-eliminate-y by (cases x; cases y; cases z; auto)

lemma intval-and-associative:
   $\text{val}[(x \ \& \ y) \ \& \ z] = \text{val}[x \ \& \ (y \ \& \ z)]$ 
  apply (cases x; cases y; cases z; auto)
  by (simp add: and.assoc)+

lemma intval-or-associative:
   $\text{val}[(x \mid y) \mid z] = \text{val}[x \mid (y \mid z)]$ 
  apply (cases x; cases y; cases z; auto)
  by (simp add: or.assoc)+

lemma intval-xor-associative:
   $\text{val}[(x \oplus y) \oplus z] = \text{val}[x \oplus (y \oplus z)]$ 
  apply (cases x; cases y; cases z; auto)
  by (simp add: xor.assoc)+

lemma exp-and-associative:
   $\text{exp}[(x \ \& \ y) \ \& \ z] \geq \text{exp}[x \ \& \ (y \ \& \ z)]$ 
  apply simp using intval-and-associative by fastforce

lemma exp-or-associative:
   $\text{exp}[(x \mid y) \mid z] \geq \text{exp}[x \mid (y \mid z)]$ 
  apply simp using intval-or-associative by fastforce

lemma exp-xor-associative:
   $\text{exp}[(x \oplus y) \oplus z] \geq \text{exp}[x \oplus (y \oplus z)]$ 
  apply simp using intval-xor-associative by fastforce

lemma intval-and-absorb-or:
  assumes  $\exists b \ v. x = \text{new-int } b \ v$ 
  assumes  $\text{val}[x \ \& \ (x \mid y)] \neq \text{UndefVal}$ 
  shows  $\text{val}[x \ \& \ (x \mid y)] = \text{val}[x]$ 
  using assms apply (cases x; cases y; auto)
  by (metis (mono-tags, lifting) intval-and.simps(5))

lemma intval-or-absorb-and:
  assumes  $\exists b \ v. x = \text{new-int } b \ v$ 
  assumes  $\text{val}[x \mid (x \ \& \ y)] \neq \text{UndefVal}$ 
  shows  $\text{val}[x \mid (x \ \& \ y)] = \text{val}[x]$ 
  using assms apply (cases x; cases y; auto)
  by (metis (mono-tags, lifting) intval-or.simps(5))

```

lemma *exp-and-absorb-or*:
 $exp[x \& (x \mid y)] \geq exp[x]$
apply *auto using intval-and-absorb-or eval-unused-bits-zero*
by (*smt (verit) evalDet intval-or.elims new-int.elims*)

lemma *exp-or-absorb-and*:
 $exp[x \mid (x \& y)] \geq exp[x]$
apply *auto using intval-or-absorb-and eval-unused-bits-zero*
by (*smt (verit) evalDet intval-or.elims new-int.elims*)

definition *IRExpr-up* :: *IRExpr* \Rightarrow *int64* **where**
IRExpr-up *e* = *not 0*

definition *IRExpr-down* :: *IRExpr* \Rightarrow *int64* **where**
IRExpr-down *e* = *0*

lemma
assumes *y* = *0*
shows *x + y* = *or x y*
using *assms*
by *simp*

lemma *no-overlap-or*:
assumes *and x y* = *0*
shows *x + y* = *or x y*
using *assms*
by (*metis bit-and-iff bit-xor-iff disjunctive-add xor-self-eq*)

context *stamp-mask*
begin

lemma *intval-up-and-zero-implies-zero*:
assumes *and* ($\uparrow x$) ($\uparrow y$) = *0*
assumes [*m*, *p*] $\vdash x \mapsto xv$
assumes [*m*, *p*] $\vdash y \mapsto yv$
assumes *val*[*xv* & *yv*] \neq *UndefVal*
shows $\exists b . val[xv \& yv] = new-int\ b\ 0$
using *assms apply* (*cases xv; cases yv; auto*)
using *up-mask-and-zero-implies-zero*

```

apply (smt (verit, best) take-bit-and take-bit-of-0)
by presburger

lemma exp-eliminate-y:
  and ( $\uparrow y$ ) ( $\uparrow z$ ) = 0  $\longrightarrow$  BinaryExpr BinAnd (BinaryExpr BinOr x y) z  $\geq$  BinaryExpr BinAnd x z
apply simp apply (rule impI; rule allI; rule allI; rule allI)
subgoal premises p for m p v apply (rule impI) subgoal premises e
proof -
  obtain xv where xv: [m,p]  $\vdash$  x  $\mapsto$  xv
  using e by auto
  obtain yv where yv: [m,p]  $\vdash$  y  $\mapsto$  yv
  using e by auto
  obtain zv where zv: [m,p]  $\vdash$  z  $\mapsto$  zv
  using e by auto
  have lhs: v = val[(xv | yv) & zv]
  using xv yv zv
  by (smt (verit, best) BinaryExprE bin-eval.simps(4) bin-eval.simps(5) e evalDet)
  then have v = val[(xv & zv) | (yv & zv)]
  by (simp add: intval-and-commute intval-distribute-and-over-or)
  also have  $\exists b. \text{val}[yv \& zv] = \text{new-int } b \ 0$ 
  using intval-up-and-zero-implies-zero
  by (metis calculation e intval-or.simps(5) p unfold-binary yv zv)
  ultimately have rhs: v = val[xv & zv]
  using intval-eliminate-y lhs by force
  from lhs rhs show ?thesis
  by (metis BinaryExpr BinaryExprE bin-eval.simps(4) e xv zv)
qed
done
done

lemma leadingZeroBounds:
  fixes x :: 'a::len word
  assumes n = numberOfLeadingZeros x
  shows  $0 \leq n \wedge n \leq \text{Nat.size } x$ 
  using assms unfolding numberOfLeadingZeros-def
  by (simp add: MaxOrNeg-def highestOneBit-def nat-le-iff)

lemma above-nth-not-set:
  fixes x :: int64
  assumes n = 64 - numberOfLeadingZeros x
  shows  $j > n \longrightarrow \neg(\text{bit } x \ j)$ 
  using assms unfolding numberOfLeadingZeros-def
  by (smt (verit, ccfv-SIG) highestOneBit-def int-nat-eq int-ops(6) less-imp-of-nat-less max-set-bit size64 zerosAboveHighestOne)

no-notation LogicNegationNotation (!-)

```

```

lemma zero-horner:
  horner-sum of-bool 2 (map (λx. False) xs) = 0
  apply (induction xs) apply simp
  by force

lemma zero-map:
  assumes  $j \leq n$ 
  assumes  $\forall i. j \leq i \longrightarrow \neg(f\ i)$ 
  shows  $\text{map } f\ [0..<n] = \text{map } f\ [0..<j] @ \text{map } (\lambda x. \text{False})\ [j..<n]$ 
  apply (insert assms)
  by (smt (verit, del-insts) add-diff-inverse-nat atLeastLessThan-iff bot-nat-0.extremum
leD map-append map-eq-conv set-upt upt-add-eq-append)

lemma map-join-horner:
  assumes  $\text{map } f\ [0..<n] = \text{map } f\ [0..<j] @ \text{map } (\lambda x. \text{False})\ [j..<n]$ 
  shows  $\text{horner-sum of-bool } (2::'a::\text{len word})\ (\text{map } f\ [0..<n]) = \text{horner-sum of-bool}$ 
 $2\ (\text{map } f\ [0..<j])$ 
proof -
  have  $\text{horner-sum of-bool } (2::'a::\text{len word})\ (\text{map } f\ [0..<n]) = \text{horner-sum of-bool}$ 
 $2\ (\text{map } f\ [0..<j]) + 2 \wedge \text{length } [0..<j] * \text{horner-sum of-bool } 2\ (\text{map } f\ [j..<n])$ 
  using horner-sum-append
  by (smt (verit) assms diff-le-self diff-zero le-add-same-cancel2 length-append
length-map length-upt map-append upt-add-eq-append)
  also have  $\dots = \text{horner-sum of-bool } 2\ (\text{map } f\ [0..<j]) + 2 \wedge \text{length } [0..<j] *$ 
 $\text{horner-sum of-bool } 2\ (\text{map } (\lambda x. \text{False})\ [j..<n])$ 
  using assms
  by (metis calculation horner-sum-append length-map)
  also have  $\dots = \text{horner-sum of-bool } 2\ (\text{map } f\ [0..<j])$ 
  using zero-horner
  using mult-not-zero by auto
  finally show ?thesis by simp
qed

lemma split-horner:
  assumes  $j \leq n$ 
  assumes  $\forall i. j \leq i \longrightarrow \neg(f\ i)$ 
  shows  $\text{horner-sum of-bool } (2::'a::\text{len word})\ (\text{map } f\ [0..<n]) = \text{horner-sum of-bool}$ 
 $2\ (\text{map } f\ [0..<j])$ 
  apply (rule map-join-horner)
  apply (rule zero-map)
  using assms by auto

lemma transfer-map:
  assumes  $\forall i. i < n \longrightarrow f\ i = f'\ i$ 
  shows  $(\text{map } f\ [0..<n]) = (\text{map } f'\ [0..<n])$ 
  using assms by simp

lemma transfer-horner:
  assumes  $\forall i. i < n \longrightarrow f\ i = f'\ i$ 

```

shows *horner-sum of-bool* ($2::'a::len$ word) ($map\ f\ [0..<n]$) = *horner-sum of-bool*
 $2\ (map\ f'\ [0..<n])$
using *assms* **using** *transfer-map*
by (*smt* (*verit*, *best*))

lemma *L1*:

assumes $n = 64 - numberOfLeadingZeros\ (\uparrow z)$
assumes $[m, p] \vdash z \mapsto IntVal\ b\ zv$
shows *and* $v\ zv = and\ (v\ mod\ 2^{\wedge}n)\ zv$
proof –
have $nle: n \leq 64$
using *assms*
using *diff-le-self* **by** *blast*
also have *and* $v\ zv = horner-sum\ of-bool\ 2\ (map\ (bit\ (and\ v\ zv))\ [0..<64])$
using *horner-sum-bit-eq-take-bit size64*
by (*metis size-word.rep-eq take-bit-length-eq*)
also have $\dots = horner-sum\ of-bool\ 2\ (map\ (\lambda i. bit\ (and\ v\ zv)\ i)\ [0..<64])$
by *blast*
also have $\dots = horner-sum\ of-bool\ 2\ (map\ (\lambda i. ((bit\ v\ i) \wedge (bit\ zv\ i)))\ [0..<64])$
using *bit-and-iff* **by** *metis*
also have $\dots = horner-sum\ of-bool\ 2\ (map\ (\lambda i. ((bit\ v\ i) \wedge (bit\ zv\ i)))\ [0..<n])$
proof –
have $\forall i. i \geq n \longrightarrow \neg(bit\ zv\ i)$
using *above-nth-not-set assms(1)*
using *assms(2) not-may-implies-false*
by (*smt* (*verit*, *ccfv-SIG*) *One-nat-def diff-less int-ops(6) leadingZerosAddHighestOne linorder-not-le nat-int-comparison(2) not-numeral-le-zero size64 zero-less-Suc zerosAboveHighestOne*)
then have $\forall i. i \geq n \longrightarrow \neg((bit\ v\ i) \wedge (bit\ zv\ i))$
by *auto*
then show *?thesis* **using** *nle split-horner*
by (*metis* (*no-types*, *lifting*))
qed
also have $\dots = horner-sum\ of-bool\ 2\ (map\ (\lambda i. ((bit\ (v\ mod\ 2^{\wedge}n)\ i) \wedge (bit\ zv\ i)))\ [0..<n])$
proof –
have $\forall i. i < n \longrightarrow bit\ (v\ mod\ 2^{\wedge}n)\ i = bit\ v\ i$
by (*metis bit-take-bit-iff take-bit-eq-mod*)
then have $\forall i. i < n \longrightarrow ((bit\ v\ i) \wedge (bit\ zv\ i)) = ((bit\ (v\ mod\ 2^{\wedge}n)\ i) \wedge (bit\ zv\ i))$
by *force*
then show *?thesis*
by (*rule transfer-horner*)
qed
also have $\dots = horner-sum\ of-bool\ 2\ (map\ (\lambda i. ((bit\ (v\ mod\ 2^{\wedge}n)\ i) \wedge (bit\ zv\ i)))\ [0..<64])$
proof –
have $\forall i. i \geq n \longrightarrow \neg(bit\ zv\ i)$
using *above-nth-not-set assms(1)*

```

    using assms(2) not-may-implies-false
  by (smt (verit, ccfv-SIG) One-nat-def diff-less int-ops(6) leadingZerosAddHighestOne linorder-not-le nat-int-comparison(2) not-numeral-le-zero size64 zero-less-Suc zerosAboveHighestOne)
  then show ?thesis
    by (metis (no-types, lifting) assms(1) diff-le-self split-horner)
qed
also have ... = horner-sum of-bool 2 (map (bit (and (v mod 2n) zv)) [0..<64])
  by (meson bit-and-iff)
also have ... = and (v mod 2n) zv
  using horner-sum-bit-eq-take-bit size64
  by (metis size-word.rep-eq take-bit-length-eq)
finally show ?thesis
  using ⟨and (v::64 word) (zv::64 word) = horner-sum of-bool (2::64 word) (map (bit (and v zv)) [0::nat..<64::nat])⟩ ⟨horner-sum of-bool (2::64 word) (map (λi::nat. bit ((v::64 word) mod (2::64 word) ^ (n::nat)) i) ∧ bit (zv::64 word) i) [0::nat..<64::nat]) = horner-sum of-bool (2::64 word) (map (bit (and (v mod (2::64 word) ^ n) zv)) [0::nat..<64::nat])⟩ ⟨horner-sum of-bool (2::64 word) (map (λi::nat. bit ((v::64 word) mod (2::64 word) ^ (n::nat)) i) ∧ bit (zv::64 word) i) [0::nat..

```

lemma *up-mask-upper-bound*:

```

  assumes [m, p] ⊢ x ↦ IntVal b xv
  shows xv ≤ (↑x)
  using assms
  by (metis (no-types, lifting) and.idem and.right-neutral bit.conj-cancel-left bit.conj-disj-distrib(1) bit.double-compl ucast-id up-spec word-and-le1 word-not-dist(2))

```

lemma *L2*:

```

  assumes numberOfLeadingZeros (↑z) + numberOfTrailingZeros (↑y) ≥ 64
  assumes n = 64 - numberOfLeadingZeros (↑z)
  assumes [m, p] ⊢ z ↦ IntVal b zv
  assumes [m, p] ⊢ y ↦ IntVal b yv
  shows yv mod 2n = 0

```

proof –

```

  have yv mod 2n = horner-sum of-bool 2 (map (bit yv) [0..

```



```

also have ...  $\leq$  horner-sum of-bool 2 (map (bit ( $\uparrow y$ )) [0.. $n$ ])
  using up-mask-upper-bound assms(4)
  by (metis (no-types, opaque-lifting) and.right-neutral bit.conj-cancel-right bit.conj-disj-distrib(1)
bit.double-compl horner-sum-bit-eq-take-bit take-bit-and ucast-id up-spec word-and-le1
word-not-dist(2))
  also have horner-sum of-bool 2 (map (bit ( $\uparrow y$ )) [0.. $n$ ]) = horner-sum of-bool 2
(map ( $\lambda x$ . False) [0.. $n$ ])
  proof -
    have  $\forall i < n. \neg(\text{bit } (\uparrow y) i)$ 
      using assms(1,2) zerosBelowLowestOne
      by (metis add commute add-diff-inverse-nat add-lessD1 leD le-diff-conv num-
berOfTrailingZeros-def)
    then show ?thesis
      by (metis (full-types) transfer-map)
  qed
also have horner-sum of-bool 2 (map ( $\lambda x$ . False) [0.. $n$ ]) = 0
  using zero-horner
  by blast
finally show ?thesis
  by auto
qed

```

thm-oracles $L1\ L2$

lemma *unfold-binary-width-add:*

```

shows ( $[m,p] \vdash \text{BinaryExpr BinAdd } xe\ ye \mapsto \text{IntVal } b\ val$ ) = ( $\exists\ x\ y.$ 
  ( $[m,p] \vdash xe \mapsto \text{IntVal } b\ x$ )  $\wedge$ 
  ( $[m,p] \vdash ye \mapsto \text{IntVal } b\ y$ )  $\wedge$ 
  ( $\text{IntVal } b\ val = \text{bin-eval BinAdd } (\text{IntVal } b\ x) (\text{IntVal } b\ y)$ )  $\wedge$ 
  ( $\text{IntVal } b\ val \neq \text{UndefVal}$ )
  ) (is ?L = ?R)
proof (intro iffI)
  assume  $\exists: ?L$ 
  show ?R apply (rule evaltree.cases[OF  $\exists$ ])
  apply force+ apply auto[1]
  apply (smt (verit) intval-add.elims intval-bits.simps)
  by blast
next
  assume  $R: ?R$ 
  then obtain  $x\ y$  where  $[m,p] \vdash xe \mapsto \text{IntVal } b\ x$ 
    and  $[m,p] \vdash ye \mapsto \text{IntVal } b\ y$ 
    and  $\text{new-int } b\ val = \text{bin-eval BinAdd } (\text{IntVal } b\ x) (\text{IntVal } b\ y)$ 
    and  $\text{new-int } b\ val \neq \text{UndefVal}$ 
  by auto
  then show ?L
  using  $R$  by blast
qed

```

lemma *unfold-binary-width-and:*

```

shows ([m,p] ⊢ BinaryExpr BinAnd xe ye ↦ IntVal b val) = (∃ x y.
  (([m,p] ⊢ xe ↦ IntVal b x) ∧
   ([m,p] ⊢ ye ↦ IntVal b y) ∧
   (IntVal b val = bin-eval BinAnd (IntVal b x) (IntVal b y)) ∧
   (IntVal b val ≠ UndefVal))
  )) (is ?L = ?R)
proof (intro iffI)
  assume ?3: ?L
  show ?R apply (rule evaltree.cases[OF ?3])
  apply force+ apply auto[1] using intval-and.elims intval-bits.simps
  apply (smt (verit) new-int.simps new-int-bin.simps take-bit-and)
  by blast
next
  assume R: ?R
  then obtain x y where [m,p] ⊢ xe ↦ IntVal b x
    and [m,p] ⊢ ye ↦ IntVal b y
    and new-int b val = bin-eval BinAnd (IntVal b x) (IntVal b y)
    and new-int b val ≠ UndefVal
  by auto
  then show ?L
  using R by blast
qed

```

```

lemma mod-dist-over-add-right:
  fixes a b c :: int64
  fixes n :: nat
  assumes 1: 0 < n
  assumes 2: n < 64
  shows (a + b mod 2n) mod 2n = (a + b) mod 2n
  using mod-dist-over-add
  by (simp add: 1 2 add.commute)

```

```

lemma numberOfLeadingZeros-range:
  0 ≤ numberOfLeadingZeros n ∧ numberOfLeadingZeros n ≤ Nat.size n
  unfolding numberOfLeadingZeros-def highestOneBit-def using max-set-bit
  by (simp add: highestOneBit-def leadingZeroBounds numberOfLeadingZeros-def)

```

```

lemma improved-opt:
  assumes numberOfLeadingZeros (↑z) + numberOfTrailingZeros (↑y) ≥ 64
  shows exp[(x + y) & z] ≥ exp[x & z]
  apply simp apply ((rule allI)+; rule impI)
  subgoal premises eval for m p v

```

```

proof –
  obtain n where n: n = 64 – numberOfLeadingZeros (↑z)
  by simp
  obtain b val where val: [m, p] ⊢ exp[(x + y) & z] ↦ IntVal b val
  by (metis BinaryExprE bin-eval-new-int eval new-int.simps)
  then obtain xv yv where addv: [m, p] ⊢ exp[x + y] ↦ IntVal b (xv + yv)
  apply (subst (asm) unfold-binary-width-and) by (metis add.right-neutral)

```

```

then obtain yv where yv:  $[m, p] \vdash y \mapsto \text{IntVal } b \ yv$ 
  apply (subst (asm) unfold-binary-width-add) by blast
from addv obtain xv where xv:  $[m, p] \vdash x \mapsto \text{IntVal } b \ xv$ 
  apply (subst (asm) unfold-binary-width-add) by blast
from val obtain zv where zv:  $[m, p] \vdash z \mapsto \text{IntVal } b \ zv$ 
  apply (subst (asm) unfold-binary-width-and) by blast
have addv:  $[m, p] \vdash \text{exp}[x + y] \mapsto \text{new-int } b \ (xv + yv)$ 
  apply (rule evaltree.BinaryExpr)
  using xv apply simp
  using yv apply simp
  by simp+
have lhs:  $[m, p] \vdash \text{exp}[(x + y) \ \& \ z] \mapsto \text{new-int } b \ (\text{and } (xv + yv) \ zv)$ 
  apply (rule evaltree.BinaryExpr)
  using addv apply simp
  using zv apply simp
  using addv apply auto[1]
  by simp
have rhs:  $[m, p] \vdash \text{exp}[x \ \& \ z] \mapsto \text{new-int } b \ (\text{and } xv \ zv)$ 
  apply (rule evaltree.BinaryExpr)
  using xv apply simp
  using zv apply simp
  apply force
  by simp
then show ?thesis
proof (cases numberOfLeadingZeros ( $\uparrow z$ ) > 0)
  case True
  have n-bounds:  $0 \leq n \wedge n < 64$ 
    using diff-le-self n numberOfLeadingZeros-range
    by (simp add: True)
  have and  $(xv + yv) \ zv = \text{and } ((xv + yv) \bmod 2^n) \ zv$ 
    using L1 n zv by blast
  also have  $\dots = \text{and } ((xv + (yv \bmod 2^n)) \bmod 2^n) \ zv$ 
    using mod-dist-over-add-right n-bounds
    by (metis take-bit-0 take-bit-eq-mod zero-less-iff-neq-zero)
  also have  $\dots = \text{and } ((xv \bmod 2^n) + (yv \bmod 2^n)) \bmod 2^n \ zv$ 
    by (metis bits-mod-by-1 mod-dist-over-add n-bounds order-le-imp-less-or-eq
power-0)
  also have  $\dots = \text{and } ((xv \bmod 2^n) \bmod 2^n) \ zv$ 
    using L2 n zv yv
    using assms by auto
  also have  $\dots = \text{and } (xv \bmod 2^n) \ zv$ 
    using mod-mod-trivial
  by (smt (verit, best) and.idem take-bit-eq-mask take-bit-eq-mod word-bw-assocs(1))
  also have  $\dots = \text{and } xv \ zv$ 
    using L1 n zv by metis
  finally show ?thesis
    using eval lhs rhs
    by (metis evalDet)
next

```

```

case False
then have numberOfLeadingZeros ( $\uparrow z$ ) = 0
  by simp
then have numberOfTrailingZeros ( $\uparrow y$ )  $\geq$  64
  using assms(1)
  by fastforce
then have yv = 0
  using yv
  by (metis (no-types, lifting) L1 L2 add-diff-cancel-left' and.comm-neutral
and.idem bit.compl-zero bit.conj-cancel-right bit.conj-disj-distrib(1) bit.double-compl
less-imp-diff-less linorder-not-le word-not-dist(2))
  then show ?thesis
    by (metis add.right-neutral eval evalDet lhs rhs)
qed
qed
done

thm-oracles improved-opt

lemma falseBelowN-nBelowLowest:
  assumes n  $\leq$  Nat.size a
  assumes  $\forall i < n. \neg(\text{bit } a \ i)$ 
  shows lowestOneBit a  $\geq$  n
proof (cases {i. bit a i} = {})
  case True
    then show ?thesis unfolding lowestOneBit-def MinOrHighest-def
      using assms(1) trans-le-add1 by presburger
  next
    case False
    have n  $\leq$  Min (Collect (bit a))
      by (metis False Min-ge-iff assms(2) finite-bit-word linorder-le-less-linear mem-Collect-eq)
    then show ?thesis unfolding lowestOneBit-def MinOrHighest-def
      using False by presburger
qed

lemma noZeros:
  fixes a :: 64 word
  assumes zeroCount a = 0
  shows i < Nat.size a  $\longrightarrow$  bit a i
  using assms unfolding zeroCount-def size64
  using zeroCount-finite by auto

lemma zerosAboveOnly:
  fixes a :: 64 word
  assumes numberOfLeadingZeros a = zeroCount a
  shows  $\neg(\text{bit } a \ i) \longrightarrow i \geq (64 - \text{numberOfLeadingZeros } a)$ 
  sorry

```

lemma *consumes*:

assumes $\text{numberOfLeadingZeros } (\uparrow z) + \text{bitCount } (\uparrow z) = 64$
and $\uparrow z \neq 0$
and $\text{and } (\uparrow y) (\uparrow z) = 0$
shows $\text{numberOfLeadingZeros } (\uparrow z) + \text{numberOfTrailingZeros } (\uparrow y) \geq 64$
proof –
obtain n **where** $n = 64 - \text{numberOfLeadingZeros } (\uparrow z)$
by *simp*
then have $n = \text{bitCount } (\uparrow z)$
by (*metis add-diff-cancel-left' assms(1)*)
have $\text{numberOfLeadingZeros } (\uparrow z) = \text{zeroCount } (\uparrow z)$
using *assms(1) size64 ones-zero-sum-to-width*
by (*metis add.commute add-left-imp-eq*)
then have $\forall i. \neg(\text{bit } (\uparrow z) i) \longrightarrow i \geq n$
using *assms(1) zerosAboveOnly*
using $\langle (n::\text{nat}) = (64::\text{nat}) - \text{numberOfLeadingZeros } (\uparrow (z::\text{IRExpr})) \rangle$ **by** *blast*
then have $\forall i < n. \text{bit } (\uparrow z) i$
using *leD* **by** *blast*
then have $\forall i < n. \neg(\text{bit } (\uparrow y) i)$
using *assms(3)*
by (*metis bit.conj-cancel-right bit-and-iff bit-not-iff*)
then have $\text{lowestOneBit } (\uparrow y) \geq n$
by (*simp add: \langle (n::nat) = (64::nat) - numberOfLeadingZeros } (\uparrow (z::\text{IRExpr})) \rangle*)
falseBelowN-nBelowLowest size64
then have $n \leq \text{numberOfTrailingZeros } (\uparrow y)$
unfolding *numberOfTrailingZeros-def*
by *simp*
have $\text{card } \{i. i < n\} = \text{bitCount } (\uparrow z)$
by (*simp add: \langle (n::nat) = bitCount } (\uparrow (z::\text{IRExpr})) \rangle*)
then have $\text{bitCount } (\uparrow z) \leq \text{numberOfTrailingZeros } (\uparrow y)$
using $\langle (n::\text{nat}) \sqsubseteq \text{numberOfTrailingZeros } (\uparrow (y::\text{IRExpr})) \rangle$ **by** *auto*
then show *?thesis* **using** *assms(1)* **by** *auto*
qed

thm-oracles *consumes*

lemma *right*:

assumes $\text{numberOfLeadingZeros } (\uparrow z) + \text{bitCount } (\uparrow z) = 64$
assumes $\uparrow z \neq 0$
assumes $\text{and } (\uparrow y) (\uparrow z) = 0$
shows $\text{exp}[(x + y) \& z] \geq \text{exp}[x \& z]$
apply *simp* **apply** (*rule allI*) +
subgoal **premises** p **for** $m \ p \ v$ **apply** (*rule impI*) **subgoal** **premises** e
proof –
obtain j **where** $j: j = \text{highestOneBit } (\uparrow z)$
by *simp*

```

obtain  $xv$   $b$  where  $xv$ :  $[m, p] \vdash x \mapsto \text{IntVal } b \text{ } xv$ 
  using  $e$ 
  by (metis EvalTreeE(5) bin-eval-inputs-are-ints bin-eval-new-int new-int.simps)
obtain  $yv$  where  $yv$ :  $[m, p] \vdash y \mapsto \text{IntVal } b \text{ } yv$ 
  using  $e$  EvalTreeE(5) bin-eval-inputs-are-ints bin-eval-new-int new-int.simps
  by (smt (verit) Value.sel(1) bin-eval.simps(1) evalDet intval-add.elims  $xv$ )
obtain  $xyv$  where  $xyv$ :  $[m, p] \vdash \text{exp}[x + y] \mapsto \text{IntVal } b \text{ } xyv$ 
  using  $e$  EvalTreeE(5) bin-eval-inputs-are-ints bin-eval-new-int new-int.simps
   $xv$   $yv$ 
  by (metis BinaryExpr Value.distinct(1) bin-eval.simps(1) intval-add.simps(1))
then obtain  $zv$  where  $zv$ :  $[m, p] \vdash z \mapsto \text{IntVal } b \text{ } zv$ 
  using  $e$  EvalTreeE(5) bin-eval-inputs-are-ints bin-eval-new-int new-int.simps
  Value.sel(1) bin-eval.simps(4) evalDet intval-and.elims
  by (smt (verit) new-int-bin.simps)
have  $xyv = \text{take-bit } b \text{ } (xv + yv)$ 
  using  $xv$   $yv$   $xyv$ 
  by (metis BinaryExprE Value.sel(2) bin-eval.simps(1) evalDet intval-add.simps(1))
then have  $v = \text{IntVal } b \text{ } (\text{take-bit } b \text{ } (\text{and } (\text{take-bit } b \text{ } (xv + yv)) \text{ } zv))$ 
  using  $zv$ 
  by (smt (verit) EvalTreeE(5) Value.sel(1) Value.sel(2) bin-eval.simps(4)  $e$ 
evalDet intval-and.elims new-int.simps new-int-bin.simps  $xyv$ )
  then have  $\text{veval}: v = \text{IntVal } b \text{ } (\text{and } (xv + yv) \text{ } zv)$ 
  by (metis (no-types, lifting) eval-unused-bits-zero take-bit-eq-mask word-bw-comms(1)
word-bw-lcs(1)  $zv$ )
  have obligation:  $(\text{and } (xv + yv) \text{ } zv) = (\text{and } xv \text{ } zv) \implies [m, p] \vdash \text{BinaryExpr}$ 
BinAnd  $x \text{ } z \mapsto v$ 
  by (smt (verit) EvalTreeE(5) Value.inject(1)  $\langle (v::\text{Value}) = \text{IntVal } (b::\text{nat})$ 
 $(\text{take-bit } b \text{ } (\text{and } (\text{take-bit } b \text{ } ((xv::64 \text{ word}) + (yv::64 \text{ word}))) \text{ } (zv::64 \text{ word}))) \rangle$ 
 $\langle (xyv::64 \text{ word}) = \text{take-bit } (b::\text{nat}) \text{ } ((xv::64 \text{ word}) + (yv::64 \text{ word})) \rangle$ 
bin-eval.simps(4)  $e$ 
evalDet eval-unused-bits-zero evaltree.simps intval-and.simps(1) take-bit-and  $xv$   $xyv$ 
 $zv$ )
  have per-bit:  $\forall n . \text{bit } (\text{and } (xv + yv) \text{ } zv) \text{ } n = \text{bit } (\text{and } xv \text{ } zv) \text{ } n \implies (\text{and } (xv +$ 
 $yv) \text{ } zv) = (\text{and } xv \text{ } zv)$ 
  by (simp add: bit-eq-iff)
show ?thesis
  apply (rule obligation)
  apply (rule per-bit)
  apply (rule allI)
  subgoal for  $n$ 
proof (cases  $n \leq j$ )
  case True

  then show ?thesis sorry

next
  case False
  then have  $\neg(\text{bit } zv \text{ } n)$ 
  by (metis  $j$  linorder-not-less not-may-implies-false zerosAboveHighestOne  $zv$ )
  then have  $v$ :  $\neg(\text{bit } (\text{and } (xv + yv) \text{ } zv) \text{ } n)$ 

```

```

    by (simp add: bit-and-iff)
  then have v':  $\neg(\text{bit } (\text{and } xv \ zv) \ n)$ 
    by (simp add:  $\langle \neg \text{bit } (zv::64 \ \text{word}) \ (n::\text{nat}) \rangle \text{ bit-and-iff}$ )
  from v v' show ?thesis
    by simp
qed
done
qed
done
done

```

end

```

lemma ucast-zero:  $(\text{ucast } (0::\text{int64})::\text{int32}) = 0$ 
  by simp

```

```

lemma ucast-minus-one:  $(\text{ucast } (-1::\text{int64})::\text{int32}) = -1$ 
  apply transfer by auto

```

```

interpretation simple-mask: stamp-mask
  IRExp-up :: IRExp  $\Rightarrow$  int64
  IRExp-down :: IRExp  $\Rightarrow$  int64
  unfolding IRExp-up-def IRExp-down-def
  apply unfold-locales
  by (simp add: ucast-minus-one)+

```

```

phase NewAnd
  terminating size
begin

```

```

optimization redundant-lhs-y-or:  $((x \mid y) \ \& \ z) \mapsto x \ \& \ z$ 
  when  $((\text{and } (\text{IRExp-up } y) (\text{IRExp-up } z)) = 0)$ 
  using simple-mask.exp-eliminate-y by blast

```

```

optimization redundant-lhs-x-or:  $((x \mid y) \ \& \ z) \mapsto y \ \& \ z$ 
  when  $((\text{and } (\text{IRExp-up } x) (\text{IRExp-up } z)) = 0)$ 
  using simple-mask.exp-eliminate-y
  by (meson exp-or-commute mono-binary order-refl order-trans)

```

```

optimization redundant-rhs-y-or:  $(z \ \& \ (x \mid y)) \mapsto z \ \& \ x$ 
  when  $((\text{and } (\text{IRExp-up } y) (\text{IRExp-up } z)) = 0)$ 
  using simple-mask.exp-eliminate-y
  by (meson exp-and-commute order.trans)

```

```

optimization redundant-rhs-x-or:  $(z \ \& \ (x \mid y)) \mapsto z \ \& \ y$ 
  when  $((\text{and } (\text{IRExp-up } x) (\text{IRExp-up } z)) = 0)$ 
  using simple-mask.exp-eliminate-y

```

by (*meson dual-order.trans exp-and-commute exp-or-commute mono-binary order-refl*)

end

end

1.8 NotNode Phase

theory *NotPhase*

imports

Common

begin

phase *NotNode*

terminating *size*

begin

lemma *bin-not-cancel*:

$\text{bin}[\neg(\neg(e))] = \text{bin}[e]$

by *auto*

lemma *val-not-cancel*:

assumes $\text{val}[\sim(\text{new-int } b \ v)] \neq \text{UndefVal}$

shows $\text{val}[\sim(\sim(\text{new-int } b \ v))] = (\text{new-int } b \ v)$

using *bin-not-cancel*

by (*simp add: take-bit-not-take-bit*)

lemma *exp-not-cancel*:

shows $\text{exp}[\sim(\sim a)] \geq \text{exp}[a]$

using *val-not-cancel* **apply** *auto*

by (*metis eval-unused-bits-zero intval-logic-negation.cases intval-not.simps(1) intval-not.simps(2) intval-not.simps(3) intval-not.simps(4) new-int.simps*)

Optimisations

optimization *NotCancel*: $\text{exp}[\sim(\sim a)] \mapsto a$

by (*metis exp-not-cancel*)

end

end

1.9 OrNode Phase

theory *OrPhase*


```

imports
  Common
begin

phase OrNode
  terminating size
begin

lemma bin-or-equal:
   $bin[x \mid x] = bin[x]$ 
  by simp

lemma bin-shift-const-right-helper:
   $x \mid y = y \mid x$ 
  by simp

lemma bin-or-not-operands:
   $(\sim x \mid \sim y) = (\sim(x \& y))$ 
  by simp

lemma val-or-equal:
  assumes  $x = new\_int\ b\ v$ 
  and  $(val[x \mid x] \neq UndefVal)$ 
  shows  $val[x \mid x] = val[x]$ 
  apply (cases  $x$ ; auto) using bin-or-equal assms
  by auto+
```

```

lemma val-elim-redundant-false:
  assumes  $x = new\_int\ b\ v$ 
  and  $val[x \mid false] \neq UndefVal$ 
  shows  $val[x \mid false] = val[x]$ 
  using assms apply (cases  $x$ ; auto) by presburger

lemma val-shift-const-right-helper:
   $val[x \mid y] = val[y \mid x]$ 
  apply (cases  $x$ ; cases  $y$ ; auto)
  by (simp add: or.commute) +

lemma val-or-not-operands:
   $val[\sim x \mid \sim y] = val[\sim(x \& y)]$ 
  apply (cases  $x$ ; cases  $y$ ; auto)
  by (simp add: take-bit-not-take-bit)

lemma exp-or-equal:
   $exp[x \mid x] \geq exp[x]$ 
  using val-or-equal apply auto
```

```

by (smt (verit, ccfv-SIG) evalDet eval-unused-bits-zero intval-negate.elims int-
val-or.simps(2)
      intval-or.simps(6) intval-or.simps(7) new-int.simps val-or-equal)

```

```

lemma exp-elim-redundant-false:
  exp[x | false] ≥ exp[x]
  using val-elim-redundant-false apply auto
  by (smt (verit) Value.sel(1) eval-unused-bits-zero intval-or.elims new-int.simps
      new-int-bin.simps val-elim-redundant-false)

```

Optimisations

```

optimization OrEqual:  $x \mid x \mapsto x$ 
  by (meson exp-or-equal le-expr-def)

```

```

optimization OrShiftConstantRight:  $((\text{const } x) \mid y) \mapsto y \mid (\text{const } x)$  when  $\neg(\text{is-ConstantExpr } y)$ 
  using size-non-const apply force
  apply auto
  by (simp add: BinaryExpr unfold-const val-shift-const-right-helper)

```

```

optimization EliminateRedundantFalse:  $x \mid \text{false} \mapsto x$ 
  by (meson exp-elim-redundant-false le-expr-def)

```

```

optimization OrNotOperands:  $(\sim x \mid \sim y) \mapsto \sim(x \ \& \ y)$ 
  defer
  apply auto using val-or-not-operands
  apply (metis BinaryExpr UnaryExpr bin-eval.simps(4) intval-not.simps(2) unary-eval.simps(3))
  sorry

```

end

```

context stamp-mask
begin

```

Taking advantage of the truth table of or operations.

#	x	y	$x y$
1	0	0	0
2	0	1	1
3	1	0	1
4	1	1	1

If row 2 never applies, that is, canBeZero x & canBeOne y = 0, then $(x|y) = x$.

Likewise, if row 3 never applies, canBeZero y & canBeOne x = 0, then $(x|y) = y$.

```

lemma OrLeftFallthrough:
  assumes (and (not ( $\downarrow x$ )) ( $\uparrow y$ )) = 0
  shows  $\text{exp}[x \mid y] \geq \text{exp}[x]$ 
  using assms
  apply simp apply ((rule allI)+; rule impI)
  subgoal premises eval for m p v
  proof –
    obtain b vv where e:  $[m, p] \vdash \text{exp}[x \mid y] \mapsto \text{IntVal } b \text{ } vv$ 
    using eval
    by (metis BinaryExprE bin-eval-new-int new-int.simps)
    from e obtain xv where xv:  $[m, p] \vdash x \mapsto \text{IntVal } b \text{ } xv$ 
    apply (subst (asm) unfold-binary-width)
    by force+
    from e obtain yv where yv:  $[m, p] \vdash y \mapsto \text{IntVal } b \text{ } yv$ 
    apply (subst (asm) unfold-binary-width)
    by force+
    have vdef:  $v = \text{intval-or } (\text{IntVal } b \text{ } xv) (\text{IntVal } b \text{ } yv)$ 
    using e xv yv
    by (metis bin-eval.simps(5) eval(2) evalDet unfold-binary)
    have  $\forall i. (\text{bit } xv \text{ } i) \mid (\text{bit } yv \text{ } i) = (\text{bit } xv \text{ } i)$ 
    by (metis assms bit-and-iff not-down-up-mask-and-zero-implies-zero xv yv)
    then have  $\text{IntVal } b \text{ } xv = \text{intval-or } (\text{IntVal } b \text{ } xv) (\text{IntVal } b \text{ } yv)$ 
    by (smt (verit, ccfv-threshold) and.idem assms bit.conj-disj-distrib eval-unused-bits-zero
intval-or.simps(1) new-int.simps new-int-bin.simps not-down-up-mask-and-zero-implies-zero
word-ao-absorbs(3) xv yv)
    then show ?thesis
    using vdef
    using xv by presburger
  qed
done

```

```

lemma OrRightFallthrough:
  assumes (and (not ( $\downarrow y$ )) ( $\uparrow x$ )) = 0
  shows  $\text{exp}[x \mid y] \geq \text{exp}[y]$ 
  using assms
  apply simp apply ((rule allI)+; rule impI)
  subgoal premises eval for m p v
  proof –
    obtain b vv where e:  $[m, p] \vdash \text{exp}[x \mid y] \mapsto \text{IntVal } b \text{ } vv$ 
    using eval
    by (metis BinaryExprE bin-eval-new-int new-int.simps)
    from e obtain xv where xv:  $[m, p] \vdash x \mapsto \text{IntVal } b \text{ } xv$ 
    apply (subst (asm) unfold-binary-width)
    by force+
    from e obtain yv where yv:  $[m, p] \vdash y \mapsto \text{IntVal } b \text{ } yv$ 
    apply (subst (asm) unfold-binary-width)
    by force+
    have vdef:  $v = \text{intval-or } (\text{IntVal } b \text{ } xv) (\text{IntVal } b \text{ } yv)$ 
    using e xv yv

```

```

    by (metis bin-eval.simps(5) eval(2) evalDet unfold-binary)
  have  $\forall i. (\text{bit } xv \ i) \mid (\text{bit } yv \ i) = (\text{bit } yv \ i)$ 
    by (metis assms bit-and-iff not-down-up-mask-and-zero-implies-zero xv yv)
  then have  $\text{IntVal } b \ yv = \text{intval-or } (\text{IntVal } b \ xv) (\text{IntVal } b \ yv)$ 
    by (metis (no-types, lifting) assms eval-unused-bits-zero intval-or.simps(1)
    new-int.elims new-int-bin.elims stamp-mask.not-down-up-mask-and-zero-implies-zero
    stamp-mask-axioms word-ao-absorbs(8) xv yv)
  then show ?thesis
    using vdef
    using yv by presburger
qed
done

end

end

```

1.10 ShiftNode Phase

```

theory ShiftPhase
  imports
    Common
begin

phase ShiftNode
  terminating size
begin

fun intval-log2 :: Value  $\Rightarrow$  Value where
  intval-log2 (IntVal b v) = IntVal b (word-of-int (SOME e. v=2e)) |
  intval-log2 - = UndefVal

fun in-bounds :: Value  $\Rightarrow$  int  $\Rightarrow$  int  $\Rightarrow$  bool where
  in-bounds (IntVal b v) l h = (l < sint v  $\wedge$  sint v < h) |
  in-bounds - l h = False

lemma
  assumes in-bounds (intval-log2 val-c) 0 32
  shows intval-left-shift x (intval-log2 val-c) = intval-mul x val-c
  apply (cases val-c; auto) using intval-left-shift.simps(1) intval-mul.simps(1)
  intval-log2.simps(1)
  sorry

lemma e-intval:
  n = intval-log2 val-c  $\wedge$  in-bounds n 0 32  $\longrightarrow$ 
  intval-left-shift x (intval-log2 val-c) =
  intval-mul x val-c
proof (rule impI)
  assume n = intval-log2 val-c  $\wedge$  in-bounds n 0 32

```

```

show intval-left-shift x (intval-log2 val-c) =
intval-mul x val-c
proof (cases  $\exists v . val-c = IntVal\ 32\ v$ )
  case True
    obtain vc where val-c = IntVal 32 vc
    using True by blast
    then have n = IntVal 32 (word-of-int (SOME e. vc=2e))
    using  $\langle n = intval-log2\ val-c \wedge in-bounds\ n\ 0\ 32 \rangle\ intval-log2.simps(1)$  by
presburger
    then show ?thesis sorry
  next
    case False
    then have  $\exists v . val-c = IntVal\ 64\ v$ 
    sorry
    then obtain vc where val-c = IntVal 64 vc
    by auto
    then have n = IntVal 64 (word-of-int (SOME e. vc=2e))
    using  $\langle n = intval-log2\ val-c \wedge in-bounds\ n\ 0\ 32 \rangle\ intval-log2.simps(1)$  by
presburger
    then show ?thesis sorry
qed
qed

```

```

optimization e:
   $x * (const\ c) \mapsto x << (const\ n)\ when\ (n = intval-log2\ c \wedge in-bounds\ n\ 0\ 32)$ 
  using e-intval
  using BinaryExprE ConstantExprE bin-eval.simps(2,7) sorry

end

end

```

1.11 SignedDivNode Phase

```

theory SignedDivPhase
  imports
    Common
  begin

  phase SignedDivNode
    terminating size
  begin

```

```

lemma val-division-by-one-is-self-32:
  assumes x = new-int 32 v
  shows intval-div x (IntVal 32 1) = x

```

```

using assms apply (cases x; auto)
by (simp add: take-bit-signed-take-bit)

end

end



### 1.12 SignedRemNode Phase

theory SignedRemPhase
  imports
    Common
begin

phase SignedRemNode
  terminating size
begin

lemma val-remainder-one:
  assumes intval-mod x (IntVal 32 1) ≠ UndefVal
  shows intval-mod x (IntVal 32 1) = IntVal 32 0
  using assms apply (cases x; auto) sorry

value word-of-int (sint (x2::32 word) smod 1)

end

end



### 1.13 SubNode Phase

theory SubPhase
  imports
    Common
begin

phase SubNode
  terminating size
begin

lemma bin-sub-after-right-add:
  shows  $((x::('a::len) \text{ word}) + (y::('a::len) \text{ word})) - y = x$ 
  by simp

lemma sub-self-is-zero:

```

```

shows (x::('a::len) word) - x = 0
by simp

lemma bin-sub-then-left-add:
  shows (x::('a::len) word) - (x + (y::('a::len) word)) = -y
  by simp

lemma bin-sub-then-left-sub:
  shows (x::('a::len) word) - (x - (y::('a::len) word)) = y
  by simp

lemma bin-subtract-zero:
  shows (x :: 'a::len word) - (0 :: 'a::len word) = x
  by simp

lemma bin-sub-negative-value:
  (x :: ('a::len) word) - (-(y :: ('a::len) word)) = x + y
  by simp

lemma bin-sub-self-is-zero:
  (x :: ('a::len) word) - x = 0
  by simp

lemma bin-sub-negative-const:
  (x :: 'a::len word) - (-(y :: 'a::len word)) = x + y
  by simp

lemma val-sub-after-right-add-2:
  assumes x = new-int b v
  assumes val[(x + y) - y] ≠ UndefVal
  shows val[(x + y) - y] = val[x]
  using bin-sub-after-right-add
  using assms apply (cases x; cases y; auto)
  by (metis (full-types) intval-sub.simps(2))

lemma val-sub-after-left-sub:
  assumes val[(x - y) - x] ≠ UndefVal
  shows val[(x - y) - x] = val[-y]
  using assms apply (cases x; cases y; auto)
  using intval-sub.elims by fastforce

lemma val-sub-then-left-sub:
  assumes y = new-int b v
  assumes val[x - (x - y)] ≠ UndefVal
  shows val[x - (x - y)] = val[y]
  using assms apply (cases x; cases y; auto)
  by (metis (mono-tags) intval-sub.simps(5))

```

lemma *val-subtract-zero*:
assumes $x = \text{new-int } b \ v$
assumes $\text{intval-sub } x \ (\text{IntVal } b \ 0) \neq \text{UndefVal}$
shows $\text{intval-sub } x \ (\text{IntVal } b \ 0) = \text{val}[x]$
using *assms* **by** (*induction* x ; *simp*)

lemma *val-zero-subtract-value*:
assumes $x = \text{new-int } b \ v$
assumes $\text{intval-sub } (\text{IntVal } b \ 0) \ x \neq \text{UndefVal}$
shows $\text{intval-sub } (\text{IntVal } b \ 0) \ x = \text{val}[-x]$
using *assms* **by** (*induction* x ; *simp*)

lemma *val-sub-then-left-add*:
assumes $\text{val}[x - (x + y)] \neq \text{UndefVal}$
shows $\text{val}[x - (x + y)] = \text{val}[-y]$
using *assms* **apply** (*cases* x ; *cases* y ; *auto*)
by (*metis* (*mono-tags*, *lifting*) *intval-sub.simps*(5))

lemma *val-sub-negative-value*:
assumes $\text{val}[x - (-y)] \neq \text{UndefVal}$
shows $\text{val}[x - (-y)] = \text{val}[x + y]$
using *assms* **by** (*cases* x ; *cases* y ; *auto*)

lemma *val-sub-self-is-zero*:
assumes $x = \text{new-int } b \ v \wedge \text{val}[x - x] \neq \text{UndefVal}$
shows $\text{val}[x - x] = \text{new-int } b \ 0$
using *assms* **by** (*cases* x ; *auto*)

lemma *val-sub-negative-const*:
assumes $y = \text{new-int } b \ v \wedge \text{val}[x - (-y)] \neq \text{UndefVal}$
shows $\text{val}[x - (-y)] = \text{val}[x + y]$
using *assms* **by** (*cases* x ; *cases* y ; *auto*)

lemma *exp-sub-after-right-add*:
shows $\text{exp}[(x + y) - y] \geq \text{exp}[x]$
apply *auto* **using** *val-sub-after-right-add-2*
using *evalDet eval-unused-bits-zero intval-add.elims new-int.simps*
by (*smt* (*verit*))

lemma *exp-sub-after-right-add2*:
shows $\text{exp}[(x + y) - x] \geq \text{exp}[y]$
using *exp-sub-after-right-add* **apply** *auto*
using *bin-eval.simps*(1) *bin-eval.simps*(3) *intval-add-sym* *unfold-binary*
by (*smt* (*z3*) *Value.inject*(1) *diff-eq-eq evalDet eval-unused-bits-zero intval-add.elims*
 $\text{intval-sub.elims new-int.simps new-int-bin.simps take-bit-dist-subL}$)

lemma *exp-sub-negative-value*:


```

exp[x - (-y)] ≥ exp[x + y]
apply simp using val-sub-negative-value
by (smt (verit) bin-eval.simps(1) bin-eval.simps(3) evaltree-not-undef
    unary-eval.simps(2) unfold-binary unfold-unary)

```

definition *wf-stamp* :: *IRExpr* ⇒ *bool* **where**
wf-stamp e = (∀ m p v. ([m, p] ⊢ e ↦ v) ⟶ valid-value v (stamp-expr e))

lemma *exp-sub-then-left-sub*:
assumes *wf-stamp* x ∧ *stamp-expr* x = *IntegerStamp* b lo hi
shows exp[x - (x - y)] ≥ exp[y]
using val-sub-then-left-sub *assms* **apply** auto
subgoal **premises** p **for** m p xa xaa ya
proof –
obtain xa **where** xa: [m, p] ⊢ x ↦ xa
using p(4) **by** blast
obtain ya **where** ya: [m, p] ⊢ y ↦ ya
using p(7) **by** auto
obtain xaa **where** xaa: [m, p] ⊢ x ↦ xaa
using p(4) **by** blast
have 1: val[xa - (xaa - ya)] ≠ *UndefVal*
by (metis evalDet p(4) p(5) p(6) p(7) xa xaa ya)
then have val[xaa - ya] ≠ *UndefVal*
by auto
then have [m,p] ⊢ y ↦ val[xa - (xaa - ya)]
by (smt (verit) 1 evalDet eval-unused-bits-zero intval-sub.elims new-int-bin.simps
p(1) p(7) xa xaa ya)
then show ?thesis
by (metis evalDet p(4) p(6) p(7) xa xaa ya)
qed
done

Optimisations

optimization *SubAfterAddRight*: ((x + y) - y) ⟶ x
using exp-sub-after-right-add **by** blast

optimization *SubAfterAddLeft*: ((x + y) - x) ⟶ y
using exp-sub-after-right-add2 **by** blast

optimization *SubAfterSubLeft*: ((x - y) - x) ⟶ -y
apply auto
by (metis evalDet unary-eval.simps(2) unfold-unary val-sub-after-left-sub)

optimization *SubThenAddLeft*: (x - (x + y)) ⟶ -y
apply auto
by (metis evalDet unary-eval.simps(2) unfold-unary)

val-sub-then-left-add)

optimization *SubThenAddRight*: $(y - (x + y)) \mapsto -x$

apply *auto*

by (*metis evalDet intval-add-sym unary-eval.simps(2) unfold-unary
val-sub-then-left-add*)

optimization *SubThenSubLeft*: $(x - (x - y)) \mapsto y$

when (wf-stamp x ∧ stamp-expr x = IntegerStamp b lo hi)

using *exp-sub-then-left-sub* **by** *blast*

optimization *SubtractZero*: $(x - (\text{const IntVal } b \ 0)) \mapsto x$

when (wf-stamp x ∧ stamp-expr x = IntegerStamp b lo hi)

apply *auto*

by (*smt (verit) add.right-neutral diff-add-cancel eval-unused-bits-zero intval-sub.elims*

intval-word.simps new-int.simps new-int-bin.simps)

optimization *SubNegativeValue*: $(x - (-y)) \mapsto x + y$

using *exp-sub-negative-value* **by** *simp*

thm-oracles *SubNegativeValue*

optimization *SubNegativeConstant*: $x - (\text{const (intval-negate } y)) \mapsto x + (\text{const } y)$

defer

apply *auto sorry*

optimization *ZeroSubtractValue*: $((\text{const IntVal } b \ 0) - x) \mapsto (-x)$

when (wf-stamp x ∧ stamp-expr x = IntegerStamp b lo

hi)

apply *auto unfolding wf-stamp-def*

by (*smt (verit) diff-0 intval-negate.simps(1) intval-sub.elims intval-word.simps
new-int-bin.simps unary-eval.simps(2) unfold-unary*)

fun *forPrimitive* :: *Stamp* \Rightarrow *int64* \Rightarrow *IRExpr* **where**

forPrimitive (IntegerStamp b lo hi) v = ConstantExpr (if take-bit b v = v then
(IntVal b v) else UndefVal) |

forPrimitive - - = ConstantExpr UndefVal

lemma *unfold-forPrimitive*:

forPrimitive s v = ConstantExpr (if is-IntegerStamp s ∧ take-bit (stp-bits s) v =
v then (IntVal (stp-bits s) v) else UndefVal)

by (*cases s; auto*)

lemma *forPrimitive-size*[*size-simps*]: *size (forPrimitive s v) = 1*
by (*cases s*; *auto*)

lemma *forPrimitive-eval*:

assumes *s = IntegerStamp b lo hi*
assumes *take-bit b v = v*
shows $[m, p] \vdash \text{forPrimitive } s \ v \mapsto (\text{IntVal } b \ v)$
unfolding *unfold-forPrimitive* **using** *assms* **apply** *auto*
apply (*rule evaltree.ConstantExpr*)
sorry

lemma *evalSubStamp*:

assumes $[m, p] \vdash \text{exp}[x - y] \mapsto v$
assumes *wf-stamp exp[x - y]*
shows $\exists b \ lo \ hi. \text{stamp-expr exp}[x - y] = \text{IntegerStamp } b \ lo \ hi$
proof –
have *valid-value v (stamp-expr exp[x - y])*
using *assms* **unfolding** *wf-stamp-def* **by** *auto*
then have *stamp-expr exp[x - y] \neq IllegalStamp*
by *force*
then show *?thesis*
unfolding *stamp-expr.simps* **using** *stamp-binary.simps*
by (*smt (z3) stamp-binary.elims unrestricted-stamp.simps(2)*)
qed

lemma *evalSubArgsStamp*:

assumes $[m, p] \vdash \text{exp}[x - y] \mapsto v$
assumes $\exists lo \ hi. \text{stamp-expr exp}[x - y] = \text{IntegerStamp } b \ lo \ hi$
shows $\exists lo \ hi. \text{stamp-expr exp}[x] = \text{IntegerStamp } b \ lo \ hi$
using *assms* **sorry**

optimization *SubSelfIsZero*: $(x - x) \mapsto \text{forPrimitive (stamp-expr exp}[x - x]) \ 0$
when ((wf-stamp x) \wedge (wf-stamp exp[x - x]))

apply (*simp add: Suc-lessI size-pos*)
apply *simp* **apply** (*rule impI*; (*rule allI*) $+$; *rule impI*)
subgoal premises *eval* **for** *m p v*
proof –
obtain *b* **where** $\exists lo \ hi. \text{stamp-expr exp}[x - x] = \text{IntegerStamp } b \ lo \ hi$
using *evalSubStamp eval*
by *meson*
then show *?thesis* **sorry**
qed
done

end

end

1.14 XorNode Phase

theory *XorPhase*

imports

Common

Proofs.StampEvalThms

begin

phase *XorNode*

terminating *size*

begin

lemma *bin-xor-self-is-false*:

$\text{bin}[x \oplus x] = 0$

by *simp*

lemma *bin-xor-commute*:

$\text{bin}[x \oplus y] = \text{bin}[y \oplus x]$

by (*simp add: xor.commute*)

lemma *bin-eliminate-redundant-false*:

$\text{bin}[x \oplus 0] = \text{bin}[x]$

by *simp*

lemma *val-xor-self-is-false*:

assumes $\text{val}[x \oplus x] \neq \text{UndefVal}$

shows $\text{val-to-bool}(\text{val}[x \oplus x]) = \text{False}$

using *assms* **by** (*cases x; auto*)

lemma *val-xor-self-is-false-2*:

assumes $(\text{val}[x \oplus x]) \neq \text{UndefVal}$

and $x = \text{IntVal } 32 \ v$

shows $\text{val}[x \oplus x] = \text{bool-to-val False}$

using *assms* **by** (*cases x; auto*)

lemma *val-xor-self-is-false-3*:

assumes $\text{val}[x \oplus x] \neq \text{UndefVal} \wedge x = \text{IntVal } 64 \ v$

shows $\text{val}[x \oplus x] = \text{IntVal } 64 \ 0$

using *assms* **by** (*cases x; auto*)

lemma *val-xor-commute*:

$\text{val}[x \oplus y] = \text{val}[y \oplus x]$

apply (*cases x; cases y; auto*)

```

by (simp add: xor.commute)+

lemma val-eliminate-redundant-false:
  assumes  $x = \text{new-int } b \ v$ 
  assumes  $\text{val}[x \oplus (\text{bool-to-val } \text{False})] \neq \text{UndefVal}$ 
  shows  $\text{val}[x \oplus (\text{bool-to-val } \text{False})] = x$ 
  using assms apply (cases x; auto)
  by meson

lemma exp-xor-self-is-false:
  assumes  $\text{wf-stamp } x \wedge \text{stamp-expr } x = \text{default-stamp}$ 
  shows  $\text{exp}[x \oplus x] \geq \text{exp}[\text{false}]$ 
  using assms apply auto unfolding wf-stamp-def
  using IntVal0 Value.inject(1) bool-to-val.simps(2) constantAsStamp.simps(1)
  evalDet
  int-signed-value-bounds new-int.simps unfold-const val-xor-self-is-false-2
  valid-int
  valid-stamp.simps(1) valid-value.simps(1)
  by (smt (z3) validDefIntConst)

lemma exp-eliminate-redundant-false:
  shows  $\text{exp}[x \oplus \text{false}] \geq \text{exp}[x]$ 
  using val-eliminate-redundant-false apply auto
  subgoal premises p for m p xa
  proof -
    obtain xa where  $xa: [m, p] \vdash x \mapsto xa$ 
    using p(2) by blast
    then have  $\text{val}[xa \oplus (\text{IntVal } 32 \ 0)] \neq \text{UndefVal}$ 
    using evalDet p(2) p(3) by blast
    then have  $[m, p] \vdash x \mapsto \text{val}[xa \oplus (\text{IntVal } 32 \ 0)]$ 
    apply (cases xa; auto) using eval-unused-bits-zero xa by auto
    then show ?thesis
    using evalDet p(2) xa by blast
  qed
done

Optimisations

optimization XorSelfIsFalse:  $(x \oplus x) \mapsto \text{false}$  when
   $(\text{wf-stamp } x \wedge \text{stamp-expr } x = \text{default-stamp})$ 
  apply (metis One-nat-def Suc-lessI eval-nat-numeral(3) less-Suc-eq mult.right-neutral

  numeral-2-eq-2 one-less-mult size-pos)
  using exp-xor-self-is-false by auto

optimization XorShiftConstantRight:  $((\text{const } x) \oplus y) \mapsto y \oplus (\text{const } x)$  when
 $\neg(\text{is-ConstantExpr } y)$ 
  unfolding le-expr-def using val-xor-commute size-non-const
  apply simp apply auto

```

```

    using val-xor-commute by auto

optimization EliminateRedundantFalse:  $(x \oplus \text{false}) \mapsto x$ 
    using exp-eliminate-redundant-false by blast

```

```

end

```

```

end

```

1.15 NegateNode Phase

```

theory NegatePhase
  imports
    Common
begin

  phase NegateNode
    terminating size
begin

```

```

lemma bin-negative-cancel:
   $-1 * (-1 * ((x::('a::len) \text{word}))) = x$ 
  by auto

```

```

lemma val-negative-cancel:
  assumes intval-negate (new-int b v)  $\neq \text{UndefVal}$ 
  shows  $\text{val}[-(-(\text{new-int } b \ v))] = \text{val}[\text{new-int } b \ v]$ 
  using assms by simp

```

```

lemma val-distribute-sub:
  assumes  $x \neq \text{UndefVal} \wedge y \neq \text{UndefVal}$ 
  shows  $\text{val}[-(x - y)] = \text{val}[y - x]$ 
  using assms by (cases x; cases y; auto)

```

```

lemma exp-distribute-sub:
  shows  $\text{exp}[-(x - y)] \geq \text{exp}[y - x]$ 
  using val-distribute-sub apply auto
  using evaltree-not-undef by auto

```

```

thm-oracles exp-distribute-sub

```

```

lemma exp-negative-cancel:

```

```

shows  $\exp[-(-x)] \geq \exp[x]$ 
using val-negative-cancel apply auto
by (metis (no-types, opaque-lifting) eval-unused-bits-zero intval-negate.elims
      intval-negate.simps(1) minus-equation-iff new-int.simps take-bit-dist-neg)

lemma exp-negative-shift:
  assumes stamp-expr  $x = \text{IntegerStamp } b' \text{ lo hi}$ 
  and  $\text{unat } y = (b' - 1)$ 
  shows  $\exp[-(x >> (\text{const } (\text{new-int } b \ y)))] \geq \exp[x >>> (\text{const } (\text{new-int } b \ y))]$ 
  apply auto
  subgoal premises  $p$  for  $m \ p \ x a$ 
  proof –
    obtain  $x a$  where  $x a: [m, p] \vdash x \mapsto x a$ 
    using  $p(2)$  by auto
    then have 1:  $\text{intval-negate } (\text{intval-right-shift } x a \ (\text{IntVal } b \ (\text{take-bit } b \ y))) \neq$ 
      UndefVal
    using evalDet  $p(1) \ p(2)$  by blast
    then have 2:  $\text{intval-right-shift } x a \ (\text{IntVal } b \ (\text{take-bit } b \ y)) \neq \text{UndefVal}$ 
    by auto
    then have 3:  $-( (2::\text{int}) \wedge b \text{ div } (2::\text{int})) \sqsubseteq \text{sint } (\text{signed-take-bit } (b - \text{Suc } (0::\text{nat})) \ (\text{take-bit } b \ y))$ 
    by (simp add:  $p(6)$ )
    then have 4:  $\text{sint } (\text{signed-take-bit } (b - \text{Suc } (0::\text{nat})) \ (\text{take-bit } b \ y)) < (2::\text{int})$ 
       $\wedge b \text{ div } (2::\text{int})$ 
    using  $p(7)$  by blast
    then have 5:  $(0::\text{nat}) < b$ 
    by (simp add:  $p(4)$ )
    then have 6:  $b \sqsubseteq (64::\text{nat})$ 
    by (simp add:  $p(5)$ )
    then have 7:  $[m, p] \vdash \text{BinaryExpr BinURightShift } x$ 
       $(\text{ConstantExpr } (\text{IntVal } b \ (\text{take-bit } b \ y))) \mapsto$ 
       $\text{intval-negate } (\text{intval-right-shift } x a \ (\text{IntVal } b \ (\text{take-bit } b \ y)))$ 
    apply (cases  $y$ ; auto)

  subgoal premises  $p$  for  $n$ 
  proof –
    have  $sg1: y = \text{word-of-nat } n$ 
    by (simp add:  $p(1)$ )
    then have  $sg2: n < (18446744073709551616::\text{nat})$ 
    by (simp add:  $p(2)$ )
    then have  $sg3: b \sqsubseteq (64::\text{nat})$ 
    by (simp add: 6)
    then have  $sg4: [m, p] \vdash \text{BinaryExpr BinURightShift } x$ 
       $(\text{ConstantExpr } (\text{IntVal } b \ (\text{take-bit } b \ (\text{word-of-nat } n)))) \mapsto$ 
       $\text{intval-negate } (\text{intval-right-shift } x a \ (\text{IntVal } b \ (\text{take-bit } b \ (\text{word-of-nat } n))))$ 
    sorry
    then show ?thesis
    by simp

```

```

      qed
    done
  then show ?thesis
  by (metis evalDet p(2) xa)
qed
done

Optimisations

optimization NegateCancel:  $-( -(x) ) \mapsto x$ 
  using val-negative-cancel exp-negative-cancel by blast

optimization DistributeSubtraction:  $-(x - y) \mapsto (y - x)$ 
  using exp-distribute-sub by simp

optimization NegativeShift:  $-(x >> (\text{const } (\text{new-int } b \ y))) \mapsto x >>> (\text{const } (\text{new-int } b \ y))$ 
  when (stamp-expr  $x = \text{IntegerStamp } b' \text{ lo hi} \wedge \text{unat } y = (b' - 1)$ )
  using exp-negative-shift by simp

end

end

theory TacticSolving
  imports Common
begin

fun size :: IRExpr  $\Rightarrow$  nat where
  size (UnaryExpr op e) = (size e) * 2 |
  size (BinaryExpr BinAdd x y) = (size x) + ((size y) * 2) |
  size (BinaryExpr op x y) = (size x) + (size y) |
  size (ConditionalExpr cond t f) = (size cond) + (size t) + (size f) + 2 |
  size (ConstantExpr c) = 1 |
  size (ParameterExpr ind s) = 2 |
  size (LeafExpr nid s) = 2 |
  size (ConstantVar c) = 2 |
  size (VariableExpr x s) = 2

lemma size-pos[simp]:  $0 < \text{size } y$ 
  apply (induction y; auto?)
  subgoal premises prems for op a b
    using prems by (induction op; auto)
  done

phase TacticSolving
  terminating size

```


begin

1.16 AddNode

lemma *value-approx-implies-refinement*:

assumes $lhs \approx rhs$
assumes $\forall m\ p\ v. ([m, p] \vdash elhs \mapsto v) \longrightarrow v = lhs$
assumes $\forall m\ p\ v. ([m, p] \vdash erhs \mapsto v) \longrightarrow v = rhs$
assumes $\forall m\ p\ v1\ v2. ([m, p] \vdash elhs \mapsto v1) \longrightarrow ([m, p] \vdash erhs \mapsto v2)$
shows $elhs \geq erhs$
using *assms unfolding le-expr-def well-formed-equal-def*
using *evalDet evaltree-not-undef*
by *metis*

method *explore-cases* **for** $x\ y :: Value =$
(cases x; cases y; auto)

method *explore-cases-bin* **for** $x :: IRExpr =$
(cases x; auto)

method *obtain-approx-eq* **for** $lhs\ rhs\ x\ y :: Value =$
*(rule meta-mp[**where** $P = lhs \approx rhs$], defer-tac, explore-cases x y)*

method *obtain-eval* **for** $exp :: IRExpr$ **and** $val :: Value =$
*(rule meta-mp[**where** $P = \bigwedge m\ p\ v. ([m, p] \vdash exp \mapsto v) \implies v = val$], defer-tac)*

method *solve* **for** $lhs\ rhs\ x\ y :: Value =$
*(match **conclusion** in size - < size - \Rightarrow $\langle simp \rangle$)?,*
*(match **conclusion** in $(elhs :: IRExpr) \geq (erhs :: IRExpr)$ **for** $elhs\ erhs \Rightarrow$ \langle*
(obtain-approx-eq lhs rhs x y) \rangle ?)

print-methods

thm *BinaryExprE*

optimization *opt-add-left-negate-to-sub*:

$-x + y \mapsto y - x$

apply *(solve val[-x1 + y1] val[y1 - x1] x1 y1)*
apply *simp apply auto using evaltree-not-undef sorry*

1.17 NegateNode

lemma *val-distribute-sub*:

$val[-(x-y)] \approx val[y-x]$
by *(cases x; cases y; auto)*

optimization *distribute-sub*: $-(x-y) \mapsto (y-x)$

apply *simp*
using *val-distribute-sub apply simp*

```

using unfold-binary unfold-unary by auto

lemma val-xor-self-is-false:
  assumes  $x = \text{IntVal } 32 \ v$ 
  shows  $\text{val}[x \oplus x] \approx \text{val}[\text{false}]$ 
  apply simp using assms by (cases  $x$ ; auto)

definition wf-stamp ::  $\text{IRExpr} \Rightarrow \text{bool}$  where
  wf-stamp  $e = (\forall m \ p \ v. ([m, p] \vdash e \mapsto v) \longrightarrow \text{valid-value } v \ (\text{stamp-expr } e))$ 

lemma exp-xor-self-is-false:
  assumes  $\text{stamp-expr } x = \text{IntegerStamp } 32 \ l \ h$ 
  assumes wf-stamp  $x$ 
  shows  $\text{exp}[x \oplus x] \geq \text{exp}[\text{false}]$ 
  unfolding le-expr-def using assms unfolding wf-stamp-def
  using val-xor-self-is-false evaltree-not-undef
  by (smt (z3) bin-eval.simps(6) bin-eval-new-int constantAsStamp.simps(1) evalDet
int-signed-value-bounds new-int.simps new-int-take-bits unfold-binary unfold-const
valid-int valid-stamp.simps(1) valid-value.simps(1) well-formed-equal-defn)

lemma val-or-commute[simp]:
   $\text{val}[x \mid y] = \text{val}[y \mid x]$ 
  apply (cases  $x$ ; cases  $y$ ; auto)
  by (simp add: or.commute)+

lemma val-xor-commute[simp]:
   $\text{val}[x \oplus y] = \text{val}[y \oplus x]$ 
  apply (cases  $x$ ; cases  $y$ ; auto)
  by (simp add: word-bw-comms(3))

lemma exp-or-commutative:
   $\text{exp}[x \mid y] \geq \text{exp}[y \mid x]$ 
  by auto

lemma exp-xor-commutative:
   $\text{exp}[x \oplus y] \geq \text{exp}[y \oplus x]$ 
  by auto

lemma OrInverseVal:
  assumes  $n = \text{IntVal } 32 \ v$ 
  shows  $\text{val}[n \mid \sim n] \approx \text{new-int } 32 \ (-1)$ 
  apply simp using assms using word-or-not apply (cases  $n$ ; auto) using take-bit-or
  by (metis bit.disj-cancel-right mask-eq-take-bit-minus-one)

optimization OrInverse:  $\text{exp}[n \mid \sim n] \mapsto (\text{const } (\text{new-int } 32 \ (\text{not } 0)))$ 
  when (stamp-expr  $n = \text{IntegerStamp } 32 \ l \ h \wedge \text{wf-stamp } n$ )

```

```

unfolding size.simps apply (simp add: Suc-lessI)
apply auto using OrInverseVal unfolding wf-stamp-def
by (smt (z3) constantAsStamp.simps(1) evalDet int-signed-value-bounds mask-eq-take-bit-minus-one

    new-int.elims new-int-take-bits unfold-const valid-int valid-stamp.simps(1)
    valid-value.simps(1) well-formed-equal-defn)

optimization OrInverse2:  $\text{exp}[\sim n \mid n] \mapsto (\text{const } (\text{new-int } 32 \text{ (not } 0)))$ 
    when (stamp-expr n = IntegerStamp 32 l h  $\wedge$  wf-stamp n)
using OrInverse apply simp
using OrInverse exp-or-commutative
by auto

lemma XorInverseVal:
  assumes n = IntVal 32 v
  shows val[n  $\oplus$   $\sim$ n]  $\approx$  new-int 32 (-1)
  apply simp using assms using word-or-not apply (cases n; auto)
  by (metis (no-types, opaque-lifting) bit.compl-zero bit.xor-compl-right bit.xor-self

    mask-eq-take-bit-minus-one take-bit-xor)

optimization XorInverse:  $\text{exp}[n \oplus \sim n] \mapsto (\text{const } (\text{new-int } 32 \text{ (not } 0)))$ 
    when (stamp-expr n = IntegerStamp 32 l h  $\wedge$  wf-stamp n)
unfolding size.simps apply (simp add: Suc-lessI)
apply auto using XorInverseVal
by (smt (verit) constantAsStamp.simps(1) evalDet int-signed-value-bounds int-
val-xor.elims

    mask-eq-take-bit-minus-one new-int.elims new-int-take-bits unfold-const valid-stamp.simps(1)

    valid-value.simps(1) well-formed-equal-defn wf-stamp-def)

optimization XorInverse2:  $\text{exp}[(\sim n) \oplus n] \mapsto (\text{const } (\text{new-int } 32 \text{ (not } 0)))$ 
    when (stamp-expr n = IntegerStamp 32 l h  $\wedge$  wf-stamp n)
using XorInverse apply simp
using XorInverse exp-xor-commutative
by simp

end

end
theory ProofStatus
imports
  AbsPhase
  AddPhase
  AndPhase
  ConditionalPhase
  MulPhase

```

```

    NegatePhase
    NewAnd
    NotPhase
    OrPhase
    ShiftPhase
    SignedDivPhase
    SignedRemPhase
    SubPhase
    TacticSolving
    XorPhase
begin

declare [[show-types=false]]
print-phases
print-phases!

print-methods

print-theorems

thm opt-add-left-negate-to-sub
thm-oracles AbsNegate

export-phases ‹Full›

end

```