

Veriopt Theories

September 22, 2022

Contents

1	Canonicalization Optimizations	1
1.1	AbsNode Phase	3
1.2	AddNode Phase	8
1.3	AndNode Phase	11
1.4	BinaryNode Phase	15
1.5	ConditionalNode Phase	16
1.6	MulNode Phase	19
1.7	Experimental AndNode Phase	28
1.8	NotNode Phase	42
1.9	OrNode Phase	42
1.10	ShiftNode Phase	46
1.11	SignedDivNode Phase	47
1.12	SignedRemNode Phase	48
1.13	SubNode Phase	48
1.14	XorNode Phase	53
1.15	NegateNode Phase	55
1.16	AddNode	58
1.17	NegateNode	58

1 Canonicalization Optimizations

```
theory Common
imports
  OptimizationDSL.Canonicalization
  Semantics.IRTreeEvalThms
begin

lemma size-pos[size-simps]: 0 < size y
apply (induction y; auto?)
by (smt (z3) add-2-eq-Suc' add-is-0 not-gr0 size.elims size.simps(12) size.simps(13)
size.simps(14) size.simps(15) zero-neq-numeral zero-neq-one)
```

lemma *size-non-add*[*size-simps*]: $\text{size } (\text{BinaryExpr op } a \ b) = \text{size } a + \text{size } b + 2$
 $\longleftrightarrow \neg(\text{is-ConstantExpr } b)$

by (*induction b*; *induction op*; *auto simp: is-ConstantExpr-def*)

lemma *size-non-const*[*size-simps*]:

$\neg \text{is-ConstantExpr } y \implies 1 < \text{size } y$

using *size-pos* **apply** (*induction y*; *auto*)

by (*metis Suc-lessI add-is-1 is-ConstantExpr-def le-less linorder-not-le n-not-Suc-n numeral-2-eq-2 pos2 size.simps(2) size-non-add*)

lemma *size-binary-const*[*size-simps*]:

$\text{size } (\text{BinaryExpr op } a \ b) = \text{size } a + 2 \longleftrightarrow (\text{is-ConstantExpr } b)$

by (*induction b*; *auto simp: is-ConstantExpr-def size-pos*)

lemma *size-flip-binary*[*size-simps*]:

$\neg(\text{is-ConstantExpr } y) \longrightarrow \text{size } (\text{BinaryExpr op } (\text{ConstantExpr } x) \ y) > \text{size } (\text{BinaryExpr op } y \ (\text{ConstantExpr } x))$

by (*metis add-Suc not-less-eq order-less-asm plus-1-eq-Suc size.simps(11) size.simps(2) size-non-add*)

lemma *size-binary-lhs-a*[*size-simps*]:

$\text{size } (\text{BinaryExpr op } (\text{BinaryExpr op}' a \ b) \ c) > \text{size } a$

by (*metis add-lessD1 less-add-same-cancel1 pos2 size-binary-const size-non-add*)

lemma *size-binary-lhs-b*[*size-simps*]:

$\text{size } (\text{BinaryExpr op } (\text{BinaryExpr op}' a \ b) \ c) > \text{size } b$

by (*metis IRExpr.disc(42) One-nat-def add.left-commute add.right-neutral is-ConstantExpr-def less-add-Suc2 numeral-2-eq-2 plus-1-eq-Suc size.simps(11) size-binary-const size-non-add size-non-const trans-less-add1*)

lemma *size-binary-lhs-c*[*size-simps*]:

$\text{size } (\text{BinaryExpr op } (\text{BinaryExpr op}' a \ b) \ c) > \text{size } c$

by (*metis IRExpr.disc(42) add.left-commute add.right-neutral is-ConstantExpr-def less-Suc-eq numeral-2-eq-2 plus-1-eq-Suc size.simps(11) size-non-add size-non-const trans-less-add2*)

lemma *size-binary-rhs-a*[*size-simps*]:

$\text{size } (\text{BinaryExpr op } c \ (\text{BinaryExpr op}' a \ b)) > \text{size } a$

by (*smt (verit, best) less-Suc-eq less-add-Suc2 less-add-same-cancel1 linorder-neqE-nat not-add-less1 order-less-trans pos2 size.simps(4) size-binary-const size-non-add*)

lemma *size-binary-rhs-b*[*size-simps*]:

$\text{size } (\text{BinaryExpr op } c \ (\text{BinaryExpr op}' a \ b)) > \text{size } b$

by (*metis add.left-commute add.right-neutral is-ConstantExpr-def lessI numeral-2-eq-2 plus-1-eq-Suc size.simps(11) size.simps(4) size-non-add trans-less-add2*)

lemma *size-binary-rhs-c*[*size-simps*]:

$\text{size } (\text{BinaryExpr op } c \ (\text{BinaryExpr op}' a \ b)) > \text{size } c$

```

by simp

lemma size-binary-lhs[size-simps]:
  size (BinaryExpr op x y) > size x
  by (metis One-nat-def Suc-eq-plus1 add-Suc-right less-add-Suc1 numeral-2-eq-2
size-binary-const size-non-add)

lemma size-binary-rhs[size-simps]:
  size (BinaryExpr op x y) > size y
  by (metis IRExpr.disc(42) add-strict-increasing is-ConstantExpr-def linorder-not-le
not-add-less1 size.simps(11) size-non-add size-non-const size-pos)

lemmas arith[size-simps] = Suc-leI add-strict-increasing order-less-trans trans-less-add2

definition well-formed-equal :: Value  $\Rightarrow$  Value  $\Rightarrow$  bool
  (infix  $\approx$  50) where
    well-formed-equal v1 v2 = (v1  $\neq$  UndefVal  $\longrightarrow$  v1 = v2)

lemma well-formed-equal-defn [simp]:
  well-formed-equal v1 v2 = (v1  $\neq$  UndefVal  $\longrightarrow$  v1 = v2)
  unfolding well-formed-equal-def by simp

end

1.1 AbsNode Phase

theory AbsPhase
  imports
    Common
  begin

  phase AbsNode
    terminating size
  begin

```

```

lemma abs-pos:
  fixes v :: ('a :: len word)
  assumes  $0 \leq_s v$ 
  shows (if v <s 0 then - v else v) = v
  by (simp add: assms signed.leD)

lemma abs-neg:
  fixes v :: ('a :: len word)
  assumes  $v <_s 0$ 
  assumes  $-(2 \wedge (Nat.size\ v - 1)) <_s v$ 
  shows (if v <s 0 then - v else v) = - v  $\wedge$   $0 <_s -v$ 

```

by (smt (verit, ccfv-SIG) assms(1) assms(2) signed-take-bit-int-greater-eq-minus-exp
 signed-take-bit-int-greater-eq-self-iff sint-0 sint-word-ariths(4) word-sless-alt)

lemma *abs-max-neg*:
 fixes $v :: ('a :: \text{len word})$
 assumes $v <_s 0$
 assumes $-(2^{\wedge}(\text{Nat.size } v - 1)) = v$
 shows $-v = v$
 using *assms*
 by (metis *One-nat-def add.inverse-neutral double-eq-zero-iff mult-minus-right size-word.rep-eq*)

lemma *final-abs*:
 fixes $v :: ('a :: \text{len word})$
 assumes *take-bit* (*Nat.size* v) $v = v$
 assumes $-(2^{\wedge}(\text{Nat.size } v - 1)) \neq v$
 shows $0 \leq_s$ (if $v <_s 0$ then $-v$ else v)

proof (cases $v <_s 0$)
 case *True*
 then show ?thesis
proof (cases $v = -(2^{\wedge}(\text{Nat.size } v - 1))$)
 case *True*
 then show ?thesis using *abs-max-neg*
 using *assms* by *presburger*
 next
 case *False*
 then have $-(2^{\wedge}(\text{Nat.size } v - 1)) <_s v$
unfolding *word-sless-def* **using** *signed-take-bit-int-greater-self-iff*
 by (smt (verit, best) *One-nat-def diff-less double-eq-zero-iff len-gt-0 lessI less-irrefl*
mult-minus-right neg-equal-0-iff-equal signed.rep-eq signed-of-int
signed-take-bit-int-greater-eq-self-iff signed-word-eqI sint-0 sint-range-size
sint-sbintrunc' sint-word-ariths(4) size-word.rep-eq unsigned-0 word-2p-lem
word-sless.rep-eq word-sless-def)
 then show ?thesis
 using *abs-neg abs-pos signed.nless-le* by *auto*
 qed
 next
 case *False*
 then show ?thesis using *abs-pos* by *auto*
 qed

lemma *wf-abs*: $\text{is-IntVal } x \implies \text{intval-abs } x \neq \text{UndefVal}$
 using *intval-abs.simps* **unfolding** *new-int.simps*
 using *is-IntVal-def* by *force*

fun *bin-abs* :: 'a :: len word \Rightarrow 'a :: len word **where**
bin-abs v = (if (v < s 0) then (- v) else v)

lemma *val-abs-zero*:
intval-abs (new-int b 0) = new-int b 0
by *simp*

lemma *less-eq-zero*:
assumes *val-to-bool* (val[(IntVal b 0) < (IntVal b v)])
shows *int-signed-value* b v > 0
using *assms* **unfolding** *intval-less-than.simps*(1) **apply** *simp*
by (metis *bool-to-val.elims val-to-bool.simps*(1))

lemma *val-abs-pos*:
assumes *val-to-bool*(val[(new-int b 0) < (new-int b v)])
shows *intval-abs* (new-int b v) = (new-int b v)
using *assms* **using** *less-eq-zero* **unfolding** *intval-abs.simps new-int.simps*
by *force*

lemma *val-abs-neg*:
assumes *val-to-bool*(val[(new-int b v) < (new-int b 0)])
shows *intval-abs* (new-int b v) = *intval-negate* (new-int b v)
using *assms* **using** *less-eq-zero* **unfolding** *intval-abs.simps new-int.simps*
by *force*

lemma *val-bool-unwrap*:
val-to-bool (*bool-to-val* v) = v
by (metis *bool-to-val.elims one-neq-zero val-to-bool.simps*(1))

lemma *take-bit-unwrap*:
b = 64 \Rightarrow *take-bit* b (v1::64 word) = v1
by (metis *size64 size-word.rep-eq take-bit-length-eq*)

lemma *bit-less-eq-def*:
fixes v1 v2 :: 64 word
assumes b \leq 64
shows *sint* (*signed-take-bit* (b - Suc (0::nat)) (*take-bit* b v1))
< *sint* (*signed-take-bit* (b - Suc (0::nat)) (*take-bit* b v2)) \longleftrightarrow
signed-take-bit (63::nat) (*Word.rep* v1) < *signed-take-bit* (63::nat) (*Word.rep*
v2)
using *assms* **sorry**

lemma *less-eq-def*:
shows *val-to-bool*(val[(new-int b v1) < (new-int b v2)]) \longleftrightarrow v1 < s v2
unfolding *new-int.simps intval-less-than.simps bool-to-val-bin.simps bool-to-val.simps*

```

int-signed-value.simps apply (simp add: val-bool-unwrap)
apply auto unfolding word-sless-def apply auto
unfolding signed-def apply auto using bit-less-eq-def
apply (metis bot-nat-0.extremum take-bit-0)
by (metis bit-less-eq-def bot-nat-0.extremum take-bit-0)

lemma val-abs-always-pos:
  assumes intval-abs (new-int b v) = (new-int b v')
  shows  $0 \leq_s v'$ 
  using assms
proof (cases v = 0)
  case True
  then have v' = 0
    using val-abs-zero assms
    by (smt (verit, ccfv-threshold) Suc-diff-1 bit-less-eq-def bot-nat-0.extremum
diff-is-0-eq len-gt-0 len-of-numeral-defs(2) order-le-less signed-eq-0-iff take-bit-0 take-bit-signed-take-bit
take-bit-unwrap)
  then show ?thesis by simp
next
  case neq0: False
  then show ?thesis
  proof (cases val-to-bool(val[(new-int b 0) < (new-int b v)]))
  case True
  then show ?thesis using less-eq-def
    using assms val-abs-pos
    by (smt (verit, ccfv-SIG) One-nat-def Suc-leI bit.compl-one bit-less-eq-def
cancel-comm-monoid-add-class.diff-cancel diff-zero len-gt-0 len-of-numeral-defs(2)
mask-0 mask-1 one-le-numeral one-neq-zero signed-word-eqI take-bit-dist-subL take-bit-minus-one-eq-mask
take-bit-not-eq-mask-diff take-bit-signed-take-bit zero-le-numeral)
  next
  case False
  then have val-to-bool(val[(new-int b v) < (new-int b 0)])
    using neq0 less-eq-def
    by (metis signed.neqE)
  then show ?thesis using val-abs-neg less-eq-def unfolding new-int.simps
intval-negate.simps
    by (metis signed.nless-le take-bit-0)
  qed

qed

lemma intval-abs-elim:
  assumes intval-abs x  $\neq$  UndefinedVal
  shows  $\exists t v . x = \text{IntVal } t v \wedge \text{intval-abs } x = \text{new-int } t \text{ (if int-signed-value } t v < 0 \text{ then } -v \text{ else } v)$ 
  using assms
  by (meson intval-abs.elims)

```

```

lemma wf-abs-new-int:
  assumes intval-abs (IntVal t v)  $\neq$  UndefVal
  shows intval-abs (IntVal t v) = new-int t v  $\vee$  intval-abs (IntVal t v) = new-int
t ( $-v$ )
  using assms
  using intval-abs.simps(1) by presburger

lemma mono-undef-abs:
  assumes intval-abs (intval-abs x)  $\neq$  UndefVal
  shows intval-abs x  $\neq$  UndefVal
  using assms
  by force

lemma val-abs-idem:
  assumes intval-abs(intval-abs(x))  $\neq$  UndefVal
  shows intval-abs(intval-abs(x)) = intval-abs x
  using assms
proof  $-$ 
  obtain b v where in-def: intval-abs x = new-int b v
    using assms intval-abs-elim mono-undef-abs by blast
  then show ?thesis
  proof (cases val-to-bool(val[(new-int b v) < (new-int b 0)]))
    case True
    then have nested: (intval-abs (intval-abs x)) = new-int b ( $-v$ )
      using val-abs-neg intval-negate.simps in-def
      by simp
    then have x = new-int b ( $-v$ )
      using in-def True unfolding new-int.simps
    by (smt (verit, best) intval-abs.simps(1) less-eq-def less-eq-zero less-numeral-extra(1)

      mask-1 mask-eq-take-bit-minus-one neg-one.elims neg-one-signed new-int.simps

      one-le-numeral one-neq-zero signed.neqE signed.not-less take-bit-of-0
val-abs-always-pos)
    then show ?thesis using val-abs-always-pos
      using True in-def less-eq-def signed.leD
      using signed.nless-le by blast
  next
    case False
    then show ?thesis
      using in-def by force
  qed
qed

lemma val-abs-negate:
  assumes intval-abs (intval-negate x)  $\neq$  UndefVal
  shows intval-abs (intval-negate x) = intval-abs x
  using assms apply (cases x; auto)

```

```

apply (metis less-eq-def new-int.simps signed.dual-order.strict-iff-not signed.less-linear
        take-bit-0)
by (smt (verit, ccfu-threshold) add.inverse-neutral intval-abs.simps(1) less-eq-def
less-eq-zero
less-numeral-extra(1) mask-1 mask-eq-take-bit-minus-one neg-one.elims neg-one-signed

new-int.simps one-le-numeral one-neq-zero signed.order.order-iff-strict take-bit-of-0

val-abs-always-pos)

```

Optimisations

```

optimization AbsIdempotence:  $\text{abs}(\text{abs}(x)) \mapsto \text{abs}(x)$ 
apply auto
by (metis UnaryExpr unary-eval.simps(1) val-abs-idem)

```

```

optimization AbsNegate:  $\text{abs}(-x) \mapsto \text{abs}(x)$ 
apply auto using val-abs-negate
by (metis unary-eval.simps(1) unfold-unary)

```

end

end

1.2 AddNode Phase

```

theory AddPhase
imports
  Common
begin

```

```

phase AddNode
terminating size
begin

```

```

lemma binadd-commute:
assumes bin-eval BinAdd  $x \ y \neq \text{UndefVal}$ 
shows bin-eval BinAdd  $x \ y = \text{bin-eval BinAdd } y \ x$ 
using assms intval-add-sym by simp

```

```

optimization AddShiftConstantRight:  $((\text{const } v) + y) \mapsto y + (\text{const } v)$  when
 $\neg(\text{is-ConstantExpr } y)$ 
using size-non-const
apply (metis add-2-eq-Suc' less-Suc-eq plus-1-eq-Suc size.simps(11) size-non-add)
unfolding le-expr-def
apply (rule impI)
subgoal premises 1

```



```

apply (rule allI impI) +

subgoal premises 2 for m p va
  apply (rule BinaryExprE[OF 2])
subgoal premises 3 for x ya
  apply (rule BinaryExpr)
  using 3 apply simp
  using 3 apply simp
  using 3 binadd-commute apply auto
done
done
done
done

optimization AddShiftConstantRight2:  $((\text{const } v) + y) \mapsto y + (\text{const } v)$  when
 $\neg(\text{is-ConstantExpr } y)$ 
unfolding le-expr-def
apply (auto simp: intval-add-sym)

using size-non-const
by (metis add-2-eq-Suc' lessI plus-1-eq-Suc size.simps(11) size-non-add)

lemma is-neutral-0 [simp]:
  assumes 1: intval-add (IntVal b x) (IntVal b 0)  $\neq$  UndefVal
  shows intval-add (IntVal b x) (IntVal b 0) = (new-int b x)
  using 1 by auto

optimization AddNeutral:  $(e + (\text{const } (\text{IntVal } 32\ 0))) \mapsto e$ 
unfolding le-expr-def apply auto
using is-neutral-0 eval-unused-bits-zero
by (smt (verit) add-cancel-left-right intval-add.elims val-to-bool.simps(1))

ML-val  $\langle @\{term \langle x = y \rangle\} \rangle$ 

lemma NeutralLeftSubVal:
  assumes e1 = new-int b ival
  shows val[(e1 - e2) + e2]  $\approx$  e1
  apply simp using assms by (cases e1; cases e2; auto)

optimization RedundantSubAdd:  $((e_1 - e_2) + e_2) \mapsto e_1$ 
apply auto using eval-unused-bits-zero NeutralLeftSubVal
unfolding well-formed-equal-defn

```

```

by (smt (verit) evalDet intval-sub.elims new-int.elims)

lemma allE2:  $(\forall x y. P x y) \implies (P a b \implies R) \implies R$ 
by simp

lemma just-goal2:
  assumes 1:  $(\forall a b. (intval-add (intval-sub a b) b \neq UndefinedVal \wedge a \neq UndefinedVal$ 
 $\longrightarrow$ 
 $intval-add (intval-sub a b) b = a))$ 
  shows  $(BinaryExpr BinAdd (BinaryExpr BinSub e_1 e_2) e_2) \geq e_1$ 
  unfolding le-expr-def unfold-binary bin-eval.simps
  by (metis 1 evalDet evaltree-not-undef)

optimization RedundantSubAdd2:  $e_2 + (e_1 - e_2) \mapsto e_1$ 
  apply (metis add.commute add-less-cancel-right less-add-Suc2 plus-1-eq-Suc size-binary-const
size-non-add trans-less-add2)
  by (smt (verit, del-insts) BinaryExpr BinaryExprE RedundantSubAdd(1) bi-
nadd-commute le-expr-def rewrite-preservation.simps(1))

lemma AddToSubHelperLowLevel:
  shows  $intval-add (intval-negate e) y = intval-sub y e$  (is  $?x = ?y$ )
  by (induction y; induction e; auto)

print-phases

lemma val-redundant-add-sub:
  assumes  $a = new-int\ bb\ ival$ 
  assumes  $val[b + a] \neq UndefinedVal$ 
  shows  $val[(b + a) - b] = a$ 
  using assms apply (cases a; cases b; auto)
  by presburger

lemma val-add-right-negate-to-sub:
  assumes  $val[x + e] \neq UndefinedVal$ 
  shows  $val[x + (-e)] = val[x - e]$ 
  using assms by (cases x; cases e; auto)

```

lemma *exp-add-left-negate-to-sub*:

$\text{exp}[-e + y] \geq \text{exp}[y - e]$

apply (*cases e; cases y; auto*)

using *AddToSubHelperLowLevel* **by** *auto+*

Optimisations

optimization *RedundantAddSub*: $(b + a) - b \mapsto a$

apply *auto* **using** *val-redundant-add-sub eval-unused-bits-zero*

by (*smt (verit) evalDet intval-add.elims new-int.elims*)

optimization *AddRightNegateToSub*: $x + -e \mapsto x - e$

apply (*metis Nat.add-0-right add-2-eq-Suc' add-less-mono1 add-mono-thms-linordered-field(2)*
less-SucI not-less-less-Suc-eq size-binary-const size-non-add size-pos)

using *AddToSubHelperLowLevel intval-add-sym* **by** *auto*

optimization *AddLeftNegateToSub*: $-e + y \mapsto y - e$

defer

using *exp-add-left-negate-to-sub* **apply** *blast*

by (*smt (verit, best) One-nat-def add.commute add-Suc-right is-ConstantExpr-def*
less-add-Suc2 numeral-2-eq-2 plus-1-eq-Suc size.simps(1) size.simps(11) size-binary-const
size-non-add)

end

end

1.3 AndNode Phase

theory *AndPhase*

imports

Common

Proofs.StampEvalThms

begin

phase *AndNode*

terminating *size*

begin

lemma *bin-and-nots*:

$(\sim x \ \& \ \sim y) = (\sim (x \mid y))$

by *simp*

lemma *bin-and-neutral*:

$(x \& \sim False) = x$

by *simp*

lemma *val-and-equal*:

assumes $x = \text{new-int } b \ v$

and $\text{val}[x \& x] \neq \text{UndefVal}$

shows $\text{val}[x \& x] = x$

using *assms* **by** (*cases x; auto*)

lemma *val-and-nots*:

$\text{val}[\sim x \& \sim y] = \text{val}[\sim(x \mid y)]$

apply (*cases x; cases y; auto*) **by** (*simp add: take-bit-not-take-bit*)

lemma *val-and-neutral*:

assumes $x = \text{new-int } b \ v$

and $\text{val}[x \& \sim(\text{new-int } b' \ 0)] \neq \text{UndefVal}$

shows $\text{val}[x \& \sim(\text{new-int } b' \ 0)] = x$

using *assms* **apply** (*cases x; auto*) **apply** (*simp add: take-bit-eq-mask*)
by *presburger*

lemma *val-and-zero*:

assumes $x = \text{new-int } b \ v$

shows $\text{val}[x \& (\text{IntVal } b \ 0)] = \text{IntVal } b \ 0$

using *assms* **by** (*cases x; auto*)

lemma *exp-and-equal*:

$\text{exp}[x \& x] \geq \text{exp}[x]$

apply *auto* **using** *val-and-equal eval-unused-bits-zero*

by (*smt (verit) evalDet intval-and.elims new-int.elims*)

lemma *exp-and-nots*:

$\text{exp}[\sim x \& \sim y] \geq \text{exp}[\sim(x \mid y)]$

apply (*cases x; cases y; auto*) **using** *val-and-nots*

by *fastforce+*

lemma *exp-sign-extend*:

assumes $e = (1 \ll In) - 1$

shows $\text{BinaryExpr } \text{BinAnd } (\text{UnaryExpr } (\text{UnarySignExtend } In \ Out) \ x)$
 $\quad (\text{ConstantExpr } (\text{new-int } b \ e))$

$\geq (\text{UnaryExpr } (\text{UnaryZeroExtend } In \ Out) \ x)$

apply *auto*

subgoal *premises p for m p va*

```

proof –
  obtain va where va:  $[m,p] \vdash x \mapsto va$ 
    using p(2) by auto
  then have va  $\neq$  UndefVal
    by (simp add: evaltree-not-undef)
  then have 1: intval-and (intval-sign-extend In Out va) (IntVal b (take-bit b
e))  $\neq$  UndefVal
    using evalDet p(1) p(2) va by blast
  then have 2: intval-sign-extend In Out va  $\neq$  UndefVal
    by auto
  then have 21:  $(0::nat) < b$ 
    by (simp add: p(4))
  then have 3:  $b \sqsubseteq (64::nat)$ 
    by (simp add: p(5))
  then have 4:  $-((2::int) \wedge b \text{ div } (2::int)) \sqsubseteq \text{sint } (\text{signed-take-bit } (b - \text{Suc } (0::nat)) (\text{take-bit } b \text{ e}))$ 
    by (simp add: p(6))
  then have 5:  $\text{sint } (\text{signed-take-bit } (b - \text{Suc } (0::nat)) (\text{take-bit } b \text{ e})) < (2::int) \wedge b \text{ div } (2::int)$ 
    by (simp add: p(7))
  then have 6:  $[m,p] \vdash \text{UnaryExpr } (\text{UnaryZeroExtend In Out})$ 
     $x \mapsto \text{intval-and } (\text{intval-sign-extend In Out va}) (\text{IntVal } b (\text{take-bit } b \text{ e}))$ 
    apply (cases va; simp)
  apply (simp add: <(va::Value)  $\neq$  UndefVal>) defer
  subgoal premises p for x3
    proof –
      have va = ObjRef x3
        using p(1) by auto
      then have  $\text{sint } (\text{signed-take-bit } (b - \text{Suc } (0::nat)) (\text{take-bit } b \text{ e})) < (2::int) \wedge b \text{ div } (2::int)$ 
        by (simp add: 5)
      then show ?thesis
        using 2 intval-sign-extend.simps(3) p(1) by blast
    qed

  subgoal premises p for x4
    proof –
      have sg1: va = ObjStr x4
        using 2 p(1) by auto
      then have  $\text{sint } (\text{signed-take-bit } (b - \text{Suc } (0::nat)) (\text{take-bit } b \text{ e})) < (2::int) \wedge b \text{ div } (2::int)$ 
        by (simp add: 5)
      then show ?thesis
        using 1 sg1 by auto
    qed

  subgoal premises p for x21 x22
    proof –

```

```

      have sgg1: va = IntVal x21 x22
      by (simp add: p(1))
    then have sgg2: sint (signed-take-bit (b - Suc (0::nat)) (take-bit b e))
    < (2::int) ^ b div (2::int)
      by (simp add: 5)
    then show ?thesis
      sorry
    qed
  done
  then show ?thesis
    by (metis evalDet p(2) va)
  qed
done

```

```

lemma val-and-commute[simp]:
  val[x & y] = val[y & x]
  apply (cases x; cases y; auto)
  by (simp add: word-bw-comms(1))

```

Optimisations

```

optimization AndEqual: x & x ⟶ x
  using exp-and-equal by blast

```

```

optimization AndShiftConstantRight: ((const x) & y) ⟶ y & (const x)
  when ¬(is-ConstantExpr y)
  using size-flip-binary by auto

```

```

optimization AndNots: (~x) & (~y) ⟶ ~(x | y)
  defer using exp-and-nots
  apply presburger
  by (metis add-2-eq-Suc' less-SucI less-add-Suc1 not-less-eq size-binary-const size-non-add)

```

```

optimization AndSignExtend: BinaryExpr BinAnd (UnaryExpr (UnarySignExtend
In Out) x)

```

```

  (const (new-int b e))
  ⟶ (UnaryExpr (UnaryZeroExtend In Out) x)
  when (e = (1 << In) - 1)

```

```

  using exp-sign-extend by simp

```

```

optimization AndNeutral: (x & ~(const (IntVal b 0))) ⟶ x
  when (wf-stamp x ∧ stamp-expr x = IntegerStamp b lo hi)
  apply auto using val-and-neutral

```

```

by (smt (verit) Value.sel(1) eval-unused-bits-zero intval-and.elims intval-word.simps
      new-int.simps new-int-bin.simps take-bit-eq-mask)

end

context stamp-mask
begin

lemma AndRightFallthrough: (((and (not ( $\downarrow$  x)) ( $\uparrow$  y)) = 0))  $\longrightarrow$  exp[x & y]  $\geq$ 
exp[y]
  apply simp apply (rule impI; (rule allI)+)
  apply (rule impI)
  subgoal premises p for m p v
  proof –
    obtain xv where xv: [m, p]  $\vdash$  x  $\mapsto$  xv
    using p(2) by blast
    obtain yv where yv: [m, p]  $\vdash$  y  $\mapsto$  yv
    using p(2) by blast
    have v = val[xv & yv]
    using p(2) xv yv
    by (metis BinaryExprE bin-eval.simps(4) evalDet)
    then have v = yv
    using p(1) not-down-up-mask-and-zero-implies-zero
    by (smt (verit) eval-unused-bits-zero intval-and.elims new-int.elims new-int-bin.elims
      p(2) unfold-binary xv yv)
    then show ?thesis using yv by simp
  qed
done

lemma AndLeftFallthrough: (((and (not ( $\downarrow$  y)) ( $\uparrow$  x)) = 0))  $\longrightarrow$  exp[x & y]  $\geq$ 
exp[x]
  apply simp apply (rule impI; (rule allI)+)
  apply (rule impI)
  subgoal premises p for m p v
  proof –
    obtain xv where xv: [m, p]  $\vdash$  x  $\mapsto$  xv
    using p(2) by blast
    obtain yv where yv: [m, p]  $\vdash$  y  $\mapsto$  yv
    using p(2) by blast
    have v = val[xv & yv]
    using p(2) xv yv
    by (metis BinaryExprE bin-eval.simps(4) evalDet)
    then have v = xv
    using p(1) not-down-up-mask-and-zero-implies-zero
    by (smt (verit) and commute eval-unused-bits-zero intval-and.elims new-int.simps
      new-int-bin.simps p(2) unfold-binary xv yv)

```

```

    then show ?thesis using xv by simp
  qed
done

```

```
end
```

```
end
```

1.4 BinaryNode Phase

```

theory BinaryNode
  imports
    Common
begin

```

```

phase BinaryNode
  terminating size
begin

```

```

optimization BinaryFoldConstant: BinaryExpr op (const v1) (const v2)  $\mapsto$  ConstantExpr (bin-eval op v1 v2)

```

```

  unfolding le-expr-def
  apply (rule allI impI)+
  subgoal premises bin for m p v
  print-facts
  apply (rule BinaryExprE[OF bin])
  subgoal premises prems for x y
  print-facts

```

```

proof –

```

```

  have x: x = v1 using prems by auto
  have y: y = v2 using prems by auto
  have xy: v = bin-eval op x y using prems x y by simp
  have int:  $\exists b vv . v = \text{new-int } b \text{ } vv$  using bin-eval-new-int prems by fast
  show ?thesis
    unfolding prems x y xy
    apply (rule ConstantExpr)
    apply (rule validDefIntConst)
    using prems x y xy int sorry

```

```

  qed

```

```

done

```

```

done

```

```

print-facts

```

```

end

```


end

1.5 ConditionalNode Phase

theory *ConditionalPhase*

imports

Common

Proofs.StampEvalThms

begin

phase *ConditionalNode*

terminating *size*

begin

lemma *negates*: $\exists v b. e = \text{IntVal } b \ v \wedge b > 0 \implies \text{val-to-bool } (\text{val}[e]) \longleftrightarrow \neg(\text{val-to-bool } (\text{val}[\neg e]))$
unfolding *intval-logic-negation.simps*
by (*metis* (*mono-tags*, *lifting*) *intval-logic-negation.simps(1)* *logic-negate-def new-int.simps of-bool-eq(2)* *one-neq-zero take-bit-of-0 take-bit-of-1 val-to-bool.simps(1)*)

lemma *negation-condition-intval*:

assumes $e = \text{IntVal } b \ ie$

assumes $0 < b$

shows $\text{val}[(\neg e) \ ? \ x : y] = \text{val}[e \ ? \ y : x]$

using *assms* **by** (*cases* *e*; *auto simp: negates logic-negate-def*)

lemma *negation-preserve-eval*:

assumes $[m, p] \vdash \text{exp}[\neg e] \mapsto v$

shows $\exists v'. ([m, p] \vdash \text{exp}[e] \mapsto v') \wedge v = \text{val}[\neg v']$

using *assms* **by** *auto*

lemma *negation-preserve-eval-intval*:

assumes $[m, p] \vdash \text{exp}[\neg e] \mapsto v$

shows $\exists v' b vv. ([m, p] \vdash \text{exp}[e] \mapsto v') \wedge v' = \text{IntVal } b \ vv \wedge b > 0$

using *assms*

by (*metis eval-bits-1-64 intval-logic-negation.elims negation-preserve-eval unfold-unary*)

optimization *NegateConditionFlipBranches*: $((\neg e) \ ? \ x : y) \mapsto (e \ ? \ y : x)$

apply *simp* **using** *negation-condition-intval negation-preserve-eval-intval*

by (*smt (z3) ConditionalExpr ConditionalExprE evalDet negates negation-preserve-eval*)

optimization *DefaultTrueBranch*: $(\text{true} \ ? \ x : y) \mapsto x$.

optimization *DefaultFalseBranch*: $(\text{false} \ ? \ x : y) \mapsto y$.

optimization *ConditionalEqualBranches*: $(e \ ? \ x : x) \mapsto x$.

optimization *condition-bounds-x*: $((u < v) \ ? \ x : y) \mapsto x$

when (*stamp-under* (*stamp-expr* *u*) (*stamp-expr* *v*) \wedge *wf-stamp* *u* \wedge *wf-stamp* *v*)

using *stamp-under-defn* **by** *auto*

optimization *condition-bounds-y*: $((u < v) ? x : y) \mapsto y$
when (*stamp-under* (*stamp-expr* *v*) (*stamp-expr* *u*) \wedge *wf-stamp* *u* \wedge *wf-stamp* *v*)
using *stamp-under-defn-inverse* **by** *auto*

lemma *val-optimise-integer-test*:
assumes $\exists v. x = \text{IntVal } 32 \ v$
shows $\text{val}[(x \ \& \ (\text{IntVal } 32 \ 1)) \ \text{eq} \ (\text{IntVal } 32 \ 0)) \ ? \ (\text{IntVal } 32 \ 0) : (\text{IntVal } 32 \ 1)] =$
 $\text{val}[x \ \& \ \text{IntVal } 32 \ 1]$
using *assms* **apply** *auto*
apply (*metis* (*full-types*) *bool-to-val.simps*(2) *val-to-bool.simps*(1))
by (*metis* (*mono-tags*, *lifting*) *and-one-eq* *bool-to-val.simps*(1) *even-iff-mod-2-eq-zero* *odd-iff-mod-2-eq-one* *val-to-bool.simps*(1))

optimization *ConditionalEliminateKnownLess*: $((x < y) ? x : y) \mapsto x$
when (*stamp-under* (*stamp-expr* *x*) (*stamp-expr* *y*)
 \wedge *wf-stamp* *x* \wedge *wf-stamp* *y*)
using *stamp-under-defn* **by** *auto*

optimization *ConditionalEqualIsRHS*: $((x \ \text{eq} \ y) ? x : y) \mapsto y$
apply *auto*
by (*smt* (*verit*) *Value.inject*(1) *bool-to-val.simps*(2) *bool-to-val-bin.simps* *evalDet* *intval-equals.elims* *val-to-bool.elims*(1))

optimization *normalizeX*: $((x \ \text{eq} \ \text{const} \ (\text{IntVal } 32 \ 0)) ?$
 $(\text{const} \ (\text{IntVal } 32 \ 0)) : (\text{const} \ (\text{IntVal } 32 \ 1))) \mapsto x$
when ($x = \text{ConstantExpr} \ (\text{IntVal } 32 \ 0) \mid (x = \text{ConstantExpr}$
 $(\text{IntVal } 32 \ 1)))$.

optimization *normalizeX2*: $((x \ \text{eq} \ (\text{const} \ (\text{IntVal } 32 \ 1))) ?$
 $(\text{const} \ (\text{IntVal } 32 \ 1)) : (\text{const} \ (\text{IntVal } 32 \ 0))) \mapsto x$
when ($x = \text{ConstantExpr} \ (\text{IntVal } 32 \ 0) \mid (x =$
 $\text{ConstantExpr} \ (\text{IntVal } 32 \ 1)))$.

optimization *flipX*: $((x \ \text{eq} \ (\text{const} \ (\text{IntVal } 32 \ 0))) ?$
 $(\text{const} \ (\text{IntVal } 32 \ 1)) : (\text{const} \ (\text{IntVal } 32 \ 0))) \mapsto$
 $x \oplus (\text{const} \ (\text{IntVal } 32 \ 1))$
when ($x = \text{ConstantExpr} \ (\text{IntVal } 32 \ 0) \mid (x = \text{ConstantExpr}$
 $(\text{IntVal } 32 \ 1)))$.

optimization *flipX2*: $((x \text{ eq } (\text{const } (\text{IntVal } 32 \ 1)))) \ ?$
 $(\text{const } (\text{IntVal } 32 \ 0)) : (\text{const } (\text{IntVal } 32 \ 1))) \mapsto$
 $x \oplus (\text{const } (\text{IntVal } 32 \ 1))$
 $\text{when } (x = \text{ConstantExpr } (\text{IntVal } 32 \ 0) \mid (x = \text{ConstantExpr } (\text{IntVal } 32 \ 1))) .$

lemma *stamp-of-default*:
assumes *stamp-expr* $x = \text{default-stamp}$
assumes *wf-stamp* x
shows $([m, p] \vdash x \mapsto v) \longrightarrow (\exists vv. v = \text{IntVal } 32 \ vv)$
using *assms*
by (*metis default-stamp valid-value-elim*(3) *wf-stamp-def*)

optimization *OptimiseIntegerTest*:
 $((x \ \& \ (\text{const } (\text{IntVal } 32 \ 1))) \text{ eq } (\text{const } (\text{IntVal } 32 \ 0))) \ ?$
 $(\text{const } (\text{IntVal } 32 \ 0)) : (\text{const } (\text{IntVal } 32 \ 1))) \mapsto$
 $x \ \& \ (\text{const } (\text{IntVal } 32 \ 1))$
 $\text{when } (\text{stamp-expr } x = \text{default-stamp} \wedge \text{wf-stamp } x)$
apply *simp* **apply** (*rule impI*; (*rule allI*) $+$; *rule impI*)
subgoal **premises** *eval* **for** $m \ p \ v$
proof –
obtain xv **where** $xv: [m, p] \vdash x \mapsto xv$
using *eval* **by** *fast*
then **have** $x32: \exists v. xv = \text{IntVal } 32 \ v$
using *stamp-of-default eval* **by** *auto*
obtain lhs **where** $lhs: [m, p] \vdash \text{exp}[(((x \ \& \ (\text{const } (\text{IntVal } 32 \ 1))) \text{ eq } (\text{const } (\text{IntVal } 32 \ 0)))) \ ?$
 $(\text{const } (\text{IntVal } 32 \ 0)) : (\text{const } (\text{IntVal } 32 \ 1)))] \mapsto lhs$
using *eval*(2) **by** *auto*
then **have** $lhsV: lhs = \text{val}[((xv \ \& \ (\text{IntVal } 32 \ 1)) \text{ eq } (\text{IntVal } 32 \ 0)) \ ? (\text{IntVal } 32 \ 0)) : (\text{IntVal } 32 \ 1)]$
using $xv \text{ evaltree.BinaryExpr evaltree.ConstantExpr evaltree.ConditionalExpr}$
by (*smt* (*verit*) *ConditionalExprE ConstantExprE bin-eval.simps*(11) *bin-eval.simps*(4) *evalDet intval-conditional.simps* *unfold-binary*)
obtain rhs **where** $rhs: [m, p] \vdash \text{exp}[x \ \& \ (\text{const } (\text{IntVal } 32 \ 1))] \mapsto rhs$
using *eval*(2) **by** *blast*
then **have** $rhsV: rhs = \text{val}[xv \ \& \ \text{IntVal } 32 \ 1]$
by (*metis BinaryExprE ConstantExprE bin-eval.simps*(4) *evalDet xv*)
have $lhs = rhs$ **using** *val-optimize-integer-test x32*
using $lhsV \ rhsV$ **by** *presburger*
then **show** *?thesis*
by (*metis eval*(2) *evalDet lhs rhs*)
qed
done

optimization *opt-optimize-integer-test-2*:
 $((x \ \& \ (\text{const } (\text{IntVal } 32 \ 1))) \text{ eq } (\text{const } (\text{IntVal } 32 \ 0))) \ ?$

$(\text{const } (\text{IntVal } 32 \ 0)) : (\text{const } (\text{IntVal } 32 \ 1))) \mapsto$
 $\quad \quad \quad x$
 $\text{when } (x = \text{ConstantExpr } (\text{IntVal } 32 \ 0) \mid (x = \text{ConstantExpr } (\text{IntVal } 32 \ 1))) .$

end

end

1.6 MulNode Phase

theory *MulPhase*

imports

Common

Proofs.StampEvalThms

begin

fun *mul-size* :: *IRExpr* \Rightarrow *nat* **where**

$\text{mul-size } (\text{UnaryExpr } \text{op } e) = (\text{mul-size } e) + 2 \mid$
 $\text{mul-size } (\text{BinaryExpr } \text{BinMul } x \ y) = ((\text{mul-size } x) + (\text{mul-size } y) + 2) * 2 \mid$
 $\text{mul-size } (\text{BinaryExpr } \text{op } x \ y) = (\text{mul-size } x) + (\text{mul-size } y) + 2 \mid$
 $\text{mul-size } (\text{ConditionalExpr } \text{cond } t \ f) = (\text{mul-size } \text{cond}) + (\text{mul-size } t) + (\text{mul-size } f) + 2 \mid$
 $\text{mul-size } (\text{ConstantExpr } c) = 1 \mid$
 $\text{mul-size } (\text{ParameterExpr } \text{ind } s) = 2 \mid$
 $\text{mul-size } (\text{LeafExpr } \text{nid } s) = 2 \mid$
 $\text{mul-size } (\text{ConstantVar } c) = 2 \mid$
 $\text{mul-size } (\text{VariableExpr } x \ s) = 2$

phase *MulNode*

terminating *mul-size*

begin

lemma *bin-eliminate-redundant-negative:*

$\text{uminus } (x :: 'a::\text{len word}) * \text{uminus } (y :: 'a::\text{len word}) = x * y$
by *simp*

lemma *bin-multiply-identity:*

$(x :: 'a::\text{len word}) * 1 = x$
by *simp*

lemma *bin-multiply-eliminate:*

```

(x :: 'a::len word) * 0 = 0
by simp

```

```

lemma bin-multiply-negative:
(x :: 'a::len word) * uminus 1 = uminus x
by simp

```

```

lemma bin-multiply-power-2:
(x :: 'a::len word) * (2^j) = x << j
by simp

```

```

lemma take-bit64[simp]:
  fixes w :: int64
  shows take-bit 64 w = w
proof -
  have Nat.size w = 64
  by (simp add: size64)
  then show ?thesis
  by (metis lt2p-lem mask-eq-iff take-bit-eq-mask verit-comp-simplify1 (2) wsst-TYs(3))
qed

```

```

lemma testt:
  fixes a :: nat
  fixes b c :: 64 word
  shows take-bit a (take-bit a (b) * take-bit a (c)) =
    take-bit a (b * c)
by (smt (verit, ccfv-SIG) take-bit-mult take-bit-of-int unsigned-take-bit-eq word-mult-def)

```

```

lemma val-eliminate-redundant-negative:
  assumes val[-x * -y] ≠ UndefVal
  shows val[-x * -y] = val[x * y]
  using assms apply (cases x; cases y; auto)
  using testt by auto

```

```

lemma val-multiply-neutral:
  assumes x = new-int b v
  shows val[x * (IntVal b 1)] = val[x]
  using assms by force

```

```

lemma val-multiply-zero:
  assumes x = new-int b v
  shows val[x * (IntVal b 0)] = IntVal b 0
  using assms by simp

```

```

lemma val-multiply-negative:
  assumes  $x = \text{new-int } b \ v$ 
  shows  $\text{val}[x * \text{intval-negate } (\text{IntVal } b \ 1)] = \text{intval-negate } x$ 
  using assms
  by (smt (verit) Value.disc(1) Value.inject(1) add.inverse-neutral intval-negate.simps(1)

    is-IntVal-def mask-0 mask-eq-take-bit-minus-one new-int.elims of-bool-eq(2)
take-bit-dist-neg
    take-bit-of-1 val-eliminate-redundant-negative val-multiply-neutral val-multiply-zero

    verit-minus-simplify(4) zero-neq-one)

```

```

lemma val-MulPower2:
  fixes  $i :: 64 \text{ word}$ 
  assumes  $y = \text{IntVal } 64 \ (2 \wedge \text{unat}(i))$ 
  and  $0 < i$ 
  and  $i < 64$ 
  and  $\text{val}[x * y] \neq \text{UndefVal}$ 
  shows  $\text{val}[x * y] = \text{val}[x << \text{IntVal } 64 \ i]$ 
  using assms apply (cases  $x$ ; cases  $y$ ; auto)
  subgoal premises  $p$  for  $x2$ 
  proof –
    have  $63 :: \text{int64} = \text{mask } 6$ 
    by eval
    then have  $(2 :: \text{int}) \wedge 6 = 64$ 
    by eval
    then have  $\text{uint } i < (2 :: \text{int}) \wedge 6$ 
    by (metis linorder-not-less lt2p-lem of-int-numeral  $p(4)$  size64 word-2p-lem
word-of-int-2p wsst-TYs(3))
    then have and  $i (\text{mask } 6) = i$ 
    using mask-eq-iff by blast
    then show  $x2 << \text{unat } i = x2 << \text{unat } (\text{and } i (63 :: 64 \text{ word}))$ 
    unfolding 63
    by force
  qed
by presburger

```

```

lemma val-MulPower2Add1:
  fixes  $i :: 64 \text{ word}$ 
  assumes  $y = \text{IntVal } 64 \ ((2 \wedge \text{unat}(i)) + 1)$ 
  and  $0 < i$ 
  and  $i < 64$ 
  and  $\text{val-to-bool}(\text{val}[\text{IntVal } 64 \ 0 < x])$ 
  and  $\text{val-to-bool}(\text{val}[\text{IntVal } 64 \ 0 < y])$ 
  shows  $\text{val}[x * y] = \text{val}[(x << \text{IntVal } 64 \ i) + x]$ 
  using assms apply (cases  $x$ ; cases  $y$ ; auto)
  subgoal premises  $p$  for  $x2$ 

```

```

proof –
  have 63: (63 :: int64) = mask 6
    by eval
  then have (2::int) ^ 6 = 64
    by eval
  then have and i (mask 6) = i
    using mask-eq-iff by (simp add: less-mask-eq p(6))
  then have x2 * ((2::64 word) ^ unat i + (1::64 word)) = (x2 * ((2::64 word)
^ unat i)) + x2
    by (simp add: distrib-left)
  then show x2 * ((2::64 word) ^ unat i + (1::64 word)) = x2 << unat (and i
(63::64 word)) + x2
    by (simp add: 63 <and (i::64 word) (mask (6::nat)) = i>)
qed
using val-to-bool.simps(2) by presburger

```

```

lemma val-MulPower2Sub1:
  fixes i :: 64 word
  assumes y = IntVal 64 ((2 ^ unat(i)) - 1)
  and 0 < i
  and i < 64
  and val-to-bool(val[IntVal 64 0 < x])
  and val-to-bool(val[IntVal 64 0 < y])
  shows val[x * y] = val[(x << IntVal 64 i) - x]
  using assms apply (cases x; cases y; auto)
  subgoal premises p for x2
  proof –
    have 63: (63 :: int64) = mask 6
      by eval
    then have (2::int) ^ 6 = 64
      by eval
    then have and i (mask 6) = i
      using mask-eq-iff by (simp add: less-mask-eq p(6))
    then have x2 * ((2::64 word) ^ unat i - (1::64 word)) = (x2 * ((2::64 word)
^ unat i)) - x2
      by (simp add: right-diff-distrib')
    then show x2 * ((2::64 word) ^ unat i - (1::64 word)) = x2 << unat (and i
(63::64 word)) - x2
      by (simp add: 63 <and (i::64 word) (mask (6::nat)) = i>)
    qed
  using val-to-bool.simps(2) by presburger

```

```

lemma val-distribute-multiplication:
  assumes x = new-int 64 xx ∧ q = new-int 64 qq ∧ a = new-int 64 aa
  shows val[x * (q + a)] = val[(x * q) + (x * a)]
  apply (cases x; cases q; cases a; auto) using distrib-left assms by auto

```

```

lemma val-MulPower2AddPower2:
  fixes i j :: 64 word
  assumes y = IntVal 64 ((2 ^ unat(i)) + (2 ^ unat(j)))
  and    0 < i
  and    0 < j
  and    i < 64
  and    j < 64
  and    x = new-int 64 xx
  shows  val[x * y] = val[(x << IntVal 64 i) + (x << IntVal 64 j)]
  using assms
  proof -
    have 63: (63 :: int64) = mask 6
    by eval
    then have (2::int) ^ 6 = 64
    by eval
    then have n: IntVal 64 ((2 ^ unat(i)) + (2 ^ unat(j))) =
      val[(IntVal 64 (2 ^ unat(i))) + (IntVal 64 (2 ^ unat(j)))]

    using assms by (cases i; cases j; auto)
    then have 1: val[x * ((IntVal 64 (2 ^ unat(i))) + (IntVal 64 (2 ^ unat(j))))]
    =
      val[(x * IntVal 64 (2 ^ unat(i))) + (x * IntVal 64 (2 ^ unat(j)))]

    using assms val-distribute-multiplication val-MulPower2 by simp
    then have 2: val[(x * IntVal 64 (2 ^ unat(i)))] = val[x << IntVal 64 i]
    using assms val-MulPower2
    using Value.distinct(1) intval-mul.simps(1) new-int.simps new-int-bin.simps
    by (smt (verit))
    then show ?thesis
    using 1 Value.distinct(1) assms(1) assms(3) assms(5) assms(6) intval-mul.simps(1)
  n
    new-int.simps new-int-bin.elims val-MulPower2
    by (smt (verit, del-insts))
  qed

```

thm-oracles *val-MulPower2AddPower2*

```

lemma exp-multiply-zero-64:
  exp[x * (const (IntVal 64 0))] ≥ ConstantExpr (IntVal 64 0)
  using val-multiply-zero apply auto
  using Value.inject(1) constantAsStamp.simps(1) int-signed-value-bounds intval-mul.elims

  mult-zero-right new-int.simps new-int-bin.simps nle-le numeral-eq-Suc take-bit-of-0

  unfold-const valid-stamp.simps(1) valid-value.simps(1) zero-less-Suc
  by (smt (verit))

```



```

lemma exp-multiply-neutral:
   $\text{exp}[x * (\text{const } (\text{IntVal } b \ 1))] \geq x$ 
  using val-multiply-neutral apply auto
  by (smt (verit) Value.inject(1) eval-unused-bits-zero intval-mul.elims mult.right-neutral

    new-int.elims new-int-bin.elims)

```

thm-oracles *exp-multiply-neutral*

```

lemma exp-MulPower2:
  fixes i :: 64 word
  assumes  $y = \text{ConstantExpr } (\text{IntVal } 64 \ (2 \wedge \text{unat}(i)))$ 
  and  $0 < i$ 
  and  $i < 64$ 
  and  $\text{exp}[x > (\text{const } \text{IntVal } b \ 0)]$ 
  and  $\text{exp}[y > (\text{const } \text{IntVal } b \ 0)]$ 
  shows  $\text{exp}[x * y] \geq \text{exp}[x << \text{ConstantExpr } (\text{IntVal } 64 \ i)]$ 
  using assms apply simp using val-MulPower2
  by (metis ConstantExprE equiv-exprs-def unfold-binary)

```

```

lemma exp-MulPower2Add1:
  fixes i :: 64 word
  assumes  $y = \text{ConstantExpr } (\text{IntVal } 64 \ ((2 \wedge \text{unat}(i)) + 1))$ 
  and  $0 < i$ 
  and  $i < 64$ 
  and  $\text{exp}[x > (\text{const } \text{IntVal } b \ 0)]$ 
  and  $\text{exp}[y > (\text{const } \text{IntVal } b \ 0)]$ 
shows  $\text{exp}[x * y] = \text{exp}[(x << \text{ConstantExpr } (\text{IntVal } 64 \ i)) + x]$ 
  sorry

```

```

lemma greaterConstant:
  assumes  $a > b$ 
  and  $y = \text{ConstantExpr } (\text{IntVal } 64 \ a)$ 
  and  $x = \text{ConstantExpr } (\text{IntVal } 64 \ b)$ 
  shows  $y > x$ 
  apply auto
  sorry

```

Optimisations

```

optimization EliminateRedundantNegative:  $-x * -y \mapsto x * y$ 
  using mul-size.simps apply auto[1]
  using val-eliminate-redundant-negative bin-eval.simps(2)
  by (metis BinaryExpr)

```

```

optimization MulNeutral:  $x * \text{ConstantExpr } (\text{IntVal } b \ 1) \mapsto x$ 

```

```

using exp-multiply-neutral by blast

optimization MulEliminator:  $x * \text{ConstantExpr } (\text{IntVal } b \ 0) \mapsto \text{const } (\text{IntVal } b \ 0)$ 
apply auto using val-multiply-zero
using Value.inject(1) constantAsStamp.simps(1) int-signed-value-bounds intval-mul.elims

      mult-zero-right new-int.simps new-int-bin.simps take-bit-of-0 unfold-const
      valid-stamp.simps(1) valid-value.simps(1)
by (smt (verit))

optimization MulNegate:  $x * -(\text{const } (\text{IntVal } b \ 1)) \mapsto -x$ 
apply auto using val-multiply-negative
by (smt (verit) Value.distinct(1) Value.sel(1) add.inverse-inverse intval-mul.elims

      intval-negate.simps(1) mask-eq-take-bit-minus-one new-int.simps new-int-bin.simps

      take-bit-dist-neg unary-eval.simps(2) unfold-unary
      val-eliminate-redundant-negative)

fun isNonZero :: Stamp  $\Rightarrow$  bool where
  isNonZero (IntegerStamp b lo hi) = (lo > 0) |
  isNonZero - = False

lemma isNonZero-defn:
  assumes isNonZero (stamp-expr x)
  assumes wf-stamp x
  shows ( $[m, p] \vdash x \mapsto v \longrightarrow (\exists vv \ b. (v = \text{IntVal } b \ vv \wedge \text{val-to-bool val}[(\text{IntVal } b \ 0) < v]))$ )
  apply (rule impI) subgoal premises eval
proof –
  obtain b lo hi where xstamp: stamp-expr x = IntegerStamp b lo hi
  using assms
  by (meson isNonZero.elims(2))
  then obtain vv where vdef: v = IntVal b vv
  by (metis assms(2) eval valid-int wf-stamp-def)
  have lo > 0
  using assms(1) xstamp by force
  then have signed-above: int-signed-value b vv > 0
  using assms unfolding wf-stamp-def
  using eval vdef xstamp by fastforce
  have take-bit b vv = vv
  using eval eval-unused-bits-zero vdef by auto
  then have vv > 0
  using signed-above
  by (metis bit-take-bit-iff int-signed-value.simps not-less-zero signed-eq-0-iff signed-take-bit-eq-if-positive
    take-bit-0 take-bit-of-0 verit-comp-simplify1(1) word-gt-0)
  then show ?thesis
  using vdef using signed-above

```

```

    by simp
qed
done

optimization MulPower2:  $x * y \mapsto x << \text{const } (\text{IntVal } 64 \ i)$ 
    when  $(i > 0 \wedge$ 
         $64 > i \wedge$ 
         $y = \text{exp}[\text{const } (\text{IntVal } 64 \ (2 \wedge \text{unat}(i)))]$ )

    defer
    apply simp apply (rule impI; (rule allI)+; rule impI)
    subgoal premises eval for m p v
    proof -
        obtain xv where xv:  $[m, p] \vdash x \mapsto xv$ 
        using eval(2) by blast
        then obtain xvv where xvv:  $xv = \text{IntVal } 64 \ xvv$ 
        using eval
        using ConstantExprE bin-eval.simps(2) evalDet intval-bits.simps intval-mul.elims
        new-int-bin.simps unfold-binary
        by (smt (verit))
        obtain yv where yv:  $[m, p] \vdash y \mapsto yv$ 
        using eval(1) eval(2) by blast
        then have lhs:  $[m, p] \vdash \text{exp}[x * y] \mapsto \text{val}[xv * yv]$ 
        by (metis bin-eval.simps(2) eval(1) eval(2) evalDet unfold-binary xv)
        have  $[m, p] \vdash \text{exp}[\text{const } (\text{IntVal } 64 \ i)] \mapsto \text{val}[(\text{IntVal } 64 \ i)]$ 
        by (smt (verit, ccfv-SIG) ConstantExpr constantAsStamp.simps(1) eval-bits-1-64
            take-bit64 validStampIntConst valid-value.simps(1) xv xvv)
        then have rhs:  $[m, p] \vdash \text{exp}[x << \text{const } (\text{IntVal } 64 \ i)] \mapsto \text{val}[xv << (\text{IntVal } 64 \ i)]$ 
        using xv xvv using evaltree.BinaryExpr
        by (metis Value.simps(5) bin-eval.simps(8) intval-left-shift.simps(1) new-int.simps)
        have  $\text{val}[xv * yv] = \text{val}[xv << (\text{IntVal } 64 \ i)]$ 
        using val-MulPower2
        by (metis ConstantExprE eval(1) evaltree-not-undef lhs yv)
        then show ?thesis
        by (metis eval(1) eval(2) evalDet lhs rhs)
    qed
done

```

```

optimization MulPower2Add1:  $x * y \mapsto (x << \text{const } (\text{IntVal } 64 \ i)) + x$ 
    when  $(i > 0 \wedge$ 
         $64 > i \wedge$ 
         $y = \text{ConstantExpr } (\text{IntVal } 64 \ ((2 \wedge \text{unat}(i)) + 1))$ )

    defer
    apply simp apply (rule impI; (rule allI)+; rule impI)
    subgoal premises p for m p v
    proof -

```

```

obtain xv where xv:  $[m, p] \vdash x \mapsto xv$ 
  using p by fast
then obtain xvv where xvv:  $xv = \text{IntVal } 64 \text{ } xv$ 
  by (smt (verit) p ConstantExprE bin-eval.simps(2) evalDet intval-bits.simps
intval-mul.elims
    new-int-bin.simps unfold-binary)
obtain yv where yv:  $[m, p] \vdash y \mapsto yv$ 
  using p by blast
have ygezero:  $y > \text{ConstantExpr } (\text{IntVal } 64 \text{ } 0)$ 
  using greaterConstant p by fastforce
then have 1:  $0 < i \wedge$ 
   $i < 64 \wedge$ 
   $y = \text{ConstantExpr } (\text{IntVal } 64 \text{ } ((2 \wedge \text{unat}(i)) + 1))$ 
  using p by blast
then have lhs:  $[m, p] \vdash \text{exp}[x * y] \mapsto \text{val}[xv * yv]$ 
  by (metis bin-eval.simps(2) evalDet p(1) p(2) xv yv unfold-binary)
then have  $[m, p] \vdash \text{exp}[\text{const } (\text{IntVal } 64 \text{ } i)] \mapsto \text{val}[(\text{IntVal } 64 \text{ } i)]$ 
  by (metis verit-comp-simplify1(2) zero-less-numeral ConstantExpr constantAsStamp.simps(1)
    take-bit64 validStampIntConst valid-value.simps(1))
then have rhs2:  $[m, p] \vdash \text{exp}[x << \text{const } (\text{IntVal } 64 \text{ } i)] \mapsto \text{val}[xv << (\text{IntVal } 64 \text{ } i)]$ 
  by (metis Value.simps(5) bin-eval.simps(8) intval-left-shift.simps(1) new-int.simps
xv xvv
    evaltree.BinaryExpr)
then have rhs:  $[m, p] \vdash \text{exp}[(x << \text{const } (\text{IntVal } 64 \text{ } i)) + x] \mapsto \text{val}[(xv << (\text{IntVal } 64 \text{ } i)) + xv]$ 
  by (metis (no-types, lifting) intval-add.simps(1) rhs2 bin-eval.simps(1)
Value.simps(5)
    evaltree.BinaryExpr intval-left-shift.simps(1) new-int.simps xv xvv)
then have  $\text{val}[xv * yv] = \text{val}[(xv << (\text{IntVal } 64 \text{ } i)) + xv]$ 
  using 1 exp-MulPower2Add1 ygezero by auto
then show ?thesis
  by (metis evalDet lhs p(1) p(2) rhs)
qed
done

end

end

```

1.7 Experimental AndNode Phase

```

theory NewAnd
  imports
    Common
    Graph.Long
  begin

```

lemma *bin-distribute-and-over-or*:
 $\text{bin}[z \ \& \ (x \mid y)] = \text{bin}[(z \ \& \ x) \mid (z \ \& \ y)]$
by (*smt* (*verit*, *best*) *bit-and-iff* *bit-eqI* *bit-or-iff*)

lemma *intval-distribute-and-over-or*:
 $\text{val}[z \ \& \ (x \mid y)] = \text{val}[(z \ \& \ x) \mid (z \ \& \ y)]$
apply (*cases* *x*; *cases* *y*; *cases* *z*; *auto*)
using *bin-distribute-and-over-or* **by** *blast+*

lemma *exp-distribute-and-over-or*:
 $\text{exp}[z \ \& \ (x \mid y)] \geq \text{exp}[(z \ \& \ x) \mid (z \ \& \ y)]$
apply *simp* **using** *intval-distribute-and-over-or*
using *BinaryExpr* *bin-eval.simps*(4,5)
using *intval-or.simps*(1) **unfolding** *new-int-bin.simps* *new-int.simps* **apply** *auto*
by (*metis* *bin-eval.simps*(4) *bin-eval.simps*(5) *intval-or.simps*(2) *intval-or.simps*(5))

lemma *intval-and-commute*:
 $\text{val}[x \ \& \ y] = \text{val}[y \ \& \ x]$
by (*cases* *x*; *cases* *y*; *auto* *simp*: *and.commute*)

lemma *intval-or-commute*:
 $\text{val}[x \mid y] = \text{val}[y \mid x]$
by (*cases* *x*; *cases* *y*; *auto* *simp*: *or.commute*)

lemma *intval-xor-commute*:
 $\text{val}[x \oplus y] = \text{val}[y \oplus x]$
by (*cases* *x*; *cases* *y*; *auto* *simp*: *xor.commute*)

lemma *exp-and-commute*:
 $\text{exp}[x \ \& \ z] \geq \text{exp}[z \ \& \ x]$
apply *simp* **using** *intval-and-commute* **by** *auto*

lemma *exp-or-commute*:
 $\text{exp}[x \mid y] \geq \text{exp}[y \mid x]$
apply *simp* **using** *intval-or-commute* **by** *auto*

lemma *exp-xor-commute*:
 $\text{exp}[x \oplus y] \geq \text{exp}[y \oplus x]$
apply *simp* **using** *intval-xor-commute* **by** *auto*

lemma *bin-eliminate-y*:
assumes $\text{bin}[y \ \& \ z] = 0$
shows $\text{bin}[(x \mid y) \ \& \ z] = \text{bin}[x \ \& \ z]$
using *assms*
by (*simp* *add*: *and.commute* *bin-distribute-and-over-or*)

lemma *intval-eliminate-y*:

```

assumes  $val[y \& z] = IntVal\ b\ 0$ 
shows  $val[(x \mid y) \& z] = val[x \& z]$ 
using assms bin-eliminate-y by (cases x; cases y; cases z; auto)

lemma intval-and-associative:
   $val[(x \& y) \& z] = val[x \& (y \& z)]$ 
apply (cases x; cases y; cases z; auto)
by (simp add: and.assoc)+

lemma intval-or-associative:
   $val[(x \mid y) \mid z] = val[x \mid (y \mid z)]$ 
apply (cases x; cases y; cases z; auto)
by (simp add: or.assoc)+

lemma intval-xor-associative:
   $val[(x \oplus y) \oplus z] = val[x \oplus (y \oplus z)]$ 
apply (cases x; cases y; cases z; auto)
by (simp add: xor.assoc)+

lemma exp-and-associative:
   $exp[(x \& y) \& z] \geq exp[x \& (y \& z)]$ 
apply simp using intval-and-associative by fastforce

lemma exp-or-associative:
   $exp[(x \mid y) \mid z] \geq exp[x \mid (y \mid z)]$ 
apply simp using intval-or-associative by fastforce

lemma exp-xor-associative:
   $exp[(x \oplus y) \oplus z] \geq exp[x \oplus (y \oplus z)]$ 
apply simp using intval-xor-associative by fastforce

lemma intval-and-absorb-or:
  assumes  $\exists b\ v . x = new\_int\ b\ v$ 
  assumes  $val[x \& (x \mid y)] \neq UndefinedVal$ 
  shows  $val[x \& (x \mid y)] = val[x]$ 
  using assms apply (cases x; cases y; auto)
  by (metis (mono-tags, lifting) intval-and.simps(5))

lemma intval-or-absorb-and:
  assumes  $\exists b\ v . x = new\_int\ b\ v$ 
  assumes  $val[x \mid (x \& y)] \neq UndefinedVal$ 
  shows  $val[x \mid (x \& y)] = val[x]$ 
  using assms apply (cases x; cases y; auto)
  by (metis (mono-tags, lifting) intval-or.simps(5))

lemma exp-and-absorb-or:
   $exp[x \& (x \mid y)] \geq exp[x]$ 
apply auto using intval-and-absorb-or eval-unused-bits-zero

```

```

    by (smt (verit) evalDet intval-or.elims new-int.elims)

lemma exp-or-absorb-and:
  exp[x | (x & y)] ≥ exp[x]
  apply auto using intval-or-absorb-and eval-unused-bits-zero
  by (smt (verit) evalDet intval-or.elims new-int.elims)

definition IRExp-up :: IRExp ⇒ int64 where
  IRExp-up e = not 0

definition IRExp-down :: IRExp ⇒ int64 where
  IRExp-down e = 0

lemma
  assumes y = 0
  shows x + y = or x y
  using assms
  by simp

lemma no-overlap-or:
  assumes and x y = 0
  shows x + y = or x y
  using assms
  by (metis bit-and-iff bit-xor-iff disjunctive-add xor-self-eq)

context stamp-mask
begin

lemma intval-up-and-zero-implies-zero:
  assumes and (↑x) (↑y) = 0
  assumes [m, p] ⊢ x ↦ xv
  assumes [m, p] ⊢ y ↦ yv
  assumes val[xv & yv] ≠ UndefVal
  shows ∃ b . val[xv & yv] = new-int b 0
  using assms apply (cases xv; cases yv; auto)
  using up-mask-and-zero-implies-zero
  apply (smt (verit, best) take-bit-and take-bit-of-0)
  by presburger

lemma exp-eliminate-y:

```

```

and ( $\uparrow y$ ) ( $\uparrow z$ ) = 0  $\longrightarrow$  BinaryExpr BinAnd (BinaryExpr BinOr x y) z  $\geq$  BinaryExpr BinAnd x z
apply simp apply (rule impI; rule allI; rule allI; rule allI)
subgoal premises p for m p v apply (rule impI) subgoal premises e
proof –
  obtain xv where xv: [m,p]  $\vdash$  x  $\mapsto$  xv
  using e by auto
  obtain yv where yv: [m,p]  $\vdash$  y  $\mapsto$  yv
  using e by auto
  obtain zv where zv: [m,p]  $\vdash$  z  $\mapsto$  zv
  using e by auto
  have lhs: v = val[(xv | yv) & zv]
  using xv yv zv
  by (smt (verit, best) BinaryExprE bin-eval.simps(4) bin-eval.simps(5) e
evalDet)
  then have v = val[(xv & zv) | (yv & zv)]
  by (simp add: intval-and-commute intval-distribute-and-over-or)
  also have  $\exists b. \text{val}[yv \& zv] = \text{new-int } b \ 0$ 
  using intval-up-and-zero-implies-zero
  by (metis calculation e intval-or.simps(5) p unfold-binary yv zv)
  ultimately have rhs: v = val[xv & zv]
  using intval-eliminate-y lhs by force
  from lhs rhs show ?thesis
  by (metis BinaryExpr BinaryExprE bin-eval.simps(4) e xv zv)
qed
done
done

```

```

lemma leadingZeroBounds:
  fixes x :: 'a::len word
  assumes n = numberOfLeadingZeros x
  shows  $0 \leq n \wedge n \leq \text{Nat.size } x$ 
  using assms unfolding numberOfLeadingZeros-def
  by (simp add: MaxOrNeg-def highestOneBit-def nat-le-iff)

```

```

lemma above-nth-not-set:
  fixes x :: int64
  assumes n = 64 - numberOfLeadingZeros x
  shows  $j > n \longrightarrow \neg(\text{bit } x \ j)$ 
  using assms unfolding numberOfLeadingZeros-def
  by (smt (verit, ccfv-SIG) highestOneBit-def int-nat-eq int-ops(6) less-imp-of-nat-less
max-set-bit size64 zerosAboveHighestOne)

```

```

no-notation LogicNegationNotation (!-)

```

```

lemma zero-horner:
  horner-sum of-bool 2 (map ( $\lambda x. \text{False}$ ) xs) = 0
  apply (induction xs) apply simp
  by force

```


lemma *zero-map*:
assumes $j \leq n$
assumes $\forall i. j \leq i \longrightarrow \neg(f\ i)$
shows $\text{map } f\ [0..<n] = \text{map } f\ [0..<j] @ \text{map } (\lambda x. \text{False})\ [j..<n]$
apply (*insert assms*)
by (*smt (verit, del-insts) add-diff-inverse-nat atLeastLessThan-iff bot-nat-0.extremum leD map-append map-eq-conv set-upt upt-add-eq-append*)

lemma *map-join-horner*:
assumes $\text{map } f\ [0..<n] = \text{map } f\ [0..<j] @ \text{map } (\lambda x. \text{False})\ [j..<n]$
shows $\text{horner-sum of-bool } (2::'a::\text{len word})\ (\text{map } f\ [0..<n]) = \text{horner-sum of-bool } 2\ (\text{map } f\ [0..<j])$
proof –
have $\text{horner-sum of-bool } (2::'a::\text{len word})\ (\text{map } f\ [0..<n]) = \text{horner-sum of-bool } 2\ (\text{map } f\ [0..<j]) + 2 \wedge \text{length } [0..<j] * \text{horner-sum of-bool } 2\ (\text{map } f\ [j..<n])$
using *horner-sum-append*
by (*smt (verit) assms diff-le-self diff-zero le-add-same-cancel2 length-append length-map length-upt map-append upt-add-eq-append*)
also have $\dots = \text{horner-sum of-bool } 2\ (\text{map } f\ [0..<j]) + 2 \wedge \text{length } [0..<j] * \text{horner-sum of-bool } 2\ (\text{map } (\lambda x. \text{False})\ [j..<n])$
using *assms*
by (*metis calculation horner-sum-append length-map*)
also have $\dots = \text{horner-sum of-bool } 2\ (\text{map } f\ [0..<j])$
using *zero-horner*
using *mult-not-zero* **by** *auto*
finally show *?thesis* **by** *simp*
qed

lemma *split-horner*:
assumes $j \leq n$
assumes $\forall i. j \leq i \longrightarrow \neg(f\ i)$
shows $\text{horner-sum of-bool } (2::'a::\text{len word})\ (\text{map } f\ [0..<n]) = \text{horner-sum of-bool } 2\ (\text{map } f\ [0..<j])$
apply (*rule map-join-horner*)
apply (*rule zero-map*)
using *assms* **by** *auto*

lemma *transfer-map*:
assumes $\forall i. i < n \longrightarrow f\ i = f'\ i$
shows $(\text{map } f\ [0..<n]) = (\text{map } f'\ [0..<n])$
using *assms* **by** *simp*

lemma *transfer-horner*:
assumes $\forall i. i < n \longrightarrow f\ i = f'\ i$
shows $\text{horner-sum of-bool } (2::'a::\text{len word})\ (\text{map } f\ [0..<n]) = \text{horner-sum of-bool } 2\ (\text{map } f'\ [0..<n])$
using *assms* **using** *transfer-map*
by (*smt (verit, best)*)

```

lemma L1:
  assumes  $n = 64 - \text{numberOfLeadingZeros } (\uparrow z)$ 
  assumes  $[m, p] \vdash z \mapsto \text{IntVal } b \text{ } zv$ 
  shows  $\text{and } v \text{ } zv = \text{and } (v \bmod 2^n) \text{ } zv$ 
proof -
  have  $nle: n \leq 64$ 
  using assms
  using diff-le-self by blast
  also have  $\text{and } v \text{ } zv = \text{horner-sum of-bool } 2 \text{ (map (bit (and } v \text{ } zv)) [0..<64])}$ 
  using horner-sum-bit-eq-take-bit size64
  by (metis size-word.rep-eq take-bit-length-eq)
  also have  $\dots = \text{horner-sum of-bool } 2 \text{ (map } (\lambda i. \text{bit (and } v \text{ } zv) \text{ } i) [0..<64])}$ 
  by blast
  also have  $\dots = \text{horner-sum of-bool } 2 \text{ (map } (\lambda i. ((\text{bit } v \text{ } i) \wedge (\text{bit } zv \text{ } i))) [0..<64])}$ 
  using bit-and-iff by metis
  also have  $\dots = \text{horner-sum of-bool } 2 \text{ (map } (\lambda i. ((\text{bit } v \text{ } i) \wedge (\text{bit } zv \text{ } i))) [0..<n])}$ 
  proof -
    have  $\forall i. i \geq n \longrightarrow \neg(\text{bit } zv \text{ } i)$ 
    using above-nth-not-set assms(1)
    using assms(2) not-may-implies-false
    by (smt (verit, ccfv-SIG) One-nat-def diff-less int-ops(6) leadingZerosAddHighestOne linorder-not-le nat-int-comparison(2) not-numeral-le-zero size64 zero-less-Suc zerosAboveHighestOne)
    then have  $\forall i. i \geq n \longrightarrow \neg((\text{bit } v \text{ } i) \wedge (\text{bit } zv \text{ } i))$ 
    by auto
    then show ?thesis using nle split-horner
    by (metis (no-types, lifting))
  qed
  also have  $\dots = \text{horner-sum of-bool } 2 \text{ (map } (\lambda i. ((\text{bit } (v \bmod 2^n) \text{ } i) \wedge (\text{bit } zv \text{ } i))) [0..<n])}$ 
  proof -
    have  $\forall i. i < n \longrightarrow \text{bit } (v \bmod 2^n) \text{ } i = \text{bit } v \text{ } i$ 
    by (metis bit-take-bit-iff take-bit-eq-mod)
    then have  $\forall i. i < n \longrightarrow ((\text{bit } v \text{ } i) \wedge (\text{bit } zv \text{ } i)) = ((\text{bit } (v \bmod 2^n) \text{ } i) \wedge (\text{bit } zv \text{ } i))$ 
    by force
    then show ?thesis
    by (rule transfer-horner)
  qed
  also have  $\dots = \text{horner-sum of-bool } 2 \text{ (map } (\lambda i. ((\text{bit } (v \bmod 2^n) \text{ } i) \wedge (\text{bit } zv \text{ } i))) [0..<64])}$ 
  proof -
    have  $\forall i. i \geq n \longrightarrow \neg(\text{bit } zv \text{ } i)$ 
    using above-nth-not-set assms(1)
    using assms(2) not-may-implies-false
    by (smt (verit, ccfv-SIG) One-nat-def diff-less int-ops(6) leadingZerosAddHighestOne linorder-not-le nat-int-comparison(2) not-numeral-le-zero size64 zero-less-Suc zerosAboveHighestOne)

```

```

then show ?thesis
  by (metis (no-types, lifting) assms(1) diff-le-self split-horner)
qed
also have ... = horner-sum of-bool 2 (map (bit (and (v mod 2n) zv)) [0..64])
  by (meson bit-and-iff)
also have ... = and (v mod 2n) zv
  using horner-sum-bit-eq-take-bit size64
  by (metis size-word.rep-eq take-bit-length-eq)
finally show ?thesis
  using ‹and (v::64 word) (zv::64 word) = horner-sum of-bool (2::64 word)
    (map (bit (and v zv)) [0::nat..64::nat])› ‹horner-sum of-bool (2::64 word) (map
    (λi::nat. bit ((v::64 word) mod (2::64 word) ^ (n::nat)) i ∧ bit (zv::64 word)
    i) [0::nat..64::nat]) = horner-sum of-bool (2::64 word) (map (bit (and (v mod
    (2::64 word) ^ n) zv)) [0::nat..64::nat])› ‹horner-sum of-bool (2::64 word) (map
    (λi::nat. bit ((v::64 word) mod (2::64 word) ^ (n::nat)) i ∧ bit (zv::64 word) i)
    [0::nat..64::nat]) = horner-sum of-bool (2::64 word) (map (λi::nat. bit (v mod (2::64
    word) ^ n) i ∧ bit zv i) [0::nat..64::nat])› ‹horner-sum of-bool (2::64 word)
    (map (λi::nat. bit (v::64 word) i ∧ bit (zv::64 word) i) [0::nat..64::nat]) =
    horner-sum of-bool (2::64 word) (map (λi::nat. bit v i ∧ bit zv i) [0::nat..64::nat])›
    ‹horner-sum of-bool (2::64 word) (map (λi::nat. bit (v::64 word) i ∧ bit (zv::64
    word) i) [0::nat..64::nat]) = horner-sum of-bool (2::64 word) (map (λi::nat. bit
    (v mod (2::64 word) ^ n) i ∧ bit zv i) [0::nat..64::nat])› ‹horner-sum of-bool (2::64
    word) (map (bit (and ((v::64 word) mod (2::64 word) ^ (n::nat)) (zv::64 word)))
    [0::nat..64::nat]) = and (v mod (2::64 word) ^ n) zv› ‹horner-sum of-bool (2::64
    word) (map (bit (and (v::64 word) (zv::64 word))) [0::nat..64::nat]) = horner-sum
    of-bool (2::64 word) (map (λi::nat. bit v i ∧ bit zv i) [0::nat..64::nat])› by pres-
    burger
qed

lemma up-mask-upper-bound:
  assumes [m, p] ⊢ x ↦ IntVal b xv
  shows xv ≤ (↑x)
  using assms
  by (metis (no-types, lifting) and.idem and.right-neutral bit.conj-cancel-left bit.conj-disj-distrib(1)
    bit.double-compl ucast-id up-spec word-and-le1 word-not-dist(2))

lemma L2:
  assumes numberOfLeadingZeros (↑z) + numberOfTrailingZeros (↑y) ≥ 64
  assumes n = 64 - numberOfLeadingZeros (↑z)
  assumes [m, p] ⊢ z ↦ IntVal b zv
  assumes [m, p] ⊢ y ↦ IntVal b yv
  shows yv mod 2n = 0
proof -
  have yv mod 2n = horner-sum of-bool 2 (map (bit yv) [0..n])
    by (simp add: horner-sum-bit-eq-take-bit take-bit-eq-mod)
  also have ... ≤ horner-sum of-bool 2 (map (bit (↑y)) [0..n])
    using up-mask-upper-bound assms(4)
  by (metis (no-types, opaque-lifting) and.right-neutral bit.conj-cancel-right bit.conj-disj-distrib(1)
    bit.double-compl horner-sum-bit-eq-take-bit take-bit-and ucast-id up-spec word-and-le1)

```

```

word-not-dist(2))
  also have horner-sum of-bool 2 (map (bit (↑y)) [0.. $n$ ]) = horner-sum of-bool 2
  (map (λx. False) [0.. $n$ ])
  proof -
    have ∀ i < n. ¬(bit (↑y) i)
    using assms(1,2) zerosBelowLowestOne
    by (metis add commute add-diff-inverse-nat add-lessD1 leD le-diff-conv num-
berOfTrailingZeros-def)
    then show ?thesis
    by (metis (full-types) transfer-map)
  qed
  also have horner-sum of-bool 2 (map (λx. False) [0.. $n$ ]) = 0
  using zero-horner
  by blast
  finally show ?thesis
  by auto
qed

```

thm-oracles $L1\ L2$

lemma *unfold-binary-width-add:*

```

shows ([m,p] ⊢ BinaryExpr BinAdd xe ye ↦ IntVal b val) = (∃ x y.
  ([m,p] ⊢ xe ↦ IntVal b x) ∧
  ([m,p] ⊢ ye ↦ IntVal b y) ∧
  (IntVal b val = bin-eval BinAdd (IntVal b x) (IntVal b y)) ∧
  (IntVal b val ≠ UndefVal)
) (is ?L = ?R)

```

proof (*intro iffI*)

assume 3: ?L

show ?R **apply** (rule evaltree.cases[OF 3])

apply force+ **apply** auto[1]

apply (smt (verit) intval-add.elims intval-bits.simps)

by blast

next

assume R: ?R

then obtain x y **where** [m,p] ⊢ xe ↦ IntVal b x

and [m,p] ⊢ ye ↦ IntVal b y

and new-int b val = bin-eval BinAdd (IntVal b x) (IntVal b y)

and new-int b val ≠ UndefVal

by auto

then show ?L

using R **by** blast

qed

lemma *unfold-binary-width-and:*

```

shows ([m,p] ⊢ BinaryExpr BinAnd xe ye ↦ IntVal b val) = (∃ x y.
  ([m,p] ⊢ xe ↦ IntVal b x) ∧
  ([m,p] ⊢ ye ↦ IntVal b y) ∧
  (IntVal b val = bin-eval BinAnd (IntVal b x) (IntVal b y)) ∧

```

```

      (IntVal b val ≠ UndefVal)
    )) (is ?L = ?R)
proof (intro iffI)
  assume 3: ?L
  show ?R apply (rule evaltree.cases[OF 3])
    apply force+ apply auto[1] using intval-and.elims intval-bits.simps
    apply (smt (verit) new-int.simps new-int-bin.simps take-bit-and)
    by blast
next
  assume R: ?R
  then obtain x y where [m,p] ⊢ xe ↦ IntVal b x
    and [m,p] ⊢ ye ↦ IntVal b y
    and new-int b val = bin-eval BinAnd (IntVal b x) (IntVal b y)
    and new-int b val ≠ UndefVal
  by auto
  then show ?L
    using R by blast
qed

```

```

lemma mod-dist-over-add-right:
  fixes a b c :: int64
  fixes n :: nat
  assumes 1: 0 < n
  assumes 2: n < 64
  shows (a + b mod 2^n) mod 2^n = (a + b) mod 2^n
  using mod-dist-over-add
  by (simp add: 1 2 add.commute)

```

```

lemma numberOfLeadingZeros-range:
  0 ≤ numberOfLeadingZeros n ∧ numberOfLeadingZeros n ≤ Nat.size n
  unfolding numberOfLeadingZeros-def highestOneBit-def using max-set-bit
  by (simp add: highestOneBit-def leadingZeroBounds numberOfLeadingZeros-def)

```

```

lemma improved-opt:
  assumes numberOfLeadingZeros (↑z) + numberOfTrailingZeros (↑y) ≥ 64
  shows exp[(x + y) & z] ≥ exp[x & z]
  apply simp apply ((rule allI)+; rule impI)
  subgoal premises eval for m p v
proof -
  obtain n where n: n = 64 - numberOfLeadingZeros (↑z)
  by simp
  obtain b val where val: [m, p] ⊢ exp[(x + y) & z] ↦ IntVal b val
  by (metis BinaryExprE bin-eval-new-int eval new-int.simps)
  then obtain xv yv where addv: [m, p] ⊢ exp[x + y] ↦ IntVal b (xv + yv)
  apply (subst (asm) unfold-binary-width-and) by (metis add.right-neutral)
  then obtain yv where yv: [m, p] ⊢ y ↦ IntVal b yv
  apply (subst (asm) unfold-binary-width-add) by blast
  from addv obtain xv where xv: [m, p] ⊢ x ↦ IntVal b xv
  apply (subst (asm) unfold-binary-width-add) by blast

```

```

from val obtain zv where zv:  $[m, p] \vdash z \mapsto \text{IntVal } b \text{ } zv$ 
  apply (subst (asm) unfold-binary-width-and) by blast
have addv:  $[m, p] \vdash \text{exp}[x + y] \mapsto \text{new-int } b \text{ } (xv + yv)$ 
  apply (rule evaltree.BinaryExpr)
  using xv apply simp
  using yv apply simp
  by simp+
have lhs:  $[m, p] \vdash \text{exp}[(x + y) \& z] \mapsto \text{new-int } b \text{ } (\text{and } (xv + yv) \text{ } zv)$ 
  apply (rule evaltree.BinaryExpr)
  using addv apply simp
  using zv apply simp
  using addv apply auto[1]
  by simp
have rhs:  $[m, p] \vdash \text{exp}[x \& z] \mapsto \text{new-int } b \text{ } (\text{and } xv \text{ } zv)$ 
  apply (rule evaltree.BinaryExpr)
  using xv apply simp
  using zv apply simp
  apply force
  by simp
then show ?thesis
proof (cases numberOfLeadingZeros ( $\uparrow z$ )  $> 0$ )
  case True
  have n-bounds:  $0 \leq n \wedge n < 64$ 
    using diff-le-self n numberOfLeadingZeros-range
    by (simp add: True)
  have and  $(xv + yv) \text{ } zv = \text{and } ((xv + yv) \bmod 2^n) \text{ } zv$ 
    using L1 n zv by blast
  also have  $\dots = \text{and } ((xv + (yv \bmod 2^n)) \bmod 2^n) \text{ } zv$ 
    using mod-dist-over-add-right n-bounds
    by (metis take-bit-0 take-bit-eq-mod zero-less-iff-neq-zero)
  also have  $\dots = \text{and } (((xv \bmod 2^n) + (yv \bmod 2^n)) \bmod 2^n) \text{ } zv$ 
    by (metis bits-mod-by-1 mod-dist-over-add n-bounds order-le-imp-less-or-eq
power-0)
  also have  $\dots = \text{and } ((xv \bmod 2^n) \bmod 2^n) \text{ } zv$ 
    using L2 n zv yv
    using assms by auto
  also have  $\dots = \text{and } (xv \bmod 2^n) \text{ } zv$ 
    using mod-mod-trivial
  by (smt (verit, best) and.idem take-bit-eq-mask take-bit-eq-mod word-bw-assocs(1))
  also have  $\dots = \text{and } xv \text{ } zv$ 
    using L1 n zv by metis
  finally show ?thesis
    using eval lhs rhs
    by (metis evalDet)
next
  case False
  then have numberOfLeadingZeros ( $\uparrow z$ )  $= 0$ 
    by simp
  then have numberOfTrailingZeros ( $\uparrow y$ )  $\geq 64$ 

```

```

    using assms(1)
    by fastforce
  then have yv = 0
    using yv
    by (metis (no-types, lifting) L1 L2 add-diff-cancel-left' and.comm-neutral
and.idem bit.compl-zero bit.conj-cancel-right bit.conj-disj-distrib(1) bit.double-compl
less-imp-diff-less linorder-not-le word-not-dist(2))
    then show ?thesis
      by (metis add.right-neutral eval evalDet lhs rhs)
  qed
qed
done

thm-oracles improved-opt

lemma falseBelowN-nBelowLowest:
  assumes  $n \leq \text{Nat.size } a$ 
  assumes  $\forall i < n. \neg(\text{bit } a \ i)$ 
  shows  $\text{lowestOneBit } a \geq n$ 
proof (cases  $\{i. \text{bit } a \ i\} = \{\}$ )
  case True
  then show ?thesis unfolding lowestOneBit-def MinOrHighest-def
    using assms(1) trans-le-add1 by presburger
next
  case False
  have  $n \leq \text{Min } (\text{Collect } (\text{bit } a))$ 
  by (metis False Min-ge-iff assms(2) finite-bit-word linorder-le-less-linear mem-Collect-eq)
  then show ?thesis unfolding lowestOneBit-def MinOrHighest-def
    using False by presburger
qed

lemma noZeros-Count:
  fixes  $a :: 64 \text{ word}$ 
  assumes  $\text{zeroCount } a = 0$ 
  shows  $i < \text{Nat.size } a \longrightarrow \text{bit } a \ i$ 
  using assms unfolding zeroCount-def size64
  using zeroCount-finite by auto

lemma allZeros-Count:
  fixes  $a :: 64 \text{ word}$ 
  assumes  $\text{zeroCount } a = 64$ 
  shows  $\neg(\text{bit } a \ i)$ 
  using assms unfolding zeroCount-def size64
  using zeroCount-finite apply auto sorry

lemma zeroBits:
  fixes  $a :: 'a::\text{len word}$ 
  shows  $(\forall i. \neg(\text{bit } a \ i)) \longleftrightarrow a = 0$ 
  apply auto

```

```

by (simp add: bit-word-eqI)

lemma mask-bit-iff:
  fixes a :: 'a::len word
  assumes n ≤ Nat.size a
  shows a = mask n ⟹ bit a i ⟷ i < n
  apply auto
  using Word.bit-mask-iff
  apply auto[1] using assms
  by (simp add: Word.bit-mask-iff wsst-TYs(3))

lemma maskBitCount:
  fixes a :: 'a::len word
  assumes n ≤ Nat.size a
  shows a = mask n ⟹ card {i. bit a i} = n
  using mask-bit-iff assms
  by fastforce

lemma packedMask:
  fixes a :: 64 word
  assumes numberOfLeadingZeros a = zeroCount a
  shows a = mask (64 - numberOfLeadingZeros a)
  using assms
proof (induction 64 - numberOfLeadingZeros a)
  case 0
  have numberOfLeadingZeros a = 64
  by (metis 0.hyps local.numberOfLeadingZeros-range nat-less-le size64 zero-less-diff)
  then have zeroCount a = 64
  using assms by fastforce
  then have a = 0
  using allZeros-Count zeroBits by blast
  then show ?case
  by (simp add: 0.hyps)
next
  case (Suc x)
  then have numberOfLeadingZeros a = 64 - Suc x
  by (metis add-diff-cancel-right' add-diff-inverse-nat less-numeral-extra(3) nat-diff-split
  zero-less-Suc)
  then have zeroCount a = 64 - Suc x
  using assms by presburger
  from Suc show ?case sorry
qed

lemma zerosAboveOnly:
  fixes a :: 64 word
  assumes numberOfLeadingZeros a = zeroCount a
  shows ¬(bit a i) ⟹ i ≥ (64 - numberOfLeadingZeros a)
proof -

```



```

obtain  $n$  where  $n$ :  $n = 64 - \text{numberOfLeadingZeros } a$ 
  by simp
then have  $n\text{-range}$ :  $n \leq \text{Nat.size } a$ 
  using size64
  by presburger
then have  $a = (\text{mask } n)$ 
  using packedMask
  using assms n by blast
then have  $\neg \text{bit } a \ i \longrightarrow i \geq n$ 
  using Word.bit-mask-iff
  by (metis (mono-tags) le-antisym linorder-le-less-linear min-def n-range word-size)
then show ?thesis using  $n$ 
  by blast
qed

```

end

```

lemma ucast-zero:  $(\text{ucast } (0::\text{int64})::\text{int32}) = 0$ 
  by simp

```

```

lemma ucast-minus-one:  $(\text{ucast } (-1::\text{int64})::\text{int32}) = -1$ 
  apply transfer by auto

```

```

interpretation simple-mask: stamp-mask
   $\text{IRExpr-up} :: \text{IRExpr} \Rightarrow \text{int64}$ 
   $\text{IRExpr-down} :: \text{IRExpr} \Rightarrow \text{int64}$ 
  unfolding IRExpr-up-def IRExpr-down-def
  apply unfold-locales
  by (simp add: ucast-minus-one)+

```

```

phase NewAnd
  terminating size
begin

```

```

optimization redundant-lhs-y-or:  $((x \mid y) \ \& \ z) \longmapsto x \ \& \ z$ 
  when  $((\text{and } (\text{IRExpr-up } y) (\text{IRExpr-up } z)) = 0)$ 
  apply (simp add: IRExpr-up-def)
  using simple-mask.exp-eliminate-y by blast

```

```

optimization redundant-lhs-x-or:  $((x \mid y) \ \& \ z) \longmapsto y \ \& \ z$ 
  when  $((\text{and } (\text{IRExpr-up } x) (\text{IRExpr-up } z)) = 0)$ 
  apply (simp add: IRExpr-up-def)
  using simple-mask.exp-eliminate-y

```

```

    by (meson exp-or-commute mono-binary order-refl order-trans)

optimization redundant-rhs-y-or: (z & (x | y))  $\mapsto$  z & x
    when (((and (IRExpr-up y) (IRExpr-up z)) = 0))
    apply (simp add: IRExpr-up-def)
    using simple-mask.exp-eliminate-y
    by (meson exp-and-commute order.trans)

optimization redundant-rhs-x-or: (z & (x | y))  $\mapsto$  z & y
    when (((and (IRExpr-up x) (IRExpr-up z)) = 0))
    apply (simp add: IRExpr-up-def)
    using simple-mask.exp-eliminate-y
    by (meson dual-order.trans exp-and-commute exp-or-commute mono-binary or-
        der-refl)

end

end

```

1.8 NotNode Phase

```

theory NotPhase
  imports
    Common
  begin

  phase NotNode
    terminating size
  begin

  lemma bin-not-cancel:
    bin[¬(¬(e))] = bin[e]
    by auto

  lemma val-not-cancel:
    assumes val[¬(new-int b v)] ≠ UndefVal
    shows val[¬(¬(new-int b v))] = (new-int b v)
    using bin-not-cancel
    by (simp add: take-bit-not-take-bit)

  lemma exp-not-cancel:
    shows exp[¬(¬a)] ≥ exp[a]
    using val-not-cancel apply auto
    by (metis eval-unused-bits-zero intval-logic-negation.cases intval-not.simps(1))

```

intval-not.simps(2) intval-not.simps(3) intval-not.simps(4) new-int.simps)

Optimisations

optimization *NotCancel*: $\text{exp}[\sim(\sim a)] \mapsto a$
by (*metis exp-not-cancel*)

end

end

1.9 OrNode Phase

theory *OrPhase*

imports

Common

begin

phase *OrNode*

terminating *size*

begin

lemma *bin-or-equal*:

$\text{bin}[x \mid x] = \text{bin}[x]$

by *simp*

lemma *bin-shift-const-right-helper*:

$x \mid y = y \mid x$

by *simp*

lemma *bin-or-not-operands*:

$(\sim x \mid \sim y) = (\sim(x \& y))$

by *simp*

lemma *val-or-equal*:

assumes $x = \text{new-int } b \ v$

and $(\text{val}[x \mid x] \neq \text{UndefVal})$

shows $\text{val}[x \mid x] = \text{val}[x]$

apply (*cases x; auto*) **using** *bin-or-equal assms*

by *auto+*

lemma *val-elim-redundant-false*:

assumes $x = \text{new-int } b \ v$

and $\text{val}[x \mid \text{false}] \neq \text{UndefVal}$

shows $\text{val}[x \mid \text{false}] = \text{val}[x]$

using *assms* **apply** (*cases x; auto*) **by** *presburger*

lemma *val-shift-const-right-helper*:

```

    val[x | y] = val[y | x]
    apply (cases x; cases y; auto)
    by (simp add: or.commute)+

lemma val-or-not-operands:
  val[~x | ~y] = val[~(x & y)]
  apply (cases x; cases y; auto)
  by (simp add: take-bit-not-take-bit)

lemma exp-or-equal:
  exp[x | x] ≥ exp[x]
  using val-or-equal apply auto
  by (smt (verit, ccfv-SIG) evalDet eval-unused-bits-zero intval-negate.elims int-
    val-or.simps(2)
    intval-or.simps(6) intval-or.simps(7) new-int.simps val-or-equal)

lemma exp-elim-redundant-false:
  exp[x | false] ≥ exp[x]
  using val-elim-redundant-false apply auto
  by (smt (verit) Value.sel(1) eval-unused-bits-zero intval-or.elims new-int.simps
    new-int-bin.simps val-elim-redundant-false)

Optimisations

optimization OrEqual: x | x ⟶ x
  by (meson exp-or-equal le-expr-def)

optimization OrShiftConstantRight: ((const x) | y) ⟶ y | (const x) when ¬(is-ConstantExpr
  y)
  using size-flip-binary apply force
  apply auto
  by (simp add: BinaryExpr unfold-const val-shift-const-right-helper)

optimization EliminateRedundantFalse: x | false ⟶ x
  by (meson exp-elim-redundant-false le-expr-def)

optimization OrNotOperands: (~x | ~y) ⟶ ~(x & y)
  apply (metis add-2-eq-Suc' less-SucI not-add-less1 not-less-eq size-binary-const
    size-non-add)
  apply auto using val-or-not-operands
  by (metis BinaryExpr UnaryExpr bin-eval.simps(4) intval-not.simps(2) unary-eval.simps(3))

end

context stamp-mask
begin

```

Taking advantage of the truth table of or operations.

#	x	y	$x y$
1	0	0	0
2	0	1	1
3	1	0	1
4	1	1	1

If row 2 never applies, that is, $\text{canBeZero } x \ \& \ \text{canBeOne } y = 0$, then $(x|y) = x$.

Likewise, if row 3 never applies, $\text{canBeZero } y \ \& \ \text{canBeOne } x = 0$, then $(x|y) = y$.

lemma *OrLeftFallthrough:*

```

assumes (and (not ( $\downarrow x$ )) ( $\uparrow y$ )) = 0
shows  $\text{exp}[x \mid y] \geq \text{exp}[x]$ 
using assms
apply simp apply ((rule allI)+; rule impI)
subgoal premises eval for  $m \ p \ v$ 
proof –
  obtain  $b \ vv$  where  $e: [m, p] \vdash \text{exp}[x \mid y] \mapsto \text{IntVal } b \ vv$ 
    using eval
    by (metis BinaryExprE bin-eval-new-int new-int.simps)
  from  $e$  obtain  $xv$  where  $xv: [m, p] \vdash x \mapsto \text{IntVal } b \ xv$ 
  apply (subst (asm) unfold-binary-width)
  by force+
  from  $e$  obtain  $yv$  where  $yv: [m, p] \vdash y \mapsto \text{IntVal } b \ yv$ 
  apply (subst (asm) unfold-binary-width)
  by force+
  have vdef:  $v = \text{intval-or } (\text{IntVal } b \ xv) \ (\text{IntVal } b \ yv)$ 
    using  $e \ xv \ yv$ 
    by (metis bin-eval.simps(5) eval(2) evalDet unfold-binary)
  have  $\forall i. (\text{bit } xv \ i) \mid (\text{bit } yv \ i) = (\text{bit } xv \ i)$ 
    by (metis assms bit-and-iff not-down-up-mask-and-zero-implies-zero xv yv)
  then have  $\text{IntVal } b \ xv = \text{intval-or } (\text{IntVal } b \ xv) \ (\text{IntVal } b \ yv)$ 
    by (smt (verit, ccfv-threshold) and.idem assms bit.conj-disj-distrib eval-unused-bits-zero
intval-or.simps(1) new-int.simps new-int-bin.simps not-down-up-mask-and-zero-implies-zero
word-ao-absorbs(3) xv yv)
  then show ?thesis
    using vdef
    using  $xv$  by presburger
qed
done

```

lemma *OrRightFallthrough:*

```

assumes (and (not ( $\downarrow y$ )) ( $\uparrow x$ )) = 0
shows  $\text{exp}[x \mid y] \geq \text{exp}[y]$ 
using assms
apply simp apply ((rule allI)+; rule impI)
subgoal premises eval for  $m \ p \ v$ 
proof –

```

```

obtain  $b\ vv$  where  $e: [m, p] \vdash \text{exp}[x \mid y] \mapsto \text{IntVal } b\ vv$ 
  using  $\text{eval}$ 
  by ( $\text{metis BinaryExprE bin-eval-new-int new-int.simps}$ )
from  $e$  obtain  $xv$  where  $xv: [m, p] \vdash x \mapsto \text{IntVal } b\ xv$ 
  apply ( $\text{subst (asm) unfold-binary-width}$ )
  by  $\text{force+}$ 
from  $e$  obtain  $yv$  where  $yv: [m, p] \vdash y \mapsto \text{IntVal } b\ yv$ 
  apply ( $\text{subst (asm) unfold-binary-width}$ )
  by  $\text{force+}$ 
have  $v\text{def}: v = \text{intval-or } (\text{IntVal } b\ xv) (\text{IntVal } b\ yv)$ 
  using  $e\ xv\ yv$ 
  by ( $\text{metis bin-eval.simps(5) eval(2) evalDet unfold-binary}$ )
have  $\forall i. (\text{bit } xv\ i) \mid (\text{bit } yv\ i) = (\text{bit } yv\ i)$ 
  by ( $\text{metis assms bit-and-iff not-down-up-mask-and-zero-implies-zero } xv\ yv$ )
then have  $\text{IntVal } b\ yv = \text{intval-or } (\text{IntVal } b\ xv) (\text{IntVal } b\ yv)$ 
  by ( $\text{metis (no-types, lifting) assms eval-unused-bits-zero intval-or.simps(1)}$ 
 $\text{new-int.elims new-int-bin.elims stamp-mask.not-down-up-mask-and-zero-implies-zero}$ 
 $\text{stamp-mask-axioms word-ao-absorbs(8) } xv\ yv$ )
  then show  $?thesis$ 
    using  $v\text{def}$ 
    using  $yv$  by  $\text{presburger}$ 
qed
done

```

end

end

1.10 ShiftNode Phase

theory ShiftPhase

imports

Common

begin

phase ShiftNode

terminating size

begin

fun $\text{intval-log2} :: \text{Value} \Rightarrow \text{Value}$ **where**

$\text{intval-log2 } (\text{IntVal } b\ v) = \text{IntVal } b\ (\text{word-of-int } (\text{SOME } e. v=2^e)) \mid$

$\text{intval-log2 } - = \text{UndefVal}$

fun $\text{in-bounds} :: \text{Value} \Rightarrow \text{int} \Rightarrow \text{int} \Rightarrow \text{bool}$ **where**

$\text{in-bounds } (\text{IntVal } b\ v) \ l\ h = (l < \text{sint } v \wedge \text{sint } v < h) \mid$

$\text{in-bounds } -\ l\ h = \text{False}$

lemma

assumes $\text{in-bounds } (\text{intval-log2 } \text{val-c})\ 0\ 32$

```

shows intval-left-shift x (intval-log2 val-c) = intval-mul x val-c
apply (cases val-c; auto) using intval-left-shift.simps(1) intval-mul.simps(1)
intval-log2.simps(1)
sorry

lemma e-intval:
  n = intval-log2 val-c ∧ in-bounds n 0 32  $\longrightarrow$ 
    intval-left-shift x (intval-log2 val-c) =
      intval-mul x val-c
proof (rule impI)
  assume n = intval-log2 val-c ∧ in-bounds n 0 32
  show intval-left-shift x (intval-log2 val-c) =
    intval-mul x val-c
  proof (cases  $\exists v . val-c = IntVal\ 32\ v$ )
    case True
      obtain vc where val-c = IntVal 32 vc
      using True by blast
      then have n = IntVal 32 (word-of-int (SOME e. vc=2e))
      using  $\langle n = intval-log2\ val-c \wedge in-bounds\ n\ 0\ 32 \rangle$  intval-log2.simps(1) by
        presburger
      then show ?thesis sorry
    next
      case False
      then have  $\exists v . val-c = IntVal\ 64\ v$ 
      sorry
      then obtain vc where val-c = IntVal 64 vc
      by auto
      then have n = IntVal 64 (word-of-int (SOME e. vc=2e))
      using  $\langle n = intval-log2\ val-c \wedge in-bounds\ n\ 0\ 32 \rangle$  intval-log2.simps(1) by
        presburger
      then show ?thesis sorry
qed
qed

```

```

optimization e:
  x * (const c)  $\longmapsto$  x << (const n) when (n = intval-log2 c ∧ in-bounds n 0 32)
  using e-intval
  using BinaryExprE ConstantExprE bin-eval.simps(2,7) sorry

end

end

```

1.11 SignedDivNode Phase

```

theory SignedDivPhase
imports

```

```

    Common
begin

phase SignedDivNode
  terminating size
begin

lemma val-division-by-one-is-self-32:
  assumes  $x = \text{new-int } 32 \ v$ 
  shows  $\text{intval-div } x \ (\text{IntVal } 32 \ 1) = x$ 
  using assms apply (cases  $x$ ; auto)
  by (simp add: take-bit-signed-take-bit)

end

end

```

1.12 SignedRemNode Phase

```

theory SignedRemPhase
  imports
    Common
begin

phase SignedRemNode
  terminating size
begin

lemma val-remainder-one:
  assumes  $\text{intval-mod } x \ (\text{IntVal } 32 \ 1) \neq \text{UndefVal}$ 
  shows  $\text{intval-mod } x \ (\text{IntVal } 32 \ 1) = \text{IntVal } 32 \ 0$ 
  using assms apply (cases  $x$ ; auto) sorry

value word-of-int (sint ( $x2::32 \ \text{word}$ ) smod 1)

end

end

```

1.13 SubNode Phase

```

theory SubPhase
  imports
    Common
    Proofs.StampEvalThms

```



```

begin

phase SubNode
  terminating size
begin

lemma bin-sub-after-right-add:
  shows  $((x :: ('a :: len) \text{ word}) + (y :: ('a :: len) \text{ word})) - y = x$ 
  by simp

lemma sub-self-is-zero:
  shows  $(x :: ('a :: len) \text{ word}) - x = 0$ 
  by simp

lemma bin-sub-then-left-add:
  shows  $(x :: ('a :: len) \text{ word}) - (x + (y :: ('a :: len) \text{ word})) = -y$ 
  by simp

lemma bin-sub-then-left-sub:
  shows  $(x :: ('a :: len) \text{ word}) - (x - (y :: ('a :: len) \text{ word})) = y$ 
  by simp

lemma bin-subtract-zero:
  shows  $(x :: 'a :: len \text{ word}) - (0 :: 'a :: len \text{ word}) = x$ 
  by simp

lemma bin-sub-negative-value:
  shows  $(x :: ('a :: len) \text{ word}) - (-(y :: ('a :: len) \text{ word})) = x + y$ 
  by simp

lemma bin-sub-self-is-zero:
  shows  $(x :: ('a :: len) \text{ word}) - x = 0$ 
  by simp

lemma bin-sub-negative-const:
  shows  $(x :: 'a :: len \text{ word}) - (-(y :: 'a :: len \text{ word})) = x + y$ 
  by simp

lemma val-sub-after-right-add-2:
  assumes  $x = \text{new-int } b \ v$ 
  assumes  $\text{val}[(x + y) - y] \neq \text{UndefVal}$ 
  shows  $\text{val}[(x + y) - y] = \text{val}[x]$ 
  using bin-sub-after-right-add
  using assms apply (cases x; cases y; auto)
  by (metis (full-types) intval-sub.simps(2))

lemma val-sub-after-left-sub:

```

```

assumes  $val[(x - y) - x] \neq \text{UndefVal}$ 
shows  $val[(x - y) - x] = val[-y]$ 
using assms apply (cases x; cases y; auto)
using intval-sub.elims by fastforce

lemma val-sub-then-left-sub:
  assumes  $y = \text{new-int } b \ v$ 
  assumes  $val[x - (x - y)] \neq \text{UndefVal}$ 
  shows  $val[x - (x - y)] = val[y]$ 
  using assms apply (cases x; cases y; auto)
  by (metis (mono-tags) intval-sub.simps(5))

lemma val-subtract-zero:
  assumes  $x = \text{new-int } b \ v$ 
  assumes  $\text{intval-sub } x \ (\text{IntVal } b \ 0) \neq \text{UndefVal}$ 
  shows  $\text{intval-sub } x \ (\text{IntVal } b \ 0) = val[x]$ 
  using assms by (induction x; simp)

lemma val-zero-subtract-value:
  assumes  $x = \text{new-int } b \ v$ 
  assumes  $\text{intval-sub } (\text{IntVal } b \ 0) \ x \neq \text{UndefVal}$ 
  shows  $\text{intval-sub } (\text{IntVal } b \ 0) \ x = val[-x]$ 
  using assms by (induction x; simp)

lemma val-sub-then-left-add:
  assumes  $val[x - (x + y)] \neq \text{UndefVal}$ 
  shows  $val[x - (x + y)] = val[-y]$ 
  using assms apply (cases x; cases y; auto)
  by (metis (mono-tags, lifting) intval-sub.simps(5))

lemma val-sub-negative-value:
  assumes  $val[x - (-y)] \neq \text{UndefVal}$ 
  shows  $val[x - (-y)] = val[x + y]$ 
  using assms by (cases x; cases y; auto)

lemma val-sub-self-is-zero:
  assumes  $x = \text{new-int } b \ v \wedge val[x - x] \neq \text{UndefVal}$ 
  shows  $val[x - x] = \text{new-int } b \ 0$ 
  using assms by (cases x; auto)

lemma val-sub-negative-const:
  assumes  $y = \text{new-int } b \ v \wedge val[x - (-y)] \neq \text{UndefVal}$ 
  shows  $val[x - (-y)] = val[x + y]$ 
  using assms by (cases x; cases y; auto)

lemma exp-sub-after-right-add:
  shows  $\text{exp}[(x + y) - y] \geq \text{exp}[x]$ 
  apply auto using val-sub-after-right-add-2

```

```

using evalDet eval-unused-bits-zero intval-add.elims new-int.simps
by (smt (verit))

lemma exp-sub-after-right-add2:
shows  $\exp[(x + y) - x] \geq \exp[y]$ 
using exp-sub-after-right-add apply auto
using bin-eval.simps(1) bin-eval.simps(3) intval-add-sym unfold-binary
by (smt (z3) Value.inject(1) diff-eq-eq evalDet eval-unused-bits-zero intval-add.elims

    intval-sub.elims new-int.simps new-int-bin.simps take-bit-dist-subL)

lemma exp-sub-negative-value:
 $\exp[x - (-y)] \geq \exp[x + y]$ 
apply simp using val-sub-negative-value
by (smt (verit) bin-eval.simps(1) bin-eval.simps(3) evaltree-not-undef
    unary-eval.simps(2) unfold-binary unfold-unary)

lemma exp-sub-then-left-sub:
shows  $\exp[x - (x - y)] \geq \exp[y]$ 
using val-sub-then-left-sub apply auto
subgoal premises  $p$  for  $m$   $p$   $xa$   $xaa$   $ya$ 
proof -
  obtain  $xa$  where  $xa: [m, p] \vdash x \mapsto xa$ 
    using  $p(2)$  by blast
  obtain  $ya$  where  $ya: [m, p] \vdash y \mapsto ya$ 
    using  $p(5)$  by auto
  obtain  $xaa$  where  $xaa: [m, p] \vdash x \mapsto xaa$ 
    using  $p(2)$  by blast
  have  $1: \text{val}[xa - (xaa - ya)] \neq \text{UndefVal}$ 
    by (metis evalDet  $p(2)$   $p(3)$   $p(4)$   $p(5)$   $xa$   $xaa$   $ya$ )
  then have  $\text{val}[xaa - ya] \neq \text{UndefVal}$ 
    by auto
  then have  $[m, p] \vdash y \mapsto \text{val}[xa - (xaa - ya)]$ 
    by (metis 1 Value.exhaust evalDet eval-unused-bits-zero evaltree-not-undef
    intval-sub.simps(6) intval-sub.simps(7) new-int.simps  $p(5)$  val-sub-then-left-sub  $xa$ 
     $xaa$   $ya$ )
  then show ?thesis
    by (metis evalDet  $p(2)$   $p(4)$   $p(5)$   $xa$   $xaa$   $ya$ )
qed
done

```

thm-oracles exp-sub-then-left-sub

Optimisations

optimization SubAfterAddRight: $((x + y) - y) \mapsto x$
using exp-sub-after-right-add **by** blast

optimization SubAfterAddLeft: $((x + y) - x) \mapsto y$
using exp-sub-after-right-add2 **by** blast

optimization *SubAfterSubLeft*: $((x - y) - x) \mapsto -y$
apply (*metis Suc-lessI add-2-eq-Suc' add-less-cancel-right less-trans-Suc not-add-less1*
size-binary-const size-binary-lhs size-binary-rhs size-non-add)
apply *auto*
by (*metis evalDet unary-eval.simps(2) unfold-unary val-sub-after-left-sub*)

optimization *SubThenAddLeft*: $(x - (x + y)) \mapsto -y$
apply *auto*
by (*metis evalDet unary-eval.simps(2) unfold-unary*
val-sub-then-left-add)

optimization *SubThenAddRight*: $(y - (x + y)) \mapsto -x$
apply *auto*
by (*metis evalDet intval-add-sym unary-eval.simps(2) unfold-unary*
val-sub-then-left-add)

optimization *SubThenSubLeft*: $(x - (x - y)) \mapsto y$
using *size-simps* **apply** *simp*
using *exp-sub-then-left-sub* **by** *blast*

optimization *SubtractZero*: $(x - (\text{const IntVal } b \ 0)) \mapsto x$
apply *auto*
by (*smt (verit) add.right-neutral diff-add-cancel eval-unused-bits-zero intval-sub.elims*
intval-word.simps new-int.simps new-int-bin.simps)

thm-oracles *SubtractZero*

optimization *SubNegativeValue*: $(x - (-y)) \mapsto x + y$
apply (*metis add-2-eq-Suc' less-SucI less-add-Suc1 not-less-eq size-binary-const*
size-non-add)
using *exp-sub-negative-value* **by** *simp*

thm-oracles *SubNegativeValue*

lemma *negate-idempotent*:
assumes $x = \text{IntVal } b \ v \wedge \text{take-bit } b \ v = v$
shows $x = \text{val}[-(-x)]$
using *assms*
using *is-IntVal-def* **by** *force*

optimization *ZeroSubtractValue*: $((\text{const IntVal } b \ 0) - x) \mapsto (-x)$

```

                                when (wf-stamp x ∧ stamp-expr x = IntegerStamp b lo
hi ∧ ¬(is-ConstantExpr x))
  defer
  apply auto unfolding wf-stamp-def
  apply (smt (verit) diff-0 intval-negate.simps(1) intval-sub.elims intval-word.simps

                                new-int-bin.simps unary-eval.simps(2) unfold-unary)
  using add-2-eq-Suc' size.simps(2) size-flip-binary by presburger

```

```

optimization SubSelfIsZero:  $(x - x) \mapsto \text{const IntVal } b \ 0$  when
                                (wf-stamp x ∧ stamp-expr x = IntegerStamp b lo hi)
  apply simp-all
  apply auto
  using IRExpr.disc(42) One-nat-def size-non-const apply presburger
  by (smt (verit, best) ConstantExpr evalDet eval-bits-1-64 eval-unused-bits-zero
new-int.simps take-bit-of-0 val-sub-self-is-zero validDefIntConst valid-int wf-stamp-def)

end

end

```

1.14 XorNode Phase

```

theory XorPhase
  imports
    Common
    Proofs.StampEvalThms
begin

  phase XorNode
    terminating size
begin

```

```

lemma bin-xor-self-is-false:
  bin[x ⊕ x] = 0
  by simp

```

```

lemma bin-xor-commute:
  bin[x ⊕ y] = bin[y ⊕ x]
  by (simp add: xor.commute)

```

```

lemma bin-eliminate-redundant-false:
  bin[x ⊕ 0] = bin[x]
  by simp

```

```

lemma val-xor-self-is-false:
  assumes  $\text{val}[x \oplus x] \neq \text{UndefVal}$ 
  shows  $\text{val-to-bool} (\text{val}[x \oplus x]) = \text{False}$ 
  using assms by (cases x; auto)

lemma val-xor-self-is-false-2:
  assumes  $(\text{val}[x \oplus x]) \neq \text{UndefVal}$ 
  and  $x = \text{IntVal } 32 \ v$ 
  shows  $\text{val}[x \oplus x] = \text{bool-to-val } \text{False}$ 
  using assms by (cases x; auto)

lemma val-xor-self-is-false-3:
  assumes  $\text{val}[x \oplus x] \neq \text{UndefVal} \wedge x = \text{IntVal } 64 \ v$ 
  shows  $\text{val}[x \oplus x] = \text{IntVal } 64 \ 0$ 
  using assms by (cases x; auto)

lemma val-xor-commute:
   $\text{val}[x \oplus y] = \text{val}[y \oplus x]$ 
  apply (cases x; cases y; auto)
  by (simp add: xor.commute)+

lemma val-eliminate-redundant-false:
  assumes  $x = \text{new-int } b \ v$ 
  assumes  $\text{val}[x \oplus (\text{bool-to-val } \text{False})] \neq \text{UndefVal}$ 
  shows  $\text{val}[x \oplus (\text{bool-to-val } \text{False})] = x$ 
  using assms apply (cases x; auto)
  by meson

lemma exp-xor-self-is-false:
  assumes  $\text{wf-stamp } x \wedge \text{stamp-expr } x = \text{default-stamp}$ 
  shows  $\text{exp}[x \oplus x] \geq \text{exp}[\text{false}]$ 
  using assms apply auto unfolding wf-stamp-def
  using IntVal0 Value.inject(1) bool-to-val.simps(2) constantAsStamp.simps(1)
evalDet
  int-signed-value-bounds new-int.simps unfold-const val-xor-self-is-false-2
valid-int
  valid-stamp.simps(1) valid-value.simps(1)
  by (smt (z3) validDefIntConst)

lemma exp-eliminate-redundant-false:
  shows  $\text{exp}[x \oplus \text{false}] \geq \text{exp}[x]$ 
  using val-eliminate-redundant-false apply auto
  subgoal premises p for m p xa
  proof  $-$ 
    obtain xa where xa:  $[m, p] \vdash x \mapsto xa$ 
    using p(2) by blast

```

```

    then have  $\text{val}[xa \oplus (\text{IntVal } 32 \ 0)] \neq \text{UndefVal}$ 
    using  $\text{evalDet } p(2) \ p(3)$  by blast
    then have  $[m,p] \vdash x \mapsto \text{val}[xa \oplus (\text{IntVal } 32 \ 0)]$ 
    apply (cases  $xa$ ; auto) using  $\text{eval-unused-bits-zero } xa$  by auto
    then show ?thesis
    using  $\text{evalDet } p(2) \ xa$  by blast
  qed
done

```

Optimisations

```

optimization XorSelfIsFalse:  $(x \oplus x) \mapsto \text{false}$  when
    ( $\text{wf-stamp } x \wedge \text{stamp-expr } x = \text{default-stamp}$ )
    using  $\text{size-non-const}$  apply force
    using  $\text{exp-xor-self-is-false}$  by auto

```

```

optimization XorShiftConstantRight:  $((\text{const } x) \oplus y) \mapsto y \oplus (\text{const } x)$  when
 $\neg(\text{is-ConstantExpr } y)$ 
    using  $\text{size-flip-binary}$  apply force
    unfolding  $\text{le-expr-def}$  using  $\text{val-xor-commute}$ 
    by auto

```

```

optimization EliminateRedundantFalse:  $(x \oplus \text{false}) \mapsto x$ 
    using  $\text{exp-eliminate-redundant-false}$  by blast

```

end

end

1.15 NegateNode Phase

```

theory NegatePhase

```

```

    imports

```

```

        Common

```

```

begin

```

```

phase NegateNode

```

```

    terminating size

```

```

begin

```

```

lemma bin-negative-cancel:

```

```

     $-1 * (-1 * ((x::('a::len) \text{word}))) = x$ 

```

```

    by auto

```

```

lemma val-negative-cancel:
  assumes intval-negate (new-int b v)  $\neq$  UndefVal
  shows  $\text{val}[-(-(\text{new-int } b \ v))] = \text{val}[\text{new-int } b \ v]$ 
  using assms by simp

lemma val-distribute-sub:
  assumes  $x \neq \text{UndefVal} \wedge y \neq \text{UndefVal}$ 
  shows  $\text{val}[-(x - y)] = \text{val}[y - x]$ 
  using assms by (cases x; cases y; auto)

lemma exp-distribute-sub:
  shows  $\text{exp}[-(x - y)] \geq \text{exp}[y - x]$ 
  using val-distribute-sub apply auto
  using evaltree-not-undef by auto

thm-oracles exp-distribute-sub

lemma exp-negative-cancel:
  shows  $\text{exp}[-(-x)] \geq \text{exp}[x]$ 
  using val-negative-cancel apply auto
  by (metis (no-types, opaque-lifting) eval-unused-bits-zero intval-negate.elims
    intval-negate.simps(1) minus-equation-iff new-int.simps take-bit-dist-neg)

lemma exp-negative-shift:
  assumes stamp-expr  $x = \text{IntegerStamp } b' \text{ lo } hi$ 
  and  $\text{unat } y = (b' - 1)$ 
  shows  $\text{exp}[-(x >> (\text{const } (\text{new-int } b \ y)))] \geq \text{exp}[x >>> (\text{const } (\text{new-int } b \ y))]$ 
  apply auto
  subgoal premises p for m p xa
  proof -
    obtain xa where xa:  $[m, p] \vdash x \mapsto xa$ 
    using p(2) by auto
    then have 1: intval-negate (intval-right-shift xa (IntVal b (take-bit b y)))  $\neq$ 
UndefVal
    using evalDet p(1) p(2) by blast
    then have 2: intval-right-shift xa (IntVal b (take-bit b y)))  $\neq$  UndefVal
    by auto
    then have 3:  $-((2::\text{int}) \wedge b \text{ div } (2::\text{int})) \sqsubseteq \text{sint } (\text{signed-take-bit } (b - \text{Suc } (0::\text{nat})) (\text{take-bit } b \ y))$ 
    by (simp add: p(6))
    then have 4:  $\text{sint } (\text{signed-take-bit } (b - \text{Suc } (0::\text{nat})) (\text{take-bit } b \ y)) < (2::\text{int})$ 
     $\wedge b \text{ div } (2::\text{int})$ 
    using p(7) by blast
    then have 5:  $(0::\text{nat}) < b$ 
    by (simp add: p(4))
    then have 6:  $b \sqsubseteq (64::\text{nat})$ 
    by (simp add: p(5))
    then have 7:  $[m, p] \vdash \text{BinaryExpr } \text{BinURightShift } x$ 

```



```

      (ConstantExpr (IntVal b (take-bit b y)))  $\mapsto$ 
      intval-negate (intval-right-shift xa (IntVal b (take-bit b y)))
    apply (cases y; auto)

  subgoal premises p for n
  proof -
    have sg1: y = word-of-nat n
    by (simp add: p(1))
    then have sg2: n < (18446744073709551616::nat)
    by (simp add: p(2))
    then have sg3: b  $\sqsubseteq$  (64::nat)
    by (simp add: 6)
    then have sg4: [m,p]  $\vdash$  BinaryExpr BinURightShift x
      (ConstantExpr (IntVal b (take-bit b (word-of-nat n))))  $\mapsto$ 
      intval-negate (intval-right-shift xa (IntVal b (take-bit b (word-of-nat
n))))))
    sorry
    then show ?thesis
    by simp
  qed
done
then show ?thesis
by (metis evalDet p(2) xa)
qed
done

```

Optimisations

```

optimization NegateCancel:  $\neg(\neg(x)) \mapsto x$ 
  using val-negative-cancel exp-negative-cancel by blast

```

```

optimization DistributeSubtraction:  $\neg(x - y) \mapsto (y - x)$ 
  apply (smt (z3) add.left-commute add-2-eq-Suc' add-diff-cancel-left' is-ConstantExpr-def
less-Suc-eq-0-disj plus-1-eq-Suc size.simps(11) size-binary-const size-non-add zero-less-diff)
  using exp-distribute-sub by simp

```

```

optimization NegativeShift:  $\neg(x >> (\text{const } (\text{new-int } b \ y))) \mapsto x >>> (\text{const }
(\text{new-int } b \ y))$ 
  when (stamp-expr x = IntegerStamp b' lo hi  $\wedge$  unat y
= (b' - 1))
  using exp-negative-shift by simp

```

end

end

```

theory TacticSolving
  imports Common

```

begin

```
fun size :: IRExpr  $\Rightarrow$  nat where
  size (UnaryExpr op e) = (size e) * 2 |
  size (BinaryExpr BinAdd x y) = (size x) + ((size y) * 2) |
  size (BinaryExpr op x y) = (size x) + (size y) |
  size (ConditionalExpr cond t f) = (size cond) + (size t) + (size f) + 2 |
  size (ConstantExpr c) = 1 |
  size (ParameterExpr ind s) = 2 |
  size (LeafExpr nid s) = 2 |
  size (ConstantVar c) = 2 |
  size (VariableExpr x s) = 2
```

```
lemma size-pos[simp]: 0 < size y
apply (induction y; auto?)
subgoal premises prems for op a b
  using prems by (induction op; auto)
done
```

```
phase TacticSolving
terminating size
begin
```

1.16 AddNode

```
lemma value-approx-implies-refinement:
  assumes lhs  $\approx$  rhs
  assumes  $\forall m\ p\ v. ([m, p] \vdash elhs \mapsto v) \longrightarrow v = lhs$ 
  assumes  $\forall m\ p\ v. ([m, p] \vdash erhs \mapsto v) \longrightarrow v = rhs$ 
  assumes  $\forall m\ p\ v1\ v2. ([m, p] \vdash elhs \mapsto v1) \longrightarrow ([m, p] \vdash erhs \mapsto v2)$ 
  shows elhs  $\geq$  erhs
  using assms unfolding le-expr-def well-formed-equal-def
  using evalDet evaltree-not-undef
  by metis
```

```
method explore-cases for x y :: Value =
  (cases x; cases y; auto)
```

```
method explore-cases-bin for x :: IRExpr =
  (cases x; auto)
```

```
method obtain-approx-eq for lhs rhs x y :: Value =
  (rule meta-mp[where P=lhs  $\approx$  rhs], defer-tac, explore-cases x y)
```

```
method obtain-eval for exp::IRExpr and val::Value =
  (rule meta-mp[where P= $\bigwedge m\ p\ v. ([m, p] \vdash exp \mapsto v) \Longrightarrow v = val$ ], defer-tac)
```

```
method solve for lhs rhs x y :: Value =
  (match conclusion in size - < size -  $\Rightarrow$   $\langle simp \rangle$ )?,
```

(*match conclusion in* (*elhs::IRExpr*) \geq (*erhs::IRExpr*) **for** *elhs erhs* \Rightarrow \langle
 (*obtain-approx-eq lhs rhs x y*)?)

print-methods

thm *BinaryExprE*

optimization *opt-add-left-negate-to-sub*:

$-x + y \mapsto y - x$

apply (*solve val*[-*x1* + *y1*] *val*[*y1* - *x1*] *x1 y1*)

apply simp apply auto using evaltree-not-undef sorry

1.17 NegateNode

lemma *val-distribute-sub*:

$\text{val}[-(x-y)] \approx \text{val}[y-x]$

by (*cases x; cases y; auto*)

optimization *distribute-sub*: $-(x-y) \mapsto (y-x)$

apply simp

using *val-distribute-sub* **apply simp**

using *unfold-binary unfold-unary* **by auto**

lemma *val-xor-self-is-false*:

assumes $x = \text{IntVal } 32 \ v$

shows $\text{val}[x \oplus x] \approx \text{val}[\text{false}]$

apply simp using assms by (*cases x; auto*)

definition *wf-stamp* :: *IRExpr* \Rightarrow *bool* **where**

$\text{wf-stamp } e = (\forall m \ p \ v. ([m, p] \vdash e \mapsto v) \longrightarrow \text{valid-value } v \ (\text{stamp-expr } e))$

lemma *exp-xor-self-is-false*:

assumes $\text{stamp-expr } x = \text{IntegerStamp } 32 \ l \ h$

assumes *wf-stamp* x

shows $\text{exp}[x \oplus x] \geq \text{exp}[\text{false}]$

unfolding *le-expr-def* **using** *assms* **unfolding** *wf-stamp-def*

using *val-xor-self-is-false evaltree-not-undef*

by (*smt (z3) bin-eval.simps(6) bin-eval-new-int constantAsStamp.simps(1) evalDet
 int-signed-value-bounds new-int.simps new-int-take-bits unfold-binary unfold-const
 valid-int valid-stamp.simps(1) valid-value.simps(1) well-formed-equal-defn*)

lemma *val-or-commute[simp]*:

$\text{val}[x \mid y] = \text{val}[y \mid x]$

apply (*cases x; cases y; auto*)

by (*simp add: or.commute*)+

lemma *val-xor-commute*[simp]:
 $val[x \oplus y] = val[y \oplus x]$
apply (cases x; cases y; auto)
by (simp add: word-bw-comms(3))

lemma *exp-or-commutative*:
 $exp[x \mid y] \geq exp[y \mid x]$
by auto

lemma *exp-xor-commutative*:
 $exp[x \oplus y] \geq exp[y \oplus x]$
by auto

lemma *OrInverseVal*:
assumes $n = IntVal\ 32\ v$
shows $val[n \mid \sim n] \approx new-int\ 32\ (-1)$
apply simp **using** assms **using** word-or-not **apply** (cases n; auto) **using** take-bit-or
by (metis bit.disj-cancel-right mask-eq-take-bit-minus-one)

optimization *OrInverse*: $exp[n \mid \sim n] \mapsto (const\ (new-int\ 32\ (not\ 0)))$
 $when\ (stamp-expr\ n = IntegerStamp\ 32\ l\ h \wedge wf-stamp\ n)$
unfolding size.simps **apply** (simp add: Suc-lessI)
apply auto **using** OrInverseVal **unfolding** wf-stamp-def
by (smt (z3) constantAsStamp.simps(1) evalDet int-signed-value-bounds mask-eq-take-bit-minus-one
 $new-int.elims\ new-int-take-bits\ unfold-const\ valid-int\ valid-stamp.simps(1)$
 $valid-value.simps(1)\ well-formed-equal-defn$)

optimization *OrInverse2*: $exp[\sim n \mid n] \mapsto (const\ (new-int\ 32\ (not\ 0)))$
 $when\ (stamp-expr\ n = IntegerStamp\ 32\ l\ h \wedge wf-stamp\ n)$
using OrInverse **apply** simp
using OrInverse *exp-or-commutative*
by auto

lemma *XorInverseVal*:
assumes $n = IntVal\ 32\ v$
shows $val[n \oplus \sim n] \approx new-int\ 32\ (-1)$
apply simp **using** assms **using** word-or-not **apply** (cases n; auto)
by (metis (no-types, opaque-lifting) bit.compl-zero bit.xor-compl-right bit.xor-self
 $mask-eq-take-bit-minus-one\ take-bit-xor$)

optimization *XorInverse*: $exp[n \oplus \sim n] \mapsto (const\ (new-int\ 32\ (not\ 0)))$
 $when\ (stamp-expr\ n = IntegerStamp\ 32\ l\ h \wedge wf-stamp\ n)$
unfolding size.simps **apply** (simp add: Suc-lessI)
apply auto **using** XorInverseVal
by (smt (verit) constantAsStamp.simps(1) evalDet int-signed-value-bounds int-

```

val-xor.elims
  mask-eq-take-bit-minus-one new-int.elims new-int-take-bits unfold-const valid-stamp.simps(1)

  valid-value.simps(1) well-formed-equal-defn wf-stamp-def)

optimization XorInverse2:  $\text{exp}[(\sim n) \oplus n] \mapsto (\text{const } (\text{new-int } 32 \text{ (not } 0)))$ 
  when (stamp-expr n = IntegerStamp 32 l h  $\wedge$  wf-stamp n)
  using XorInverse apply simp
  using XorInverse exp-xor-commutative
  by simp

end

end
theory ProofStatus
  imports
    AbsPhase
    AddPhase
    AndPhase
    ConditionalPhase
    MulPhase

    NegatePhase
    NewAnd
    NotPhase
    OrPhase
    ShiftPhase
    SignedDivPhase
    SignedRemPhase
    SubPhase
    TacticSolving
    XorPhase
  begin

  declare [[show-types=false]]
  print-phases
  print-phases!

  print-methods

  print-theorems

  thm opt-add-left-negate-to-sub
  thm-oracles AbsNegate

  export-phases ⟨Full⟩

end

```