

Veriopt Theories

August 30, 2023

Contents

1	Optization DSL	1
1.1	Markup	1
1.1.1	Expression Markup	1
1.1.2	Value Markup	2
1.1.3	Word Markup	3
1.2	Optimization Phases	5
1.3	Canonicalization DSL	5
1.3.1	Semantic Preservation Obligation	8
1.3.2	Termination Obligation	8
1.3.3	Standard Termination Measure	8
1.3.4	Automated Tactics	9

1 Optization DSL

1.1 Markup

```
theory Markup
imports Semantics.IRTreeEval Snippets.Snipping
begin
```

```
datatype 'a Rewrite =
  Transform 'a 'a (-  $\mapsto$  - 10) |
  Conditional 'a 'a bool (-  $\mapsto$  - when - 11) |
  Sequential 'a Rewrite 'a Rewrite |
  Transitive 'a Rewrite
```

```
datatype 'a ExtraNotation =
  ConditionalNotation 'a 'a 'a (- ? - : - 50) |
  EqualsNotation 'a 'a (- eq -) |
  ConstantNotation 'a (const - 120) |
  TrueNotation (true) |
  FalseNotation (false) |
  ExclusiveOr 'a 'a (-  $\oplus$  -) |
  LogicNegationNotation 'a (!-) |
```

```
ShortCircuitOr 'a 'a (- || -) |
Remainder 'a 'a (- % -)
```

definition *word* :: ('a::len) *word* \Rightarrow 'a *word* **where**
word *x* = *x*

ML-val @{term <*x* % *x*>}
ML-file <*markup.ML*>

1.1.1 Expression Markup

```
ML <
structure IRExprTranslator : DSL-TRANSLATION =
struct
fun markup DSL-Tokens.Add = @{term BinaryExpr} $ @{term BinAdd}
  | markup DSL-Tokens.Sub = @{term BinaryExpr} $ @{term BinSub}
  | markup DSL-Tokens.Mul = @{term BinaryExpr} $ @{term BinMul}
  | markup DSL-Tokens.Div = @{term BinaryExpr} $ @{term BinDiv}
  | markup DSL-Tokens.Rem = @{term BinaryExpr} $ @{term BinMod}
  | markup DSL-Tokens.And = @{term BinaryExpr} $ @{term BinAnd}
  | markup DSL-Tokens.Or = @{term BinaryExpr} $ @{term BinOr}
  | markup DSL-Tokens.Xor = @{term BinaryExpr} $ @{term BinXor}
  | markup DSL-Tokens.ShortCircuitOr = @{term BinaryExpr} $ @{term Bin-
ShortCircuitOr}
  | markup DSL-Tokens.Abs = @{term UnaryExpr} $ @{term UnaryAbs}
  | markup DSL-Tokens.Less = @{term BinaryExpr} $ @{term BinIntegerLessThan}
  | markup DSL-Tokens.Equals = @{term BinaryExpr} $ @{term BinIntegerEquals}
  | markup DSL-Tokens.Not = @{term UnaryExpr} $ @{term UnaryNot}
  | markup DSL-Tokens.Negate = @{term UnaryExpr} $ @{term UnaryNeg}
  | markup DSL-Tokens.LogicNegate = @{term UnaryExpr} $ @{term UnaryLog-
icNegation}
  | markup DSL-Tokens.LeftShift = @{term BinaryExpr} $ @{term BinLeftShift}
  | markup DSL-Tokens.RightShift = @{term BinaryExpr} $ @{term BinRight-
Shift}
  | markup DSL-Tokens.UnsignedRightShift = @{term BinaryExpr} $ @{term Bin-
URightShift}
  | markup DSL-Tokens.Conditional = @{term ConditionalExpr}
  | markup DSL-Tokens.Constant = @{term ConstantExpr}
  | markup DSL-Tokens.TrueConstant = @{term ConstantExpr (IntVal 32 1)}
  | markup DSL-Tokens.FalseConstant = @{term ConstantExpr (IntVal 32 0)}
end
structure IRExprMarkup = DSL-Markup(IRExprTranslator);
>
```

ir expression translation

```
syntax -expandExpr :: term  $\Rightarrow$  term (exp[-])
parse-translation < [( @{syntax-const -expandExpr} , IREx-
prMarkup.markup-expr []) >
```

ir expression example

```

value exp[(e1 < e2) ? e1 : e2]

ConditionalExpr (BinaryExpr BinIntegerLessThan (e1::IRExpr)
(e2::IRExpr)) e1 e2

```

1.1.2 Value Markup

ML <

```

structure IntValTranslator : DSL-TRANSLATION =
struct

```

```

fun markup DSL-Tokens.Add = @{term intval-add}
| markup DSL-Tokens.Sub = @{term intval-sub}
| markup DSL-Tokens.Mul = @{term intval-mul}
| markup DSL-Tokens.Div = @{term intval-div}
| markup DSL-Tokens.Rem = @{term intval-mod}
| markup DSL-Tokens.And = @{term intval-and}
| markup DSL-Tokens.Or = @{term intval-or}
| markup DSL-Tokens.ShortCircuitOr = @{term intval-short-circuit-or}
| markup DSL-Tokens.Xor = @{term intval-xor}
| markup DSL-Tokens.Abs = @{term intval-abs}
| markup DSL-Tokens.Less = @{term intval-less-than}
| markup DSL-Tokens.Equals = @{term intval-equals}
| markup DSL-Tokens.Not = @{term intval-not}
| markup DSL-Tokens.Negate = @{term intval-negate}
| markup DSL-Tokens.LogicNegate = @{term intval-logic-negation}
| markup DSL-Tokens.LeftShift = @{term intval-left-shift}
| markup DSL-Tokens.RightShift = @{term intval-right-shift}
| markup DSL-Tokens.UnsignedRightShift = @{term intval-uright-shift}
| markup DSL-Tokens.Conditional = @{term intval-conditional}
| markup DSL-Tokens.Constant = @{term IntVal 32}
| markup DSL-Tokens.TrueConstant = @{term IntVal 32 1}
| markup DSL-Tokens.FalseConstant = @{term IntVal 32 0}

```

end

```

structure IntValMarkup = DSL-Markup(IntValTranslator);

```

>

value expression translation

```

syntax -expandIntVal :: term ⇒ term (val[-])
parse-translation < [( @{syntax-const -expandIntVal} , IntVal-
Markup.markup-expr []) ] >

```

value expression example

value `val[(e1 < e2) ? e1 : e2]`

intval-conditional (*intval-less-than* (e₁::Value) (e₂::Value)) e₁ e₂

1.1.3 Word Markup

ML <

structure `WordTranslator : DSL-TRANSLATION =`

struct

fun `markup DSL-Tokens.Add = @{term plus}`

| `markup DSL-Tokens.Sub = @{term minus}`

| `markup DSL-Tokens.Mul = @{term times}`

| `markup DSL-Tokens.Div = @{term signed-divide}`

| `markup DSL-Tokens.Rem = @{term signed-modulo}`

| `markup DSL-Tokens.And = @{term Bit-Operations.semiring-bit-operations-class.and}`

| `markup DSL-Tokens.Or = @{term or}`

| `markup DSL-Tokens.Xor = @{term xor}`

| `markup DSL-Tokens.Abs = @{term abs}`

| `markup DSL-Tokens.Less = @{term less}`

| `markup DSL-Tokens.Equals = @{term HOL.eq}`

| `markup DSL-Tokens.Not = @{term not}`

| `markup DSL-Tokens.Negate = @{term uminus}`

| `markup DSL-Tokens.LogicNegate = @{term logic-negate}`

| `markup DSL-Tokens.LeftShift = @{term shiftl}`

| `markup DSL-Tokens.RightShift = @{term signed-shiftr}`

| `markup DSL-Tokens.UnsignedRightShift = @{term shiftr}`

| `markup DSL-Tokens.Constant = @{term word}`

| `markup DSL-Tokens.TrueConstant = @{term 1}`

| `markup DSL-Tokens.FalseConstant = @{term 0}`

end

structure `WordMarkup = DSL-Markup(WordTranslator);`

>

word expression translation

syntax `-expandWord :: term ⇒ term (bin[-])`

parse-translation < [(@{syntax-const -expandWord} , Word-Markup.markup-expr [])] >

word expression example

value `bin[x & y | z]`

intval-conditional (*intval-less-than* (e₁::Value) (e₂::Value)) e₁ e₂

value `bin[-x]`

```

value val[-x]
value exp[-x]

```

```

value bin[!x]
value val[!x]
value exp[!x]

```

```

value bin[¬x]
value val[¬x]
value exp[¬x]

```

```

value bin[~x]
value val[~x]
value exp[~x]

```

```

value ~x

```

```

end

```

1.2 Optimization Phases

```

theory Phase
  imports Main
begin

```

```

ML-file map.ML
ML-file phase.ML

```

```

end

```

1.3 Canonicalization DSL

```

theory Canonicalization
  imports
    Markup
    Phase
    HOL-Eisbach.Eisbach
  keywords
    phase :: thy-decl and
    terminating :: quasi-command and
    print-phases :: diag and
    export-phases :: thy-decl and
    optimization :: thy-goal-defn
begin

```

```

print-methods

```

```

ML <
  datatype 'a Rewrite =
    Transform of 'a * 'a |

```

```

Conditional of 'a * 'a * term |
Sequential of 'a Rewrite * 'a Rewrite |
Transitive of 'a Rewrite

type rewrite = {
  name: binding,
  rewrite: term Rewrite,
  proofs: thm list,
  code: thm list,
  source: term
}

structure RewriteRule : Rule =
struct
type T = rewrite;

(*
fun pretty-rewrite ctxt (Transform (from, to)) =
  Pretty.block [
    Syntax.pretty-term ctxt from,
    Pretty.str  $\mapsto$  ,
    Syntax.pretty-term ctxt to
  ]
| pretty-rewrite ctxt (Conditional (from, to, cond)) =
  Pretty.block [
    Syntax.pretty-term ctxt from,
    Pretty.str  $\mapsto$  ,
    Syntax.pretty-term ctxt to,
    Pretty.str when ,
    Syntax.pretty-term ctxt cond
  ]
| pretty-rewrite - - = Pretty.str not implemented*)

fun pretty-thm ctxt thm =
  (Proof-Context.pretty-fact ctxt (, [thm]))

fun pretty ctxt obligations t =
  let
    val is-skipped = Thm-Deps.has-skip-proof (#proofs t);

    val warning = (if is-skipped
      then [Pretty.str (proof skipped), Pretty.brk 0]
      else []);

    val obligations = (if obligations
      then [Pretty.big-list
        obligations:
          (map (pretty-thm ctxt) (#proofs t)),
        Pretty.brk 0]

```

```

    else [];

fun pretty-bind binding =
  Pretty.markup
    (Position.markup (Binding.pos-of binding) Markup.position)
    [Pretty.str (Binding.name-of binding)];

in
  Pretty.block ([
    pretty-bind (#name t), Pretty.str : ,
    Syntax.pretty-term ctxt (#source t), Pretty.fbrk
  ] @ obligations @ warning)
end
end

structure RewritePhase = DSL-Phase(RewriteRule);

val - =
  Outer-Syntax.command command-keyword <phase> enter an optimization phase
    (Parse.binding --| Parse.$$$ terminating -- Parse.const --| Parse.begin
    >> (Toplevel.begin-main-target true o RewritePhase.setup));

fun print-phases print-obligations ctxt =
  let
    val thy = Proof-Context.theory-of ctxt;
    fun print phase = RewritePhase.pretty print-obligations phase ctxt
  in
    map print (RewritePhase.phases thy)
  end

fun print-optimizations print-obligations thy =
  print-phases print-obligations thy |> Pretty.writeln-chunks

val - =
  Outer-Syntax.command command-keyword <print-phases>
    print debug information for optimizations
    (Parse.opt-bang >>
      (fn b => Toplevel.keep ((print-optimizations b) o Toplevel.context-of)));

fun export-phases thy name =
  let
    val state = Toplevel.theory-tooplevel thy;
    val ctxt = Toplevel.context-of state;
    val content = Pretty.string-of (Pretty.chunks (print-phases false ctxt));
    val cleaned = YXML.content-of content;

    val filename = Path.explode (name ^ ".rules");
    val directory = Path.explode optimizations;

```

```

    val path = Path.binding (
      Path.append directory filename,
      Position.none);
    val thy' = thy |> Generated-Files.add-files (path, (Bytes.string content));

    val - = Export.export thy' path [YXML.parse cleaned];

    val - = writeln (Export.message thy' (Path.basic optimizations));
  in
    thy'
  end

val - =
  Outer-Syntax.command command-keyword ⟨export-phases⟩
    export information about encoded optimizations
    (Parse.path >>
      (fn name => Toplevel.theory (fn state => export-phases state name)))
,

```

ML-file *rewrites.ML*

1.3.1 Semantic Preservation Obligation

```

fun rewrite-preservation :: IRExp Rewrite  $\Rightarrow$  bool where
  rewrite-preservation (Transform x y) = (y  $\leq$  x) |
  rewrite-preservation (Conditional x y cond) = (cond  $\longrightarrow$  (y  $\leq$  x)) |
  rewrite-preservation (Sequential x y) = (rewrite-preservation x  $\wedge$  rewrite-preservation
y) |
  rewrite-preservation (Transitive x) = rewrite-preservation x

```

1.3.2 Termination Obligation

```

fun rewrite-termination :: IRExp Rewrite  $\Rightarrow$  (IRExp  $\Rightarrow$  nat)  $\Rightarrow$  bool where
  rewrite-termination (Transform x y) trm = (trm x > trm y) |
  rewrite-termination (Conditional x y cond) trm = (cond  $\longrightarrow$  (trm x > trm y)) |
  rewrite-termination (Sequential x y) trm = (rewrite-termination x trm  $\wedge$  rewrite-termination
y trm) |
  rewrite-termination (Transitive x) trm = rewrite-termination x trm

```

```

fun intval :: Value Rewrite  $\Rightarrow$  bool where
  intval (Transform x y) = (x  $\neq$  UndefVal  $\wedge$  y  $\neq$  UndefVal  $\longrightarrow$  x = y) |
  intval (Conditional x y cond) = (cond  $\longrightarrow$  (x = y)) |
  intval (Sequential x y) = (intval x  $\wedge$  intval y) |
  intval (Transitive x) = intval x

```

1.3.3 Standard Termination Measure

```

fun size :: IRExp  $\Rightarrow$  nat where
  unary-size:
  size (UnaryExpr op x) = (size x) + 2 |

```



```

bin-const-size:
size (BinaryExpr op x (ConstantExpr cy)) = (size x) + 2 |
bin-size:
size (BinaryExpr op x y) = (size x) + (size y) + 2 |
cond-size:
size (ConditionalExpr c t f) = (size c) + (size t) + (size f) + 2 |
const-size:
size (ConstantExpr c) = 1 |
param-size:
size (ParameterExpr ind s) = 2 |
leaf-size:
size (LeafExpr nid s) = 2 |
size (ConstantVar c) = 2 |
size (VariableExpr x s) = 2

```

1.3.4 Automated Tactics

named-theorems *size-simps size simplification rules*

```

method unfold-optimization =
  (unfold rewrite-preservation.simps, unfold rewrite-termination.simps,
   unfold intval.simps,
   rule conjE, simp, simp del: le-expr-def, force?)
| (unfold rewrite-preservation.simps, unfold rewrite-termination.simps,
   rule conjE, simp, simp del: le-expr-def, force?)

```

```

method unfold-size =
  (((unfold size.simps, simp add: size-simps del: le-expr-def)?
   ; (simp add: size-simps del: le-expr-def)?
   ; (auto simp: size-simps)?
   ; (unfold size.simps)?)[1])

```

print-methods

```

ML <
structure System : RewriteSystem =
struct
val preservation = @{const rewrite-preservation};
val termination = @{const rewrite-termination};
val intval = @{const intval};
end

structure DSL = DSL-Rewrites(System);

val - =
  Outer-Syntax.local-theory-to-proof command-keyword <optimization>
  define an optimization and open proof obligation

```

```
(Parse-Spec.thm-name : -- Parse.term
  >> DSL.rewrite-cmd);
>
end
```