

Veriopt

February 8, 2022

Abstract

The Veriopt project aims to prove the optimization pass of the GraalVM compiler. The GraalVM compiler includes a sophisticated Intermediate Representation (IR) in the form of a sea-of-nodes based graph structure. We first define the IR graph structure in the Isabelle/HOL interactive theorem prover. We subsequently give the evaluation of the structure a semantics based on the current understanding of the purpose of each IR graph node. Optimization phases are then encoded including the static analysis passes required for an optimization. Each optimization phase is proved to be correct by proving that a bisimulation exists between the unoptimized and optimized graphs. The following document has been automatically generated from the Isabelle/HOL source to provide a very comprehensive definition of the semantics and optimizations introduced by the Veriopt project.

Contents

1	Runtime Values and Arithmetic	3
2	Nodes	9
2.1	Types of Nodes	9
2.2	Hierarchy of Nodes	17
3	Stamp Typing	24
4	Graph Representation	27
4.0.1	Example Graphs	32
4.1	Control-flow Graph Traversal	32
4.2	Structural Graph Comparison	34
5	Data-flow Semantics	36
5.1	Data-flow Tree Representation	36
5.2	Data-flow Tree Evaluation	38
5.3	Data-flow Tree Refinement	40
5.4	Data-flow Tree Theorems	41
5.4.1	Deterministic Data-flow Evaluation	41
5.4.2	Evaluation Results are Valid	42
5.4.3	Example Data-flow Optimisations	44
5.4.4	Monotonicity of Expression Refinement	44
6	Tree to Graph	46
6.1	Subgraph to Data-flow Tree	46
6.2	Data-flow Tree to Subgraph	50
6.3	Lift Data-flow Tree Semantics	54
6.4	Graph Refinement	54
6.5	Maximal Sharing	54
6.6	Formedness Properties	54
6.7	Dynamic Frames	56
6.8	Tree to Graph Theorems	68
6.8.1	Extraction and Evaluation of Expression Trees is Deterministic.	68
6.8.2	Monotonicity of Graph Refinement	74
6.8.3	Lift Data-flow Tree Refinement to Graph Refinement	77
6.8.4	Term Graph Reconstruction	93
7	Control-flow Semantics	100
7.1	Object Heap	100
7.2	Intraprocedural Semantics	101
7.3	Interprocedural Semantics	103
7.4	Big-step Execution	105

7.4.1	Heap Testing	106
7.5	Control-flow Semantics Theorems	106
7.5.1	Control-flow Step is Deterministic	107
8	Proof Infrastructure	111
8.1	Bisimulation	111
8.2	Graph Rewriting	112
8.3	Stuttering	117
8.4	Evaluation Stamp Theorems	118
8.4.1	Evaluated Value Satisfies Stamps	118
9	Optization DSLs	129
9.1	Canonicalization DSL	131
10	Canonicalization Phase	134
10.1	Conditional Expression	134
11	Conditional Elimination Phase	136
11.1	Individual Elimination Rules	136
11.2	Control-flow Graph Traversal	147

1 Runtime Values and Arithmetic

```
theory Values
imports
  HOL-Library.Word
  HOL-Library.Signed-Division
  HOL-Library.Float
  HOL-Library.LaTeXsugar
begin
```

In order to properly implement the IR semantics we first introduce a type that represents runtime values. These runtime values represent the full range of primitive types currently allowed by our semantics, ranging from basic integer types to object references and arrays.

Note that Java supports 64, 32, 16, 8 signed ints, plus 1 bit (boolean) ints, but during calculations the smaller sizes are expanded to 32 bits, so here we model just 32 and 64 bit values.

An object reference is an option type where the *None* object reference points to the static fields. This is examined more closely in our definition of the heap.

```
type-synonym int64 = 64 word — long
type-synonym int32 = 32 word — int
type-synonym int16 = 16 word — short
type-synonym int8 = 8 word — char
type-synonym int1 = 1 word — boolean
```

```
type-synonym objref = nat option
```

```
datatype (discs-sels) Value =
  UndefVal |
  IntVal32 32 word |
  IntVal64 64 word |

  ObjRef objref |
  ObjStr string
```

```
fun wf-bool :: Value  $\Rightarrow$  bool where
  wf-bool (IntVal32 v) = (v = 0  $\vee$  v = 1) |
  wf-bool - = False
```

```
fun val-to-bool :: Value  $\Rightarrow$  bool where
  val-to-bool (IntVal32 val) = (if val = 0 then False else True) |
  val-to-bool (IntVal64 val) = (if val = 0 then False else True) |
  val-to-bool v = False
```

```
fun bool-to-val :: bool  $\Rightarrow$  Value where
  bool-to-val True = (IntVal32 1) |
```

```
bool-to-val False = (IntVal32 0)
```

```
value sint(word-of-int (1) :: int1)
```

```
fun is-int-val :: Value ⇒ bool where
  is-int-val (IntVal32 v) = True |
  is-int-val (IntVal64 v) = True |
  is-int-val - = False
```

We need to introduce arithmetic operations which agree with the JVM.

Within the JVM, bytecode arithmetic operations are performed on 32 or 64 bit integers, unboxing where appropriate.

The following collection of intval functions correspond to the JVM arithmetic operations. We merge the 32 and 64 bit operations into a single function, even though the stamp of each IRNode tells us exactly what the bit widths will be. These merged functions know to make it easier to do the instantiation of Value as 'plus', etc. It might be worse for reasoning, because it could cause more case analysis, but this does not seem to be a problem in practice.

```
fun intval-add :: Value ⇒ Value ⇒ Value where
  intval-add (IntVal32 v1) (IntVal32 v2) = (IntVal32 (v1+v2)) |
  intval-add (IntVal64 v1) (IntVal64 v2) = (IntVal64 (v1+v2)) |
  intval-add - - =.UndefVal
```

```
instantiation Value :: ab-semigroup-add
begin
```

```
definition plus-Value :: Value ⇒ Value ⇒ Value where
  plus-Value = intval-add
```

```
print-locale! ab-semigroup-add
```

```
instance proof
```

```
  fix a b c :: Value
```

```
  show a + b + c = a + (b + c)
```

```
    apply (simp add: plus-Value-def)
```

```
    apply (induction a; induction b; induction c; auto)
```

```
  done
```

```
  show a + b = b + a
```

```
    apply (simp add: plus-Value-def)
```

```
    apply (induction a; induction b; auto)
```

```
  done
```

```
qed
```

```
end
```

```
fun intval-sub :: Value ⇒ Value ⇒ Value where
  intval-sub (IntVal32 v1) (IntVal32 v2) = (IntVal32 (v1-v2)) |
```

```

    intval-sub (IntVal64 v1) (IntVal64 v2) = (IntVal64 (v1-v2)) |
    intval-sub - - = UndefVal

```

```

instantiation Value :: minus
begin

```

```

definition minus-Value :: Value ⇒ Value ⇒ Value where
    minus-Value = intval-sub

```

```

instance proof qed
end

```

```

fun intval-mul :: Value ⇒ Value ⇒ Value where
    intval-mul (IntVal32 v1) (IntVal32 v2) = (IntVal32 (v1*v2)) |
    intval-mul (IntVal64 v1) (IntVal64 v2) = (IntVal64 (v1*v2)) |
    intval-mul - - = UndefVal

```

```

instantiation Value :: times
begin

```

```

definition times-Value :: Value ⇒ Value ⇒ Value where
    times-Value = intval-mul

```

```

instance proof qed
end

```

```

fun intval-div :: Value ⇒ Value ⇒ Value where
    intval-div (IntVal32 v1) (IntVal32 v2) = (IntVal32 (word-of-int((sint v1) sdiv
(sint v2)))) |
    intval-div (IntVal64 v1) (IntVal64 v2) = (IntVal64 (word-of-int((sint v1) sdiv
(sint v2)))) |
    intval-div - - = UndefVal

```

```

instantiation Value :: divide
begin

```

```

definition divide-Value :: Value ⇒ Value ⇒ Value where
    divide-Value = intval-div

```

```

instance proof qed
end

```

```

fun intval-mod :: Value ⇒ Value ⇒ Value where
    intval-mod (IntVal32 v1) (IntVal32 v2) = (IntVal32 (word-of-int((sint v1) smod
(sint v2)))) |

```

```

    intval-mod (IntVal64 v1) (IntVal64 v2) = (IntVal64 (word-of-int((sint v1) smod
(sint v2)))) |
    intval-mod - - = UndefVal

```

```

instantiation Value :: modulo
begin

```

```

definition modulo-Value :: Value ⇒ Value ⇒ Value where
    modulo-Value = intval-mod

```

```

instance proof qed
end

```

```

context
    includes bit-operations-syntax
begin

```

```

fun intval-and :: Value ⇒ Value ⇒ Value (infix &&* 64) where
    intval-and (IntVal32 v1) (IntVal32 v2) = (IntVal32 (v1 AND v2)) |
    intval-and (IntVal64 v1) (IntVal64 v2) = (IntVal64 (v1 AND v2)) |
    intval-and - - = UndefVal

```

```

fun intval-or :: Value ⇒ Value ⇒ Value (infix ||* 59) where
    intval-or (IntVal32 v1) (IntVal32 v2) = (IntVal32 (v1 OR v2)) |
    intval-or (IntVal64 v1) (IntVal64 v2) = (IntVal64 (v1 OR v2)) |
    intval-or - - = UndefVal

```

```

fun intval-xor :: Value ⇒ Value ⇒ Value (infix ^* 59) where
    intval-xor (IntVal32 v1) (IntVal32 v2) = (IntVal32 (v1 XOR v2)) |
    intval-xor (IntVal64 v1) (IntVal64 v2) = (IntVal64 (v1 XOR v2)) |
    intval-xor - - = UndefVal

```

```

fun intval-equals :: Value ⇒ Value ⇒ Value where
    intval-equals (IntVal32 v1) (IntVal32 v2) = bool-to-val (v1 = v2) |
    intval-equals (IntVal64 v1) (IntVal64 v2) = bool-to-val (v1 = v2) |
    intval-equals - - = UndefVal

```

```

fun intval-less-than :: Value ⇒ Value ⇒ Value where
    intval-less-than (IntVal32 v1) (IntVal32 v2) = bool-to-val (v1 <s v2) |
    intval-less-than (IntVal64 v1) (IntVal64 v2) = bool-to-val (v1 <s v2) |
    intval-less-than - - = UndefVal

```

```

fun intval-below :: Value ⇒ Value ⇒ Value where
    intval-below (IntVal32 v1) (IntVal32 v2) = bool-to-val (v1 < v2) |
    intval-below (IntVal64 v1) (IntVal64 v2) = bool-to-val (v1 < v2) |

```

intval-below - = *UndefVal*

fun *intval-not* :: *Value* \Rightarrow *Value* **where**
intval-not (*IntVal32* *v*) = (*IntVal32* (*NOT* *v*)) |
intval-not (*IntVal64* *v*) = (*IntVal64* (*NOT* *v*)) |
intval-not - = *UndefVal*

fun *intval-negate* :: *Value* \Rightarrow *Value* **where**
intval-negate (*IntVal32* *v*) = *IntVal32* ($-$ *v*) |
intval-negate (*IntVal64* *v*) = *IntVal64* ($-$ *v*) |
intval-negate - = *UndefVal*

fun *intval-abs* :: *Value* \Rightarrow *Value* **where**
intval-abs (*IntVal32* *v*) = (if (*v*) <_s 0 then (*IntVal32* ($-$ *v*)) else (*IntVal32* *v*)) |
intval-abs (*IntVal64* *v*) = (if (*v*) <_s 0 then (*IntVal64* ($-$ *v*)) else (*IntVal64* *v*)) |
intval-abs - = *UndefVal*

fun *intval-conditional* :: *Value* \Rightarrow *Value* \Rightarrow *Value* \Rightarrow *Value* **where**
intval-conditional *cond* *tv* *fv* = (if (*val-to-bool* *cond*) then *tv* else *fv*)

fun *intval-logic-negation* :: *Value* \Rightarrow *Value* **where**
intval-logic-negation (*IntVal32* *v*) = (if *v* = 0 then (*IntVal32* 1) else (*IntVal32* 0)) |
intval-logic-negation (*IntVal64* *v*) = (if *v* = 0 then (*IntVal64* 1) else (*IntVal64* 0)) |
intval-logic-negation - = *UndefVal*

definition *shiffl* (**infix** << 75) **where**

shiffl *w* *n* = (*push-bit* *n*) *w*

lemma *shiffl-power*[*simp*]: (*x*::('a::len) *word*) * (2^j) = *x* << *j*
unfolding *shiffl-def* **apply** (*induction* *j*)
apply *simp* **unfolding** *funpow-Suc-right*
by (*metis* (*no-types*, *opaque-lifting*) *push-bit-eq-mult*)

lemma (*x*::('a::len) *word*) * ((2^j) + 1) = *x* << *j* + *x*
by (*simp* *add: distrib-left*)

lemma (*x*::('a::len) *word*) * ((2^j) - 1) = *x* << *j* - *x*
by (*simp* *add: right-diff-distrib*)

lemma (*x*::('a::len) *word*) * ((2^j) + (2^k)) = *x* << *j* + *x* << *k*
by (*simp* *add: distrib-left*)

lemma (*x*::('a::len) *word*) * ((2^j) - (2^k)) = *x* << *j* - *x* << *k*
by (*simp* *add: right-diff-distrib*)

definition *shiftr* (**infix** >>> 75) **where**

shiftr w n = (*drop-bit n*) *w*

value (255 :: 8 word) >>> (2 :: nat)

definition *signed-shiftr* :: 'a :: len word \Rightarrow nat \Rightarrow 'a :: len word (**infix** >> 75)
where

signed-shiftr w n = *word-of-int* ((*sint w*) *div* (2 $^$ n))

value (128 :: 8 word) >> 2

fun *intval-left-shift* :: Value \Rightarrow Value \Rightarrow Value **where**

intval-left-shift (*IntVal32 v1*) (*IntVal32 v2*) = *IntVal32* (*v1* << *unat* (*v2* AND 0x1f)) |

intval-left-shift (*IntVal64 v1*) (*IntVal64 v2*) = *IntVal64* (*v1* << *unat* (*v2* AND 0x3f)) |

intval-left-shift - - = *UndefVal*

fun *intval-right-shift* :: Value \Rightarrow Value \Rightarrow Value **where**

intval-right-shift (*IntVal32 v1*) (*IntVal32 v2*) = *IntVal32* (*v1* >> *unat* (*v2* AND 0x1f)) |

intval-right-shift (*IntVal64 v1*) (*IntVal64 v2*) = *IntVal64* (*v1* >> *unat* (*v2* AND 0x3f)) |

intval-right-shift - - = *UndefVal*

fun *intval-uright-shift* :: Value \Rightarrow Value \Rightarrow Value **where**

intval-uright-shift (*IntVal32 v1*) (*IntVal32 v2*) = *IntVal32* (*v1* >>> *unat* (*v2* AND 0x1f)) |

intval-uright-shift (*IntVal64 v1*) (*IntVal64 v2*) = *IntVal64* (*v1* >>> *unat* (*v2* AND 0x3f)) |

intval-uright-shift - - = *UndefVal*

end

lemma *intval-add-sym*:

shows *intval-add a b* = *intval-add b a*

by (*induction a*; *induction b*; *auto*)

```

code-deps intval-add
code-thms intval-add

```

```

lemma intval-add (IntVal32 ( $2^{31}-1$ )) (IntVal32 ( $2^{31}-1$ )) = IntVal32 ( $-2$ )
  by eval
lemma intval-add (IntVal64 ( $2^{31}-1$ )) (IntVal64 ( $2^{31}-1$ )) = IntVal64 4294967294
  by eval

end

```

2 Nodes

2.1 Types of Nodes

```

theory IRNodes
  imports
    Values
begin

```

The GraalVM IR is represented using a graph data structure. Here we define the nodes that are contained within the graph. Each node represents a Node subclass in the GraalVM compiler, the node classes have annotated fields to indicate input and successor edges.

We represent these classes with each IRNode constructor explicitly labelling a reference to the node IDs that it stores as inputs and successors.

The `inputs_of` and `successors_of` functions partition those labelled references into input edges and successor edges of a node.

To identify each Node, we use a simple natural number index. Zero is always the start node in a graph. For human readability, within nodes we write `INPUT` (or special case thereof) instead of `ID` for input edges, and `SUCC` instead of `ID` for control-flow successor edges. Optional edges are handled as "INPUT option" etc.

```

type-synonym ID = nat
type-synonym INPUT = ID
type-synonym INPUT-ASSOC = ID
type-synonym INPUT-STATE = ID
type-synonym INPUT-GUARD = ID
type-synonym INPUT-COND = ID
type-synonym INPUT-EXT = ID
type-synonym SUCC = ID

```

```

datatype (discs-sels) IRNode =
  AbsNode (ir-value: INPUT)
  | AddNode (ir-x: INPUT) (ir-y: INPUT)

```

- | *AndNode* (*ir-x*: INPUT) (*ir-y*: INPUT)
- | *BeginNode* (*ir-next*: SUCC)
- | *BytecodeExceptionNode* (*ir-arguments*: INPUT list) (*ir-stateAfter-opt*: INPUT-STATE option) (*ir-next*: SUCC)
- | *ConditionalNode* (*ir-condition*: INPUT-COND) (*ir-trueValue*: INPUT) (*ir-falseValue*: INPUT)
- | *ConstantNode* (*ir-const*: Value)
- | *DynamicNewArrayNode* (*ir-elementType*: INPUT) (*ir-length*: INPUT) (*ir-voidClass-opt*: INPUT option) (*ir-stateBefore-opt*: INPUT-STATE option) (*ir-next*: SUCC)
- | *EndNode*
- | *ExceptionObjectNode* (*ir-stateAfter-opt*: INPUT-STATE option) (*ir-next*: SUCC)

- | *FrameState* (*ir-monitorIds*: INPUT-ASSOC list) (*ir-outerFrameState-opt*: INPUT-STATE option) (*ir-values-opt*: INPUT list option) (*ir-virtualObjectMappings-opt*: INPUT-STATE list option)
- | *IfNode* (*ir-condition*: INPUT-COND) (*ir-trueSuccessor*: SUCC) (*ir-falseSuccessor*: SUCC)
- | *IntegerBelowNode* (*ir-x*: INPUT) (*ir-y*: INPUT)
- | *IntegerEqualsNode* (*ir-x*: INPUT) (*ir-y*: INPUT)
- | *IntegerLessThanNode* (*ir-x*: INPUT) (*ir-y*: INPUT)
- | *InvokeNode* (*ir-nid*: ID) (*ir-callTarget*: INPUT-EXT) (*ir-classInit-opt*: INPUT option) (*ir-stateDuring-opt*: INPUT-STATE option) (*ir-stateAfter-opt*: INPUT-STATE option) (*ir-next*: SUCC)
- | *InvokeWithExceptionNode* (*ir-nid*: ID) (*ir-callTarget*: INPUT-EXT) (*ir-classInit-opt*: INPUT option) (*ir-stateDuring-opt*: INPUT-STATE option) (*ir-stateAfter-opt*: INPUT-STATE option) (*ir-next*: SUCC) (*ir-exceptionEdge*: SUCC)
- | *IsNullNode* (*ir-value*: INPUT)
- | *KillingBeginNode* (*ir-next*: SUCC)
- | *LeftShiftNode* (*ir-x*: INPUT) (*ir-y*: INPUT)
- | *LoadFieldNode* (*ir-nid*: ID) (*ir-field*: string) (*ir-object-opt*: INPUT option) (*ir-next*: SUCC)
- | *LogicNegationNode* (*ir-value*: INPUT-COND)
- | *LoopBeginNode* (*ir-ends*: INPUT-ASSOC list) (*ir-overflowGuard-opt*: INPUT-GUARD option) (*ir-stateAfter-opt*: INPUT-STATE option) (*ir-next*: SUCC)
- | *LoopEndNode* (*ir-loopBegin*: INPUT-ASSOC)
- | *LoopExitNode* (*ir-loopBegin*: INPUT-ASSOC) (*ir-stateAfter-opt*: INPUT-STATE option) (*ir-next*: SUCC)
- | *MergeNode* (*ir-ends*: INPUT-ASSOC list) (*ir-stateAfter-opt*: INPUT-STATE option) (*ir-next*: SUCC)
- | *MethodCallTargetNode* (*ir-targetMethod*: string) (*ir-arguments*: INPUT list)
- | *MulNode* (*ir-x*: INPUT) (*ir-y*: INPUT)
- | *NarrowNode* (*ir-inputBits*: nat) (*ir-resultBits*: nat) (*ir-value*: INPUT)
- | *NegateNode* (*ir-value*: INPUT)
- | *NewArrayNode* (*ir-length*: INPUT) (*ir-stateBefore-opt*: INPUT-STATE option) (*ir-next*: SUCC)
- | *NewInstanceNode* (*ir-nid*: ID) (*ir-instanceClass*: string) (*ir-stateBefore-opt*: INPUT-STATE option) (*ir-next*: SUCC)
- | *NotNode* (*ir-value*: INPUT)
- | *OrNode* (*ir-x*: INPUT) (*ir-y*: INPUT)

```

| ParameterNode (ir-index: nat)
| PiNode (ir-object: INPUT) (ir-guard-opt: INPUT-GUARD option)
| ReturnNode (ir-result-opt: INPUT option) (ir-memoryMap-opt: INPUT-EXT
option)
| RightShiftNode (ir-x: INPUT) (ir-y: INPUT)
| ShortCircuitOrNode (ir-x: INPUT-COND) (ir-y: INPUT-COND)
| SignExtendNode (ir-inputBits: nat) (ir-resultBits: nat) (ir-value: INPUT)
| SignedDivNode (ir-nid: ID) (ir-x: INPUT) (ir-y: INPUT) (ir-zeroCheck-opt: IN-
PUT-GUARD option) (ir-stateBefore-opt: INPUT-STATE option) (ir-next: SUCC)

| SignedRemNode (ir-nid: ID) (ir-x: INPUT) (ir-y: INPUT) (ir-zeroCheck-opt:
INPUT-GUARD option) (ir-stateBefore-opt: INPUT-STATE option) (ir-next: SUCC)

| StartNode (ir-stateAfter-opt: INPUT-STATE option) (ir-next: SUCC)
| StoreFieldNode (ir-nid: ID) (ir-field: string) (ir-value: INPUT) (ir-stateAfter-opt:
INPUT-STATE option) (ir-object-opt: INPUT option) (ir-next: SUCC)
| SubNode (ir-x: INPUT) (ir-y: INPUT)
| UnsignedRightShiftNode (ir-x: INPUT) (ir-y: INPUT)
| UnwindNode (ir-exception: INPUT)
| ValuePhiNode (ir-nid: ID) (ir-values: INPUT list) (ir-merge: INPUT-ASSOC)
| ValueProxyNode (ir-value: INPUT) (ir-loopExit: INPUT-ASSOC)
| XORNode (ir-x: INPUT) (ir-y: INPUT)
| ZeroExtendNode (ir-inputBits: nat) (ir-resultBits: nat) (ir-value: INPUT)
| NoNode

| RefNode (ir-ref: ID)

```

```

fun opt-to-list :: 'a option ⇒ 'a list where
  opt-to-list None = [] |
  opt-to-list (Some v) = [v]

```

```

fun opt-list-to-list :: 'a list option ⇒ 'a list where
  opt-list-to-list None = [] |
  opt-list-to-list (Some x) = x

```

The following functions, `inputs_of` and `successors_of`, are automatically generated from the GraalVM compiler. Their purpose is to partition the node edges into input or successor edges.

```

fun inputs-of :: IRNode ⇒ ID list where
  inputs-of-AbsNode:
  inputs-of (AbsNode value) = [value] |
  inputs-of-AddNode:
  inputs-of (AddNode x y) = [x, y] |
  inputs-of-AndNode:
  inputs-of (AndNode x y) = [x, y] |

```

inputs-of-BeginNode:
inputs-of (BeginNode next) = [] |
inputs-of-BytecodeExceptionNode:
inputs-of (BytecodeExceptionNode arguments stateAfter next) = arguments @
(opt-to-list stateAfter) |
inputs-of-ConditionalNode:
inputs-of (ConditionalNode condition trueValue falseValue) = [condition, true-
Value, falseValue] |
inputs-of-ConstantNode:
inputs-of (ConstantNode const) = [] |
inputs-of-DynamicNewArrayNode:
inputs-of (DynamicNewArrayNode elementType length0 voidClass stateBefore
next) = [elementType, length0] @ (opt-to-list voidClass) @ (opt-to-list stateBefore)
|
inputs-of-EndNode:
inputs-of (EndNode) = [] |
inputs-of-ExceptionObjectNode:
inputs-of (ExceptionObjectNode stateAfter next) = (opt-to-list stateAfter) |
inputs-of-FrameState:
inputs-of (FrameState monitorIds outerFrameState values virtualObjectMappings)
= monitorIds @ (opt-to-list outerFrameState) @ (opt-list-to-list values) @ (opt-list-to-list
virtualObjectMappings) |
inputs-of-IfNode:
inputs-of (IfNode condition trueSuccessor falseSuccessor) = [condition] |
inputs-of-IntegerBelowNode:
inputs-of (IntegerBelowNode x y) = [x, y] |
inputs-of-IntegerEqualsNode:
inputs-of (IntegerEqualsNode x y) = [x, y] |
inputs-of-IntegerLessThanNode:
inputs-of (IntegerLessThanNode x y) = [x, y] |
inputs-of-InvokeNode:
inputs-of (InvokeNode nid0 callTarget classInit stateDuring stateAfter next)
= callTarget # (opt-to-list classInit) @ (opt-to-list stateDuring) @ (opt-to-list
stateAfter) |
inputs-of-InvokeWithExceptionNode:
inputs-of (InvokeWithExceptionNode nid0 callTarget classInit stateDuring stateAfter
next exceptionEdge) = callTarget # (opt-to-list classInit) @ (opt-to-list stateDur-
ing) @ (opt-to-list stateAfter) |
inputs-of-IsNullNode:
inputs-of (IsNullNode value) = [value] |
inputs-of-KillingBeginNode:
inputs-of (KillingBeginNode next) = [] |
inputs-of-LeftShiftNode:
inputs-of (LeftShiftNode x y) = [x, y] |
inputs-of-LoadFieldNode:
inputs-of (LoadFieldNode nid0 field object next) = (opt-to-list object) |
inputs-of-LogicNegationNode:
inputs-of (LogicNegationNode value) = [value] |
inputs-of-LoopBeginNode:

$\text{inputs-of } (\text{LoopBeginNode ends overflowGuard stateAfter next}) = \text{ends} @ (\text{opt-to-list overflowGuard}) @ (\text{opt-to-list stateAfter}) \mid$
 $\text{inputs-of-LoopEndNode:}$
 $\text{inputs-of } (\text{LoopEndNode loopBegin}) = [\text{loopBegin}] \mid$
 $\text{inputs-of-LoopExitNode:}$
 $\text{inputs-of } (\text{LoopExitNode loopBegin stateAfter next}) = \text{loopBegin} \# (\text{opt-to-list stateAfter}) \mid$
 $\text{inputs-of-MergeNode:}$
 $\text{inputs-of } (\text{MergeNode ends stateAfter next}) = \text{ends} @ (\text{opt-to-list stateAfter}) \mid$
 $\text{inputs-of-MethodCallTargetNode:}$
 $\text{inputs-of } (\text{MethodCallTargetNode targetMethod arguments}) = \text{arguments} \mid$
 $\text{inputs-of-MulNode:}$
 $\text{inputs-of } (\text{MulNode } x \ y) = [x, y] \mid$
 $\text{inputs-of-NarrowNode:}$
 $\text{inputs-of } (\text{NarrowNode inputBits resultBits value}) = [\text{value}] \mid$
 $\text{inputs-of-NegateNode:}$
 $\text{inputs-of } (\text{NegateNode value}) = [\text{value}] \mid$
 $\text{inputs-of-NewArrayNode:}$
 $\text{inputs-of } (\text{NewArrayNode length0 stateBefore next}) = \text{length0} \# (\text{opt-to-list stateBefore}) \mid$
 $\text{inputs-of-NewInstanceNode:}$
 $\text{inputs-of } (\text{NewInstanceNode nid0 instanceClass stateBefore next}) = (\text{opt-to-list stateBefore}) \mid$
 $\text{inputs-of-NotNode:}$
 $\text{inputs-of } (\text{NotNode value}) = [\text{value}] \mid$
 inputs-of-OrNode:
 $\text{inputs-of } (\text{OrNode } x \ y) = [x, y] \mid$
 $\text{inputs-of-ParameterNode:}$
 $\text{inputs-of } (\text{ParameterNode index}) = [] \mid$
 inputs-of-PiNode:
 $\text{inputs-of } (\text{PiNode object guard}) = \text{object} \# (\text{opt-to-list guard}) \mid$
 $\text{inputs-of-ReturnNode:}$
 $\text{inputs-of } (\text{ReturnNode result memoryMap}) = (\text{opt-to-list result}) @ (\text{opt-to-list memoryMap}) \mid$
 $\text{inputs-of-RightShiftNode:}$
 $\text{inputs-of } (\text{RightShiftNode } x \ y) = [x, y] \mid$
 $\text{inputs-of-ShortCircuitOrNode:}$
 $\text{inputs-of } (\text{ShortCircuitOrNode } x \ y) = [x, y] \mid$
 $\text{inputs-of-SignExtendNode:}$
 $\text{inputs-of } (\text{SignExtendNode inputBits resultBits value}) = [\text{value}] \mid$
 $\text{inputs-of-SignedDivNode:}$
 $\text{inputs-of } (\text{SignedDivNode nid0 } x \ y \ \text{zeroCheck stateBefore next}) = [x, y] @ (\text{opt-to-list zeroCheck}) @ (\text{opt-to-list stateBefore}) \mid$
 $\text{inputs-of-SignedRemNode:}$
 $\text{inputs-of } (\text{SignedRemNode nid0 } x \ y \ \text{zeroCheck stateBefore next}) = [x, y] @ (\text{opt-to-list zeroCheck}) @ (\text{opt-to-list stateBefore}) \mid$
 $\text{inputs-of-StartNode:}$
 $\text{inputs-of } (\text{StartNode stateAfter next}) = (\text{opt-to-list stateAfter}) \mid$
 $\text{inputs-of-StoreFieldNode:}$

inputs-of (*StoreFieldNode* *nid0* *field* *value* *stateAfter* *object* *next*) = *value* #
 (*opt-to-list* *stateAfter*) @ (*opt-to-list* *object*) |
inputs-of-SubNode:
inputs-of (*SubNode* *x* *y*) = [*x*, *y*] |
inputs-of-UnsignedRightShiftNode:
inputs-of (*UnsignedRightShiftNode* *x* *y*) = [*x*, *y*] |
inputs-of-UnwindNode:
inputs-of (*UnwindNode* *exception*) = [*exception*] |
inputs-of-ValuePhiNode:
inputs-of (*ValuePhiNode* *nid0* *values* *merge*) = *merge* # *values* |
inputs-of-ValueProxyNode:
inputs-of (*ValueProxyNode* *value* *loopExit*) = [*value*, *loopExit*] |
inputs-of-XorNode:
inputs-of (*XorNode* *x* *y*) = [*x*, *y*] |
inputs-of-ZeroExtendNode:
inputs-of (*ZeroExtendNode* *inputBits* *resultBits* *value*) = [*value*] |
inputs-of-NoNode: *inputs-of* (*NoNode*) = [] |

inputs-of-RefNode: *inputs-of* (*RefNode* *ref*) = [*ref*]

fun *successors-of* :: *IRNode* \Rightarrow *ID list* **where**

successors-of-AbsNode:
successors-of (*AbsNode* *value*) = [] |
successors-of-AddNode:
successors-of (*AddNode* *x* *y*) = [] |
successors-of-AndNode:
successors-of (*AndNode* *x* *y*) = [] |
successors-of-BeginNode:
successors-of (*BeginNode* *next*) = [*next*] |
successors-of-BytecodeExceptionNode:
successors-of (*BytecodeExceptionNode* *arguments* *stateAfter* *next*) = [*next*] |
successors-of-ConditionalNode:
successors-of (*ConditionalNode* *condition* *trueValue* *falseValue*) = [] |
successors-of-ConstantNode:
successors-of (*ConstantNode* *const*) = [] |
successors-of-DynamicNewArrayNode:
successors-of (*DynamicNewArrayNode* *elementType* *length0* *voidClass* *stateBefore* *next*) = [*next*] |
successors-of-EndNode:
successors-of (*EndNode*) = [] |
successors-of-ExceptionObjectNode:
successors-of (*ExceptionObjectNode* *stateAfter* *next*) = [*next*] |
successors-of-FrameState:
successors-of (*FrameState* *monitorIds* *outerFrameState* *values* *virtualObjectMappings*) = [] |
successors-of-IfNode:
successors-of (*IfNode* *condition* *trueSuccessor* *falseSuccessor*) = [*trueSuccessor*,

falseSuccessor] |
successors-of-IntegerBelowNode:
successors-of (*IntegerBelowNode* *x y*) = [] |
successors-of-IntegerEqualsNode:
successors-of (*IntegerEqualsNode* *x y*) = [] |
successors-of-IntegerLessThanNode:
successors-of (*IntegerLessThanNode* *x y*) = [] |
successors-of-InvokeNode:
successors-of (*InvokeNode* *nid0 callTarget classInit stateDuring stateAfter next*)
= [*next*] |
successors-of-InvokeWithExceptionNode:
successors-of (*InvokeWithExceptionNode* *nid0 callTarget classInit stateDuring*
stateAfter next exceptionEdge) = [*next*, *exceptionEdge*] |
successors-of-IsNullNode:
successors-of (*IsNullNode* *value*) = [] |
successors-of-KillingBeginNode:
successors-of (*KillingBeginNode* *next*) = [*next*] |
successors-of-LeftShiftNode:
successors-of (*LeftShiftNode* *x y*) = [] |
successors-of-LoadFieldNode:
successors-of (*LoadFieldNode* *nid0 field object next*) = [*next*] |
successors-of-LogicNegationNode:
successors-of (*LogicNegationNode* *value*) = [] |
successors-of-LoopBeginNode:
successors-of (*LoopBeginNode* *ends overflowGuard stateAfter next*) = [*next*] |
successors-of-LoopEndNode:
successors-of (*LoopEndNode* *loopBegin*) = [] |
successors-of-LoopExitNode:
successors-of (*LoopExitNode* *loopBegin stateAfter next*) = [*next*] |
successors-of-MergeNode:
successors-of (*MergeNode* *ends stateAfter next*) = [*next*] |
successors-of-MethodCallTargetNode:
successors-of (*MethodCallTargetNode* *targetMethod arguments*) = [] |
successors-of-MulNode:
successors-of (*MulNode* *x y*) = [] |
successors-of-NarrowNode:
successors-of (*NarrowNode* *inputBits resultBits value*) = [] |
successors-of-NegateNode:
successors-of (*NegateNode* *value*) = [] |
successors-of-NewArrayNode:
successors-of (*NewArrayNode* *length0 stateBefore next*) = [*next*] |
successors-of-NewInstanceNode:
successors-of (*NewInstanceNode* *nid0 instanceClass stateBefore next*) = [*next*] |
successors-of-NotNode:
successors-of (*NotNode* *value*) = [] |
successors-of-OrNode:
successors-of (*OrNode* *x y*) = [] |
successors-of-ParameterNode:
successors-of (*ParameterNode* *index*) = [] |

successors-of-PiNode:
successors-of (PiNode object guard) = [] |
successors-of-ReturnNode:
successors-of (ReturnNode result memoryMap) = [] |
successors-of-RightShiftNode:
successors-of (RightShiftNode x y) = [] |
successors-of-ShortCircuitOrNode:
successors-of (ShortCircuitOrNode x y) = [] |
successors-of-SignExtendNode:
successors-of (SignExtendNode inputBits resultBits value) = [] |
successors-of-SignedDivNode:
successors-of (SignedDivNode nid0 x y zeroCheck stateBefore next) = [next] |
successors-of-SignedRemNode:
successors-of (SignedRemNode nid0 x y zeroCheck stateBefore next) = [next] |
successors-of-StartNode:
successors-of (StartNode stateAfter next) = [next] |
successors-of-StoreFieldNode:
successors-of (StoreFieldNode nid0 field value stateAfter object next) = [next] |
successors-of-SubNode:
successors-of (SubNode x y) = [] |
successors-of-UnsignedRightShiftNode:
successors-of (UnsignedRightShiftNode x y) = [] |
successors-of-UnwindNode:
successors-of (UnwindNode exception) = [] |
successors-of-ValuePhiNode:
successors-of (ValuePhiNode nid0 values merge) = [] |
successors-of-ValueProxyNode:
successors-of (ValueProxyNode value loopExit) = [] |
successors-of-XorNode:
successors-of (XorNode x y) = [] |
successors-of-ZeroExtendNode:
successors-of (ZeroExtendNode inputBits resultBits value) = [] |
successors-of-NoNode: successors-of (NoNode) = [] |

successors-of-RefNode: successors-of (RefNode ref) = [ref]

lemma *inputs-of (FrameState x (Some y) (Some z) None) = x @ [y] @ z*
unfolding *inputs-of-FrameState by simp*
lemma *successors-of (FrameState x (Some y) (Some z) None) = []*
unfolding *inputs-of-FrameState by simp*

lemma *inputs-of (IfNode c t f) = [c]*
unfolding *inputs-of-IfNode by simp*
lemma *successors-of (IfNode c t f) = [t, f]*
unfolding *successors-of-IfNode by simp*

```

lemma inputs-of (EndNode) = []  $\wedge$  successors-of (EndNode) = []
  unfolding inputs-of-EndNode successors-of-EndNode by simp

end

```

2.2 Hierarchy of Nodes

```

theory IRNodeHierarchy
imports IRNodes
begin

```

It is helpful to introduce a node hierarchy into our formalization. Often the GraalVM compiler relies on explicit type checks to determine which operations to perform on a given node, we try to mimic the same functionality by using a suite of predicate functions over the *IRNode* class to determine inheritance.

As one would expect, the function *is*<ClassName>Type will be true if the node parameter is a subclass of the *ClassName* within the GraalVM compiler.

These functions have been automatically generated from the compiler.

```

fun is-EndNode :: IRNode  $\Rightarrow$  bool where
  is-EndNode EndNode = True |
  is-EndNode - = False

```

```

fun is-VirtualState :: IRNode  $\Rightarrow$  bool where
  is-VirtualState n = ((is-FrameState n))

```

```

fun is-BinaryArithmeticNode :: IRNode  $\Rightarrow$  bool where
  is-BinaryArithmeticNode n = ((is-AddNode n)  $\vee$  (is-AndNode n)  $\vee$  (is-MulNode n)  $\vee$  (is-OrNode n)  $\vee$  (is-SubNode n)  $\vee$  (is-XorNode n))

```

```

fun is-ShiftNode :: IRNode  $\Rightarrow$  bool where
  is-ShiftNode n = ((is-LeftShiftNode n)  $\vee$  (is-RightShiftNode n)  $\vee$  (is-UnsignedRightShiftNode n))

```

```

fun is-BinaryNode :: IRNode  $\Rightarrow$  bool where
  is-BinaryNode n = ((is-BinaryArithmeticNode n)  $\vee$  (is-ShiftNode n))

```

```

fun is-AbstractLocalNode :: IRNode  $\Rightarrow$  bool where
  is-AbstractLocalNode n = ((is-ParameterNode n))

```

```

fun is-IntegerConvertNode :: IRNode  $\Rightarrow$  bool where
  is-IntegerConvertNode n = ((is-NarrowNode n)  $\vee$  (is-SignExtendNode n)  $\vee$  (is-ZeroExtendNode n))

```

```

fun is-UnaryArithmeticNode :: IRNode  $\Rightarrow$  bool where

```

is-UnaryArithmeticNode *n* = ((*is-AbsNode* *n*) ∨ (*is-NegateNode* *n*) ∨ (*is-NotNode* *n*))

fun *is-UnaryNode* :: *IRNode* ⇒ *bool* **where**
is-UnaryNode *n* = ((*is-IntegerConvertNode* *n*) ∨ (*is-UnaryArithmeticNode* *n*))

fun *is-PhiNode* :: *IRNode* ⇒ *bool* **where**
is-PhiNode *n* = ((*is-ValuePhiNode* *n*))

fun *is-FloatingGuardedNode* :: *IRNode* ⇒ *bool* **where**
is-FloatingGuardedNode *n* = ((*is-PiNode* *n*))

fun *is-UnaryOpLogicNode* :: *IRNode* ⇒ *bool* **where**
is-UnaryOpLogicNode *n* = ((*is-IsNullNode* *n*))

fun *is-IntegerLowerThanNode* :: *IRNode* ⇒ *bool* **where**
is-IntegerLowerThanNode *n* = ((*is-IntegerBelowNode* *n*) ∨ (*is-IntegerLessThanNode* *n*))

fun *is-CompareNode* :: *IRNode* ⇒ *bool* **where**
is-CompareNode *n* = ((*is-IntegerEqualsNode* *n*) ∨ (*is-IntegerLowerThanNode* *n*))

fun *is-BinaryOpLogicNode* :: *IRNode* ⇒ *bool* **where**
is-BinaryOpLogicNode *n* = ((*is-CompareNode* *n*))

fun *is-LogicNode* :: *IRNode* ⇒ *bool* **where**
is-LogicNode *n* = ((*is-BinaryOpLogicNode* *n*) ∨ (*is-LogicNegationNode* *n*) ∨ (*is-ShortCircuitOrNode* *n*) ∨ (*is-UnaryOpLogicNode* *n*))

fun *is-ProxyNode* :: *IRNode* ⇒ *bool* **where**
is-ProxyNode *n* = ((*is-ValueProxyNode* *n*))

fun *is-FloatingNode* :: *IRNode* ⇒ *bool* **where**
is-FloatingNode *n* = ((*is-AbstractLocalNode* *n*) ∨ (*is-BinaryNode* *n*) ∨ (*is-ConditionalNode* *n*) ∨ (*is-ConstantNode* *n*) ∨ (*is-FloatingGuardedNode* *n*) ∨ (*is-LogicNode* *n*) ∨ (*is-PhiNode* *n*) ∨ (*is-ProxyNode* *n*) ∨ (*is-UnaryNode* *n*))

fun *is-AccessFieldNode* :: *IRNode* ⇒ *bool* **where**
is-AccessFieldNode *n* = ((*is-LoadFieldNode* *n*) ∨ (*is-StoreFieldNode* *n*))

fun *is-AbstractNewArrayNode* :: *IRNode* ⇒ *bool* **where**
is-AbstractNewArrayNode *n* = ((*is-DynamicNewArrayNode* *n*) ∨ (*is-NewArrayNode* *n*))

fun *is-AbstractNewObjectNode* :: *IRNode* ⇒ *bool* **where**
is-AbstractNewObjectNode *n* = ((*is-AbstractNewArrayNode* *n*) ∨ (*is-NewInstanceNode* *n*))

fun *is-IntegerDivRemNode* :: *IRNode* ⇒ *bool* **where**

```

is-IntegerDivRemNode n = ((is-SignedDivNode n) ∨ (is-SignedRemNode n))

fun is-FixedBinaryNode :: IRNode ⇒ bool where
  is-FixedBinaryNode n = ((is-IntegerDivRemNode n))

fun is-DeoptimizingFixedWithNextNode :: IRNode ⇒ bool where
  is-DeoptimizingFixedWithNextNode n = ((is-AbstractNewObjectNode n) ∨ (is-FixedBinaryNode n))

fun is-AbstractMemoryCheckpoint :: IRNode ⇒ bool where
  is-AbstractMemoryCheckpoint n = ((is-BytecodeExceptionNode n) ∨ (is-InvokeNode n))

fun is-AbstractStateSplit :: IRNode ⇒ bool where
  is-AbstractStateSplit n = ((is-AbstractMemoryCheckpoint n))

fun is-AbstractMergeNode :: IRNode ⇒ bool where
  is-AbstractMergeNode n = ((is-LoopBeginNode n) ∨ (is-MergeNode n))

fun is-BeginStateSplitNode :: IRNode ⇒ bool where
  is-BeginStateSplitNode n = ((is-AbstractMergeNode n) ∨ (is-ExceptionObjectNode n) ∨ (is-LoopExitNode n) ∨ (is-StartNode n))

fun is-AbstractBeginNode :: IRNode ⇒ bool where
  is-AbstractBeginNode n = ((is-BeginNode n) ∨ (is-BeginStateSplitNode n) ∨ (is-KillingBeginNode n))

fun is-FixedWithNextNode :: IRNode ⇒ bool where
  is-FixedWithNextNode n = ((is-AbstractBeginNode n) ∨ (is-AbstractStateSplit n) ∨ (is-AccessFieldNode n) ∨ (is-DeoptimizingFixedWithNextNode n))

fun is-WithExceptionNode :: IRNode ⇒ bool where
  is-WithExceptionNode n = ((is-InvokeWithExceptionNode n))

fun is-ControlSplitNode :: IRNode ⇒ bool where
  is-ControlSplitNode n = ((is-IfNode n) ∨ (is-WithExceptionNode n))

fun is-ControlSinkNode :: IRNode ⇒ bool where
  is-ControlSinkNode n = ((is-ReturnNode n) ∨ (is-UnwindNode n))

fun is-AbstractEndNode :: IRNode ⇒ bool where
  is-AbstractEndNode n = ((is-EndNode n) ∨ (is-LoopEndNode n))

fun is-FixedNode :: IRNode ⇒ bool where
  is-FixedNode n = ((is-AbstractEndNode n) ∨ (is-ControlSinkNode n) ∨ (is-ControlSplitNode n) ∨ (is-FixedWithNextNode n))

fun is-CallTargetNode :: IRNode ⇒ bool where
  is-CallTargetNode n = ((is-MethodCallTargetNode n))

```

```

fun is-ValueNode :: IRNode  $\Rightarrow$  bool where
  is-ValueNode n = ((is-CallTargetNode n)  $\vee$  (is-FixedNode n)  $\vee$  (is-FloatingNode
n))

fun is-Node :: IRNode  $\Rightarrow$  bool where
  is-Node n = ((is-ValueNode n)  $\vee$  (is-VirtualState n))

fun is-MemoryKill :: IRNode  $\Rightarrow$  bool where
  is-MemoryKill n = ((is-AbstractMemoryCheckpoint n))

fun is-NarrowableArithmeticNode :: IRNode  $\Rightarrow$  bool where
  is-NarrowableArithmeticNode n = ((is-AbsNode n)  $\vee$  (is-AddNode n)  $\vee$  (is-AndNode
n)  $\vee$  (is-MulNode n)  $\vee$  (is-NegateNode n)  $\vee$  (is-NotNode n)  $\vee$  (is-OrNode n)  $\vee$ 
(is-ShiftNode n)  $\vee$  (is-SubNode n)  $\vee$  (is-XorNode n))

fun is-AnchoringNode :: IRNode  $\Rightarrow$  bool where
  is-AnchoringNode n = ((is-AbstractBeginNode n))

fun is-DeoptBefore :: IRNode  $\Rightarrow$  bool where
  is-DeoptBefore n = ((is-DeoptimizingFixedWithNextNode n))

fun is-IndirectCanonicalization :: IRNode  $\Rightarrow$  bool where
  is-IndirectCanonicalization n = ((is-LogicNode n))

fun is-IterableNodeType :: IRNode  $\Rightarrow$  bool where
  is-IterableNodeType n = ((is-AbstractBeginNode n)  $\vee$  (is-AbstractMergeNode n)  $\vee$ 
(is-FrameState n)  $\vee$  (is-IfNode n)  $\vee$  (is-IntegerDivRemNode n)  $\vee$  (is-InvokeWithExceptionNode
n)  $\vee$  (is-LoopBeginNode n)  $\vee$  (is-LoopExitNode n)  $\vee$  (is-MethodCallTargetNode n)
 $\vee$  (is-ParameterNode n)  $\vee$  (is-ReturnNode n)  $\vee$  (is-ShortCircuitOrNode n))

fun is-Invoke :: IRNode  $\Rightarrow$  bool where
  is-Invoke n = ((is-InvokeNode n)  $\vee$  (is-InvokeWithExceptionNode n))

fun is-Proxy :: IRNode  $\Rightarrow$  bool where
  is-Proxy n = ((is-ProxyNode n))

fun is-ValueProxy :: IRNode  $\Rightarrow$  bool where
  is-ValueProxy n = ((is-PiNode n)  $\vee$  (is-ValueProxyNode n))

fun is-ValueNodeInterface :: IRNode  $\Rightarrow$  bool where
  is-ValueNodeInterface n = ((is-ValueNode n))

fun is-ArrayLengthProvider :: IRNode  $\Rightarrow$  bool where
  is-ArrayLengthProvider n = ((is-AbstractNewArrayNode n)  $\vee$  (is-ConstantNode
n))

fun is-StampInverter :: IRNode  $\Rightarrow$  bool where
  is-StampInverter n = ((is-IntegerConvertNode n)  $\vee$  (is-NegateNode n)  $\vee$  (is-NotNode
n))

```

n))

fun *is-GuardingNode* :: *IRNode* \Rightarrow *bool* **where**
is-GuardingNode *n* = ((*is-AbstractBeginNode* *n*))

fun *is-SingleMemoryKill* :: *IRNode* \Rightarrow *bool* **where**
is-SingleMemoryKill *n* = ((*is-BytecodeExceptionNode* *n*) \vee (*is-ExceptionObjectNode* *n*) \vee (*is-InvokeNode* *n*) \vee (*is-InvokeWithExceptionNode* *n*) \vee (*is-KillingBeginNode* *n*) \vee (*is-StartNode* *n*))

fun *is-LIRLowerable* :: *IRNode* \Rightarrow *bool* **where**
is-LIRLowerable *n* = ((*is-AbstractBeginNode* *n*) \vee (*is-AbstractEndNode* *n*) \vee (*is-AbstractMergeNode* *n*) \vee (*is-BinaryOpLogicNode* *n*) \vee (*is-CallTargetNode* *n*) \vee (*is-ConditionalNode* *n*) \vee (*is-ConstantNode* *n*) \vee (*is-IfNode* *n*) \vee (*is-InvokeNode* *n*) \vee (*is-InvokeWithExceptionNode* *n*) \vee (*is-IsNullNode* *n*) \vee (*is-LoopBeginNode* *n*) \vee (*is-PiNode* *n*) \vee (*is-ReturnNode* *n*) \vee (*is-SignedDivNode* *n*) \vee (*is-SignedRemNode* *n*) \vee (*is-UnaryOpLogicNode* *n*) \vee (*is-UnwindNode* *n*))

fun *is-GuardedNode* :: *IRNode* \Rightarrow *bool* **where**
is-GuardedNode *n* = ((*is-FloatingGuardedNode* *n*))

fun *is-ArithmeticLIRLowerable* :: *IRNode* \Rightarrow *bool* **where**
is-ArithmeticLIRLowerable *n* = ((*is-AbsNode* *n*) \vee (*is-BinaryArithmeticNode* *n*) \vee (*is-IntegerConvertNode* *n*) \vee (*is-NotNode* *n*) \vee (*is-ShiftNode* *n*) \vee (*is-UnaryArithmeticNode* *n*))

fun *is-SwitchFoldable* :: *IRNode* \Rightarrow *bool* **where**
is-SwitchFoldable *n* = ((*is-IfNode* *n*))

fun *is-VirtualizableAllocation* :: *IRNode* \Rightarrow *bool* **where**
is-VirtualizableAllocation *n* = ((*is-NewArrayNode* *n*) \vee (*is-NewInstanceNode* *n*))

fun *is-Unary* :: *IRNode* \Rightarrow *bool* **where**
is-Unary *n* = ((*is-LoadFieldNode* *n*) \vee (*is-LogicNegationNode* *n*) \vee (*is-UnaryNode* *n*) \vee (*is-UnaryOpLogicNode* *n*))

fun *is-FixedNodeInterface* :: *IRNode* \Rightarrow *bool* **where**
is-FixedNodeInterface *n* = ((*is-FixedNode* *n*))

fun *is-BinaryCommutative* :: *IRNode* \Rightarrow *bool* **where**
is-BinaryCommutative *n* = ((*is-AddNode* *n*) \vee (*is-AndNode* *n*) \vee (*is-IntegerEqualsNode* *n*) \vee (*is-MulNode* *n*) \vee (*is-OrNode* *n*) \vee (*is-XorNode* *n*))

fun *is-Canonicalizable* :: *IRNode* \Rightarrow *bool* **where**
is-Canonicalizable *n* = ((*is-BytecodeExceptionNode* *n*) \vee (*is-ConditionalNode* *n*) \vee (*is-DynamicNewArrayNode* *n*) \vee (*is-PhiNode* *n*) \vee (*is-PiNode* *n*) \vee (*is-ProxyNode* *n*) \vee (*is-StoreFieldNode* *n*) \vee (*is-ValueProxyNode* *n*))

fun *is-UncheckedInterfaceProvider* :: *IRNode* \Rightarrow *bool* **where**

```

    is-UncheckedInterfaceProvider n = ((is-InvokeNode n) ∨ (is-InvokeWithExceptionNode
n) ∨ (is-LoadFieldNode n) ∨ (is-ParameterNode n))

```

```

fun is-Binary :: IRNode ⇒ bool where
    is-Binary n = ((is-BinaryArithmeticNode n) ∨ (is-BinaryNode n) ∨ (is-BinaryOpLogicNode
n) ∨ (is-CompareNode n) ∨ (is-FixedBinaryNode n) ∨ (is-ShortCircuitOrNode n))

```

```

fun is-ArithmeticOperation :: IRNode ⇒ bool where
    is-ArithmeticOperation n = ((is-BinaryArithmeticNode n) ∨ (is-IntegerConvertNode
n) ∨ (is-ShiftNode n) ∨ (is-UnaryArithmeticNode n))

```

```

fun is-ValueNumberable :: IRNode ⇒ bool where
    is-ValueNumberable n = ((is-FloatingNode n) ∨ (is-ProxyNode n))

```

```

fun is-Lowerable :: IRNode ⇒ bool where
    is-Lowerable n = ((is-AbstractNewObjectNode n) ∨ (is-AccessFieldNode n) ∨
(is-BytecodeExceptionNode n) ∨ (is-ExceptionObjectNode n) ∨ (is-IntegerDivRemNode
n) ∨ (is-UnwindNode n))

```

```

fun is-Virtualizable :: IRNode ⇒ bool where
    is-Virtualizable n = ((is-IsNullNode n) ∨ (is-LoadFieldNode n) ∨ (is-PiNode n)
∨ (is-StoreFieldNode n) ∨ (is-ValueProxyNode n))

```

```

fun is-Simplifiable :: IRNode ⇒ bool where
    is-Simplifiable n = ((is-AbstractMergeNode n) ∨ (is-BeginNode n) ∨ (is-IfNode
n) ∨ (is-LoopExitNode n) ∨ (is-MethodCallTargetNode n) ∨ (is-NewArrayNode n))

```

```

fun is-StateSplit :: IRNode ⇒ bool where
    is-StateSplit n = ((is-AbstractStateSplit n) ∨ (is-BeginStateSplitNode n) ∨ (is-StoreFieldNode
n))

```

```

fun is-ConvertNode :: IRNode ⇒ bool where
    is-ConvertNode n = ((is-IntegerConvertNode n))

```

```

fun is-sequential-node :: IRNode ⇒ bool where
    is-sequential-node (StartNode -) = True |
    is-sequential-node (BeginNode -) = True |
    is-sequential-node (KillingBeginNode -) = True |
    is-sequential-node (LoopBeginNode - - -) = True |
    is-sequential-node (LoopExitNode - -) = True |
    is-sequential-node (MergeNode - -) = True |
    is-sequential-node (RefNode -) = True |
    is-sequential-node - = False

```

The following convenience function is useful in determining if two IRNodes are of the same type irregardless of their edges. It will return true if both the node parameters are the same node class.

```

fun is-same-ir-node-type :: IRNode ⇒ IRNode ⇒ bool where

```

```

is-same-ir-node-type n1 n2 = (
  ((is-AbsNode n1) ∧ (is-AbsNode n2)) ∨
  ((is-AddNode n1) ∧ (is-AddNode n2)) ∨
  ((is-AndNode n1) ∧ (is-AndNode n2)) ∨
  ((is-BEGINNode n1) ∧ (is-BEGINNode n2)) ∨
  ((is-BytecodeExceptionNode n1) ∧ (is-BytecodeExceptionNode n2)) ∨
  ((is-ConditionalNode n1) ∧ (is-ConditionalNode n2)) ∨
  ((is-ConstantNode n1) ∧ (is-ConstantNode n2)) ∨
  ((is-DynamicNewArrayNode n1) ∧ (is-DynamicNewArrayNode n2)) ∨
  ((is-EndNode n1) ∧ (is-EndNode n2)) ∨
  ((is-ExceptionObjectNode n1) ∧ (is-ExceptionObjectNode n2)) ∨
  ((is-FrameState n1) ∧ (is-FrameState n2)) ∨
  ((is-IfNode n1) ∧ (is-IfNode n2)) ∨
  ((is-IntegerBelowNode n1) ∧ (is-IntegerBelowNode n2)) ∨
  ((is-IntegerEqualsNode n1) ∧ (is-IntegerEqualsNode n2)) ∨
  ((is-IntegerLessThanNode n1) ∧ (is-IntegerLessThanNode n2)) ∨
  ((is-InvokeNode n1) ∧ (is-InvokeNode n2)) ∨
  ((is-InvokeWithExceptionNode n1) ∧ (is-InvokeWithExceptionNode n2)) ∨
  ((is-IsNullNode n1) ∧ (is-IsNullNode n2)) ∨
  ((is-Killing-BEGINNode n1) ∧ (is-Killing-BEGINNode n2)) ∨
  ((is-LoadFieldNode n1) ∧ (is-LoadFieldNode n2)) ∨
  ((is-LogicNegationNode n1) ∧ (is-LogicNegationNode n2)) ∨
  ((is-Loop-BEGINNode n1) ∧ (is-Loop-BEGINNode n2)) ∨
  ((is-Loop-EndNode n1) ∧ (is-Loop-EndNode n2)) ∨
  ((is-Loop-ExitNode n1) ∧ (is-Loop-ExitNode n2)) ∨
  ((is-MergeNode n1) ∧ (is-MergeNode n2)) ∨
  ((is-MethodCallTargetNode n1) ∧ (is-MethodCallTargetNode n2)) ∨
  ((is-MulNode n1) ∧ (is-MulNode n2)) ∨
  ((is-NegateNode n1) ∧ (is-NegateNode n2)) ∨
  ((is-NewArrayNode n1) ∧ (is-NewArrayNode n2)) ∨
  ((is-NewInstanceNode n1) ∧ (is-NewInstanceNode n2)) ∨
  ((is-NotNode n1) ∧ (is-NotNode n2)) ∨
  ((is-OrNode n1) ∧ (is-OrNode n2)) ∨
  ((is-ParameterNode n1) ∧ (is-ParameterNode n2)) ∨
  ((is-PiNode n1) ∧ (is-PiNode n2)) ∨
  ((is-ReturnNode n1) ∧ (is-ReturnNode n2)) ∨
  ((is-ShortCircuitOrNode n1) ∧ (is-ShortCircuitOrNode n2)) ∨
  ((is-SignedDivNode n1) ∧ (is-SignedDivNode n2)) ∨
  ((is-StartNode n1) ∧ (is-StartNode n2)) ∨
  ((is-StoreFieldNode n1) ∧ (is-StoreFieldNode n2)) ∨
  ((is-SubNode n1) ∧ (is-SubNode n2)) ∨
  ((is-UnwindNode n1) ∧ (is-UnwindNode n2)) ∨
  ((is-ValuePhiNode n1) ∧ (is-ValuePhiNode n2)) ∨
  ((is-ValueProxyNode n1) ∧ (is-ValueProxyNode n2)) ∨
  ((is-XorNode n1) ∧ (is-XorNode n2)))

```

end

3 Stamp Typing

```
theory Stamp
  imports Values
begin
```

The GraalVM compiler uses the Stamp class to store range and type information for a given node in the IR graph. We model the Stamp class as a datatype, Stamp, and provide a number of functions on the datatype which correspond to the class methods within the compiler.

Stamp information is used in a variety of ways in optimizations, and so, we additionally provide a number of lemmas which help to prove future optimizations.

```
datatype Stamp =
  VoidStamp
| IntegerStamp (stp-bits: nat) (stp-lower: int) (stp-upper: int)
| KlassPointerStamp (stp-nonNull: bool) (stp-alwaysNull: bool)
| MethodCountersPointerStamp (stp-nonNull: bool) (stp-alwaysNull: bool)
| MethodPointersStamp (stp-nonNull: bool) (stp-alwaysNull: bool)
| ObjectStamp (stp-type: string) (stp-exactType: bool) (stp-nonNull: bool) (stp-alwaysNull:
bool)
| RawPointerStamp (stp-nonNull: bool) (stp-alwaysNull: bool)
| IllegalStamp
```

```
fun bit-bounds :: nat  $\Rightarrow$  (int  $\times$  int) where
  bit-bounds bits = (((2  $\wedge$  bits) div 2) * -1, ((2  $\wedge$  bits) div 2) - 1)
```

— A stamp which includes the full range of the type

```
fun unrestricted-stamp :: Stamp  $\Rightarrow$  Stamp where
  unrestricted-stamp VoidStamp = VoidStamp |
  unrestricted-stamp (IntegerStamp bits lower upper) = (IntegerStamp bits (fst
(bit-bounds bits)) (snd (bit-bounds bits))) |
  unrestricted-stamp (KlassPointerStamp nonNull alwaysNull) = (KlassPointerStamp
False False) |
  unrestricted-stamp (MethodCountersPointerStamp nonNull alwaysNull) = (MethodCountersPointerStamp
False False) |
  unrestricted-stamp (MethodPointersStamp nonNull alwaysNull) = (MethodPointersStamp
False False) |
  unrestricted-stamp (ObjectStamp type exactType nonNull alwaysNull) = (ObjectStamp
"" False False False) |
  unrestricted-stamp - = IllegalStamp
```

```
fun is-stamp-unrestricted :: Stamp  $\Rightarrow$  bool where
```

is-stamp-unrestricted $s = (s = \text{unrestricted-stamp } s)$

— A stamp which provides type information but has an empty range of values

```
fun empty-stamp :: Stamp  $\Rightarrow$  Stamp where
  empty-stamp VoidStamp = VoidStamp |
  empty-stamp (IntegerStamp bits lower upper) = (IntegerStamp bits (snd (bit-bounds
bits)) (fst (bit-bounds bits))) |

  empty-stamp (KlassPointerStamp nonNull alwaysNull) = (KlassPointerStamp
nonNull alwaysNull) |
  empty-stamp (MethodCountersPointerStamp nonNull alwaysNull) = (MethodCountersPointerStamp
nonNull alwaysNull) |
  empty-stamp (MethodPointersStamp nonNull alwaysNull) = (MethodPointersStamp
nonNull alwaysNull) |
  empty-stamp (ObjectStamp type exactType nonNull alwaysNull) = (ObjectStamp
"" True True False) |
  empty-stamp stamp = IllegalStamp

fun is-stamp-empty :: Stamp  $\Rightarrow$  bool where
  is-stamp-empty (IntegerStamp b lower upper) = (upper < lower) |

  is-stamp-empty x = False
```

— Calculate the meet stamp of two stamps

```
fun meet :: Stamp  $\Rightarrow$  Stamp  $\Rightarrow$  Stamp where
  meet VoidStamp VoidStamp = VoidStamp |
  meet (IntegerStamp b1 l1 u1) (IntegerStamp b2 l2 u2) = (
    if b1  $\neq$  b2 then IllegalStamp else
    (IntegerStamp b1 (min l1 l2) (max u1 u2))
  ) |

  meet (KlassPointerStamp nn1 an1) (KlassPointerStamp nn2 an2) = (
    KlassPointerStamp (nn1  $\wedge$  nn2) (an1  $\wedge$  an2)
  ) |
  meet (MethodCountersPointerStamp nn1 an1) (MethodCountersPointerStamp
nn2 an2) = (
    MethodCountersPointerStamp (nn1  $\wedge$  nn2) (an1  $\wedge$  an2)
  ) |
  meet (MethodPointersStamp nn1 an1) (MethodPointersStamp nn2 an2) = (
    MethodPointersStamp (nn1  $\wedge$  nn2) (an1  $\wedge$  an2)
  ) |
  meet s1 s2 = IllegalStamp
```

— Calculate the join stamp of two stamps

```
fun join :: Stamp  $\Rightarrow$  Stamp  $\Rightarrow$  Stamp where
  join VoidStamp VoidStamp = VoidStamp |
  join (IntegerStamp b1 l1 u1) (IntegerStamp b2 l2 u2) = (
    if b1  $\neq$  b2 then IllegalStamp else
    (IntegerStamp b1 (max l1 l2) (min u1 u2))
  )
```

```

) |
join (KlassPointerStamp nn1 an1) (KlassPointerStamp nn2 an2) = (
  if ((nn1 ∨ nn2) ∧ (an1 ∨ an2))
  then (empty-stamp (KlassPointerStamp nn1 an1))
  else (KlassPointerStamp (nn1 ∨ nn2) (an1 ∨ an2))
) |
join (MethodCountersPointerStamp nn1 an1) (MethodCountersPointerStamp nn2
an2) = (
  if ((nn1 ∨ nn2) ∧ (an1 ∨ an2))
  then (empty-stamp (MethodCountersPointerStamp nn1 an1))
  else (MethodCountersPointerStamp (nn1 ∨ nn2) (an1 ∨ an2))
) |
join (MethodPointersStamp nn1 an1) (MethodPointersStamp nn2 an2) = (
  if ((nn1 ∨ nn2) ∧ (an1 ∨ an2))
  then (empty-stamp (MethodPointersStamp nn1 an1))
  else (MethodPointersStamp (nn1 ∨ nn2) (an1 ∨ an2))
) |
join s1 s2 = IllegalStamp

```

— In certain circumstances a stamp provides enough information to evaluate a value as a stamp, the `asConstant` function converts the stamp to a value where one can be inferred.

```

fun asConstant :: Stamp ⇒ Value where
  asConstant (IntegerStamp b l h) = (if l = h then IntVal64 (word-of-int l) else
 .UndefVal) |
  asConstant - =.UndefVal

```

— Determine if two stamps never have value overlaps i.e. their join is empty

```

fun alwaysDistinct :: Stamp ⇒ Stamp ⇒ bool where
  alwaysDistinct stamp1 stamp2 = is-stamp-empty (join stamp1 stamp2)

```

— Determine if two stamps must always be the same value i.e. two equal constants

```

fun neverDistinct :: Stamp ⇒ Stamp ⇒ bool where
  neverDistinct stamp1 stamp2 = (asConstant stamp1 = asConstant stamp2 ∧
  asConstant stamp1 ≠.UndefVal)

```

```

fun constantAsStamp :: Value ⇒ Stamp where
  constantAsStamp (IntVal32 v) = (IntegerStamp (nat 32) (sint v) (sint v)) |
  constantAsStamp (IntVal64 v) = (IntegerStamp (nat 64) (sint v) (sint v)) |

  constantAsStamp - = IllegalStamp

```

— Define when a runtime value is valid for a stamp

```

fun valid-value :: Value ⇒ Stamp ⇒ bool where
  valid-value (IntVal32 v) (IntegerStamp b l h) = (b=32 ∧ (sint v ≥ l) ∧ (sint v ≤
  h)) |
  valid-value (IntVal64 v) (IntegerStamp b l h) = (b=64 ∧ (sint v ≥ l) ∧ (sint v ≤

```

$h)) \mid$

$valid_value (ObjRef\ ref) (ObjectStamp\ klass\ exact\ nonNull\ alwaysNull) = False \mid$
 $valid_value\ stamp\ val = False$

fun *compatible* :: *Stamp* \Rightarrow *Stamp* \Rightarrow *bool* **where**
 compatible (*IntegerStamp* *b1* - -) (*IntegerStamp* *b2* - -) = (*b1* = *b2*) \mid
 compatible (*VoidStamp*) (*VoidStamp*) = *True* \mid
 compatible - - = *False*

fun *stamp-under* :: *Stamp* \Rightarrow *Stamp* \Rightarrow *bool* **where**
 stamp-under *x y* = ((*stpi-upper* *x*) < (*stpi-lower* *y*))

— The most common type of stamp within the compiler (apart from the Void-Stamp) is a 32 bit integer stamp with an unrestricted range. We use *default-stamp* as it is a frequently used stamp.

definition *default-stamp* :: *Stamp* **where**
 default-stamp = (*unrestricted-stamp* (*IntegerStamp* 32 0 0))

end

4 Graph Representation

theory *IRGraph*
 imports
 IRNodeHierarchy
 Stamp
 HOL-Library.FSet
 HOL.Relation

begin

This theory defines the main Graal data structure - an entire IR Graph.

IRGraph is defined as a partial map with a finite domain. The finite domain is required to be able to generate code and produce an interpreter.

typedef *IRGraph* = {*g* :: *ID* \rightarrow (*IRNode* \times *Stamp*) . *finite* (*dom* *g*)}

proof –

have *finite*(*dom*(*Map.empty*)) \wedge *ran* *Map.empty* = {} **by** *auto*
 then show *?thesis*
 by *fastforce*

qed

setup-lifting *type-definition-IRGraph*

lift-definition *ids* :: *IRGraph* \Rightarrow *ID* *set*
 is $\lambda g. \{nid \in dom\ g . \nexists s. g\ nid = (Some\ (NoNode,\ s))\}$.

fun *with-default* :: 'c \Rightarrow ('b \Rightarrow 'c) \Rightarrow (('a \rightarrow 'b) \Rightarrow 'a \Rightarrow 'c) **where**
with-default def conv = ($\lambda m k.$
 (case m k of None \Rightarrow def | Some v \Rightarrow conv v))

lift-definition *kind* :: IRGraph \Rightarrow (ID \Rightarrow IRNode)
is *with-default* NoNode fst .

lift-definition *stamp* :: IRGraph \Rightarrow ID \Rightarrow Stamp
is *with-default* IllegalStamp snd .

lift-definition *add-node* :: ID \Rightarrow (IRNode \times Stamp) \Rightarrow IRGraph \Rightarrow IRGraph
is $\lambda nid k g.$ if fst k = NoNode then g else g(nid \mapsto k) **by** simp

lift-definition *remove-node* :: ID \Rightarrow IRGraph \Rightarrow IRGraph
is $\lambda nid g.$ g(nid := None) **by** simp

lift-definition *replace-node* :: ID \Rightarrow (IRNode \times Stamp) \Rightarrow IRGraph \Rightarrow IRGraph
is $\lambda nid k g.$ if fst k = NoNode then g else g(nid \mapsto k) **by** simp

lift-definition *as-list* :: IRGraph \Rightarrow (ID \times IRNode \times Stamp) list
is $\lambda g.$ map ($\lambda k. (k, \text{the } (g k))$) (sorted-list-of-set (dom g)) .

fun *no-node* :: (ID \times (IRNode \times Stamp)) list \Rightarrow (ID \times (IRNode \times Stamp)) list
where
no-node g = filter ($\lambda n. \text{fst } (\text{snd } n) \neq \text{NoNode}$) g

lift-definition *irgraph* :: (ID \times (IRNode \times Stamp)) list \Rightarrow IRGraph
is map-of \circ *no-node*
by (simp add: finite-dom-map-of)

definition *as-set* :: IRGraph \Rightarrow (ID \times (IRNode \times Stamp)) set **where**
as-set g = {(n, kind g n, stamp g n) | n . n \in ids g}

definition *true-ids* :: IRGraph \Rightarrow ID set **where**
true-ids g = ids g - {n \in ids g . $\exists n' . \text{kind } g n = \text{RefNode } n'$ }

definition *domain-subtraction* :: 'a set \Rightarrow ('a \times 'b) set \Rightarrow ('a \times 'b) set
(infix ≤ 30) **where**
domain-subtraction s r = {(x, y) . (x, y) \in r \wedge x \notin s}

notation (*latex*)
domain-subtraction (- \triangleleft -)

code-datatype *irgraph*

fun *filter-none* **where**
filter-none g = {nid \in dom g . $\nexists s. g \text{ nid} = (\text{Some } (\text{NoNode}, s))$ }

lemma *no-node-clears*:

res = *no-node xs* \longrightarrow $(\forall x \in \text{set } \text{res}. \text{fst } (\text{snd } x) \neq \text{NoNode})$
by *simp*

lemma *dom-eq*:

assumes $\forall x \in \text{set } \text{xs}. \text{fst } (\text{snd } x) \neq \text{NoNode}$
shows *filter-none* (*map-of xs*) = *dom* (*map-of xs*)
unfolding *filter-none.simps* **using** *assms map-of-SomeD*
by *fastforce*

lemma *fil-eq*:

filter-none (*map-of* (*no-node xs*)) = *set* (*map fst* (*no-node xs*))
using *no-node-clears*
by (*metis dom-eq dom-map-of-conv-image-fst list.set-map*)

lemma *irgraph[code]*: *ids* (*irgraph m*) = *set* (*map fst* (*no-node m*))

unfolding *irgraph-def ids-def* **using** *fil-eq*
by (*smt Rep-IRGraph comp-apply eq-onp-same-args filter-none.simps ids.abs-eq*
ids-def irgraph.abs-eq irgraph.rep-eq irgraph-def mem-Collect-eq)

lemma *[code]*: *Rep-IRGraph* (*irgraph m*) = *map-of* (*no-node m*)

using *Abs-IRGraph-inverse*
by (*simp add: irgraph.rep-eq*)

— Get the inputs set of a given node ID

fun *inputs* :: *IRGraph* \Rightarrow *ID* \Rightarrow *ID set* **where**

inputs g nid = *set* (*inputs-of* (*kind g nid*))

— Get the successor set of a given node ID

fun *succ* :: *IRGraph* \Rightarrow *ID* \Rightarrow *ID set* **where**

succ g nid = *set* (*successors-of* (*kind g nid*))

— Gives a relation between node IDs - between a node and its input nodes

fun *input-edges* :: *IRGraph* \Rightarrow *ID rel* **where**

input-edges g = $(\bigcup i \in \text{ids } g. \{(i,j) | j. j \in (\text{inputs } g i)\})$

— Find all the nodes in the graph that have nid as an input - the usages of nid

fun *usages* :: *IRGraph* \Rightarrow *ID* \Rightarrow *ID set* **where**

usages g nid = $\{j. j \in \text{ids } g \wedge (j, \text{nid}) \in \text{input-edges } g\}$

fun *successor-edges* :: *IRGraph* \Rightarrow *ID rel* **where**

successor-edges g = $(\bigcup i \in \text{ids } g. \{(i,j) | j. j \in (\text{succ } g i)\})$

fun *predecessors* :: *IRGraph* \Rightarrow *ID* \Rightarrow *ID set* **where**

predecessors g nid = $\{j. j \in \text{ids } g \wedge (j, \text{nid}) \in \text{successor-edges } g\}$

fun *nodes-of* :: *IRGraph* \Rightarrow (*IRNode* \Rightarrow *bool*) \Rightarrow *ID set* **where**

nodes-of g sel = $\{\text{nid} \in \text{ids } g. \text{sel } (\text{kind } g \text{ nid})\}$

fun *edge* :: (*IRNode* \Rightarrow 'a) \Rightarrow *ID* \Rightarrow *IRGraph* \Rightarrow 'a **where**

edge sel nid g = *sel* (*kind g nid*)

fun *filtered-inputs* :: *IRGraph* \Rightarrow *ID* \Rightarrow (*IRNode* \Rightarrow *bool*) \Rightarrow *ID list* **where**

filtered-inputs g nid f = *filter* (*f* \circ (*kind g*)) (*inputs-of* (*kind g nid*))

```

fun filtered-successors :: IRGraph  $\Rightarrow$  ID  $\Rightarrow$  (IRNode  $\Rightarrow$  bool)  $\Rightarrow$  ID list where
  filtered-successors g nid f = filter (f  $\circ$  (kind g)) (successors-of (kind g nid))
fun filtered-usages :: IRGraph  $\Rightarrow$  ID  $\Rightarrow$  (IRNode  $\Rightarrow$  bool)  $\Rightarrow$  ID set where
  filtered-usages g nid f = {n  $\in$  (usages g nid). f (kind g n)}

fun is-empty :: IRGraph  $\Rightarrow$  bool where
  is-empty g = (ids g = {})

fun any-usage :: IRGraph  $\Rightarrow$  ID  $\Rightarrow$  ID where
  any-usage g nid = hd (sorted-list-of-set (usages g nid))

lemma ids-some[simp]: x  $\in$  ids g  $\longleftrightarrow$  kind g x  $\neq$  NoNode
proof –
  have that: x  $\in$  ids g  $\longrightarrow$  kind g x  $\neq$  NoNode
  using ids.rep-eq kind.rep-eq by force
  have kind g x  $\neq$  NoNode  $\longrightarrow$  x  $\in$  ids g
  unfolding with-default.simps kind-def ids-def
  by (cases Rep-IRGraph g x = None; auto)
  from this that show ?thesis by auto
qed

lemma not-in-g:
  assumes nid  $\notin$  ids g
  shows kind g nid = NoNode
  using asms ids-some by blast

lemma valid-creation[simp]:
  finite (dom g)  $\longleftrightarrow$  Rep-IRGraph (Abs-IRGraph g) = g
  using Abs-IRGraph-inverse by (metis Rep-IRGraph mem-Collect-eq)

lemma [simp]: finite (ids g)
  using Rep-IRGraph ids.rep-eq by simp

lemma [simp]: finite (ids (irgraph g))
  by (simp add: finite-dom-map-of)

lemma [simp]: finite (dom g)  $\longrightarrow$  ids (Abs-IRGraph g) = {nid  $\in$  dom g .  $\nexists$  s. g
  nid = Some (NoNode, s)}
  using ids.rep-eq by simp

lemma [simp]: finite (dom g)  $\longrightarrow$  kind (Abs-IRGraph g) = ( $\lambda$ x . (case g x of None
 $\Rightarrow$  NoNode | Some n  $\Rightarrow$  fst n))
  by (simp add: kind.rep-eq)

lemma [simp]: finite (dom g)  $\longrightarrow$  stamp (Abs-IRGraph g) = ( $\lambda$ x . (case g x of
  None  $\Rightarrow$  IllegalStamp | Some n  $\Rightarrow$  snd n))
  using stamp.abs-eq stamp.rep-eq by auto

lemma [simp]: ids (irgraph g) = set (map fst (no-node g))

```

```

using irgraph by auto

lemma [simp]: kind (irgraph g) = ( $\lambda$ nid. (case (map-of (no-node g)) nid of None
 $\Rightarrow$  NoNode | Some n  $\Rightarrow$  fst n))
using irgraph.rep-eq kind.transfer kind.rep-eq by auto

lemma [simp]: stamp (irgraph g) = ( $\lambda$ nid. (case (map-of (no-node g)) nid of None
 $\Rightarrow$  IllegalStamp | Some n  $\Rightarrow$  snd n))
using irgraph.rep-eq stamp.transfer stamp.rep-eq by auto

lemma map-of-upd: (map-of g)(k  $\mapsto$  v) = (map-of ((k, v) # g))
by simp

lemma [code]: replace-node nid k (irgraph g) = (irgraph ( ((nid, k) # g)))
proof (cases fst k = NoNode)
  case True
    then show ?thesis
    by (metis (mono-tags, lifting) Rep-IRGraph-inject filter.simps(2) irgraph.abs-eq
no-node.simps replace-node.rep-eq snd-conv)
  next
    case False
    then show ?thesis unfolding irgraph-def replace-node-def no-node.simps
    by (smt (verit, best) Rep-IRGraph comp-apply eq-onp-same-args filter.simps(2)
id-def irgraph.rep-eq map-fun-apply map-of-upd mem-Collect-eq no-node.elims re-
place-node.abs-eq replace-node-def snd-eqD)
  qed

lemma [code]: add-node nid k (irgraph g) = (irgraph (((nid, k) # g)))
by (smt (z3) Rep-IRGraph-inject add-node.rep-eq filter.simps(2) irgraph.rep-eq
map-of-upd no-node.simps snd-conv)

lemma add-node-lookup:
  gup = add-node nid (k, s) g  $\longrightarrow$ 
    (if k  $\neq$  NoNode then kind gup nid = k  $\wedge$  stamp gup nid = s else kind gup nid
    = kind g nid)
proof (cases k = NoNode)
  case True
    then show ?thesis
    by (simp add: add-node.rep-eq kind.rep-eq)
  next
    case False
    then show ?thesis
    by (simp add: kind.rep-eq add-node.rep-eq stamp.rep-eq)
  qed

lemma remove-node-lookup:
  gup = remove-node nid g  $\longrightarrow$  kind gup nid = NoNode  $\wedge$  stamp gup nid =
IllegalStamp

```


by (*simp add: kind.rep-eq remove-node.rep-eq stamp.rep-eq*)

lemma *replace-node-lookup*[*simp*]:

gup = replace-node nid (k, s) g \wedge *k* \neq *NoNode* \longrightarrow *kind gup nid = k* \wedge *stamp gup nid = s*

by (*simp add: replace-node.rep-eq kind.rep-eq stamp.rep-eq*)

lemma *replace-node-unchanged*:

gup = replace-node nid (k, s) g \longrightarrow $(\forall n \in (ids\ g - \{nid\}) . n \in ids\ g \wedge n \in ids\ gup \wedge kind\ g\ n = kind\ gup\ n)$

by (*simp add: kind.rep-eq replace-node.rep-eq*)

4.0.1 Example Graphs

Example 1: empty graph (just a start and end node)

definition *start-end-graph*:: *IRGraph* **where**

start-end-graph = irgraph [(0, StartNode None 1, VoidStamp), (1, ReturnNode None None, VoidStamp)]

Example 2: public static int sq(int x) return x * x;

[1 P(0)] / [0 Start] [4 *] | / V / [5 Return]

definition *eg2-sq* :: *IRGraph* **where**

eg2-sq = irgraph [
(0, StartNode None 5, VoidStamp),
(1, ParameterNode 0, default-stamp),
(4, MulNode 1 1, default-stamp),
(5, ReturnNode (Some 4) None, default-stamp)
]

value *input-edges eg2-sq*

value *usages eg2-sq 1*

end

4.1 Control-flow Graph Traversal

theory

Traversal

imports

IRGraph

begin

type-synonym *Seen* = *ID set*

nextEdge helps determine which node to traverse next by returning the first

successor edge that isn't in the set of already visited nodes. If there is not an appropriate successor, None is returned instead.

```
fun nextEdge :: Seen  $\Rightarrow$  ID  $\Rightarrow$  IRGraph  $\Rightarrow$  ID option where
  nextEdge seen nid g =
    (let nids = (filter ( $\lambda$ nid'. nid'  $\notin$  seen) (successors-of (kind g nid))) in
     (if length nids > 0 then Some (hd nids) else None))
```

pred determines which node, if any, acts as the predecessor of another.

Merge nodes represent a special case where-in the predecessor exists as an input edge of the merge node, to simplify the traversal we treat only the first input end node as the predecessor, ignoring that multiple nodes may act as a successor.

For all other nodes, the predecessor is the first element of the predecessors set. Note that in a well-formed graph there should only be one element in the predecessor set.

```
fun pred :: IRGraph  $\Rightarrow$  ID  $\Rightarrow$  ID option where
  pred g nid = (case kind g nid of
    (MergeNode ends -)  $\Rightarrow$  Some (hd ends) |
    -  $\Rightarrow$ 
      (if IRGraph.predecessors g nid = {}
       then None else
        Some (hd (sorted-list-of-set (IRGraph.predecessors g nid))))
  )
```

Here we try to implement a generic fork of the control-flow traversal algorithm that was initially implemented for the ConditionalElimination phase

type-synonym 'a TraversalState = (ID \times Seen \times 'a)

inductive Step

```
:: ('a TraversalState  $\Rightarrow$  'a)  $\Rightarrow$  IRGraph  $\Rightarrow$  'a TraversalState  $\Rightarrow$  'a TraversalState
option  $\Rightarrow$  bool
```

for sa g **where**

— Hit a BeginNode with an IfNode predecessor which represents the start of a basic block for the IfNode. 1. nid' will be the successor of the begin node. 2. Find the first and only predecessor. 3. Extract condition from the preceding IfNode. 4. Negate condition if the begin node is second branch (we've taken the else branch of the condition) 5. Add the condition or the negated condition to stack 6. Perform any stamp updates based on the condition using the registerNewCondition function and place them on the top of the stack of stamp information

```
[[kind g nid = BeginNode nid';
```

```
  nid  $\notin$  seen;
  seen' = {nid}  $\cup$  seen;
```

```
  Some ifcond = pred g nid;
  kind g ifcond = IfNode cond t f;
```

$$\begin{aligned} & \text{analysis}' = \text{sa } (nid, \text{seen}, \text{analysis}) \\ \implies & \text{Step sa } g \text{ } (nid, \text{seen}, \text{analysis}) \text{ } (\text{Some } (nid', \text{seen}', \text{analysis}')) \mid \end{aligned}$$

— Hit an EndNode 1. nid' will be the usage of EndNode 2. pop the conditions and stamp stack

$$\begin{aligned} & \llbracket \text{kind } g \text{ } nid = \text{EndNode}; \\ & \text{nid} \notin \text{seen}; \\ & \text{seen}' = \{nid\} \cup \text{seen}; \\ & \text{nid}' = \text{any-usage } g \text{ } nid; \\ & \text{analysis}' = \text{sa } (nid, \text{seen}, \text{analysis}) \\ \implies & \text{Step sa } g \text{ } (nid, \text{seen}, \text{analysis}) \text{ } (\text{Some } (nid', \text{seen}', \text{analysis}')) \mid \end{aligned}$$

— We can find a successor edge that is not in seen, go there

$$\begin{aligned} & \llbracket \neg(\text{is-EndNode } (kind \text{ } g \text{ } nid)); \\ & \neg(\text{is-BEGINNode } (kind \text{ } g \text{ } nid)); \\ & \text{nid} \notin \text{seen}; \\ & \text{seen}' = \{nid\} \cup \text{seen}; \\ & \text{Some } nid' = \text{nextEdge seen}' \text{ } nid \text{ } g; \\ & \text{analysis}' = \text{sa } (nid, \text{seen}, \text{analysis}) \\ \implies & \text{Step sa } g \text{ } (nid, \text{seen}, \text{analysis}) \text{ } (\text{Some } (nid', \text{seen}', \text{analysis}')) \mid \end{aligned}$$

— We can cannot find a successor edge that is not in seen, give back None

$$\begin{aligned} & \llbracket \neg(\text{is-EndNode } (kind \text{ } g \text{ } nid)); \\ & \neg(\text{is-BEGINNode } (kind \text{ } g \text{ } nid)); \\ & \text{nid} \notin \text{seen}; \\ & \text{seen}' = \{nid\} \cup \text{seen}; \\ & \text{None} = \text{nextEdge seen}' \text{ } nid \text{ } g \\ \implies & \text{Step sa } g \text{ } (nid, \text{seen}, \text{analysis}) \text{ } \text{None} \mid \end{aligned}$$

— We've already seen this node, give back None

$$\llbracket nid \in \text{seen} \rrbracket \implies \text{Step sa } g \text{ } (nid, \text{seen}, \text{analysis}) \text{ } \text{None}$$

code-pred (*modes*: $i \Rightarrow i \Rightarrow i \Rightarrow o \Rightarrow \text{bool}$) *Step* .

end

4.2 Structural Graph Comparison

theory

Comparison

```

imports
  IRGraph
begin

```

We introduce a form of structural graph comparison that is able to assert structural equivalence of graphs which differ in zero or more reference node chains for any given nodes.

```

fun find-ref-nodes :: IRGraph  $\Rightarrow$  (ID  $\rightarrow$  ID) where
find-ref-nodes g = map-of
  (map ( $\lambda n.$  (n, ir-ref (kind g n))) (filter ( $\lambda id.$  is-RefNode (kind g id)) (sorted-list-of-set
    (ids g))))

```

```

fun replace-ref-nodes :: IRGraph  $\Rightarrow$  (ID  $\rightarrow$  ID)  $\Rightarrow$  ID list  $\Rightarrow$  ID list where
replace-ref-nodes g m xs = map ( $\lambda id.$  (case (m id) of Some other  $\Rightarrow$  other | None
 $\Rightarrow$  id)) xs

```

```

fun find-next :: ID list  $\Rightarrow$  ID set  $\Rightarrow$  ID option where
find-next to-see seen = (let l = (filter ( $\lambda nid.$  nid  $\notin$  seen) to-see)
  in (case l of []  $\Rightarrow$  None | xs  $\Rightarrow$  Some (hd xs)))

```

```

inductive reachables :: IRGraph  $\Rightarrow$  ID list  $\Rightarrow$  ID set  $\Rightarrow$  ID set  $\Rightarrow$  bool where
reachables g [] {} {} |
[[None = find-next to-see seen]  $\implies$  reachables g to-see seen seen |
[Some n = find-next to-see seen;
  node = kind g n;
  new = (inputs-of node) @ (successors-of node);
  reachables g (to-see @ new) ({n}  $\cup$  seen) seen']  $\implies$  reachables g to-see seen
seen'

```

```

code-pred (modes: i  $\Rightarrow$  i  $\Rightarrow$  i  $\Rightarrow$  o  $\Rightarrow$  bool) [show-steps, show-mode-inference, show-intermediate-results]
reachables .

```

```

inductive nodeEq :: (ID  $\rightarrow$  ID)  $\Rightarrow$  IRGraph  $\Rightarrow$  ID  $\Rightarrow$  IRGraph  $\Rightarrow$  ID  $\Rightarrow$  bool
where
[[ kind g1 n1 = RefNode ref; nodeEq m g1 ref g2 n2 ]  $\implies$  nodeEq m g1 n1 g2 n2 |
[ x = kind g1 n1;
  y = kind g2 n2;
  is-same-ir-node-type x y;
  replace-ref-nodes g1 m (successors-of x) = successors-of y;
  replace-ref-nodes g1 m (inputs-of x) = inputs-of y ]
 $\implies$  nodeEq m g1 n1 g2 n2

```

```

code-pred [show-modes] nodeEq .

```

```

fun diffNodesGraph :: IRGraph  $\Rightarrow$  IRGraph  $\Rightarrow$  ID set where
diffNodesGraph g1 g2 = (let refNodes = find-ref-nodes g1 in
  { n . n  $\in$  Predicate.the (reachables-i-i-i-o g1 [0] {})  $\wedge$  (case refNodes n of Some
    -  $\Rightarrow$  False | -  $\Rightarrow$  True)  $\wedge$   $\neg$ (nodeEq refNodes g1 n g2 n)})

```

```
fun diffNodesInfo :: IRGraph  $\Rightarrow$  IRGraph  $\Rightarrow$  (ID  $\times$  IRNode  $\times$  IRNode) set where
diffNodesInfo g1 g2 = {(nid, kind g1 nid, kind g2 nid) | nid . nid  $\in$  diffNodesGraph
g1 g2}
```

```
fun eqGraph :: IRGraph  $\Rightarrow$  IRGraph  $\Rightarrow$  bool where
eqGraph isabelle-graph graal-graph = ((diffNodesGraph isabelle-graph graal-graph)
= {})
```

```
end
```

5 Data-flow Semantics

```
theory IRTreeEval
imports
  Graph.Values
  Graph.Stamp
begin
```

We define a tree representation of data-flow nodes, as an abstraction of the graph view.

Data-flow trees are evaluated in the context of a method state (currently called MapState in the theories for historical reasons).

The method state consists of the values for each method parameter, references to method parameters use an index of the parameter within the parameter list, as such we store a list of parameter values which are looked up at parameter references.

The method state also stores a mapping of node ids to values. The contents of this mapping is calculates during the traversal of the control flow graph.

As a concrete example, as the *SignedDivNode* can have side-effects (during division by zero), it is treated as part of the control-flow, since the data-flow phase is specified to be side-effect free. As a result, the control-flow semantics for *SignedDivNode* calculates the value of a node and maps the node identifier to the value within the method state. The data-flow semantics then just reads the value stored in the method state for the node.

```
type-synonym ID = nat
type-synonym MapState = ID  $\Rightarrow$  Value
type-synonym Params = Value list
```

```
definition new-map-state :: MapState where
  new-map-state = ( $\lambda x$ ..UndefVal)
```

5.1 Data-flow Tree Representation

```
datatype IRUnaryOp =
```

```

    UnaryAbs
  | UnaryNeg
  | UnaryNot
  | UnaryLogicNegation
  | UnaryNarrow (ir-inputBits: nat) (ir-resultBits: nat)
  | UnarySignExtend (ir-inputBits: nat) (ir-resultBits: nat)
  | UnaryZeroExtend (ir-inputBits: nat) (ir-resultBits: nat)

datatype IRBinaryOp =
  BinAdd
  | BinMul
  | BinSub
  | BinAnd
  | BinOr
  | BinXor
  | BinLeftShift
  | BinRightShift
  | BinURightShift
  | BinIntegerEquals
  | BinIntegerLessThan
  | BinIntegerBelow

datatype (discs-sels) IRExpr =
  UnaryExpr (ir-uop: IRUnaryOp) (ir-value: IRExpr)
  | BinaryExpr (ir-op: IRBinaryOp) (ir-x: IRExpr) (ir-y: IRExpr)
  | ConditionalExpr (ir-condition: IRExpr) (ir-trueValue: IRExpr) (ir-falseValue:
IRExpr)

  | ParameterExpr (ir-index: nat) (ir-stamp: Stamp)

  | LeafExpr (ir-nid: ID) (ir-stamp: Stamp)

  | ConstantExpr (ir-const: Value)
  | ConstantVar (ir-name: string)
  | VariableExpr (ir-name: string) (ir-stamp: Stamp)

fun is-ground :: IRExpr ⇒ bool where
  is-ground (UnaryExpr op e) = is-ground e |
  is-ground (BinaryExpr op e1 e2) = (is-ground e1 ∧ is-ground e2) |
  is-ground (ConditionalExpr b e1 e2) = (is-ground b ∧ is-ground e1 ∧ is-ground
e2) |
  is-ground (ParameterExpr i s) = True |
  is-ground (LeafExpr n s) = True |
  is-ground (ConstantExpr v) = True |
  is-ground (ConstantVar name) = False |
  is-ground (VariableExpr name s) = False

typedef GroundExpr = { e :: IRExpr . is-ground e }

```

```

using is-ground.simps(6) by blast

fun stamp-unary :: IRUnaryOp ⇒ Stamp ⇒ Stamp where
  stamp-unary op (IntegerStamp b lo hi) = unrestricted-stamp (IntegerStamp b lo
hi) |

  stamp-unary op - = IllegalStamp

definition fixed-32 :: IRBinaryOp set where
  fixed-32 = {BinIntegerEquals, BinIntegerLessThan, BinIntegerBelow}

fun stamp-binary :: IRBinaryOp ⇒ Stamp ⇒ Stamp ⇒ Stamp where
  stamp-binary op (IntegerStamp b1 lo1 hi1) (IntegerStamp b2 lo2 hi2) =
    (case op ∈ fixed-32 of True ⇒ unrestricted-stamp (IntegerStamp 32 lo1 hi1) |
```

False ⇒

```

    (if (b1 = b2) then unrestricted-stamp (IntegerStamp b1 lo1 hi1) else Illegal-
Stamp)) |

  stamp-binary op - - = IllegalStamp

fun stamp-expr :: IRExpr ⇒ Stamp where
  stamp-expr (UnaryExpr op x) = stamp-unary op (stamp-expr x) |
  stamp-expr (BinaryExpr bop x y) = stamp-binary bop (stamp-expr x) (stamp-expr
y) |
  stamp-expr (ConstantExpr val) = constantAsStamp val |
  stamp-expr (LeafExpr i s) = s |
  stamp-expr (ParameterExpr i s) = s |
  stamp-expr (ConditionalExpr c t f) = meet (stamp-expr t) (stamp-expr f)

export-code stamp-unary stamp-binary stamp-expr

```

5.2 Data-flow Tree Evaluation

```

fun unary-eval :: IRUnaryOp ⇒ Value ⇒ Value where
  unary-eval UnaryAbs v = intval-abs v |
  unary-eval UnaryNeg v = intval-negate v |
  unary-eval UnaryNot v = intval-not v |
  unary-eval UnaryLogicNegation v = intval-logic-negation v |
  unary-eval op v1 = UndefVal

fun bin-eval :: IRBinaryOp ⇒ Value ⇒ Value ⇒ Value where
  bin-eval BinAdd v1 v2 = intval-add v1 v2 |
  bin-eval BinMul v1 v2 = intval-mul v1 v2 |
  bin-eval BinSub v1 v2 = intval-sub v1 v2 |
  bin-eval BinAnd v1 v2 = intval-and v1 v2 |
  bin-eval BinOr v1 v2 = intval-or v1 v2 |
  bin-eval BinXor v1 v2 = intval-xor v1 v2 |
  bin-eval BinLeftShift v1 v2 = intval-left-shift v1 v2 |

```

$\text{bin-eval BinRightShift } v1 \ v2 = \text{intval-right-shift } v1 \ v2 \mid$
 $\text{bin-eval BinURightShift } v1 \ v2 = \text{intval-uright-shift } v1 \ v2 \mid$
 $\text{bin-eval BinIntegerEquals } v1 \ v2 = \text{intval-equals } v1 \ v2 \mid$
 $\text{bin-eval BinIntegerLessThan } v1 \ v2 = \text{intval-less-than } v1 \ v2 \mid$
 $\text{bin-eval BinIntegerBelow } v1 \ v2 = \text{intval-below } v1 \ v2$

inductive *not-undef-or-fail* :: *Value* \Rightarrow *Value* \Rightarrow *bool* **where**
 $\llbracket \text{value} \neq \text{UndefVal} \rrbracket \implies \text{not-undef-or-fail value value}$

notation (*latex output*)
 $\text{not-undef-or-fail } (- = -)$

inductive
 $\text{evaltree} :: \text{MapState} \Rightarrow \text{Params} \Rightarrow \text{IRExpr} \Rightarrow \text{Value} \Rightarrow \text{bool} \ (\llbracket -, - \rrbracket \vdash - \mapsto - \ 55)$
for *m p* **where**

ConstantExpr:
 $\llbracket \text{valid-value } c \ (\text{constantAsStamp } c) \rrbracket$
 $\implies [m, p] \vdash (\text{ConstantExpr } c) \mapsto c \mid$

ParameterExpr:
 $\llbracket i < \text{length } p; \text{valid-value } (p!i) \ s \rrbracket$
 $\implies [m, p] \vdash (\text{ParameterExpr } i \ s) \mapsto p!i \mid$

ConditionalExpr:
 $\llbracket [m, p] \vdash ce \mapsto \text{cond};$
 $\text{branch} = (\text{if val-to-bool cond then te else fe});$
 $[m, p] \vdash \text{branch} \mapsto v;$
 $v \neq \text{UndefVal} \rrbracket$
 $\implies [m, p] \vdash (\text{ConditionalExpr } ce \ te \ fe) \mapsto v \mid$

UnaryExpr:
 $\llbracket [m, p] \vdash xe \mapsto v;$
 $\text{result} = (\text{unary-eval op } v);$
 $\text{result} \neq \text{UndefVal} \rrbracket$
 $\implies [m, p] \vdash (\text{UnaryExpr op } xe) \mapsto \text{result} \mid$

BinaryExpr:
 $\llbracket [m, p] \vdash xe \mapsto x;$
 $[m, p] \vdash ye \mapsto y;$
 $\text{result} = (\text{bin-eval op } x \ y);$
 $\text{result} \neq \text{UndefVal} \rrbracket$
 $\implies [m, p] \vdash (\text{BinaryExpr op } xe \ ye) \mapsto \text{result} \mid$

LeafExpr:
 $\llbracket \text{val} = m \ n;$
 $\text{valid-value val } s \rrbracket$

$\implies [m,p] \vdash \text{LeafExpr } n \ s \mapsto \text{val}$

code-pred (*modes*: $i \Rightarrow i \Rightarrow i \Rightarrow o \Rightarrow \text{bool}$ as *evalT*)
 [*show-steps, show-mode-inference, show-intermediate-results*]
evaltree .

inductive

evaltrees :: *MapState* \Rightarrow *Params* \Rightarrow *IRExpr list* \Rightarrow *Value list* \Rightarrow *bool* ($[-, -] \vdash - \mapsto_L$
 - 55)

for *m p* **where**

EvalNil:

$[m,p] \vdash [] \mapsto_L []$ |

EvalCons:

$[[m,p] \vdash x \mapsto \text{xval};$

$[m,p] \vdash yy \mapsto_L \text{yyval}]$

$\implies [m,p] \vdash (x \# yy) \mapsto_L (\text{xval} \# \text{yyval})$

code-pred (*modes*: $i \Rightarrow i \Rightarrow i \Rightarrow o \Rightarrow \text{bool}$ as *evalTs*)
evaltrees .

definition *sq-param0* :: *IRExpr* **where**

sq-param0 = *BinaryExpr BinMul*

(*ParameterExpr* 0 (*IntegerStamp* 32 (− 2147483648) 2147483647))

(*ParameterExpr* 0 (*IntegerStamp* 32 (− 2147483648) 2147483647))

values {*v. evaltree new-map-state [IntVal32 5] sq-param0 v*}

declare *evaltree.intros* [*intro*]

declare *evaltrees.intros* [*intro*]

5.3 Data-flow Tree Refinement

We define the induced semantic equivalence relation between expressions. Note that syntactic equality implies semantic equivalence, but not vice versa.

definition *equiv-exprs* :: *IRExpr* \Rightarrow *IRExpr* \Rightarrow *bool* ($- \doteq -$ 55) **where**

($e1 \doteq e2$) = ($\forall \ m \ p \ v. ([m,p] \vdash e1 \mapsto v) \longleftrightarrow ([m,p] \vdash e2 \mapsto v)$)

We also prove that this is a total equivalence relation (*equivp equiv-exprs*) (HOL.Equiv_Relations), so that we can reuse standard results about equivalence relations.

lemma *equivp equiv-exprs*

apply (*auto simp add: equivp-def equiv-exprs-def*)

by (*metis equiv-exprs-def*)+

We define a refinement ordering over $IRExpr$ and show that it is a preorder. Note that it is asymmetric because e_2 may refer to fewer variables than e_1 .

instantiation $IRExpr :: preorder$ **begin**

notation $less-eq$ (**infix** \sqsubseteq 65)

definition

$le-expr-def$ [*simp*]:

$(e_2 \leq e_1) \longleftrightarrow (\forall m p v. ([m,p] \vdash e_1 \mapsto v) \longrightarrow ([m,p] \vdash e_2 \mapsto v))$

definition

$lt-expr-def$ [*simp*]:

$(e_1 < e_2) \longleftrightarrow (e_1 \leq e_2 \wedge \neg (e_1 \doteq e_2))$

instance proof

fix $x y z :: IRExpr$

show $x < y \longleftrightarrow x \leq y \wedge \neg (y \leq x)$ **by** (*simp add: equiv-exprs-def; auto*)

show $x \leq x$ **by** *simp*

show $x \leq y \implies y \leq z \implies x \leq z$ **by** *simp*

qed

end

abbreviation (**output**) $Refines :: IRExpr \Rightarrow IRExpr \Rightarrow bool$ (**infix** \sqsupseteq 64)

where $e_1 \sqsupseteq e_2 \equiv (e_2 \leq e_1)$

end

5.4 Data-flow Tree Theorems

theory $IRTreeEvalThms$

imports

$IRTreeEval$

begin

5.4.1 Deterministic Data-flow Evaluation

lemma $evalDet$:

$[m,p] \vdash e \mapsto v_1 \implies$

$[m,p] \vdash e \mapsto v_2 \implies$

$v_1 = v_2$

apply (*induction arbitrary: v2 rule: evaltree.induct*)

by (*elim EvalTreeE; auto*)+

lemma $evalAllDet$:

$[m,p] \vdash e \mapsto_L v1 \implies$

$[m,p] \vdash e \mapsto_L v2 \implies$

$v1 = v2$

apply (*induction arbitrary: v2 rule: evaltrees.induct*)

```

apply (elim EvalTreeE; auto)
using evalDet by force

```

5.4.2 Evaluation Results are Valid

A valid value cannot be *UndefVal*.

```

lemma valid-not-undef:
  assumes a1: valid-value val s
  assumes a2: s ≠ VoidStamp
  shows val ≠ UndefVal
  apply (rule valid-value.elims(1)[of val s True])
  using a1 a2 by auto

```

```

lemma valid-VoidStamp[elim]:
  shows valid-value val VoidStamp  $\implies$ 
    val = UndefVal
  using valid-value.simps by metis

```

```

lemma valid-ObjStamp[elim]:
  shows valid-value val (ObjectStamp klass exact nonNull alwaysNull)  $\implies$ 
    ( $\exists v. val = ObjRef v$ )
  using valid-value.simps by (metis val-to-bool.cases)

```

```

lemma valid-int32[elim]:
  shows valid-value val (IntegerStamp 32 l h)  $\implies$ 
    ( $\exists v. val = IntVal32 v$ )
  apply (rule val-to-bool.cases[of val])
  using Value.distinct by simp+

```

```

lemma valid-int64[elim]:
  shows valid-value val (IntegerStamp 64 l h)  $\implies$ 
    ( $\exists v. val = IntVal64 v$ )
  apply (rule val-to-bool.cases[of val])
  using Value.distinct by simp+

```

```

lemmas valid-value-elim =
  valid-VoidStamp
  valid-ObjStamp
  valid-int32
  valid-int64

```

```

lemma evaltree-not-undef:
  fixes m p e v
  shows ( $[m,p] \vdash e \mapsto v$ )  $\implies v \neq UndefVal$ 
  apply (induction rule: evaltree.induct)
  using valid-not-undef by auto

```

lemma *leafint32*:

assumes *ev*: $[m,p] \vdash \text{LeafExpr } i \text{ (IntegerStamp 32 lo hi)} \mapsto \text{val}$
shows $\exists v. \text{val} = (\text{IntVal32 } v)$

proof –

have *valid-value* *val* (IntegerStamp 32 lo hi)
using *ev* **by** (rule LeafExprE; simp)
then show ?thesis **by** auto

qed

lemma *leafint64*:

assumes *ev*: $[m,p] \vdash \text{LeafExpr } i \text{ (IntegerStamp 64 lo hi)} \mapsto \text{val}$
shows $\exists v. \text{val} = (\text{IntVal64 } v)$

proof –

have *valid-value* *val* (IntegerStamp 64 lo hi)
using *ev* **by** (rule LeafExprE; simp)
then show ?thesis **by** auto

qed

lemma *default-stamp* [*simp*]: *default-stamp* = IntegerStamp 32 (–2147483648)
2147483647

using *default-stamp-def* **by** auto

lemma *valid32* [*simp*]:

assumes *valid-value* *val* (IntegerStamp 32 lo hi)
shows $\exists v. (\text{val} = (\text{IntVal32 } v) \wedge \text{lo} \leq \text{sint } v \wedge \text{sint } v \leq \text{hi})$
using *assms valid-int32* **by** force

lemma *valid64* [*simp*]:

assumes *valid-value* *val* (IntegerStamp 64 lo hi)
shows $\exists v. (\text{val} = (\text{IntVal64 } v) \wedge \text{lo} \leq \text{sint } v \wedge \text{sint } v \leq \text{hi})$
using *assms valid-int64* **by** force

lemma *valid32or64*:

assumes *valid-value* *x* (IntegerStamp *b* lo hi)
shows $(\exists v1. (x = \text{IntVal32 } v1)) \vee (\exists v2. (x = \text{IntVal64 } v2))$
using *valid32 valid64 assms valid-value.elims(2)* **by** blast

lemma *valid32or64-both*:

assumes *valid-value* *x* (IntegerStamp *b* lox hix)
and *valid-value* *y* (IntegerStamp *b* loy hiy)
shows $(\exists v1 v2. x = \text{IntVal32 } v1 \wedge y = \text{IntVal32 } v2) \vee (\exists v3 v4. x = \text{IntVal64 } v3 \wedge y = \text{IntVal64 } v4)$
using *assms valid32or64 valid32 valid-value.elims(2) valid-value.simps(1)* **by** metis

5.4.3 Example Data-flow Optimisations

```

lemma a0a-helper [simp]:
  assumes a: valid-value v (IntegerStamp 32 lo hi)
  shows intval-add v (IntVal32 0) = v
proof –
  obtain v32 :: int32 where v = (IntVal32 v32) using a valid32 by blast
  then show ?thesis by simp
qed

lemma a0a: (BinaryExpr BinAdd (LeafExpr 1 default-stamp) (ConstantExpr (IntVal32
0)))
  ≥ (LeafExpr 1 default-stamp)
by (auto simp add: evaltree.LeanExpr)

```

```

lemma xyx-y-helper [simp]:
  assumes valid-value x (IntegerStamp 32 lox hix)
  assumes valid-value y (IntegerStamp 32 loy hiy)
  shows intval-add x (intval-sub y x) = y
proof –
  obtain x32 :: int32 where x: x = (IntVal32 x32) using assms valid32 by blast
  obtain y32 :: int32 where y: y = (IntVal32 y32) using assms valid32 by blast
  show ?thesis using x y by simp
qed

```

```

lemma xyx-y:
  (BinaryExpr BinAdd
    (LeafExpr x (IntegerStamp 32 lox hix))
    (BinaryExpr BinSub
      (LeafExpr y (IntegerStamp 32 loy hiy))
      (LeafExpr x (IntegerStamp 32 lox hix))))
  ≥ (LeafExpr y (IntegerStamp 32 loy hiy))
by (auto simp add: LeafExpr)

```

5.4.4 Monotonicity of Expression Refinement

We prove that each subexpression position is monotonic. That is, optimizing a subexpression anywhere deep inside a top-level expression also optimizes that top-level expression.

Note that we might also be able to do this via reusing Isabelle’s ‘mono’ operator (HOL.Orderings theory), proving instantiations like ‘mono (UnaryExpr op)’, but it is not obvious how to do this for both arguments of the binary expressions.

```

lemma mono-unary:
  assumes e ≥ e'
  shows (UnaryExpr op e) ≥ (UnaryExpr op e')

```

```

using UnaryExpr assms by auto

lemma mono-binary:
  assumes  $x \geq x'$ 
  assumes  $y \geq y'$ 
  shows  $(BinaryExpr\ op\ x\ y) \geq (BinaryExpr\ op\ x'\ y')$ 
  using BinaryExpr assms by auto

lemma never-void:
  assumes  $[m, p] \vdash x \mapsto xv$ 
  assumes valid-value  $xv$  (stamp-expr  $xe$ )
  shows stamp-expr  $xe \neq VoidStamp$ 
  using valid-value.simps
  using assms(2) by force

lemma stamp32:
   $\exists v . xv = IntVal32\ v \longleftrightarrow \text{valid-value } xv\ (IntegerStamp\ 32\ lo\ hi)$ 
  using valid-int32
  by (metis (full-types) Value.inject(1) zero-neq-one)

lemma stamp64:
   $\exists v . xv = IntVal64\ v \longleftrightarrow \text{valid-value } xv\ (IntegerStamp\ 64\ lo\ hi)$ 
  using valid-int64
  by (metis (full-types) Value.inject(2) zero-neq-one)

lemma stamprange:
  valid-value  $v\ s \longrightarrow (\exists b\ lo\ hi. (s = IntegerStamp\ b\ lo\ hi) \wedge (b = 32 \vee b = 64))$ 
  using valid-value.elims stamp32 stamp64
  by (smt (verit, del-insts))

lemma compatible-trans:
  compatible  $x\ y \wedge \text{compatible } y\ z \implies \text{compatible } x\ z$ 
  by (smt (verit, best) compatible.elims(2) compatible.simps(1))

lemma compatible-refl:
  compatible  $x\ y \implies \text{compatible } y\ x$ 
  using compatible.elims(2) by fastforce

lemma mono-conditional:
  assumes  $ce \geq ce'$ 
  assumes  $te \geq te'$ 
  assumes  $fe \geq fe'$ 
  shows  $(ConditionalExpr\ ce\ te\ fe) \geq (ConditionalExpr\ ce'\ te'\ fe')$ 
proof (simp only: le-expr-def; (rule allI) $+$ ; rule impI)
  fix  $m\ p\ v$ 
  assume  $a: [m, p] \vdash ConditionalExpr\ ce\ te\ fe \mapsto v$ 
  then obtain cond where  $ce: [m, p] \vdash ce \mapsto cond$  by auto

```

```

then have ce': [m,p] ⊢ ce' ↦ cond using assms by auto

define branch where b: branch = (if val-to-bool cond then te else fe)
define branch' where b': branch' = (if val-to-bool cond then te' else fe')
then have beval: [m,p] ⊢ branch ↦ v using a b ce evalDet by blast

from beval have [m,p] ⊢ branch' ↦ v using assms b b' by auto
then show [m,p] ⊢ ConditionalExpr ce' te' fe' ↦ v
  using ConditionalExpr ce' b'
  using a by blast
qed

end

```

6 Tree to Graph

```

theory TreeToGraph
  imports
    Semantics.IRTreeEval
    Graph.IRGraph
begin

```

6.1 Subgraph to Data-flow Tree

```

fun find-node-and-stamp :: IRGraph ⇒ (IRNode × Stamp) ⇒ ID option where
  find-node-and-stamp g (n,s) =
    find (λi. kind g i = n ∧ stamp g i = s) (sorted-list-of-set(ids g))

export-code find-node-and-stamp

```

```

fun is-preevaluated :: IRNode ⇒ bool where
  is-preevaluated (InvokeNode n - - - -) = True |
  is-preevaluated (InvokeWithExceptionNode n - - - -) = True |
  is-preevaluated (NewInstanceNode n - -) = True |
  is-preevaluated (LoadFieldNode n - -) = True |
  is-preevaluated (SignedDivNode n - - - -) = True |
  is-preevaluated (SignedRemNode n - - - -) = True |
  is-preevaluated (ValuePhiNode n -) = True |
  is-preevaluated - = False

```

```

inductive
  rep :: IRGraph ⇒ ID ⇒ IRExpr ⇒ bool (- ⊢ - ≃ - 55)
  for g where

  ConstantNode:
    [[kind g n = ConstantNode c]]

```

$$\implies g \vdash n \simeq (\text{ConstantExpr } c) \mid$$

ParameterNode:

$$\begin{aligned} & \llbracket \text{kind } g \ n = \text{ParameterNode } i; \\ & \quad \text{stamp } g \ n = s \rrbracket \\ & \implies g \vdash n \simeq (\text{ParameterExpr } i \ s) \mid \end{aligned}$$

ConditionalNode:

$$\begin{aligned} & \llbracket \text{kind } g \ n = \text{ConditionalNode } c \ t \ f; \\ & \quad g \vdash c \simeq ce; \\ & \quad g \vdash t \simeq te; \\ & \quad g \vdash f \simeq fe \rrbracket \\ & \implies g \vdash n \simeq (\text{ConditionalExpr } ce \ te \ fe) \mid \end{aligned}$$

AbsNode:

$$\begin{aligned} & \llbracket \text{kind } g \ n = \text{AbsNode } x; \\ & \quad g \vdash x \simeq xe \rrbracket \\ & \implies g \vdash n \simeq (\text{UnaryExpr } \text{UnaryAbs } xe) \mid \end{aligned}$$

NotNode:

$$\begin{aligned} & \llbracket \text{kind } g \ n = \text{NotNode } x; \\ & \quad g \vdash x \simeq xe \rrbracket \\ & \implies g \vdash n \simeq (\text{UnaryExpr } \text{UnaryNot } xe) \mid \end{aligned}$$

NegateNode:

$$\begin{aligned} & \llbracket \text{kind } g \ n = \text{NegateNode } x; \\ & \quad g \vdash x \simeq xe \rrbracket \\ & \implies g \vdash n \simeq (\text{UnaryExpr } \text{UnaryNeg } xe) \mid \end{aligned}$$

LogicNegationNode:

$$\begin{aligned} & \llbracket \text{kind } g \ n = \text{LogicNegationNode } x; \\ & \quad g \vdash x \simeq xe \rrbracket \\ & \implies g \vdash n \simeq (\text{UnaryExpr } \text{UnaryLogicNegation } xe) \mid \end{aligned}$$

AddNode:

$$\begin{aligned} & \llbracket \text{kind } g \ n = \text{AddNode } x \ y; \\ & \quad g \vdash x \simeq xe; \\ & \quad g \vdash y \simeq ye \rrbracket \\ & \implies g \vdash n \simeq (\text{BinaryExpr } \text{BinAdd } xe \ ye) \mid \end{aligned}$$

MulNode:

$$\begin{aligned} & \llbracket \text{kind } g \ n = \text{MulNode } x \ y; \\ & \quad g \vdash x \simeq xe; \\ & \quad g \vdash y \simeq ye \rrbracket \\ & \implies g \vdash n \simeq (\text{BinaryExpr } \text{BinMul } xe \ ye) \mid \end{aligned}$$

SubNode:

$\llbracket \text{kind } g \ n = \text{SubNode } x \ y;$
 $g \vdash x \simeq xe;$
 $g \vdash y \simeq ye \rrbracket$
 $\implies g \vdash n \simeq (\text{BinaryExpr BinSub } xe \ ye) \mid$

AndNode:
 $\llbracket \text{kind } g \ n = \text{AndNode } x \ y;$
 $g \vdash x \simeq xe;$
 $g \vdash y \simeq ye \rrbracket$
 $\implies g \vdash n \simeq (\text{BinaryExpr BinAnd } xe \ ye) \mid$

OrNode:
 $\llbracket \text{kind } g \ n = \text{OrNode } x \ y;$
 $g \vdash x \simeq xe;$
 $g \vdash y \simeq ye \rrbracket$
 $\implies g \vdash n \simeq (\text{BinaryExpr BinOr } xe \ ye) \mid$

XorNode:
 $\llbracket \text{kind } g \ n = \text{XorNode } x \ y;$
 $g \vdash x \simeq xe;$
 $g \vdash y \simeq ye \rrbracket$
 $\implies g \vdash n \simeq (\text{BinaryExpr BinXor } xe \ ye) \mid$

LeftShiftNode:
 $\llbracket \text{kind } g \ n = \text{LeftShiftNode } x \ y;$
 $g \vdash x \simeq xe;$
 $g \vdash y \simeq ye \rrbracket$
 $\implies g \vdash n \simeq (\text{BinaryExpr BinLeftShift } xe \ ye) \mid$

RightShiftNode:
 $\llbracket \text{kind } g \ n = \text{RightShiftNode } x \ y;$
 $g \vdash x \simeq xe;$
 $g \vdash y \simeq ye \rrbracket$
 $\implies g \vdash n \simeq (\text{BinaryExpr BinRightShift } xe \ ye) \mid$

UnsignedRightShiftNode:
 $\llbracket \text{kind } g \ n = \text{UnsignedRightShiftNode } x \ y;$
 $g \vdash x \simeq xe;$
 $g \vdash y \simeq ye \rrbracket$
 $\implies g \vdash n \simeq (\text{BinaryExpr BinURightShift } xe \ ye) \mid$

IntegerBelowNode:
 $\llbracket \text{kind } g \ n = \text{IntegerBelowNode } x \ y;$
 $g \vdash x \simeq xe;$
 $g \vdash y \simeq ye \rrbracket$
 $\implies g \vdash n \simeq (\text{BinaryExpr BinIntegerBelow } xe \ ye) \mid$

IntegerEqualsNode:
 $\llbracket \text{kind } g \ n = \text{IntegerEqualsNode } x \ y;$

$g \vdash x \simeq xe;$
 $g \vdash y \simeq ye$
 $\implies g \vdash n \simeq (\text{BinaryExpr BinIntegerEquals } xe \ ye) \mid$

IntegerLessThanNode:

$\llbracket \text{kind } g \ n = \text{IntegerLessThanNode } x \ y;$
 $g \vdash x \simeq xe;$
 $g \vdash y \simeq ye$
 $\implies g \vdash n \simeq (\text{BinaryExpr BinIntegerLessThan } xe \ ye) \mid$

NarrowNode:

$\llbracket \text{kind } g \ n = \text{NarrowNode inputBits resultBits } x;$
 $g \vdash x \simeq xe$
 $\implies g \vdash n \simeq (\text{UnaryExpr (UnaryNarrow inputBits resultBits) } xe) \mid$

SignExtendNode:

$\llbracket \text{kind } g \ n = \text{SignExtendNode inputBits resultBits } x;$
 $g \vdash x \simeq xe$
 $\implies g \vdash n \simeq (\text{UnaryExpr (UnarySignExtend inputBits resultBits) } xe) \mid$

ZeroExtendNode:

$\llbracket \text{kind } g \ n = \text{ZeroExtendNode inputBits resultBits } x;$
 $g \vdash x \simeq xe$
 $\implies g \vdash n \simeq (\text{UnaryExpr (UnaryZeroExtend inputBits resultBits) } xe) \mid$

LeafNode:

$\llbracket \text{is-preevaluated (kind } g \ n);$
 $\text{stamp } g \ n = s$
 $\implies g \vdash n \simeq (\text{LeafExpr } n \ s) \mid$

RefNode:

$\llbracket \text{kind } g \ n = \text{RefNode } n';$
 $g \vdash n' \simeq e$
 $\implies g \vdash n \simeq e$

code-pred (*modes*: $i \Rightarrow i \Rightarrow o \Rightarrow \text{bool as exprE}$) *rep* .

inductive

$\text{replist} :: \text{IRGraph} \Rightarrow \text{ID list} \Rightarrow \text{IRExpr list} \Rightarrow \text{bool} \ (- \vdash - \simeq_L - \ 55)$
for *g* **where**

RepNil:

$g \vdash [] \simeq_L [] \mid$

RepCons:

$$\begin{aligned} & \llbracket g \vdash x \simeq xe; \\ & \quad g \vdash xs \simeq_L xse \rrbracket \\ & \implies g \vdash x \# xs \simeq_L xe \# xse \end{aligned}$$

code-pred (*modes*: $i \Rightarrow i \Rightarrow o \Rightarrow \text{bool}$ as *exprListE*) *replist* .

definition *wf-term-graph* :: *MapState* \Rightarrow *Params* \Rightarrow *IRGraph* \Rightarrow *ID* \Rightarrow *bool* **where**
wf-term-graph *m p g n* = ($\exists e. (g \vdash n \simeq e) \wedge (\exists v. ([m, p] \vdash e \mapsto v))$)

values {*t. eg2-sq* $\vdash 4 \simeq t$ }

6.2 Data-flow Tree to Subgraph

fun *unary-node* :: *IRUnaryOp* \Rightarrow *ID* \Rightarrow *IRNode* **where**

unary-node *UnaryAbs* *v* = *AbsNode* *v* |
unary-node *UnaryNot* *v* = *NotNode* *v* |
unary-node *UnaryNeg* *v* = *NegateNode* *v* |
unary-node *UnaryLogicNegation* *v* = *LogicNegationNode* *v* |
unary-node (*UnaryNarrow* *ib rb*) *v* = *NarrowNode* *ib rb v* |
unary-node (*UnarySignExtend* *ib rb*) *v* = *SignExtendNode* *ib rb v* |
unary-node (*UnaryZeroExtend* *ib rb*) *v* = *ZeroExtendNode* *ib rb v*

fun *bin-node* :: *IRBinaryOp* \Rightarrow *ID* \Rightarrow *ID* \Rightarrow *IRNode* **where**

bin-node *BinAdd* *x y* = *AddNode* *x y* |
bin-node *BinMul* *x y* = *MulNode* *x y* |
bin-node *BinSub* *x y* = *SubNode* *x y* |
bin-node *BinAnd* *x y* = *AndNode* *x y* |
bin-node *BinOr* *x y* = *OrNode* *x y* |
bin-node *BinXor* *x y* = *XorNode* *x y* |
bin-node *BinLeftShift* *x y* = *LeftShiftNode* *x y* |
bin-node *BinRightShift* *x y* = *RightShiftNode* *x y* |
bin-node *BinURightShift* *x y* = *UnsignedRightShiftNode* *x y* |
bin-node *BinIntegerEquals* *x y* = *IntegerEqualsNode* *x y* |
bin-node *BinIntegerLessThan* *x y* = *IntegerLessThanNode* *x y* |
bin-node *BinIntegerBelow* *x y* = *IntegerBelowNode* *x y*

fun *choose-32-64* :: *int* \Rightarrow *int64* \Rightarrow *Value* **where**

choose-32-64 *bits val* =
 (if *bits* = 32
 then (*IntVal32* (*ucast* *val*))
 else (*IntVal64* (*val*)))

inductive *fresh-id* :: *IRGraph* \Rightarrow *ID* \Rightarrow *bool* **where**

$n \notin \text{ids } g \implies \text{fresh-id } g \ n$

code-pred *fresh-id* .

fun *get-fresh-id* :: *IRGraph* \Rightarrow *ID* **where**

get-fresh-id *g* = *last*(*sorted-list-of-set*(*ids* *g*)) + 1

export-code *get-fresh-id*

value *get-fresh-id* *eg2-sq*

value *get-fresh-id* (*add-node* 6 (*ParameterNode* 2, *default-stamp*) *eg2-sq*)

inductive

unrep :: *IRGraph* \Rightarrow *IRExpr* \Rightarrow (*IRGraph* \times *ID*) \Rightarrow *bool* (- \triangleleft - \rightsquigarrow - 55)
where

ConstantNodeSame:

$\llbracket \text{find-node-and-stamp } g \ (\text{ConstantNode } c, \text{constantAsStamp } c) = \text{Some } n \rrbracket$
 $\implies g \triangleleft (\text{ConstantExpr } c) \rightsquigarrow (g, n) \mid$

ConstantNodeNew:

$\llbracket \text{find-node-and-stamp } g \ (\text{ConstantNode } c, \text{constantAsStamp } c) = \text{None};$
n = *get-fresh-id* *g*;
g' = *add-node* *n* (*ConstantNode* *c*, *constantAsStamp* *c*) *g*]
 $\implies g \triangleleft (\text{ConstantExpr } c) \rightsquigarrow (g', n) \mid$

ParameterNodeSame:

$\llbracket \text{find-node-and-stamp } g \ (\text{ParameterNode } i, s) = \text{Some } n \rrbracket$
 $\implies g \triangleleft (\text{ParameterExpr } i \ s) \rightsquigarrow (g, n) \mid$

ParameterNodeNew:

$\llbracket \text{find-node-and-stamp } g \ (\text{ParameterNode } i, s) = \text{None};$
n = *get-fresh-id* *g*;
g' = *add-node* *n* (*ParameterNode* *i*, *s*) *g*]
 $\implies g \triangleleft (\text{ParameterExpr } i \ s) \rightsquigarrow (g', n) \mid$

ConditionalNodeSame:

$\llbracket g \triangleleft ce \rightsquigarrow (g2, c);$
g2 $\triangleleft te \rightsquigarrow (g3, t);$
g3 $\triangleleft fe \rightsquigarrow (g4, f);$
s' = *meet* (*stamp* *g4* *t*) (*stamp* *g4* *f*);
find-node-and-stamp *g4* (*ConditionalNode* *c* *t* *f*, *s'*) = *Some* *n*]
 $\implies g \triangleleft (\text{ConditionalExpr } ce \ te \ fe) \rightsquigarrow (g4, n) \mid$

ConditionalNodeNew:

$\llbracket g \triangleleft ce \rightsquigarrow (g2, c);$

$g2 \triangleleft te \rightsquigarrow (g3, t);$
 $g3 \triangleleft fe \rightsquigarrow (g4, f);$
 $s' = \text{meet } (\text{stamp } g4 \ t) (\text{stamp } g4 \ f);$
 $\text{find-node-and-stamp } g4 \ (\text{ConditionalNode } c \ t \ f, s') = \text{None};$
 $n = \text{get-fresh-id } g4;$
 $g' = \text{add-node } n \ (\text{ConditionalNode } c \ t \ f, s') \ g4$
 $\implies g \triangleleft (\text{ConditionalExpr } ce \ te \ fe) \rightsquigarrow (g', n) \mid$

UnaryNodeSame:

$\llbracket g \triangleleft xe \rightsquigarrow (g2, x);$
 $s' = \text{stamp-unary } op \ (\text{stamp } g2 \ x);$
 $\text{find-node-and-stamp } g2 \ (\text{unary-node } op \ x, s') = \text{Some } n \rrbracket$
 $\implies g \triangleleft (\text{UnaryExpr } op \ xe) \rightsquigarrow (g2, n) \mid$

UnaryNodeNew:

$\llbracket g \triangleleft xe \rightsquigarrow (g2, x);$
 $s' = \text{stamp-unary } op \ (\text{stamp } g2 \ x);$
 $\text{find-node-and-stamp } g2 \ (\text{unary-node } op \ x, s') = \text{None};$
 $n = \text{get-fresh-id } g2;$
 $g' = \text{add-node } n \ (\text{unary-node } op \ x, s') \ g2$
 $\implies g \triangleleft (\text{UnaryExpr } op \ xe) \rightsquigarrow (g', n) \mid$

BinaryNodeSame:

$\llbracket g \triangleleft xe \rightsquigarrow (g2, x);$
 $g2 \triangleleft ye \rightsquigarrow (g3, y);$
 $s' = \text{stamp-binary } op \ (\text{stamp } g3 \ x) (\text{stamp } g3 \ y);$
 $\text{find-node-and-stamp } g3 \ (\text{bin-node } op \ x \ y, s') = \text{Some } n \rrbracket$
 $\implies g \triangleleft (\text{BinaryExpr } op \ xe \ ye) \rightsquigarrow (g3, n) \mid$

BinaryNodeNew:

$\llbracket g \triangleleft xe \rightsquigarrow (g2, x);$
 $g2 \triangleleft ye \rightsquigarrow (g3, y);$
 $s' = \text{stamp-binary } op \ (\text{stamp } g3 \ x) (\text{stamp } g3 \ y);$
 $\text{find-node-and-stamp } g3 \ (\text{bin-node } op \ x \ y, s') = \text{None};$
 $n = \text{get-fresh-id } g3;$
 $g' = \text{add-node } n \ (\text{bin-node } op \ x \ y, s') \ g3$
 $\implies g \triangleleft (\text{BinaryExpr } op \ xe \ ye) \rightsquigarrow (g', n) \mid$

AllLeafNodes:

$\llbracket \text{stamp } g \ n = s;$
 $\text{is-preevaluated } (\text{kind } g \ n) \rrbracket$
 $\implies g \triangleleft (\text{LeafExpr } n \ s) \rightsquigarrow (g, n)$

code-pred (*modes*: $i \Rightarrow i \Rightarrow o \Rightarrow \text{bool}$ as *unrepE*)
unrep .

$$\frac{\text{find-node-and-stamp } g \text{ (ConstantNode } c, \text{ constantAsStamp } c) = \text{Some } n}{g \triangleleft \text{ConstantExpr } c \rightsquigarrow (g, n)}$$

$$\frac{\begin{array}{l} \text{find-node-and-stamp } g \text{ (ConstantNode } c, \text{ constantAsStamp } c) = \text{None} \\ n = \text{get-fresh-id } g \\ g' = \text{add-node } n \text{ (ConstantNode } c, \text{ constantAsStamp } c) \end{array} \quad g}{g \triangleleft \text{ConstantExpr } c \rightsquigarrow (g', n)}$$

$$\frac{\text{find-node-and-stamp } g \text{ (ParameterNode } i, s) = \text{Some } n}{g \triangleleft \text{ParameterExpr } i \text{ } s \rightsquigarrow (g, n)}$$

$$\frac{\begin{array}{l} \text{find-node-and-stamp } g \text{ (ParameterNode } i, s) = \text{None} \\ n = \text{get-fresh-id } g \quad g' = \text{add-node } n \text{ (ParameterNode } i, s) \end{array} \quad g}{g \triangleleft \text{ParameterExpr } i \text{ } s \rightsquigarrow (g', n)}$$

$$\frac{\begin{array}{l} g \triangleleft ce \rightsquigarrow (g2, c) \quad g2 \triangleleft te \rightsquigarrow (g3, t) \\ g3 \triangleleft fe \rightsquigarrow (g4, f) \quad s' = \text{meet (stamp } g4 \text{ } t) \text{ (stamp } g4 \text{ } f) \\ \text{find-node-and-stamp } g4 \text{ (ConditionalNode } c \text{ } t \text{ } f, s') = \text{Some } n \end{array}}{g \triangleleft \text{ConditionalExpr } ce \text{ } te \text{ } fe \rightsquigarrow (g4, n)}$$

$$\frac{\begin{array}{l} g \triangleleft ce \rightsquigarrow (g2, c) \quad g2 \triangleleft te \rightsquigarrow (g3, t) \\ g3 \triangleleft fe \rightsquigarrow (g4, f) \quad s' = \text{meet (stamp } g4 \text{ } t) \text{ (stamp } g4 \text{ } f) \\ \text{find-node-and-stamp } g4 \text{ (ConditionalNode } c \text{ } t \text{ } f, s') = \text{None} \\ n = \text{get-fresh-id } g4 \quad g' = \text{add-node } n \text{ (ConditionalNode } c \text{ } t \text{ } f, s') \end{array} \quad g4}{g \triangleleft \text{ConditionalExpr } ce \text{ } te \text{ } fe \rightsquigarrow (g', n)}$$

$$\frac{\begin{array}{l} g \triangleleft xe \rightsquigarrow (g2, x) \\ g2 \triangleleft ye \rightsquigarrow (g3, y) \quad s' = \text{stamp-binary op (stamp } g3 \text{ } x) \text{ (stamp } g3 \text{ } y) \\ \text{find-node-and-stamp } g3 \text{ (bin-node op } x \text{ } y, s') = \text{Some } n \end{array}}{g \triangleleft \text{BinaryExpr op } xe \text{ } ye \rightsquigarrow (g3, n)}$$

$$\frac{\begin{array}{l} g \triangleleft xe \rightsquigarrow (g2, x) \\ g2 \triangleleft ye \rightsquigarrow (g3, y) \quad s' = \text{stamp-binary op (stamp } g3 \text{ } x) \text{ (stamp } g3 \text{ } y) \\ \text{find-node-and-stamp } g3 \text{ (bin-node op } x \text{ } y, s') = \text{None} \\ n = \text{get-fresh-id } g3 \quad g' = \text{add-node } n \text{ (bin-node op } x \text{ } y, s') \end{array} \quad g3}{g \triangleleft \text{BinaryExpr op } xe \text{ } ye \rightsquigarrow (g', n)}$$

$$\frac{\begin{array}{l} g \triangleleft xe \rightsquigarrow (g2, x) \quad s' = \text{stamp-unary op (stamp } g2 \text{ } x) \\ \text{find-node-and-stamp } g2 \text{ (unary-node op } x, s') = \text{Some } n \end{array}}{g \triangleleft \text{UnaryExpr op } xe \rightsquigarrow (g2, n)}$$

$$\frac{\begin{array}{l} g \triangleleft xe \rightsquigarrow (g2, x) \quad s' = \text{stamp-unary op (stamp } g2 \text{ } x) \\ \text{find-node-and-stamp } g2 \text{ (unary-node op } x, s') = \text{None} \\ n = \text{get-fresh-id } g2 \quad g' = \text{add-node } n \text{ (unary-node op } x, s') \end{array} \quad g2}{g \triangleleft \text{UnaryExpr op } xe \rightsquigarrow (g', n)}$$

$$\frac{\text{stamp } g \text{ } n = s \quad \text{is-preevaluated (kind } g \text{ } n)}{g \triangleleft \text{LeafExpr } n \text{ } s \rightsquigarrow (g, n)}$$

$values \{(n, g) . (eg2-sq \triangleleft sq-param0 \rightsquigarrow (g, n))\}$

6.3 Lift Data-flow Tree Semantics

definition $encodeeval :: IRGraph \Rightarrow MapState \Rightarrow Params \Rightarrow ID \Rightarrow Value \Rightarrow bool$
 $([\cdot, \cdot, \cdot] \vdash \cdot \mapsto \cdot \ 50)$
where
 $encodeeval \ g \ m \ p \ n \ v = (\exists \ e. (g \vdash n \simeq e) \wedge ([m, p] \vdash e \mapsto v))$

6.4 Graph Refinement

definition $graph-represents-expression :: IRGraph \Rightarrow ID \Rightarrow IRExpr \Rightarrow bool$
 $(\cdot \vdash \cdot \leq \cdot \ 50)$
where
 $(g \vdash n \leq e) = (\exists \ e' . (g \vdash n \simeq e') \wedge (e' \leq e))$

definition $graph-refinement :: IRGraph \Rightarrow IRGraph \Rightarrow bool$ **where**
 $graph-refinement \ g_1 \ g_2 =$
 $((ids \ g_1 \subseteq ids \ g_2) \wedge$
 $(\forall \ n . n \in ids \ g_1 \longrightarrow (\forall \ e. (g_1 \vdash n \simeq e) \longrightarrow (g_2 \vdash n \leq e))))$

lemma $graph-refinement$:

$graph-refinement \ g_1 \ g_2 \implies (\forall \ n \ m \ p \ v. n \in ids \ g_1 \longrightarrow ([g_1, m, p] \vdash n \mapsto v) \longrightarrow$
 $([g_2, m, p] \vdash n \mapsto v))$
by ($meson \ encodeeval-def \ graph-refinement-def \ graph-represents-expression-def \ le-expr-def$)

6.5 Maximal Sharing

definition $maximal-sharing$:
 $maximal-sharing \ g = (\forall \ n_1 \ n_2 . n_1 \in true-ids \ g \wedge n_2 \in true-ids \ g \longrightarrow$
 $(\forall \ e. (g \vdash n_1 \simeq e) \wedge (g \vdash n_2 \simeq e) \longrightarrow n_1 = n_2))$

end

6.6 Formedness Properties

theory $Form$
imports
 $Semantics.TreeToGraph$
begin

definition $wf-start$ **where**
 $wf-start \ g = (0 \in ids \ g \wedge$
 $is-StartNode \ (kind \ g \ 0))$

definition $wf-closed$ **where**
 $wf-closed \ g =$
 $(\forall \ n \in ids \ g .$
 $inputs \ g \ n \subseteq ids \ g \wedge$

$$\text{succ } g \ n \subseteq \text{ids } g \wedge \\ \text{kind } g \ n \neq \text{NoNode})$$

definition *wf-phis* **where**

$$\text{wf-phis } g = \\ (\forall \ n \in \text{ids } g. \\ \text{is-PhiNode } (\text{kind } g \ n) \longrightarrow \\ \text{length } (\text{ir-values } (\text{kind } g \ n)) \\ = \text{length } (\text{ir-ends } \\ (\text{kind } g \ (\text{ir-merge } (\text{kind } g \ n)))))$$

definition *wf-ends* **where**

$$\text{wf-ends } g = \\ (\forall \ n \in \text{ids } g . \\ \text{is-AbstractEndNode } (\text{kind } g \ n) \longrightarrow \\ \text{card } (\text{usages } g \ n) > 0)$$

fun *wf-graph* :: *IRGraph* \Rightarrow *bool* **where**

$$\text{wf-graph } g = (\text{wf-start } g \wedge \text{wf-closed } g \wedge \text{wf-phis } g \wedge \text{wf-ends } g)$$

lemmas *wf-folds* =

wf-graph.simps
wf-start-def
wf-closed-def
wf-phis-def
wf-ends-def

fun *wf-stamps* :: *IRGraph* \Rightarrow *bool* **where**

$$\text{wf-stamps } g = (\forall \ n \in \text{ids } g . \\ (\forall \ v \ m \ p \ e . (g \vdash n \simeq e) \wedge ([m, p] \vdash e \mapsto v) \longrightarrow \text{valid-value } v \ (\text{stamp-expr } e)))$$

fun *wf-stamp* :: *IRGraph* \Rightarrow (*ID* \Rightarrow *Stamp*) \Rightarrow *bool* **where**

$$\text{wf-stamp } g \ s = (\forall \ n \in \text{ids } g . \\ (\forall \ v \ m \ p \ e . (g \vdash n \simeq e) \wedge ([m, p] \vdash e \mapsto v) \longrightarrow \text{valid-value } v \ (s \ n)))$$

lemma *wf-empty*: *wf-graph start-end-graph*

unfolding *start-end-graph-def wf-folds by simp*

lemma *wf-eg2-sq*: *wf-graph eg2-sq*

unfolding *eg2-sq-def wf-folds by simp*

fun *wf-logic-node-inputs* :: *IRGraph* \Rightarrow *ID* \Rightarrow *bool* **where**

$$\text{wf-logic-node-inputs } g \ n = \\ (\forall \ \text{inp} \in \text{set } (\text{inputs-of } (\text{kind } g \ n)) . (\forall \ v \ m \ p . ([g, m, p] \vdash \text{inp} \mapsto v) \longrightarrow \text{wf-bool } v))$$

fun *wf-values* :: *IRGraph* \Rightarrow *bool* **where**

$$\text{wf-values } g = (\forall \ n \in \text{ids } g . \\ (\forall \ v \ m \ p . ([g, m, p] \vdash n \mapsto v) \longrightarrow$$


```

(is-LogicNode (kind g n)  $\longrightarrow$ 
  wf-bool v  $\wedge$  wf-logic-node-inputs g n)))

```

end

6.7 Dynamic Frames

This theory defines two operators, 'unchanged' and 'changeonly', that are useful for specifying which nodes in an IRGraph can change. The dynamic framing idea originates from 'Dynamic Frames' in software verification, started by Ioannis T. Kassios in "Dynamic frames: Support for framing, dependencies and sharing without restrictions", In FM 2006.

theory *IRGraphFrames*

imports

Form

Semantics.IRTreeEval

begin

fun *unchanged* :: *ID set* \Rightarrow *IRGraph* \Rightarrow *IRGraph* \Rightarrow *bool* **where**

unchanged ns g1 g2 = (\forall *n* . *n* \in *ns* \longrightarrow
 (*n* \in *ids g1* \wedge *n* \in *ids g2* \wedge *kind g1 n* = *kind g2 n* \wedge *stamp g1 n* = *stamp g2 n*))

fun *changeonly* :: *ID set* \Rightarrow *IRGraph* \Rightarrow *IRGraph* \Rightarrow *bool* **where**

changeonly ns g1 g2 = (\forall *n* . *n* \in *ids g1* \wedge *n* \notin *ns* \longrightarrow
 (*n* \in *ids g1* \wedge *n* \in *ids g2* \wedge *kind g1 n* = *kind g2 n* \wedge *stamp g1 n* = *stamp g2 n*))

lemma *node-unchanged*:

assumes *unchanged ns g1 g2*

assumes *nid* \in *ns*

shows *kind g1 nid* = *kind g2 nid*

using *assms* **by** *auto*

lemma *other-node-unchanged*:

assumes *changeonly ns g1 g2*

assumes *nid* \in *ids g1*

assumes *nid* \notin *ns*

shows *kind g1 nid* = *kind g2 nid*

using *assms*

using *changeonly.simps* **by** *blast*

Some notation for input nodes used

inductive *eval-uses*:: *IRGraph* \Rightarrow *ID* \Rightarrow *ID* \Rightarrow *bool*

for *g* **where**

use0: *nid* \in *ids g*

\implies *eval-uses g nid nid* |

```

use-inp:  $nid' \in inputs\ g\ n$ 
 $\implies eval\text{-}uses\ g\ nid\ nid' \mid$ 

use-trans:  $\llbracket eval\text{-}uses\ g\ nid\ nid';$ 
 $eval\text{-}uses\ g\ nid'\ nid'' \rrbracket$ 
 $\implies eval\text{-}uses\ g\ nid\ nid''$ 

fun eval-usages :: IRGraph  $\Rightarrow$  ID  $\Rightarrow$  ID set where
  eval-usages g nid = {n  $\in$  ids g . eval-uses g nid n}

lemma eval-usages-self:
  assumes nid  $\in$  ids g
  shows nid  $\in$  eval-usages g nid
  using assms eval-usages.simps eval-uses.intros(1)
  by (simp add: ids.rep-eq)

lemma not-in-g-inputs:
  assumes nid  $\notin$  ids g
  shows inputs g nid = {}
proof –
  have k: kind g nid = NoNode using assms not-in-g by blast
  then show ?thesis by (simp add: k)
qed

lemma child-member:
  assumes n = kind g nid
  assumes n  $\neq$  NoNode
  assumes List.member (inputs-of n) child
  shows child  $\in$  inputs g nid
  unfolding inputs.simps using assms
  by (metis in-set-member)

lemma child-member-in:
  assumes nid  $\in$  ids g
  assumes List.member (inputs-of (kind g nid)) child
  shows child  $\in$  inputs g nid
  unfolding inputs.simps using assms
  by (metis child-member ids-some inputs.elims)

lemma inp-in-g:
  assumes n  $\in$  inputs g nid
  shows nid  $\in$  ids g
proof –
  have inputs g nid  $\neq$  {}
  using assms
  by (metis empty-iff empty-set)

```

```

then have kind g nid  $\neq$  NoNode
  using not-in-g-inputs
  using ids-some by blast
then show ?thesis
  using not-in-g
  by metis
qed

```

```

lemma inp-in-g-wf:
  assumes wf-graph g
  assumes  $n \in \text{inputs } g \text{ nid}$ 
  shows  $n \in \text{ids } g$ 
  using assms unfolding wf-folds
  using inp-in-g by blast

```

```

lemma kind-unchanged:
  assumes nid  $\in \text{ids } g1$ 
  assumes unchanged (eval-usages g1 nid) g1 g2
  shows kind g1 nid = kind g2 nid
proof -
  show ?thesis
    using assms eval-usages-self
    using unchanged.simps by blast
qed

```

```

lemma stamp-unchanged:
  assumes nid  $\in \text{ids } g1$ 
  assumes unchanged (eval-usages g1 nid) g1 g2
  shows stamp g1 nid = stamp g2 nid
  by (meson assms(1) assms(2) eval-usages-self unchanged.elims(2))

```

```

lemma child-unchanged:
  assumes child  $\in \text{inputs } g1 \text{ nid}$ 
  assumes unchanged (eval-usages g1 nid) g1 g2
  shows unchanged (eval-usages g1 child) g1 g2
  by (smt assms(1) assms(2) eval-usages.simps mem-Collect-eq
      unchanged.simps use-inp use-trans)

```

```

lemma eval-usages:
  assumes us = eval-usages g nid
  assumes nid'  $\in \text{ids } g$ 
  shows eval-uses g nid nid'  $\longleftrightarrow$  nid'  $\in \text{us}$  (is ?P  $\longleftrightarrow$  ?Q)
  using assms eval-usages.simps
  by (simp add: ids.rep-eq)

```

```

lemma inputs-are-uses:
  assumes nid'  $\in \text{inputs } g \text{ nid}$ 

```

shows *eval-uses* *g nid nid'*
by (*metis assms use-inp*)

lemma *inputs-are-usages*:
assumes *nid' ∈ inputs g nid*
assumes *nid' ∈ ids g*
shows *nid' ∈ eval-usages g nid*
using *assms(1) assms(2) eval-usages inputs-are-uses* **by** *blast*

lemma *inputs-of-are-usages*:
assumes *List.member (inputs-of (kind g nid)) nid'*
assumes *nid' ∈ ids g*
shows *nid' ∈ eval-usages g nid*
by (*metis assms(1) assms(2) in-set-member inputs.elims inputs-are-usages*)

lemma *usage-includes-inputs*:
assumes *us = eval-usages g nid*
assumes *ls = inputs g nid*
assumes *ls ⊆ ids g*
shows *ls ⊆ us*
using *inputs-are-usages eval-usages*
using *assms(1) assms(2) assms(3)* **by** *blast*

lemma *elim-inp-set*:
assumes *k = kind g nid*
assumes *k ≠ NoNode*
assumes *child ∈ set (inputs-of k)*
shows *child ∈ inputs g nid*
using *assms* **by** *auto*

lemma *encode-in-ids*:
assumes *g ⊢ nid ≃ e*
shows *nid ∈ ids g*
using *assms*
apply (*induction rule: rep.induct*)
apply *simp+*
by *fastforce+*

lemma *eval-in-ids*:
assumes *[g, m, p] ⊢ nid ↦ v*
shows *nid ∈ ids g*
using *assms* **using** *encodeeval-def encode-in-ids*
by *auto*

lemma *transitive-kind-same*:
assumes *unchanged (eval-usages g1 nid) g1 g2*
shows $\forall \text{nid}' \in (\text{eval-usages } g1 \text{ nid}) . \text{kind } g1 \text{ nid}' = \text{kind } g2 \text{ nid}'$
using *assms*
by (*meson unchanged.elims(1)*)

```

theorem stay-same-encoding:
  assumes nc: unchanged (eval-usages g1 nid) g1 g2
  assumes g1:  $g1 \vdash nid \simeq e$ 
  assumes wf: wf-graph g1
  shows  $g2 \vdash nid \simeq e$ 
proof –
  have dom:  $nid \in ids\ g1$ 
  using g1 encode-in-ids by simp
  show ?thesis
using g1 nc wf dom proof (induction e rule: rep.induct)
  case (ConstantNode n c)
  then have kind  $g2\ n = ConstantNode\ c$ 
  using dom nc kind-unchanged
  by metis
  then show ?case using rep.ConstantNode
  by presburger
next
  case (ParameterNode n i s)
  then have kind  $g2\ n = ParameterNode\ i$ 
  by (metis kind-unchanged)
  then show ?case
  by (metis ParameterNode.hyps(2) ParameterNode.prems(1) ParameterNode.prems(3)
rep.ParameterNode stamp-unchanged)
next
  case (ConditionalNode n c t f ce te fe)
  then have kind  $g2\ n = ConditionalNode\ c\ t\ f$ 
  by (metis kind-unchanged)
  have  $c \in eval-usages\ g1\ n \wedge t \in eval-usages\ g1\ n \wedge f \in eval-usages\ g1\ n$ 
  using inputs-of-ConditionalNode
  by (metis ConditionalNode.hyps(1) ConditionalNode.hyps(2) ConditionalNode.hyps(3)
ConditionalNode.hyps(4) encode-in-ids inputs.simps inputs-are-usages
list.set-intros(1) set-subset-Cons subset-code(1))
  then show ?case using transitive-kind-same
  by (metis ConditionalNode.hyps(1) ConditionalNode.prems(1) IRNodes.inputs-of-ConditionalNode
 $\langle kind\ g2\ n = ConditionalNode\ c\ t\ f \rangle$  child-unchanged inputs.simps list.set-intros(1)
local.ConditionalNode(5) local.ConditionalNode(6) local.ConditionalNode(7) local.ConditionalNode(9)
rep.ConditionalNode set-subset-Cons subset-code(1) unchanged.elims(2))
next
  case (AbsNode n x xe)
  then have kind  $g2\ n = AbsNode\ x$ 
  using kind-unchanged
  by metis
  then have  $x \in eval-usages\ g1\ n$ 
  using inputs-of-AbsNode
  by (metis AbsNode.hyps(1) AbsNode.hyps(2) encode-in-ids inputs.simps inputs-are-usages
list.set-intros(1))
  then show ?case
  by (metis AbsNode.IH AbsNode.hyps(1) AbsNode.prems(1) AbsNode.prems(3))

```

```

IRNodes.inputs-of-AbsNode ⟨kind g2 n = AbsNode x⟩ child-member-in child-unchanged
local.wf member-rec(1) rep.AbsNode unchanged.simps)
next
  case (NotNode n x xe)
  then have kind g2 n = NotNode x
    using kind-unchanged
    by metis
  then have x ∈ eval-usages g1 n
    using inputs-of-NotNode
    by (metis NotNode.hyps(1) NotNode.hyps(2) encode-in-ids inputs.simps in-
      puts-are-usages list.set-intros(1))
  then show ?case
    by (metis NotNode.IH NotNode.hyps(1) NotNode.prem(1) NotNode.prem(3)
      IRNodes.inputs-of-NotNode ⟨kind g2 n = NotNode x⟩ child-member-in child-unchanged
      local.wf member-rec(1) rep.NotNode unchanged.simps)
next
  case (NegateNode n x xe)
  then have kind g2 n = NegateNode x
    using kind-unchanged by metis
  then have x ∈ eval-usages g1 n
    using inputs-of-NegateNode
    by (metis NegateNode.hyps(1) NegateNode.hyps(2) encode-in-ids inputs.simps
      inputs-are-usages list.set-intros(1))
  then show ?case
    by (metis IRNodes.inputs-of-NegateNode NegateNode.IH NegateNode.hyps(1)
      NegateNode.prem(1) NegateNode.prem(3) ⟨kind g2 n = NegateNode x⟩ child-member-in
      child-unchanged local.wf member-rec(1) rep.NegateNode unchanged.elims(1))
next
  case (LogicNegationNode n x xe)
  then have kind g2 n = LogicNegationNode x
    using kind-unchanged by metis
  then have x ∈ eval-usages g1 n
    using inputs-of-LogicNegationNode inputs-of-are-usages
    by (metis LogicNegationNode.hyps(1) LogicNegationNode.hyps(2) encode-in-ids
      member-rec(1))
  then show ?case
    by (metis IRNodes.inputs-of-LogicNegationNode LogicNegationNode.IH Logic-
      NegationNode.hyps(1) LogicNegationNode.hyps(2) LogicNegationNode.prem(1) ⟨kind
      g2 n = LogicNegationNode x⟩ child-unchanged encode-in-ids inputs.simps list.set-intros(1)
      local.wf rep.LogicNegationNode)
next
  case (AddNode n x y xe ye)
  then have kind g2 n = AddNode x y
    using kind-unchanged by metis
  then have x ∈ eval-usages g1 n ∧ y ∈ eval-usages g1 n
    using inputs-of-LogicNegationNode inputs-of-are-usages
    by (metis AddNode.hyps(1) AddNode.hyps(2) AddNode.hyps(3) IRNodes.inputs-of-AddNode
      encode-in-ids in-mono inputs.simps inputs-are-usages list.set-intros(1) set-subset-Cons)
  then show ?case

```

```

    by (metis AddNode.IH(1) AddNode.IH(2) AddNode.hyps(1) AddNode.hyps(2)
AddNode.hyps(3) AddNode.premis(1) IRNodes.inputs-of-AddNode ⟨kind g2 n = AddNode
x y⟩ child-unchanged encode-in-ids in-set-member inputs.simps local.wf member-rec(1)
rep.AddNode)
next
  case (MulNode n x y xe ye)
  then have kind g2 n = MulNode x y
    using kind-unchanged by metis
  then have x ∈ eval-usages g1 n ∧ y ∈ eval-usages g1 n
    using inputs-of-LogicNegationNode inputs-of-are-usages
  by (metis MulNode.hyps(1) MulNode.hyps(2) MulNode.hyps(3) IRNodes.inputs-of-MulNode
encode-in-ids in-mono inputs.simps inputs-are-usages list.set-intros(1) set-subset-Cons)
  then show ?case using MulNode inputs-of-MulNode
    by (metis ⟨kind g2 n = MulNode x y⟩ child-unchanged inputs.simps list.set-intros(1)
rep.MulNode set-subset-Cons subset-iff unchanged.elims(2))
next
  case (SubNode n x y xe ye)
  then have kind g2 n = SubNode x y
    using kind-unchanged by metis
  then have x ∈ eval-usages g1 n ∧ y ∈ eval-usages g1 n
    using inputs-of-LogicNegationNode inputs-of-are-usages
  by (metis SubNode.hyps(1) SubNode.hyps(2) SubNode.hyps(3) IRNodes.inputs-of-SubNode
encode-in-ids in-mono inputs.simps inputs-are-usages list.set-intros(1) set-subset-Cons)
  then show ?case using SubNode inputs-of-SubNode
    by (metis ⟨kind g2 n = SubNode x y⟩ child-member child-unchanged encode-in-ids
ids-some member-rec(1) rep.SubNode)
next
  case (AndNode n x y xe ye)
  then have kind g2 n = AndNode x y
    using kind-unchanged by metis
  then have x ∈ eval-usages g1 n ∧ y ∈ eval-usages g1 n
    using inputs-of-LogicNegationNode inputs-of-are-usages
  by (metis AndNode.hyps(1) AndNode.hyps(2) AndNode.hyps(3) IRNodes.inputs-of-AndNode
encode-in-ids in-mono inputs.simps inputs-are-usages list.set-intros(1) set-subset-Cons)
  then show ?case using AndNode inputs-of-AndNode
    by (metis ⟨kind g2 n = AndNode x y⟩ child-unchanged inputs.simps list.set-intros(1)
rep.AndNode set-subset-Cons subset-iff unchanged.elims(2))
next
  case (OrNode n x y xe ye)
  then have kind g2 n = OrNode x y
    using kind-unchanged by metis
  then have x ∈ eval-usages g1 n ∧ y ∈ eval-usages g1 n
    using inputs-of-OrNode inputs-of-are-usages
  by (metis OrNode.hyps(1) OrNode.hyps(2) OrNode.hyps(3) IRNodes.inputs-of-OrNode
encode-in-ids in-mono inputs.simps inputs-are-usages list.set-intros(1) set-subset-Cons)
  then show ?case using OrNode inputs-of-OrNode
    by (metis ⟨kind g2 n = OrNode x y⟩ child-member child-unchanged encode-in-ids
ids-some member-rec(1) rep.OrNode)
next

```

```

case (XorNode n x y xe ye)
then have kind g2 n = XorNode x y
  using kind-unchanged by metis
then have x ∈ eval-usages g1 n ∧ y ∈ eval-usages g1 n
  using inputs-of-XorNode inputs-of-are-usages
  by (metis XorNode.hyps(1) XorNode.hyps(2) XorNode.hyps(3) IRNodes.inputs-of-XorNode
encode-in-ids in-mono inputs.simps inputs-are-usages list.set-intros(1) set-subset-Cons)
  then show ?case using XorNode inputs-of-XorNode
  by (metis ⟨kind g2 n = XorNode x y⟩ child-member child-unchanged encode-in-ids
ids-some member-rec(1) rep.XorNode)
next
case (LeftShiftNode n x y xe ye)
  then have kind g2 n = LeftShiftNode x y
  using kind-unchanged by metis
  then have x ∈ eval-usages g1 n ∧ y ∈ eval-usages g1 n
  using inputs-of-XorNode inputs-of-are-usages
  by (metis LeftShiftNode.hyps(1) LeftShiftNode.hyps(2) LeftShiftNode.hyps(3)
IRNodes.inputs-of-LeftShiftNode encode-in-ids in-mono inputs.simps inputs-are-usages
list.set-intros(1) set-subset-Cons)
  then show ?case using LeftShiftNode inputs-of-LeftShiftNode
  by (metis ⟨kind g2 n = LeftShiftNode x y⟩ child-member child-unchanged
encode-in-ids ids-some member-rec(1) rep.LeftShiftNode)
next
case (RightShiftNode n x y xe ye)
  then have kind g2 n = RightShiftNode x y
  using kind-unchanged by metis
  then have x ∈ eval-usages g1 n ∧ y ∈ eval-usages g1 n
  using inputs-of-RightShiftNode inputs-of-are-usages
  by (metis RightShiftNode.hyps(1) RightShiftNode.hyps(2) RightShiftNode.hyps(3)
IRNodes.inputs-of-RightShiftNode encode-in-ids in-mono inputs.simps inputs-are-usages
list.set-intros(1) set-subset-Cons)
  then show ?case using RightShiftNode inputs-of-RightShiftNode
  by (metis ⟨kind g2 n = RightShiftNode x y⟩ child-member child-unchanged
encode-in-ids ids-some member-rec(1) rep.RightShiftNode)
next
case (UnsignedRightShiftNode n x y xe ye)
  then have kind g2 n = UnsignedRightShiftNode x y
  using kind-unchanged by metis
  then have x ∈ eval-usages g1 n ∧ y ∈ eval-usages g1 n
  using inputs-of-UnsignedRightShiftNode inputs-of-are-usages
  by (metis UnsignedRightShiftNode.hyps(1) UnsignedRightShiftNode.hyps(2) Un-
signedRightShiftNode.hyps(3) IRNodes.inputs-of-UnsignedRightShiftNode encode-in-ids
in-mono inputs.simps inputs-are-usages list.set-intros(1) set-subset-Cons)
  then show ?case using UnsignedRightShiftNode inputs-of-UnsignedRightShiftNode
  by (metis ⟨kind g2 n = UnsignedRightShiftNode x y⟩ child-member child-unchanged
encode-in-ids ids-some member-rec(1) rep.UnsignedRightShiftNode)
next
case (IntegerBelowNode n x y xe ye)
  then have kind g2 n = IntegerBelowNode x y

```



```

    using kind-unchanged by metis
  then have  $x \in \text{eval-usages } g1 \ n \wedge y \in \text{eval-usages } g1 \ n$ 
    using inputs-of-IntegerBelowNode inputs-of-are-usages
    by (metis IntegerBelowNode.hyps(1) IntegerBelowNode.hyps(2) IntegerBelowNode.hyps(3) IRNodes.inputs-of-IntegerBelowNode encode-in-ids in-mono inputs.simps inputs-are-usages list.set-intros(1) set-subset-Cons)
    then show ?case using IntegerBelowNode inputs-of-IntegerBelowNode
      by (metis  $\langle \text{kind } g2 \ n = \text{IntegerBelowNode } x \ y \rangle$  child-member child-unchanged encode-in-ids ids-some member-rec(1) rep.IntegerBelowNode)
next
  case (IntegerEqualsNode  $n \ x \ y \ x_e \ y_e$ )
  then have  $\text{kind } g2 \ n = \text{IntegerEqualsNode } x \ y$ 
    using kind-unchanged by metis
  then have  $x \in \text{eval-usages } g1 \ n \wedge y \in \text{eval-usages } g1 \ n$ 
    using inputs-of-IntegerEqualsNode inputs-of-are-usages
    by (metis IntegerEqualsNode.hyps(1) IntegerEqualsNode.hyps(2) IntegerEqualsNode.hyps(3) IRNodes.inputs-of-IntegerEqualsNode encode-in-ids in-mono inputs.simps inputs-are-usages list.set-intros(1) set-subset-Cons)
    then show ?case using IntegerEqualsNode inputs-of-IntegerEqualsNode
      by (metis  $\langle \text{kind } g2 \ n = \text{IntegerEqualsNode } x \ y \rangle$  child-member child-unchanged encode-in-ids ids-some member-rec(1) rep.IntegerEqualsNode)
next
  case (IntegerLessThanNode  $n \ x \ y \ x_e \ y_e$ )
  then have  $\text{kind } g2 \ n = \text{IntegerLessThanNode } x \ y$ 
    using kind-unchanged by metis
  then have  $x \in \text{eval-usages } g1 \ n \wedge y \in \text{eval-usages } g1 \ n$ 
    using inputs-of-IntegerLessThanNode inputs-of-are-usages
    by (metis IntegerLessThanNode.hyps(1) IntegerLessThanNode.hyps(2) IntegerLessThanNode.hyps(3) IRNodes.inputs-of-IntegerLessThanNode encode-in-ids in-mono inputs.simps inputs-are-usages list.set-intros(1) set-subset-Cons)
    then show ?case using IntegerLessThanNode inputs-of-IntegerLessThanNode
      by (metis  $\langle \text{kind } g2 \ n = \text{IntegerLessThanNode } x \ y \rangle$  child-member child-unchanged encode-in-ids ids-some member-rec(1) rep.IntegerLessThanNode)
next
  case (NarrowNode  $n \ ib \ rb \ x \ x_e$ )
  then have  $\text{kind } g2 \ n = \text{NarrowNode } ib \ rb \ x$ 
    using kind-unchanged by metis
  then have  $x \in \text{eval-usages } g1 \ n$ 
    using inputs-of-NarrowNode inputs-of-are-usages
    by (metis NarrowNode.hyps(1) NarrowNode.hyps(2) IRNodes.inputs-of-NarrowNode encode-in-ids inputs.simps inputs-are-usages list.set-intros(1))
    then show ?case using NarrowNode inputs-of-NarrowNode
      by (metis  $\langle \text{kind } g2 \ n = \text{NarrowNode } ib \ rb \ x \rangle$  child-unchanged inputs.elims list.set-intros(1) rep.NarrowNode unchanged.simps)
next
  case (SignExtendNode  $n \ ib \ rb \ x \ x_e$ )
  then have  $\text{kind } g2 \ n = \text{SignExtendNode } ib \ rb \ x$ 
    using kind-unchanged by metis
  then have  $x \in \text{eval-usages } g1 \ n$ 

```

```

    using inputs-of-SignExtendNode inputs-of-are-usages
    by (metis SignExtendNode.hyps(1) SignExtendNode.hyps(2) encode-in-ids in-
inputs.simps inputs-are-usages list.set-intros(1))
    then show ?case using SignExtendNode inputs-of-SignExtendNode
    by (metis ⟨kind g2 n = SignExtendNode ib rb x⟩ child-member-in child-unchanged
in-set-member list.set-intros(1) rep.SignExtendNode unchanged.elims(2))
next
case (ZeroExtendNode n ib rb x xe)
then have kind g2 n = ZeroExtendNode ib rb x
    using kind-unchanged by metis
then have x ∈ eval-usages g1 n
    using inputs-of-ZeroExtendNode inputs-of-are-usages
    by (metis ZeroExtendNode.hyps(1) ZeroExtendNode.hyps(2) IRNodes.inputs-of-ZeroExtendNode
encode-in-ids inputs.simps inputs-are-usages list.set-intros(1))
    then show ?case using ZeroExtendNode inputs-of-ZeroExtendNode
    by (metis ⟨kind g2 n = ZeroExtendNode ib rb x⟩ child-member-in child-unchanged
member-rec(1) rep.ZeroExtendNode unchanged.simps)
next
case (LeafNode n s)
then show ?case
    by (metis kind-unchanged rep.LeafNode stamp-unchanged)
next
case (RefNode n n')
then have kind g2 n = RefNode n'
    using kind-unchanged by metis
then have n' ∈ eval-usages g1 n
    by (metis IRNodes.inputs-of-RefNode RefNode.hyps(1) RefNode.hyps(2) en-
code-in-ids inputs.elims inputs-are-usages list.set-intros(1))
    then show ?case
    by (metis IRNodes.inputs-of-RefNode RefNode.IH RefNode.hyps(1) RefNode.hyps(2)
RefNode.premis(1) ⟨kind g2 n = RefNode n'⟩ child-unchanged encode-in-ids in-
puts.elims list.set-intros(1) local.wf rep.RefNode)
qed
qed

```

theorem *stay-same*:

```

assumes nc: unchanged (eval-usages g1 nid) g1 g2
assumes g1: [g1, m, p] ⊢ nid ↦ v1
assumes wf: wf-graph g1
shows [g2, m, p] ⊢ nid ↦ v1
proof –
  have nid: nid ∈ ids g1
    using g1 eval-in-ids by simp
  then have nid ∈ eval-usages g1 nid
    using eval-usages-self by blast
  then have kind-same: kind g1 nid = kind g2 nid
    using nc node-unchanged by blast

```

```

obtain  $e$  where  $e$ : ( $g1 \vdash nid \simeq e$ )  $\wedge$  ( $[m,p] \vdash e \mapsto v1$ )
  using encodeeval-def  $g1$ 
  by auto
then have  $val$ :  $[m,p] \vdash e \mapsto v1$ 
  using  $g1$  encodeeval-def
  by simp
then show ?thesis using  $e$   $nid$   $nc$ 
  unfolding encodeeval-def
proof (induct  $e$   $v1$  arbitrary:  $nid$  rule: evaltree.induct)
  case (ConstantExpr  $c$ )
  then show ?case
    by (meson local.wf stay-same-encoding)
next
  case (ParameterExpr  $i$   $s$ )
  have  $g2 \vdash nid \simeq \text{ParameterExpr } i \ s$ 
    using stay-same-encoding ParameterExpr
    by (meson local.wf)
  then show ?case using evaltree.ParameterExpr
    by (meson ParameterExpr.hyps)
next
  case (ConditionalExpr  $ce$  cond  $te$   $fe$   $v$ )
  then have  $g2 \vdash nid \simeq \text{ConditionalExpr } ce \ te \ fe$ 
  using ConditionalExpr.prems(1) ConditionalExpr.prems(3) local.wf stay-same-encoding
    by presburger
  then show ?case
    by (meson ConditionalExpr.prems(1) ConditionalExpr.prems(3) local.wf
stay-same-encoding)
next
  case (UnaryExpr  $xe$   $v$   $op$ )
  then show ?case
    using local.wf stay-same-encoding by blast
next
  case (BinaryExpr  $xe$   $x$   $ye$   $y$   $op$ )
  then show ?case
    using local.wf stay-same-encoding by blast
next
  case (LeafExpr  $val$   $nid$   $s$ )
  then show ?case
    by (metis local.wf stay-same-encoding)
qed
qed

```

```

lemma add-changed:
  assumes  $gup = \text{add-node } new \ k \ g$ 
  shows changeonly {new}  $g$   $gup$ 
  using assms unfolding add-node-def changeonly.simps
  using add-node.rep-eq add-node-def kind.rep-eq stamp.rep-eq by simp

```

```

lemma disjoint-change:
  assumes changeonly change g gup
  assumes nochange = ids g - change
  shows unchanged nochange g gup
  using assms unfolding changeonly.simps unchanged.simps
  by blast

lemma add-node-unchanged:
  assumes new ∉ ids g
  assumes nid ∈ ids g
  assumes gup = add-node new k g
  assumes wf-graph g
  shows unchanged (eval-usages g nid) g gup
proof –
  have new ∉ (eval-usages g nid) using assms
    using eval-usages.simps by blast
  then have changeonly {new} g gup
    using assms add-changed by blast
  then show ?thesis using assms add-node-def disjoint-change
    using Diff-insert-absorb by auto
qed

lemma eval-uses-imp:
   $((nid' \in ids\ g \wedge nid = nid') \vee$ 
     $nid' \in inputs\ g\ nid \vee (\exists nid'' . eval-uses\ g\ nid\ nid'' \wedge eval-uses\ g\ nid''\ nid'))$ 
     $\longleftrightarrow eval-uses\ g\ nid\ nid'$ 
  using use0 use-inp use-trans
  by (meson eval-uses.simps)

lemma wf-use-ids:
  assumes wf-graph g
  assumes nid ∈ ids g
  assumes eval-uses g nid nid'
  shows nid' ∈ ids g
  using assms(3)
proof (induction rule: eval-uses.induct)
  case use0
    then show ?case by simp
  next
    case use-inp
    then show ?case
      using assms(1) inp-in-g-wf by blast
  next
    case use-trans
    then show ?case by blast
qed

lemma no-external-use:

```

```

assumes wf-graph  $g$ 
assumes  $nid' \notin ids\ g$ 
assumes  $nid \in ids\ g$ 
shows  $\neg(eval\text{-}uses\ g\ nid\ nid')$ 
proof –
  have  $0: nid \neq nid'$ 
    using assms by blast
  have inp:  $nid' \notin inputs\ g\ nid$ 
    using assms
    using inp-in-g-wf by blast
  have rec-0:  $\nexists n. n \in ids\ g \wedge n = nid'$ 
    using assms by blast
  have rec-inp:  $\nexists n. n \in ids\ g \wedge n \in inputs\ g\ nid'$ 
    using assms(2) inp-in-g by blast
  have rec:  $\nexists nid''. eval\text{-}uses\ g\ nid\ nid'' \wedge eval\text{-}uses\ g\ nid''\ nid'$ 
    using wf-use-ids assms(1) assms(2) assms(3) by blast
  from inp 0 rec show ?thesis
    using eval-uses-imp by blast
qed

end

```

6.8 Tree to Graph Theorems

```

theory TreeToGraphThms
imports
  TreeToGraph
  IRTreeEvalThms
  IRGraphFrames
  HOL-Eisbach.Eisbach
  HOL-Eisbach.Eisbach-Tools
begin

```

6.8.1 Extraction and Evaluation of Expression Trees is Deterministic.

First, we prove some extra rules that relate each type of `IRNode` to the corresponding `IRExpr` type that 'rep' will produce. These are very helpful for proving that 'rep' is deterministic.

named-theorems *rep*

```

lemma rep-constant [rep]:
   $g \vdash n \simeq e \implies$ 
   $kind\ g\ n = ConstantNode\ c \implies$ 
   $e = ConstantExpr\ c$ 
  by (induction rule: rep.induct; auto)

```

```

lemma rep-parameter [rep]:
   $g \vdash n \simeq e \implies$ 

```

$kind\ g\ n = ParameterNode\ i \implies$
 $(\exists\ s.\ e = ParameterExpr\ i\ s)$
by (induction rule: *rep.induct*; *auto*)

lemma *rep-conditional* [*rep*]:
 $g \vdash n \simeq e \implies$
 $kind\ g\ n = ConditionalNode\ c\ t\ f \implies$
 $(\exists\ ce\ te\ fe.\ e = ConditionalExpr\ ce\ te\ fe)$
by (induction rule: *rep.induct*; *auto*)

lemma *rep-abs* [*rep*]:
 $g \vdash n \simeq e \implies$
 $kind\ g\ n = AbsNode\ x \implies$
 $(\exists\ xe.\ e = UnaryExpr\ UnaryAbs\ xe)$
by (induction rule: *rep.induct*; *auto*)

lemma *rep-not* [*rep*]:
 $g \vdash n \simeq e \implies$
 $kind\ g\ n = NotNode\ x \implies$
 $(\exists\ xe.\ e = UnaryExpr\ UnaryNot\ xe)$
by (induction rule: *rep.induct*; *auto*)

lemma *rep-negate* [*rep*]:
 $g \vdash n \simeq e \implies$
 $kind\ g\ n = NegateNode\ x \implies$
 $(\exists\ xe.\ e = UnaryExpr\ UnaryNeg\ xe)$
by (induction rule: *rep.induct*; *auto*)

lemma *rep-logicnegation* [*rep*]:
 $g \vdash n \simeq e \implies$
 $kind\ g\ n = LogicNegationNode\ x \implies$
 $(\exists\ xe.\ e = UnaryExpr\ UnaryLogicNegation\ xe)$
by (induction rule: *rep.induct*; *auto*)

lemma *rep-add* [*rep*]:
 $g \vdash n \simeq e \implies$
 $kind\ g\ n = AddNode\ x\ y \implies$
 $(\exists\ xe\ ye.\ e = BinaryExpr\ BinAdd\ xe\ ye)$
by (induction rule: *rep.induct*; *auto*)

lemma *rep-sub* [*rep*]:
 $g \vdash n \simeq e \implies$
 $kind\ g\ n = SubNode\ x\ y \implies$
 $(\exists\ xe\ ye.\ e = BinaryExpr\ BinSub\ xe\ ye)$
by (induction rule: *rep.induct*; *auto*)

lemma *rep-mul* [*rep*]:
 $g \vdash n \simeq e \implies$
 $kind\ g\ n = MulNode\ x\ y \implies$

($\exists xe ye. e = \text{BinaryExpr BinMul } xe ye$)
by (induction rule: *rep.induct*; *auto*)

lemma *rep-and* [*rep*]:
 $g \vdash n \simeq e \implies$
 $\text{kind } g \ n = \text{AndNode } x \ y \implies$
($\exists xe ye. e = \text{BinaryExpr BinAnd } xe ye$)
by (induction rule: *rep.induct*; *auto*)

lemma *rep-or* [*rep*]:
 $g \vdash n \simeq e \implies$
 $\text{kind } g \ n = \text{OrNode } x \ y \implies$
($\exists xe ye. e = \text{BinaryExpr BinOr } xe ye$)
by (induction rule: *rep.induct*; *auto*)

lemma *rep-xor* [*rep*]:
 $g \vdash n \simeq e \implies$
 $\text{kind } g \ n = \text{XorNode } x \ y \implies$
($\exists xe ye. e = \text{BinaryExpr BinXor } xe ye$)
by (induction rule: *rep.induct*; *auto*)

lemma *rep-left-shift* [*rep*]:
 $g \vdash n \simeq e \implies$
 $\text{kind } g \ n = \text{LeftShiftNode } x \ y \implies$
($\exists xe ye. e = \text{BinaryExpr BinLeftShift } xe ye$)
by (induction rule: *rep.induct*; *auto*)

lemma *rep-right-shift* [*rep*]:
 $g \vdash n \simeq e \implies$
 $\text{kind } g \ n = \text{RightShiftNode } x \ y \implies$
($\exists xe ye. e = \text{BinaryExpr BinRightShift } xe ye$)
by (induction rule: *rep.induct*; *auto*)

lemma *rep-unsigned-right-shift* [*rep*]:
 $g \vdash n \simeq e \implies$
 $\text{kind } g \ n = \text{UnsignedRightShiftNode } x \ y \implies$
($\exists xe ye. e = \text{BinaryExpr BinURightShift } xe ye$)
by (induction rule: *rep.induct*; *auto*)

lemma *rep-integer-below* [*rep*]:
 $g \vdash n \simeq e \implies$
 $\text{kind } g \ n = \text{IntegerBelowNode } x \ y \implies$
($\exists xe ye. e = \text{BinaryExpr BinIntegerBelow } xe ye$)
by (induction rule: *rep.induct*; *auto*)

lemma *rep-integer-equals* [*rep*]:
 $g \vdash n \simeq e \implies$
 $\text{kind } g \ n = \text{IntegerEqualsNode } x \ y \implies$
($\exists xe ye. e = \text{BinaryExpr BinIntegerEquals } xe ye$)

```

by (induction rule: rep.induct; auto)

lemma rep-integer-less-than [rep]:
   $g \vdash n \simeq e \implies$ 
   $\text{kind } g \ n = \text{IntegerLessThanNode } x \ y \implies$ 
   $(\exists x \ e \ ye. \ e = \text{BinaryExpr } \text{BinIntegerLessThan } xe \ ye)$ 
by (induction rule: rep.induct; auto)

lemma rep-narrow [rep]:
   $g \vdash n \simeq e \implies$ 
   $\text{kind } g \ n = \text{NarrowNode } ib \ rb \ x \implies$ 
   $(\exists x. \ e = \text{UnaryExpr } (\text{UnaryNarrow } ib \ rb) \ x)$ 
by (induction rule: rep.induct; auto)

lemma rep-sign-extend [rep]:
   $g \vdash n \simeq e \implies$ 
   $\text{kind } g \ n = \text{SignExtendNode } ib \ rb \ x \implies$ 
   $(\exists x. \ e = \text{UnaryExpr } (\text{UnarySignExtend } ib \ rb) \ x)$ 
by (induction rule: rep.induct; auto)

lemma rep-zero-extend [rep]:
   $g \vdash n \simeq e \implies$ 
   $\text{kind } g \ n = \text{ZeroExtendNode } ib \ rb \ x \implies$ 
   $(\exists x. \ e = \text{UnaryExpr } (\text{UnaryZeroExtend } ib \ rb) \ x)$ 
by (induction rule: rep.induct; auto)

lemma rep-load-field [rep]:
   $g \vdash n \simeq e \implies$ 
   $\text{is-preevaluated } (\text{kind } g \ n) \implies$ 
   $(\exists s. \ e = \text{LeafExpr } n \ s)$ 
by (induction rule: rep.induct; auto)

lemma rep-ref [rep]:
   $g \vdash n \simeq e \implies$ 
   $\text{kind } g \ n = \text{RefNode } n' \implies$ 
   $g \vdash n' \simeq e$ 
by (induction rule: rep.induct; auto)

method solve-det uses node =
  (match node in kind - - = node - for node  $\implies$ 
    <match rep in r: -  $\implies$  - = node -  $\implies$  -  $\implies$ 
      <match IRNode.inject in i: (node - = node -) = -  $\implies$ 
        <match RepE in e: -  $\implies$  ( $\bigwedge x. - = \text{node } x \implies -$ )  $\implies$  -  $\implies$ 
          <match IRNode.distinct in d: node -  $\neq$  RefNode -  $\implies$ 
            <metis i e r d>>>> |
      match node in kind - - = node - - for node  $\implies$ 
        <match rep in r: -  $\implies$  - = node - -  $\implies$  -  $\implies$ 
          <match IRNode.inject in i: (node - - = node - -) = -  $\implies$ 
```



```

    <match RepE in e: - ==> (∧ x y. - = node x y ==> -) ==> - ==>
    <match IRNode.distinct in d: node - - ≠ RefNode - ==>
    <metis i e r d>>>> |
  match node in kind - - = node - - - for node ==>
  <match rep in r: - ==> - = node - - - ==> - ==>
  <match IRNode.inject in i: (node - - - = node - - -) = - ==>
  <match RepE in e: - ==> (∧ x y z. - = node x y z ==> -) ==> - ==>
  <match IRNode.distinct in d: node - - - ≠ RefNode - ==>
  <metis i e r d>>>> |
  match node in kind - - = node - - - for node ==>
  <match rep in r: - ==> - = node - - - ==> - ==>
  <match IRNode.inject in i: (node - - - = node - - -) = - ==>
  <match RepE in e: - ==> (∧ x. - = node - - x ==> -) ==> - ==>
  <match IRNode.distinct in d: node - - - ≠ RefNode - ==>
  <metis i e r d>>>>)

```

Now we can prove that 'rep' and 'eval', and their list versions, are deterministic.

lemma *repDet*:

shows $(g \vdash n \simeq e_1) \implies (g \vdash n \simeq e_2) \implies e_1 = e_2$

proof (*induction arbitrary: e₂ rule: rep.induct*)

case (*ConstantNode n c*)

then show ?case **using** *rep-constant* **by** *auto*

next

case (*ParameterNode n i s*)

then show ?case

by (*metis IRNode.disc(2685) ParameterNodeE is-RefNode-def rep-parameter*)

next

case (*ConditionalNode n c t f ce te fe*)

then show ?case

using *IRNode.distinct(593)*

using *IRNode.inject(6) ConditionalNodeE rep-conditional*

by *metis*

next

case (*AbsNode n x xe*)

then show ?case

by (*solve-det node: AbsNode*)

next

case (*NotNode n x xe*)

then show ?case

by (*solve-det node: NotNode*)

next

case (*NegateNode n x xe*)

then show ?case

by (*solve-det node: NegateNode*)

next

case (*LogicNegationNode n x xe*)

then show ?case

by (*solve-det node: LogicNegationNode*)

```

next
  case (AddNode n x y xe ye)
  then show ?case
    by (solve-det node: AddNode)
next
  case (MulNode n x y xe ye)
  then show ?case
    by (solve-det node: MulNode)
next
  case (SubNode n x y xe ye)
  then show ?case
    by (solve-det node: SubNode)
next
  case (AndNode n x y xe ye)
  then show ?case
    by (solve-det node: AndNode)
next
  case (OrNode n x y xe ye)
  then show ?case
    by (solve-det node: OrNode)
next
  case (XorNode n x y xe ye)
  then show ?case
    by (solve-det node: XorNode)
next
  case (LeftShiftNode n x y xe ye)
  then show ?case
    by (solve-det node: LeftShiftNode)
next
  case (RightShiftNode n x y xe ye)
  then show ?case
    by (solve-det node: RightShiftNode)
next
  case (UnsignedRightShiftNode n x y xe ye)
  then show ?case
    by (solve-det node: UnsignedRightShiftNode)
next
  case (IntegerBelowNode n x y xe ye)
  then show ?case
    by (solve-det node: IntegerBelowNode)
next
  case (IntegerEqualsNode n x y xe ye)
  then show ?case
    by (solve-det node: IntegerEqualsNode)
next
  case (IntegerLessThanNode n x y xe ye)
  then show ?case
    by (solve-det node: IntegerLessThanNode)
next

```

```

    case (NarrowNode n x xe)
    then show ?case
      by (metis IRNode.distinct(2203) IRNode.inject(28) NarrowNodeE rep-narrow)
next
    case (SignExtendNode n x xe)
    then show ?case
      by (metis IRNode.distinct(2599) IRNode.inject(39) SignExtendNodeE rep-sign-extend)
next
    case (ZeroExtendNode n x xe)
    then show ?case
      by (metis IRNode.distinct(2753) IRNode.inject(50) ZeroExtendNodeE rep-zero-extend)
next
    case (LeafNode n s)
    then show ?case using rep-load-field LeafNodeE
      by (metis is-preevaluated.simps(53))
next
    case (RefNode n')
    then show ?case
      using rep-ref by blast
qed

```

lemma *repAllDet*:

```

  g ⊢ xs ≃L e1 ⟹
  g ⊢ xs ≃L e2 ⟹
  e1 = e2

```

proof (*induction arbitrary: e2 rule: replist.induct*)

```

  case RepNil
  then show ?case
    using replist.cases by auto
next
  case (RepCons x xe xs xse)
  then show ?case
    by (metis list.distinct(1) list.sel(1) list.sel(3) repDet replist.cases)
qed

```

lemma *encodeEvalDet*:

```

  [g,m,p] ⊢ e ↦ v1 ⟹
  [g,m,p] ⊢ e ↦ v2 ⟹
  v1 = v2

```

by (*metis encodeeval-def evalDet repDet*)

lemma *graphDet*: $([g,m,p] \vdash n \mapsto v_1) \wedge ([g,m,p] \vdash n \mapsto v_2) \implies v_1 = v_2$
using *encodeEvalDet* **by** *blast*

6.8.2 Monotonicity of Graph Refinement

Lift refinement monotonicity to graph level. Hopefully these shouldn't really be required.

lemma *mono-abs*:

assumes $\text{kind } g1 \ n = \text{AbsNode } x \wedge \text{kind } g2 \ n = \text{AbsNode } x$
assumes $(g1 \vdash x \simeq xe1) \wedge (g2 \vdash x \simeq xe2)$
assumes $xe1 \geq xe2$
assumes $(g1 \vdash n \simeq e1) \wedge (g2 \vdash n \simeq e2)$
shows $e1 \geq e2$
by (*metis AbsNode assms(1) assms(2) assms(3) assms(4) mono-unary repDet*)

lemma *mono-not*:

assumes $\text{kind } g1 \ n = \text{NotNode } x \wedge \text{kind } g2 \ n = \text{NotNode } x$
assumes $(g1 \vdash x \simeq xe1) \wedge (g2 \vdash x \simeq xe2)$
assumes $xe1 \geq xe2$
assumes $(g1 \vdash n \simeq e1) \wedge (g2 \vdash n \simeq e2)$
shows $e1 \geq e2$
by (*metis NotNode assms(1) assms(2) assms(3) assms(4) mono-unary repDet*)

lemma *mono-negate*:

assumes $\text{kind } g1 \ n = \text{NegateNode } x \wedge \text{kind } g2 \ n = \text{NegateNode } x$
assumes $(g1 \vdash x \simeq xe1) \wedge (g2 \vdash x \simeq xe2)$
assumes $xe1 \geq xe2$
assumes $(g1 \vdash n \simeq e1) \wedge (g2 \vdash n \simeq e2)$
shows $e1 \geq e2$
by (*metis NegateNode assms(1) assms(2) assms(3) assms(4) mono-unary repDet*)

lemma *mono-logic-negation*:

assumes $\text{kind } g1 \ n = \text{LogicNegationNode } x \wedge \text{kind } g2 \ n = \text{LogicNegationNode } x$
assumes $(g1 \vdash x \simeq xe1) \wedge (g2 \vdash x \simeq xe2)$
assumes $xe1 \geq xe2$
assumes $(g1 \vdash n \simeq e1) \wedge (g2 \vdash n \simeq e2)$
shows $e1 \geq e2$
by (*metis LogicNegationNode assms(1) assms(2) assms(3) assms(4) mono-unary repDet*)

lemma *mono-narrow*:

assumes $\text{kind } g1 \ n = \text{NarrowNode } ib \ rb \ x \wedge \text{kind } g2 \ n = \text{NarrowNode } ib \ rb \ x$
assumes $(g1 \vdash x \simeq xe1) \wedge (g2 \vdash x \simeq xe2)$
assumes $xe1 \geq xe2$
assumes $(g1 \vdash n \simeq e1) \wedge (g2 \vdash n \simeq e2)$
shows $e1 \geq e2$
using *assms mono-unary repDet NarrowNode*
by *metis*

lemma *mono-sign-extend*:

assumes $\text{kind } g1 \ n = \text{SignExtendNode } ib \ rb \ x \wedge \text{kind } g2 \ n = \text{SignExtendNode } ib \ rb \ x$
assumes $(g1 \vdash x \simeq xe1) \wedge (g2 \vdash x \simeq xe2)$
assumes $xe1 \geq xe2$
assumes $(g1 \vdash n \simeq e1) \wedge (g2 \vdash n \simeq e2)$
shows $e1 \geq e2$
by (*metis SignExtendNode assms(1) assms(2) assms(3) assms(4) mono-unary*)

repDet)

lemma *mono-zero-extend*:

assumes *kind g1 n = ZeroExtendNode ib rb x* \wedge *kind g2 n = ZeroExtendNode ib rb x*
assumes $(g1 \vdash x \simeq xe1) \wedge (g2 \vdash x \simeq xe2)$
assumes $xe1 \geq xe2$
assumes $(g1 \vdash n \simeq e1) \wedge (g2 \vdash n \simeq e2)$
shows $e1 \geq e2$
using *assms mono-unary repDet ZeroExtendNode*
by *metis*

lemma *mono-conditional-graph*:

assumes *kind g1 n = ConditionalNode c t f* \wedge *kind g2 n = ConditionalNode c t f*
assumes $(g1 \vdash c \simeq ce1) \wedge (g2 \vdash c \simeq ce2)$
assumes $(g1 \vdash t \simeq te1) \wedge (g2 \vdash t \simeq te2)$
assumes $(g1 \vdash f \simeq fe1) \wedge (g2 \vdash f \simeq fe2)$
assumes $ce1 \geq ce2 \wedge te1 \geq te2 \wedge fe1 \geq fe2$
assumes $(g1 \vdash n \simeq e1) \wedge (g2 \vdash n \simeq e2)$
shows $e1 \geq e2$
using *ConditionalNodeE IRNode.inject(6) assms(1) assms(2) assms(3) assms(4) assms(5) assms(6) mono-conditional repDet rep-conditional*
by (*smt (verit, best) ConditionalNode*)

lemma *mono-add*:

assumes *kind g1 n = AddNode x y* \wedge *kind g2 n = AddNode x y*
assumes $(g1 \vdash x \simeq xe1) \wedge (g2 \vdash x \simeq xe2)$
assumes $(g1 \vdash y \simeq ye1) \wedge (g2 \vdash y \simeq ye2)$
assumes $xe1 \geq xe2 \wedge ye1 \geq ye2$
assumes $(g1 \vdash n \simeq e1) \wedge (g2 \vdash n \simeq e2)$
shows $e1 \geq e2$
using *mono-binary assms AddNodeE IRNode.inject(2) repDet rep-add*
by (*metis IRNode.distinct(205)*)

lemma *mono-mul*:

assumes *kind g1 n = MulNode x y* \wedge *kind g2 n = MulNode x y*
assumes $(g1 \vdash x \simeq xe1) \wedge (g2 \vdash x \simeq xe2)$
assumes $(g1 \vdash y \simeq ye1) \wedge (g2 \vdash y \simeq ye2)$
assumes $xe1 \geq xe2 \wedge ye1 \geq ye2$
assumes $(g1 \vdash n \simeq e1) \wedge (g2 \vdash n \simeq e2)$
shows $e1 \geq e2$
using *mono-binary assms IRNode.inject(27) MulNodeE repDet rep-mul*
by (*smt (verit, best) MulNode*)

lemma *term-graph-evaluation*:

$(g \vdash n \sqsubseteq e) \implies (\forall m p v . ([m, p] \vdash e \mapsto v) \longrightarrow ([g, m, p] \vdash n \mapsto v))$
unfolding *graph-represents-expression-def* **apply** *auto*
by (*meson encodeeval-def*)

lemma *encodes-contains:*

$g \vdash n \simeq e \implies$
 $\text{kind } g \ n \neq \text{NoNode}$
apply (*induction rule: rep.induct*)
apply (*match IRNode.distinct in e: ?n \neq NoNode \implies*
 $\langle \text{presburger add: } e \rangle +$
apply *force*
by *fastforce*

lemma *no-encoding:*

assumes $n \notin \text{ids } g$
shows $\neg(g \vdash n \simeq e)$
using *assms apply simp apply (rule notI) by (induction e; simp add: en-*
codes-contains)

lemma *not-excluded-keep-type:*

assumes $n \in \text{ids } g1$
assumes $n \notin \text{excluded}$
assumes $(\text{excluded} \trianglelefteq \text{as-set } g1) \subseteq \text{as-set } g2$
shows $\text{kind } g1 \ n = \text{kind } g2 \ n \wedge \text{stamp } g1 \ n = \text{stamp } g2 \ n$
using *assms unfolding as-set-def domain-subtraction-def by blast*

method *metis-node-eq-unary* **for** $\text{node} :: 'a \Rightarrow \text{IRNode} =$

$(\text{match IRNode.inject in } i: (\text{node } - = \text{node } -) = - \Rightarrow$
 $\langle \text{metis } i \rangle)$

method *metis-node-eq-binary* **for** $\text{node} :: 'a \Rightarrow 'a \Rightarrow \text{IRNode} =$

$(\text{match IRNode.inject in } i: (\text{node } - - = \text{node } - -) = - \Rightarrow$
 $\langle \text{metis } i \rangle)$

method *metis-node-eq-ternary* **for** $\text{node} :: 'a \Rightarrow 'a \Rightarrow 'a \Rightarrow \text{IRNode} =$

$(\text{match IRNode.inject in } i: (\text{node } - - - = \text{node } - - -) = - \Rightarrow$
 $\langle \text{metis } i \rangle)$

6.8.3 Lift Data-flow Tree Refinement to Graph Refinement

theorem *graph-semantics-preservation:*

assumes $a: e1' \geq e2'$
assumes $b: (\{n'\} \trianglelefteq \text{as-set } g1) \subseteq \text{as-set } g2$
assumes $c: g1 \vdash n' \simeq e1'$
assumes $d: g2 \vdash n' \simeq e2'$
shows *graph-refinement* $g1 \ g2$
unfolding *graph-refinement-def* **apply** *rule*
apply (*metis b d ids-some no-encoding not-excluded-keep-type singleton-iff sub-*
setI)
apply (*rule allI*) **apply** (*rule impI*) **apply** (*rule allI*) **apply** (*rule impI*)
unfolding *graph-represents-expression-def*

proof —

fix $n \ e1$

assume $e: n \in \text{ids } g1$

```

assume  $f$ : ( $g1 \vdash n \simeq e1$ )

show  $\exists e2. (g2 \vdash n \simeq e2) \wedge e1 \geq e2$ 
proof (cases  $n = n'$ )
  case True
    have  $g: e1 = e1'$  using  $c\ f\ True\ repDet$  by simp
    have  $h: (g2 \vdash n \simeq e2') \wedge e1' \geq e2'$ 
      using  $True\ a\ d$  by blast
    then show ?thesis
      using  $g$  by blast
  next
    case False
    have  $n \notin \{n'\}$ 
      using False by simp
    then have  $i: kind\ g1\ n = kind\ g2\ n \wedge stamp\ g1\ n = stamp\ g2\ n$ 
      using not-excluded-keep-type
      using  $b\ e$  by presburger
    show ?thesis using  $f\ i$ 
    proof (induction  $e1$ )
      case (ConstantNode  $n\ c$ )
        then show ?case
          by (metis eq-refl rep.ConstantNode)
      next
        case (ParameterNode  $n\ i\ s$ )
        then show ?case
          by (metis eq-refl rep.ParameterNode)
      next
        case (ConditionalNode  $n\ c\ t\ f\ ce1\ te1\ fe1$ )
        have  $k: g1 \vdash n \simeq ConditionalExpr\ ce1\ te1\ fe1$  using  $f\ ConditionalNode$ 
          by (simp add: ConditionalNode.hyps(2) rep.ConditionalNode)
        obtain  $cn\ tn\ fn$  where  $l: kind\ g1\ n = ConditionalNode\ cn\ tn\ fn$ 
          using ConditionalNode.hyps(1) by blast
        then have  $mc: g1 \vdash cn \simeq ce1$ 
          using ConditionalNode.hyps(1) ConditionalNode.hyps(2) by fastforce
        from  $l$  have  $mt: g1 \vdash tn \simeq te1$ 
          using ConditionalNode.hyps(1) ConditionalNode.hyps(3) by fastforce
        from  $l$  have  $mf: g1 \vdash fn \simeq fe1$ 
          using ConditionalNode.hyps(1) ConditionalNode.hyps(4) by fastforce
        then show ?case
        proof –
          have  $g1 \vdash cn \simeq ce1$  using  $mc$  by simp
          have  $g1 \vdash tn \simeq te1$  using  $mt$  by simp
          have  $g1 \vdash fn \simeq fe1$  using  $mf$  by simp
          have  $cer: \exists ce2. (g2 \vdash cn \simeq ce2) \wedge ce1 \geq ce2$ 
            using ConditionalNode
            using  $a\ b\ c\ d\ l\ no-encoding\ not-excluded-keep-type\ repDet\ singletonD$ 
            by (metis node-eq-ternary ConditionalNode)
          have  $ter: \exists te2. (g2 \vdash tn \simeq te2) \wedge te1 \geq te2$ 
            using ConditionalNode a b c d l no-encoding not-excluded-keep-type repDet

```

```

singletonD
  by (metis-node-eq-ternary ConditionalNode)
  have  $\exists fe2. (g2 \vdash fn \simeq fe2) \wedge fe1 \geq fe2$ 
  using ConditionalNode a b c d l no-encoding not-excluded-keep-type repDet
singletonD
  by (metis-node-eq-ternary ConditionalNode)
  then have  $\exists ce2 te2 fe2. (g2 \vdash n \simeq ConditionalExpr\ ce2\ te2\ fe2) \wedge$ 
ConditionalExpr ce1 te1 fe1  $\geq ConditionalExpr\ ce2\ te2\ fe2$ 
  using ConditionalNode.premis l rep.ConditionalNode cer ter
  by (smt (verit) mono-conditional)
  then show ?thesis
  by meson
qed
next
case (AbsNode n x xe1)
have k:  $g1 \vdash n \simeq UnaryExpr\ UnaryAbs\ xe1$  using f AbsNode
  by (simp add: AbsNode.hyps(2) rep.AbsNode)
obtain xn where l: kind g1 n = AbsNode xn
  using AbsNode.hyps(1) by blast
then have m:  $g1 \vdash xn \simeq xe1$ 
  using AbsNode.hyps(1) AbsNode.hyps(2) by fastforce
then show ?case
proof (cases xn = n')
case True
  then have n:  $xe1 = e1'$  using c m repDet by simp
  then have ev:  $g2 \vdash n \simeq UnaryExpr\ UnaryAbs\ e2'$  using AbsNode.hyps(1)
l m n
    using AbsNode.premis True d rep.AbsNode by simp
  then have r:  $UnaryExpr\ UnaryAbs\ e1' \geq UnaryExpr\ UnaryAbs\ e2'$ 
  by (meson a mono-unary)
  then show ?thesis using ev r
  by (metis n)
next
case False
have  $g1 \vdash xn \simeq xe1$  using m by simp
have  $\exists xe2. (g2 \vdash xn \simeq xe2) \wedge xe1 \geq xe2$ 
  using AbsNode
  using False b encodes-contains l not-excluded-keep-type not-in-g singleton-iff
  by (metis-node-eq-unary AbsNode)
  then have  $\exists xe2. (g2 \vdash n \simeq UnaryExpr\ UnaryAbs\ xe2) \wedge UnaryExpr$ 
UnaryAbs xe1  $\geq UnaryExpr\ UnaryAbs\ xe2$ 
  by (metis AbsNode.premis l mono-unary rep.AbsNode)
  then show ?thesis
  by meson
qed
next
case (NotNode n x xe1)
have k:  $g1 \vdash n \simeq UnaryExpr\ UnaryNot\ xe1$  using f NotNode
  by (simp add: NotNode.hyps(2) rep.NotNode)

```



```

obtain  $xn$  where  $l$ :  $\text{kind } g1 \ n = \text{NotNode } xn$ 
  using  $\text{NotNode.hyps}(1)$  by  $\text{blast}$ 
then have  $m$ :  $g1 \vdash xn \simeq xe1$ 
  using  $\text{NotNode.hyps}(1)$   $\text{NotNode.hyps}(2)$  by  $\text{fastforce}$ 
then show  $?case$ 
proof ( $\text{cases } xn = n'$ )
  case  $\text{True}$ 
    then have  $n$ :  $xe1 = e1'$  using  $c \ m \ \text{repDet}$  by  $\text{simp}$ 
    then have  $ev$ :  $g2 \vdash n \simeq \text{UnaryExpr } \text{UnaryNot } e2'$  using  $\text{NotNode.hyps}(1)$ 
   $l \ m \ n$ 
    using  $\text{NotNode.premis } \text{True } d \ \text{rep.NotNode}$  by  $\text{simp}$ 
    then have  $r$ :  $\text{UnaryExpr } \text{UnaryNot } e1' \geq \text{UnaryExpr } \text{UnaryNot } e2'$ 
      by ( $\text{meson } a \ \text{mono-unary}$ )
    then show  $?thesis$  using  $ev \ r$ 
      by ( $\text{metis } n$ )
  next
    case  $\text{False}$ 
    have  $g1 \vdash xn \simeq xe1$  using  $m$  by  $\text{simp}$ 
    have  $\exists \ xe2. (g2 \vdash xn \simeq xe2) \wedge xe1 \geq xe2$ 
      using  $\text{NotNode}$ 
      using  $\text{False } i \ b \ l \ \text{not-excluded-keep-type singletonD no-encoding}$ 
      by ( $\text{metis-node-eq-unary } \text{NotNode}$ )
    then have  $\exists \ xe2. (g2 \vdash n \simeq \text{UnaryExpr } \text{UnaryNot } xe2) \wedge \text{UnaryExpr } \text{UnaryNot } xe1 \geq \text{UnaryExpr } \text{UnaryNot } xe2$ 
      by ( $\text{metis } \text{NotNode.premis } l \ \text{mono-unary } \text{rep.NotNode}$ )
    then show  $?thesis$ 
      by  $\text{meson}$ 
  qed
next
  case ( $\text{NegateNode } n \ x \ xe1$ )
  have  $k$ :  $g1 \vdash n \simeq \text{UnaryExpr } \text{UnaryNeg } xe1$  using  $f \ \text{NegateNode}$ 
    by ( $\text{simp add: } \text{NegateNode.hyps}(2) \ \text{rep.NegateNode}$ )
  obtain  $xn$  where  $l$ :  $\text{kind } g1 \ n = \text{NegateNode } xn$ 
    using  $\text{NegateNode.hyps}(1)$  by  $\text{blast}$ 
  then have  $m$ :  $g1 \vdash xn \simeq xe1$ 
    using  $\text{NegateNode.hyps}(1) \ \text{NegateNode.hyps}(2)$  by  $\text{fastforce}$ 
  then show  $?case$ 
  proof ( $\text{cases } xn = n'$ )
    case  $\text{True}$ 
      then have  $n$ :  $xe1 = e1'$  using  $c \ m \ \text{repDet}$  by  $\text{simp}$ 
      then have  $ev$ :  $g2 \vdash n \simeq \text{UnaryExpr } \text{UnaryNeg } e2'$  using  $\text{NegateNode.hyps}(1)$ 
     $l \ m \ n$ 
      using  $\text{NegateNode.premis } \text{True } d \ \text{rep.NegateNode}$  by  $\text{simp}$ 
      then have  $r$ :  $\text{UnaryExpr } \text{UnaryNeg } e1' \geq \text{UnaryExpr } \text{UnaryNeg } e2'$ 
        by ( $\text{meson } a \ \text{mono-unary}$ )
      then show  $?thesis$  using  $ev \ r$ 
        by ( $\text{metis } n$ )
    next
      case  $\text{False}$ 

```

```

    have  $g1 \vdash xn \simeq xe1$  using  $m$  by simp
    have  $\exists xe2. (g2 \vdash xn \simeq xe2) \wedge xe1 \geq xe2$ 
      using NegateNode
      using False i b l not-excluded-keep-type singletonD no-encoding
      by (metis-node-eq-unary NegateNode)
      then have  $\exists xe2. (g2 \vdash n \simeq \text{UnaryExpr UnaryNeg } xe2) \wedge \text{UnaryExpr}$ 
        UnaryNeg } xe1 \geq \text{UnaryExpr UnaryNeg } xe2
      by (metis NegateNode.prem s l mono-unary rep.NegateNode)
      then show ?thesis
        by meson
    qed
  next
    case (LogicNegationNode n x xe1)
      have  $k: g1 \vdash n \simeq \text{UnaryExpr UnaryLogicNegation } xe1$  using  $f$  LogicNegationNode
        by (simp add: LogicNegationNode.hyps(2) rep.LogicNegationNode)
      obtain  $xn$  where  $l: \text{kind } g1 \ n = \text{LogicNegationNode } xn$ 
        using LogicNegationNode.hyps(1) by blast
      then have  $m: g1 \vdash xn \simeq xe1$ 
        using LogicNegationNode.hyps(1) LogicNegationNode.hyps(2) by fastforce
      then show ?case
        proof (cases xn = n')
          case True
            then have  $n: xe1 = e1'$  using  $c \ m \ repDet$  by simp
            then have  $ev: g2 \vdash n \simeq \text{UnaryExpr UnaryLogicNegation } e2'$  using
              LogicNegationNode.hyps(1) l m n
              using LogicNegationNode.prem s True d rep.LogicNegationNode by simp
            then have  $r: \text{UnaryExpr UnaryLogicNegation } e1' \geq \text{UnaryExpr UnaryLogicNegation } e2'$ 
              by (meson a mono-unary)
            then show ?thesis using  $ev \ r$ 
              by (metis n)
          next
            case False
              have  $g1 \vdash xn \simeq xe1$  using  $m$  by simp
              have  $\exists xe2. (g2 \vdash xn \simeq xe2) \wedge xe1 \geq xe2$ 
                using LogicNegationNode
                using False i b l not-excluded-keep-type singletonD no-encoding
                by (metis-node-eq-unary LogicNegationNode)
              then have  $\exists xe2. (g2 \vdash n \simeq \text{UnaryExpr UnaryLogicNegation } xe2) \wedge$ 
                UnaryExpr UnaryLogicNegation } xe1 \geq \text{UnaryExpr UnaryLogicNegation } xe2
              by (metis LogicNegationNode.prem s l mono-unary rep.LogicNegationNode)
              then show ?thesis
                by meson
        qed
    next
      case (AddNode n x y xe1 ye1)
      have  $k: g1 \vdash n \simeq \text{BinaryExpr BinAdd } xe1 \ ye1$  using  $f$  AddNode
        by (simp add: AddNode.hyps(2) rep.AddNode)

```

```

obtain  $xn\ yn$  where  $l$ :  $kind\ g1\ n = AddNode\ xn\ yn$ 
  using  $AddNode.hyps(1)$  by blast
then have  $mx$ :  $g1 \vdash xn \simeq xe1$ 
  using  $AddNode.hyps(1)\ AddNode.hyps(2)$  by fastforce
from  $l$  have  $my$ :  $g1 \vdash yn \simeq ye1$ 
  using  $AddNode.hyps(1)\ AddNode.hyps(3)$  by fastforce
then show ?case
proof –
  have  $g1 \vdash xn \simeq xe1$  using  $mx$  by simp
  have  $g1 \vdash yn \simeq ye1$  using  $my$  by simp
  have  $xer$ :  $\exists\ xe2. (g2 \vdash xn \simeq xe2) \wedge xe1 \geq xe2$ 
    using  $AddNode$ 
    using  $a\ b\ c\ d\ l\ no-encoding\ not-excluded-keep-type\ repDet\ singletonD$ 
    by (metis-node-eq-binary  $AddNode$ )
  have  $\exists\ ye2. (g2 \vdash yn \simeq ye2) \wedge ye1 \geq ye2$ 
    using  $AddNode$ 
    using  $a\ b\ c\ d\ l\ no-encoding\ not-excluded-keep-type\ repDet\ singletonD$ 
    by (metis-node-eq-binary  $AddNode$ )
  then have  $\exists\ xe2\ ye2. (g2 \vdash n \simeq BinaryExpr\ BinAdd\ xe2\ ye2) \wedge BinaryExpr$ 
     $BinAdd\ xe1\ ye1 \geq BinaryExpr\ BinAdd\ xe2\ ye2$ 
    by (metis  $AddNode.premis\ l\ mono-binary\ rep.AddNode\ xer$ )
  then show ?thesis
    by meson
qed
next
case ( $MulNode\ n\ x\ y\ xe1\ ye1$ )
have  $k$ :  $g1 \vdash n \simeq BinaryExpr\ BinMul\ xe1\ ye1$  using  $f\ MulNode$ 
  by (simp  $add$ :  $MulNode.hyps(2)\ rep.MulNode$ )
obtain  $xn\ yn$  where  $l$ :  $kind\ g1\ n = MulNode\ xn\ yn$ 
  using  $MulNode.hyps(1)$  by blast
then have  $mx$ :  $g1 \vdash xn \simeq xe1$ 
  using  $MulNode.hyps(1)\ MulNode.hyps(2)$  by fastforce
from  $l$  have  $my$ :  $g1 \vdash yn \simeq ye1$ 
  using  $MulNode.hyps(1)\ MulNode.hyps(3)$  by fastforce
then show ?case
proof –
  have  $g1 \vdash xn \simeq xe1$  using  $mx$  by simp
  have  $g1 \vdash yn \simeq ye1$  using  $my$  by simp
  have  $xer$ :  $\exists\ xe2. (g2 \vdash xn \simeq xe2) \wedge xe1 \geq xe2$ 
    using  $MulNode$ 
    using  $a\ b\ c\ d\ l\ no-encoding\ not-excluded-keep-type\ repDet\ singletonD$ 
    by (metis-node-eq-binary  $MulNode$ )
  have  $\exists\ ye2. (g2 \vdash yn \simeq ye2) \wedge ye1 \geq ye2$ 
    using  $MulNode$ 
    using  $a\ b\ c\ d\ l\ no-encoding\ not-excluded-keep-type\ repDet\ singletonD$ 
    by (metis-node-eq-binary  $MulNode$ )
  then have  $\exists\ xe2\ ye2. (g2 \vdash n \simeq BinaryExpr\ BinMul\ xe2\ ye2) \wedge BinaryExpr$ 
     $BinMul\ xe1\ ye1 \geq BinaryExpr\ BinMul\ xe2\ ye2$ 
    by (metis  $MulNode.premis\ l\ mono-binary\ rep.MulNode\ xer$ )

```

```

    then show ?thesis
      by meson
  qed
next
case (SubNode n x y xe1 ye1)
have k:  $g1 \vdash n \simeq \text{BinaryExpr BinSub } xe1 \text{ ye1}$  using f SubNode
  by (simp add: SubNode.hyps(2) rep.SubNode)
obtain xn yn where l: kind g1 n = SubNode xn yn
  using SubNode.hyps(1) by blast
then have mx:  $g1 \vdash xn \simeq xe1$ 
  using SubNode.hyps(1) SubNode.hyps(2) by fastforce
from l have my:  $g1 \vdash yn \simeq ye1$ 
  using SubNode.hyps(1) SubNode.hyps(3) by fastforce
then show ?case
proof -
  have  $g1 \vdash xn \simeq xe1$  using mx by simp
  have  $g1 \vdash yn \simeq ye1$  using my by simp
  have xer:  $\exists xe2. (g2 \vdash xn \simeq xe2) \wedge xe1 \geq xe2$ 
    using SubNode
    using a b c d l no-encoding not-excluded-keep-type repDet singletonD
    by (metis-node-eq-binary SubNode)
  have  $\exists ye2. (g2 \vdash yn \simeq ye2) \wedge ye1 \geq ye2$ 
  using SubNode a b c d l no-encoding not-excluded-keep-type repDet singletonD
    by (metis-node-eq-binary SubNode)
  then have  $\exists xe2 ye2. (g2 \vdash n \simeq \text{BinaryExpr BinSub } xe2 \text{ ye2}) \wedge \text{BinaryExpr BinSub } xe1 \text{ ye1} \geq \text{BinaryExpr BinSub } xe2 \text{ ye2}$ 
    by (metis SubNode.premis l mono-binary rep.SubNode xer)
  then show ?thesis
    by meson
  qed
next
case (AndNode n x y xe1 ye1)
have k:  $g1 \vdash n \simeq \text{BinaryExpr BinAnd } xe1 \text{ ye1}$  using f AndNode
  by (simp add: AndNode.hyps(2) rep.AndNode)
obtain xn yn where l: kind g1 n = AndNode xn yn
  using AndNode.hyps(1) by blast
then have mx:  $g1 \vdash xn \simeq xe1$ 
  using AndNode.hyps(1) AndNode.hyps(2) by fastforce
from l have my:  $g1 \vdash yn \simeq ye1$ 
  using AndNode.hyps(1) AndNode.hyps(3) by fastforce
then show ?case
proof -
  have  $g1 \vdash xn \simeq xe1$  using mx by simp
  have  $g1 \vdash yn \simeq ye1$  using my by simp
  have xer:  $\exists xe2. (g2 \vdash xn \simeq xe2) \wedge xe1 \geq xe2$ 
    using AndNode
    using a b c d l no-encoding not-excluded-keep-type repDet singletonD
    by (metis-node-eq-binary AndNode)
  have  $\exists ye2. (g2 \vdash yn \simeq ye2) \wedge ye1 \geq ye2$ 

```

```

      using AndNode a b c d l no-encoding not-excluded-keep-type repDet
singletonD
    by (metis-node-eq-binary AndNode)
  then have  $\exists xe2 ye2. (g2 \vdash n \simeq BinaryExpr BinAnd xe2 ye2) \wedge BinaryExpr$ 
    BinAnd xe1 ye1  $\geq BinaryExpr BinAnd xe2 ye2$ 
    by (metis AndNode.premis l mono-binary rep.AndNode xer)
  then show ?thesis
    by meson
qed
next
case (OrNode n x y xe1 ye1)
have k:  $g1 \vdash n \simeq BinaryExpr BinOr xe1 ye1$  using f OrNode
  by (simp add: OrNode.hyps(2) rep.OrNode)
obtain xn yn where l: kind g1 n = OrNode xn yn
  using OrNode.hyps(1) by blast
then have mx:  $g1 \vdash xn \simeq xe1$ 
  using OrNode.hyps(1) OrNode.hyps(2) by fastforce
from l have my:  $g1 \vdash yn \simeq ye1$ 
  using OrNode.hyps(1) OrNode.hyps(3) by fastforce
then show ?case
proof -
  have  $g1 \vdash xn \simeq xe1$  using mx by simp
  have  $g1 \vdash yn \simeq ye1$  using my by simp
  have xer:  $\exists xe2. (g2 \vdash xn \simeq xe2) \wedge xe1 \geq xe2$ 
    using OrNode
    using a b c d l no-encoding not-excluded-keep-type repDet singletonD
    by (metis-node-eq-binary OrNode)
  have  $\exists ye2. (g2 \vdash yn \simeq ye2) \wedge ye1 \geq ye2$ 
  using OrNode a b c d l no-encoding not-excluded-keep-type repDet singletonD
    by (metis-node-eq-binary OrNode)
  then have  $\exists xe2 ye2. (g2 \vdash n \simeq BinaryExpr BinOr xe2 ye2) \wedge BinaryExpr$ 
    BinOr xe1 ye1  $\geq BinaryExpr BinOr xe2 ye2$ 
    by (metis OrNode.premis l mono-binary rep.OrNode xer)
  then show ?thesis
    by meson
qed
next
case (XorNode n x y xe1 ye1)
have k:  $g1 \vdash n \simeq BinaryExpr BinXor xe1 ye1$  using f XorNode
  by (simp add: XorNode.hyps(2) rep.XorNode)
obtain xn yn where l: kind g1 n = XorNode xn yn
  using XorNode.hyps(1) by blast
then have mx:  $g1 \vdash xn \simeq xe1$ 
  using XorNode.hyps(1) XorNode.hyps(2) by fastforce
from l have my:  $g1 \vdash yn \simeq ye1$ 
  using XorNode.hyps(1) XorNode.hyps(3) by fastforce
then show ?case
proof -
  have  $g1 \vdash xn \simeq xe1$  using mx by simp

```

```

    have  $g1 \vdash yn \simeq ye1$  using my by simp
    have  $xer: \exists xe2. (g2 \vdash xn \simeq xe2) \wedge xe1 \geq xe2$ 
      using XorNode
      using a b c d l no-encoding not-excluded-keep-type repDet singletonD
      by (metis-node-eq-binary XorNode)
    have  $\exists ye2. (g2 \vdash yn \simeq ye2) \wedge ye1 \geq ye2$ 
      using XorNode a b c d l no-encoding not-excluded-keep-type repDet
singletonD
      by (metis-node-eq-binary XorNode)
    then have  $\exists xe2 ye2. (g2 \vdash n \simeq BinaryExpr BinXor xe2 ye2) \wedge BinaryExpr$ 
BinXor xe1 ye1  $\geq BinaryExpr BinXor xe2 ye2$ 
      by (metis XorNode.premis l mono-binary rep.XorNode xer)
    then show ?thesis
      by meson
  qed
next
case (LeftShiftNode n x y xe1 ye1)
have  $k: g1 \vdash n \simeq BinaryExpr BinLeftShift xe1 ye1$  using f LeftShiftNode
  by (simp add: LeftShiftNode.hyps(2) rep.LeftShiftNode)
obtain  $xn yn$  where l: kind g1 n = LeftShiftNode xn yn
  using LeftShiftNode.hyps(1) by blast
then have  $mx: g1 \vdash xn \simeq xe1$ 
  using LeftShiftNode.hyps(1) LeftShiftNode.hyps(2) by fastforce
from l have  $my: g1 \vdash yn \simeq ye1$ 
  using LeftShiftNode.hyps(1) LeftShiftNode.hyps(3) by fastforce
then show ?case
proof –
  have  $g1 \vdash xn \simeq xe1$  using mx by simp
  have  $g1 \vdash yn \simeq ye1$  using my by simp
  have  $xer: \exists xe2. (g2 \vdash xn \simeq xe2) \wedge xe1 \geq xe2$ 
    using LeftShiftNode
    using a b c d l no-encoding not-excluded-keep-type repDet singletonD
    by (metis-node-eq-binary LeftShiftNode)
  have  $\exists ye2. (g2 \vdash yn \simeq ye2) \wedge ye1 \geq ye2$ 
    using LeftShiftNode a b c d l no-encoding not-excluded-keep-type repDet
singletonD
    by (metis-node-eq-binary LeftShiftNode)
  then have  $\exists xe2 ye2. (g2 \vdash n \simeq BinaryExpr BinLeftShift xe2 ye2) \wedge$ 
BinaryExpr BinLeftShift xe1 ye1  $\geq BinaryExpr BinLeftShift xe2 ye2$ 
    by (metis LeftShiftNode.premis l mono-binary rep.LeftShiftNode xer)
  then show ?thesis
    by meson
  qed
next
case (RightShiftNode n x y xe1 ye1)
have  $k: g1 \vdash n \simeq BinaryExpr BinRightShift xe1 ye1$  using f RightShiftNode
  by (simp add: RightShiftNode.hyps(2) rep.RightShiftNode)
obtain  $xn yn$  where l: kind g1 n = RightShiftNode xn yn
  using RightShiftNode.hyps(1) by blast

```

```

then have mx:  $g1 \vdash xn \simeq xe1$ 
  using RightShiftNode.hyps(1) RightShiftNode.hyps(2) by fastforce
from l have my:  $g1 \vdash yn \simeq ye1$ 
  using RightShiftNode.hyps(1) RightShiftNode.hyps(3) by fastforce
then show ?case
proof -
  have  $g1 \vdash xn \simeq xe1$  using mx by simp
  have  $g1 \vdash yn \simeq ye1$  using my by simp
  have xer:  $\exists xe2. (g2 \vdash xn \simeq xe2) \wedge xe1 \geq xe2$ 
    using RightShiftNode
    using a b c d l no-encoding not-excluded-keep-type repDet singletonD
    by (metis-node-eq-binary RightShiftNode)
  have  $\exists ye2. (g2 \vdash yn \simeq ye2) \wedge ye1 \geq ye2$ 
    using RightShiftNode a b c d l no-encoding not-excluded-keep-type repDet
    singletonD
    by (metis-node-eq-binary RightShiftNode)
  then have  $\exists xe2 ye2. (g2 \vdash n \simeq BinaryExpr BinRightShift xe2 ye2) \wedge$ 
     $BinaryExpr BinRightShift xe1 ye1 \geq BinaryExpr BinRightShift xe2 ye2$ 
    by (metis RightShiftNode.premis l mono-binary rep.RightShiftNode xer)
  then show ?thesis
    by meson
qed
next
case (UnsignedRightShiftNode n x y xe1 ye1)
  have k:  $g1 \vdash n \simeq BinaryExpr BinURightShift xe1 ye1$  using f UnsignedRight-
    ShiftNode
    by (simp add: UnsignedRightShiftNode.hyps(2) rep.UnsignedRightShiftNode)
  obtain xn yn where l: kind  $g1 \ n = UnsignedRightShiftNode \ xn \ yn$ 
    using UnsignedRightShiftNode.hyps(1) by blast
  then have mx:  $g1 \vdash xn \simeq xe1$ 
    using UnsignedRightShiftNode.hyps(1) UnsignedRightShiftNode.hyps(2) by
    fastforce
  from l have my:  $g1 \vdash yn \simeq ye1$ 
    using UnsignedRightShiftNode.hyps(1) UnsignedRightShiftNode.hyps(3) by
    fastforce
  then show ?case
  proof -
    have  $g1 \vdash xn \simeq xe1$  using mx by simp
    have  $g1 \vdash yn \simeq ye1$  using my by simp
    have xer:  $\exists xe2. (g2 \vdash xn \simeq xe2) \wedge xe1 \geq xe2$ 
      using UnsignedRightShiftNode
      using a b c d l no-encoding not-excluded-keep-type repDet singletonD
      by (metis-node-eq-binary UnsignedRightShiftNode)
    have  $\exists ye2. (g2 \vdash yn \simeq ye2) \wedge ye1 \geq ye2$ 
      using UnsignedRightShiftNode a b c d l no-encoding not-excluded-keep-type
      repDet singletonD
      by (metis-node-eq-binary UnsignedRightShiftNode)
    then have  $\exists xe2 ye2. (g2 \vdash n \simeq BinaryExpr BinURightShift xe2 ye2) \wedge$ 
       $BinaryExpr BinURightShift xe1 ye1 \geq BinaryExpr BinURightShift xe2 ye2$ 

```

```

    by (metis UnsignedRightShiftNode.premis l mono-binary rep.UnsignedRightShiftNode
xer)
    then show ?thesis
    by meson
  qed
next
case (IntegerBelowNode n x y xe1 ye1)
  have k:  $g1 \vdash n \simeq \text{BinaryExpr BinIntegerBelow } xe1 \text{ } ye1$  using f IntegerBe-
lowNode
  by (simp add: IntegerBelowNode.hyps(2) rep.IntegerBelowNode)
  obtain xn yn where l: kind g1 n = IntegerBelowNode xn yn
  using IntegerBelowNode.hyps(1) by blast
  then have mx:  $g1 \vdash xn \simeq xe1$ 
  using IntegerBelowNode.hyps(1) IntegerBelowNode.hyps(2) by fastforce
  from l have my:  $g1 \vdash yn \simeq ye1$ 
  using IntegerBelowNode.hyps(1) IntegerBelowNode.hyps(3) by fastforce
  then show ?case
  proof -
    have  $g1 \vdash xn \simeq xe1$  using mx by simp
    have  $g1 \vdash yn \simeq ye1$  using my by simp
    have xer:  $\exists xe2. (g2 \vdash xn \simeq xe2) \wedge xe1 \geq xe2$ 
    using IntegerBelowNode
    using a b c d l no-encoding not-excluded-keep-type repDet singletonD
    by (metis-node-eq-binary IntegerBelowNode)
    have  $\exists ye2. (g2 \vdash yn \simeq ye2) \wedge ye1 \geq ye2$ 
    using IntegerBelowNode a b c d l no-encoding not-excluded-keep-type repDet
    singletonD
    by (metis-node-eq-binary IntegerBelowNode)
    then have  $\exists xe2 \ ye2. (g2 \vdash n \simeq \text{BinaryExpr BinIntegerBelow } xe2 \text{ } ye2) \wedge$ 
    BinaryExpr BinIntegerBelow xe1 ye1  $\geq$  BinaryExpr BinIntegerBelow xe2 ye2
    by (metis IntegerBelowNode.premis l mono-binary rep.IntegerBelowNode
xer)
    then show ?thesis
    by meson
  qed
next
case (IntegerEqualsNode n x y xe1 ye1)
  have k:  $g1 \vdash n \simeq \text{BinaryExpr BinIntegerEquals } xe1 \text{ } ye1$  using f IntegerEqual-
sNode
  by (simp add: IntegerEqualsNode.hyps(2) rep.IntegerEqualsNode)
  obtain xn yn where l: kind g1 n = IntegerEqualsNode xn yn
  using IntegerEqualsNode.hyps(1) by blast
  then have mx:  $g1 \vdash xn \simeq xe1$ 
  using IntegerEqualsNode.hyps(1) IntegerEqualsNode.hyps(2) by fastforce
  from l have my:  $g1 \vdash yn \simeq ye1$ 
  using IntegerEqualsNode.hyps(1) IntegerEqualsNode.hyps(3) by fastforce
  then show ?case
  proof -
    have  $g1 \vdash xn \simeq xe1$  using mx by simp

```



```

    have  $g1 \vdash yn \simeq ye1$  using my by simp
    have  $xer: \exists xe2. (g2 \vdash xn \simeq xe2) \wedge xe1 \geq xe2$ 
      using IntegerEqualsNode
      using a b c d l no-encoding not-excluded-keep-type repDet singletonD
      by (metis-node-eq-binary IntegerEqualsNode)
    have  $\exists ye2. (g2 \vdash yn \simeq ye2) \wedge ye1 \geq ye2$ 
      using IntegerEqualsNode a b c d l no-encoding not-excluded-keep-type
repDet singletonD
      by (metis-node-eq-binary IntegerEqualsNode)
    then have  $\exists xe2 ye2. (g2 \vdash n \simeq BinaryExpr BinIntegerEquals xe2 ye2) \wedge$ 
BinaryExpr BinIntegerEquals xe1 ye1  $\geq BinaryExpr BinIntegerEquals xe2 ye2$ 
      by (metis IntegerEqualsNode.premis l mono-binary rep.IntegerEqualsNode
xer)
    then show ?thesis
      by meson
  qed
next
case (IntegerLessThanNode n x y xe1 ye1)
  have  $k: g1 \vdash n \simeq BinaryExpr BinIntegerLessThan xe1 ye1$  using f IntegerLessThanNode
  by (simp add: IntegerLessThanNode.hyps(2) rep.IntegerLessThanNode)
  obtain  $xn yn$  where  $l: kind\ g1\ n = IntegerLessThanNode\ xn\ yn$ 
  using IntegerLessThanNode.hyps(1) by blast
  then have  $mx: g1 \vdash xn \simeq xe1$ 
  using IntegerLessThanNode.hyps(1) IntegerLessThanNode.hyps(2) by fast-
force
  from  $l$  have  $my: g1 \vdash yn \simeq ye1$ 
  using IntegerLessThanNode.hyps(1) IntegerLessThanNode.hyps(3) by fast-
force
  then show ?case
  proof -
    have  $g1 \vdash xn \simeq xe1$  using mx by simp
    have  $g1 \vdash yn \simeq ye1$  using my by simp
    have  $xer: \exists xe2. (g2 \vdash xn \simeq xe2) \wedge xe1 \geq xe2$ 
      using IntegerLessThanNode
      using a b c d l no-encoding not-excluded-keep-type repDet singletonD
      by (metis-node-eq-binary IntegerLessThanNode)
    have  $\exists ye2. (g2 \vdash yn \simeq ye2) \wedge ye1 \geq ye2$ 
      using IntegerLessThanNode a b c d l no-encoding not-excluded-keep-type
repDet singletonD
      by (metis-node-eq-binary IntegerLessThanNode)
    then have  $\exists xe2 ye2. (g2 \vdash n \simeq BinaryExpr BinIntegerLessThan xe2 ye2)$ 
 $\wedge BinaryExpr BinIntegerLessThan xe1 ye1 \geq BinaryExpr BinIntegerLessThan xe2$ 
 $ye2$ 
      by (metis IntegerLessThanNode.premis l mono-binary rep.IntegerLessThanNode
xer)
    then show ?thesis
      by meson
  qed

```

```

next
  case (NarrowNode n inputBits resultBits x xe1)
  have k:  $g1 \vdash n \simeq \text{UnaryExpr } (\text{UnaryNarrow inputBits resultBits}) xe1$  using
f NarrowNode
  by (simp add: NarrowNode.hyps(2) rep.NarrowNode)
  obtain xn where l: kind g1 n = NarrowNode inputBits resultBits xn
  using NarrowNode.hyps(1) by blast
  then have m:  $g1 \vdash xn \simeq xe1$ 
  using NarrowNode.hyps(1) NarrowNode.hyps(2)
  by auto
  then show ?case
  proof (cases xn = n')
    case True
    then have n:  $xe1 = e1'$  using c m repDet by simp
    then have ev:  $g2 \vdash n \simeq \text{UnaryExpr } (\text{UnaryNarrow inputBits resultBits}) e2'$ 
  using NarrowNode.hyps(1) l m n
    using NarrowNode.premis True d rep.NarrowNode by simp
    then have r:  $\text{UnaryExpr } (\text{UnaryNarrow inputBits resultBits}) e1' \geq \text{UnaryExpr } (\text{UnaryNarrow inputBits resultBits}) e2'$ 
    by (meson a mono-unary)
    then show ?thesis using ev r
    by (metis n)
  next
  case False
  have  $g1 \vdash xn \simeq xe1$  using m by simp
  have  $\exists xe2. (g2 \vdash xn \simeq xe2) \wedge xe1 \geq xe2$ 
  using NarrowNode
  using False b encodes-contains l not-excluded-keep-type not-in-g singleton-iff
  by (metis node-eq-ternary NarrowNode)
  then have  $\exists xe2. (g2 \vdash n \simeq \text{UnaryExpr } (\text{UnaryNarrow inputBits resultBits}) xe2) \wedge \text{UnaryExpr } (\text{UnaryNarrow inputBits resultBits}) xe1 \geq \text{UnaryExpr } (\text{UnaryNarrow inputBits resultBits}) xe2$ 
  by (metis NarrowNode.premis l mono-unary rep.NarrowNode)
  then show ?thesis
  by meson
qed
next
  case (SignExtendNode n inputBits resultBits x xe1)
  have k:  $g1 \vdash n \simeq \text{UnaryExpr } (\text{UnarySignExtend inputBits resultBits}) xe1$ 
  using f SignExtendNode
  by (simp add: SignExtendNode.hyps(2) rep.SignExtendNode)
  obtain xn where l: kind g1 n = SignExtendNode inputBits resultBits xn
  using SignExtendNode.hyps(1) by blast
  then have m:  $g1 \vdash xn \simeq xe1$ 
  using SignExtendNode.hyps(1) SignExtendNode.hyps(2)
  by auto
  then show ?case
  proof (cases xn = n')
    case True

```

```

      then have n:  $xe1 = e1'$  using c m repDet by simp
      then have ev:  $g2 \vdash n \simeq \text{UnaryExpr } (\text{UnarySignExtend inputBits resultBits})$ 
    e2' using SignExtendNode.hyps(1) l m n
      using SignExtendNode.premis True d rep.SignExtendNode by simp
      then have r:  $\text{UnaryExpr } (\text{UnarySignExtend inputBits resultBits}) e1' \geq$ 
 $\text{UnaryExpr } (\text{UnarySignExtend inputBits resultBits}) e2'$ 
      by (meson a mono-unary)
      then show ?thesis using ev r
      by (metis n)
    next
    case False
    have  $g1 \vdash xn \simeq xe1$  using m by simp
    have  $\exists xe2. (g2 \vdash xn \simeq xe2) \wedge xe1 \geq xe2$ 
      using SignExtendNode
    using False b encodes-contains l not-excluded-keep-type not-in-g singleton-iff
      by (metis-node-eq-ternary SignExtendNode)
    then have  $\exists xe2. (g2 \vdash n \simeq \text{UnaryExpr } (\text{UnarySignExtend inputBits result-}$ 
 $\text{Bits}) xe2) \wedge \text{UnaryExpr } (\text{UnarySignExtend inputBits resultBits}) xe1 \geq \text{UnaryExpr } (\text{UnarySignExtend inputBits resultBits}) xe2$ 
      by (metis SignExtendNode.premis l mono-unary rep.SignExtendNode)
    then show ?thesis
      by meson
    qed
  next
  case (ZeroExtendNode n inputBits resultBits x xe1)
  have k:  $g1 \vdash n \simeq \text{UnaryExpr } (\text{UnaryZeroExtend inputBits resultBits}) xe1$ 
using f ZeroExtendNode
  by (simp add: ZeroExtendNode.hyps(2) rep.ZeroExtendNode)
  obtain xn where l: kind g1 n = ZeroExtendNode inputBits resultBits xn
  using ZeroExtendNode.hyps(1) by blast
  then have m:  $g1 \vdash xn \simeq xe1$ 
  using ZeroExtendNode.hyps(1) ZeroExtendNode.hyps(2)
  by auto
  then show ?case
  proof (cases xn = n')
    case True
    then have n:  $xe1 = e1'$  using c m repDet by simp
    then have ev:  $g2 \vdash n \simeq \text{UnaryExpr } (\text{UnaryZeroExtend inputBits resultBits})$ 
  e2' using ZeroExtendNode.hyps(1) l m n
    using ZeroExtendNode.premis True d rep.ZeroExtendNode by simp
    then have r:  $\text{UnaryExpr } (\text{UnaryZeroExtend inputBits resultBits}) e1' \geq$ 
 $\text{UnaryExpr } (\text{UnaryZeroExtend inputBits resultBits}) e2'$ 
    by (meson a mono-unary)
    then show ?thesis using ev r
    by (metis n)
  next
  case False
  have  $g1 \vdash xn \simeq xe1$  using m by simp
  have  $\exists xe2. (g2 \vdash xn \simeq xe2) \wedge xe1 \geq xe2$ 

```

```

    using ZeroExtendNode
    using False b encodes-contains l not-excluded-keep-type not-in-g singleton-iff
    by (metis-node-eq-ternary ZeroExtendNode)
    then have  $\exists xe2. (g2 \vdash n \simeq \text{UnaryExpr } (\text{UnaryZeroExtend inputBits resultBits}) xe2) \wedge \text{UnaryExpr } (\text{UnaryZeroExtend inputBits resultBits}) xe1 \geq \text{UnaryExpr } (\text{UnaryZeroExtend inputBits resultBits}) xe2$ 
    by (metis ZeroExtendNode.premis l mono-unary rep.ZeroExtendNode)
    then show ?thesis
    by meson
  qed
next
case (LeafNode n s)
then show ?case
by (metis eq-refl rep.LeanNode)
next
case (RefNode n')
then show ?case
by (metis a b c d no-encoding not-excluded-keep-type rep.RefNode repDet singletonD)
qed
qed
qed

```

lemma *graph-antics-preservation-subscript*:

```

  assumes a:  $e_1' \geq e_2'$ 
  assumes b:  $(\{n\} \trianglelefteq \text{as-set } g_1) \subseteq \text{as-set } g_2$ 
  assumes c:  $g_1 \vdash n \simeq e_1'$ 
  assumes d:  $g_2 \vdash n \simeq e_2'$ 
  shows graph-refinement  $g_1 g_2$ 
  using graph-antics-preservation assms by simp

```

lemma *tree-to-graph-rewriting*:

```

   $e_1 \geq e_2$ 
   $\wedge (g_1 \vdash n \simeq e_1) \wedge \text{maximal-sharing } g_1$ 
   $\wedge (\{n\} \trianglelefteq \text{as-set } g_1) \subseteq \text{as-set } g_2$ 
   $\wedge (g_2 \vdash n \simeq e_2) \wedge \text{maximal-sharing } g_2$ 
 $\implies \text{graph-refinement } g_1 g_2$ 
  using graph-antics-preservation
  by auto

```

```

declare [[simp-trace]]
lemma equal-refines:
  fixes e1 e2 :: IRExp
  assumes e1 = e2
  shows  $e1 \geq e2$ 
  using assms
  by simp
declare [[simp-trace=false]]

```

lemma *eval-contains-id*[simp]: $g1 \vdash n \simeq e \implies n \in \text{ids } g1$
using *no-encoding* **by** *blast*

lemma *subset-kind*[simp]: $\text{as-set } g1 \subseteq \text{as-set } g2 \implies g1 \vdash n \simeq e \implies \text{kind } g1 \ n = \text{kind } g2 \ n$
using *eval-contains-id* **unfolding** *as-set-def*
by *blast*

lemma *subset-stamp*[simp]: $\text{as-set } g1 \subseteq \text{as-set } g2 \implies g1 \vdash n \simeq e \implies \text{stamp } g1 \ n = \text{stamp } g2 \ n$
using *eval-contains-id* **unfolding** *as-set-def*
by *blast*

method *solve-subset-eval* **uses** *as-set eval* =
(*metis eval as-set subset-kind subset-stamp* |
metis eval as-set subset-kind)

lemma *subset-implies-evals*:
assumes $\text{as-set } g1 \subseteq \text{as-set } g2$
assumes $(g1 \vdash n \simeq e)$
shows $(g2 \vdash n \simeq e)$
using *assms(2)*
apply (*induction e*)
apply (*solve-subset-eval as-set: assms(1) eval: ConstantNode*)
apply (*solve-subset-eval as-set: assms(1) eval: ParameterNode*)
apply (*solve-subset-eval as-set: assms(1) eval: ConditionalNode*)
apply (*solve-subset-eval as-set: assms(1) eval: AbsNode*)
apply (*solve-subset-eval as-set: assms(1) eval: NotNode*)
apply (*solve-subset-eval as-set: assms(1) eval: NegateNode*)
apply (*solve-subset-eval as-set: assms(1) eval: LogicNegationNode*)
apply (*solve-subset-eval as-set: assms(1) eval: AddNode*)
apply (*solve-subset-eval as-set: assms(1) eval: MulNode*)
apply (*solve-subset-eval as-set: assms(1) eval: SubNode*)
apply (*solve-subset-eval as-set: assms(1) eval: AndNode*)
apply (*solve-subset-eval as-set: assms(1) eval: OrNode*)
apply (*solve-subset-eval as-set: assms(1) eval: XorNode*)
apply (*solve-subset-eval as-set: assms(1) eval: LeftShiftNode*)
apply (*solve-subset-eval as-set: assms(1) eval: RightShiftNode*)
apply (*solve-subset-eval as-set: assms(1) eval: UnsignedRightShiftNode*)
apply (*solve-subset-eval as-set: assms(1) eval: IntegerBelowNode*)
apply (*solve-subset-eval as-set: assms(1) eval: IntegerEqualsNode*)
apply (*solve-subset-eval as-set: assms(1) eval: IntegerLessThanNode*)
apply (*solve-subset-eval as-set: assms(1) eval: NarrowNode*)
apply (*solve-subset-eval as-set: assms(1) eval: SignExtendNode*)
apply (*solve-subset-eval as-set: assms(1) eval: ZeroExtendNode*)

```

apply (solve-subset-eval as-set: assms(1) eval: LeafNode)
by (solve-subset-eval as-set: assms(1) eval: RefNode)

lemma subset-refines:
  assumes as-set  $g1 \subseteq as\text{-}set\ g2$ 
  shows graph-refinement  $g1\ g2$ 
proof –
  have ids  $g1 \subseteq ids\ g2$  using assms unfolding as-set-def
  by blast
  then show ?thesis unfolding graph-refinement-def apply rule
  apply (rule allI) apply (rule impI) apply (rule allI) apply (rule impI)
  unfolding graph-represents-expression-def
  proof –
    fix  $n\ e1$ 
    assume  $1:n \in ids\ g1$ 
    assume  $2:g1 \vdash n \simeq e1$ 

    show  $\exists e2. (g2 \vdash n \simeq e2) \wedge e1 \geq e2$ 
    using assms 1 2 using subset-implies-evals
    by (meson equal-refines)
  qed
qed

lemma graph-construction:
   $e_1 \geq e_2$ 
   $\wedge as\text{-}set\ g_1 \subseteq as\text{-}set\ g_2$ 
   $\wedge (g_2 \vdash n \simeq e_2)$ 
   $\implies (g_2 \vdash n \sqsubseteq e_1) \wedge graph\text{-}refinement\ g_1\ g_2$ 
  using subset-refines
  by (meson encodeeval-def graph-represents-expression-def le-expr-def)

```

6.8.4 Term Graph Reconstruction

```

lemma find-exists-kind:
  assumes find-node-and-stamp  $g\ (node, s) = Some\ nid$ 
  shows kind  $g\ nid = node$ 
  using assms unfolding find-node-and-stamp.simps
  by (metis (mono-tags, lifting) find-Some-iff)

lemma find-exists-stamp:
  assumes find-node-and-stamp  $g\ (node, s) = Some\ nid$ 
  shows stamp  $g\ nid = s$ 
  using assms unfolding find-node-and-stamp.simps
  by (metis (mono-tags, lifting) find-Some-iff)

lemma find-new-kind:
  assumes  $g' = add\text{-}node\ nid\ (node, s)\ g$ 
  assumes  $node \neq NoNode$ 
  shows kind  $g'\ nid = node$ 

```

```

using assms
using add-node-lookup by presburger

lemma find-new-stamp:
  assumes  $g' = \text{add-node } nid \ (node, s) \ g$ 
  assumes  $node \neq \text{NoNode}$ 
  shows  $\text{stamp } g' \ nid = s$ 
  using assms
  using add-node-lookup by presburger

lemma sorted-bottom:
  assumes finite xs
  assumes  $x \in xs$ 
  shows  $x \leq \text{last}(\text{sorted-list-of-set}(xs::\text{nat set}))$ 
  using assms
  using sorted2-simps(2) sorted-list-of-set(2)
  by (smt (verit, del-insts) Diff-iff Max-ge Max-in empty-iff list.set(1) snoc-eq-iff-butlast
sorted-insort-is-snoc sorted-list-of-set(1) sorted-list-of-set.fold-insort-key.infinite sorted-list-of-set.fold-insort-key)

lemma fresh:  $\text{finite } xs \implies \text{last}(\text{sorted-list-of-set}(xs::\text{nat set})) + 1 \notin xs$ 
  using sorted-bottom
  using not-le by auto

lemma fresh-ids:
  assumes  $n = \text{get-fresh-id } g$ 
  shows  $n \notin \text{ids } g$ 
proof -
  have finite (ids g) using Rep-IRGraph by auto
  then show ?thesis
    using assms fresh unfolding get-fresh-id.simps
    by blast
qed

lemma graph-unchanged-rep-unchanged:
  assumes  $\forall n \in \text{ids } g. \text{kind } g \ n = \text{kind } g' \ n$ 
  assumes  $\forall n \in \text{ids } g. \text{stamp } g \ n = \text{stamp } g' \ n$ 
  shows  $(g \vdash n \simeq e) \longrightarrow (g' \vdash n \simeq e)$ 
  apply (rule impI) subgoal premises e using e assms
    apply (induction  $n \ e$ )
      apply (metis no-encoding rep.ConstantNode)
      apply (metis no-encoding rep.ParameterNode)
      apply (metis no-encoding rep.ConditionalNode)
      apply (metis no-encoding rep.AbsNode)
      apply (metis no-encoding rep.NotNode)
      apply (metis no-encoding rep.NegateNode)
      apply (metis no-encoding rep.LogicNegationNode)
      apply (metis no-encoding rep.AddNode)
      apply (metis no-encoding rep.MulNode)
      apply (metis no-encoding rep.SubNode)

```

```

    apply (metis no-encoding rep.AndNode)
    apply (metis no-encoding rep.OrNode)
    apply (metis no-encoding rep.XorNode)
    apply (metis no-encoding rep.LeftShiftNode)
    apply (metis no-encoding rep.RightShiftNode)
    apply (metis no-encoding rep.UnsignedRightShiftNode)
    apply (metis no-encoding rep.IntegerBelowNode)
    apply (metis no-encoding rep.IntegerEqualsNode)
    apply (metis no-encoding rep.IntegerLessThanNode)
    apply (metis no-encoding rep.NarrowNode)
    apply (metis no-encoding rep.SignExtendNode)
    apply (metis no-encoding rep.ZeroExtendNode)
    apply (metis no-encoding rep.LeafNode)
  by (metis no-encoding rep.RefNode)
done

```

lemma *fresh-node-subset*:

```

  assumes  $n \notin \text{ids } g$ 
  assumes  $g' = \text{add-node } n (k, s) g$ 
  shows  $\text{as-set } g \subseteq \text{as-set } g'$ 
  using assms
  by (smt (verit, del-Insts) Collect-mono-iff Diff-idemp Diff-insert-absorb add-changed
    as-set-def disjoint-change unchanged.simps)

```

lemma *unrep-subset*:

```

  assumes  $(g \triangleleft e \rightsquigarrow (g', n))$ 
  shows  $\text{as-set } g \subseteq \text{as-set } g'$ 
  using assms proof (induction  $g e (g', n)$  arbitrary:  $g' n$ )
  case (ConstantNodeSame  $g c n$ )
  then show ?case by blast
next
  case (ConstantNodeNew  $g c n g'$ )
  then show ?case using fresh-ids fresh-node-subset
    by presburger
next
  case (ParameterNodeSame  $g i s n$ )
  then show ?case by blast
next
  case (ParameterNodeNew  $g i s n g'$ )
  then show ?case using fresh-ids fresh-node-subset
    by presburger
next
  case (ConditionalNodeSame  $g ce g2 c te g3 t fe g4 f s' n$ )
  then show ?case by blast
next
  case (ConditionalNodeNew  $g ce g2 c te g3 t fe g4 f s' n g'$ )
  then show ?case using fresh-ids fresh-node-subset
    by (meson subset-trans)
next

```



```

    case (UnaryNodeSame g xe g2 x s' op n)
    then show ?case by blast
next
    case (UnaryNodeNew g xe g2 x s' op n g')
    then show ?case using fresh-ids fresh-node-subset
    by (meson subset-trans)
next
    case (BinaryNodeSame g xe g2 x ye g3 y s' op n)
    then show ?case by blast
next
    case (BinaryNodeNew g xe g2 x ye g3 y s' op n g')
    then show ?case using fresh-ids fresh-node-subset
    by (meson subset-trans)
next
    case (AllLeafNodes g n s)
    then show ?case by blast
qed

lemma fresh-node-preserves-other-nodes:
  assumes n' = get-fresh-id g
  assumes g' = add-node n' (k, s) g
  shows  $\forall n \in \text{ids } g. (g \vdash n \simeq e) \longrightarrow (g' \vdash n \simeq e)$ 
  using assms
  by (smt (verit, ccfv-SIG) Diff-idemp Diff-insert-absorb add-changed disjoint-change
    fresh-ids graph-unchanged-rep-unchanged unchanged.elims(2))

lemma found-node-preserves-other-nodes:
  assumes find-node-and-stamp g (k, s) = Some n
  shows  $\forall n \in \text{ids } g. (g \vdash n \simeq e) \longleftrightarrow (g \vdash n \simeq e)$ 
  using assms
  by blast

lemma unrep-ids-subset[simp]:
  assumes  $g \triangleleft e \rightsquigarrow (g', n)$ 
  shows  $\text{ids } g \subseteq \text{ids } g'$ 
  using assms unrep-subset
  by (meson graph-refinement-def subset-refines)

lemma unrep-unchanged:
  assumes  $g \triangleleft e \rightsquigarrow (g', n)$ 
  shows  $\forall n \in \text{ids } g. \forall e. (g \vdash n \simeq e) \longrightarrow (g' \vdash n \simeq e)$ 
  using assms unrep-subset fresh-node-preserves-other-nodes
  by (meson subset-implies-evals)

theorem term-graph-reconstruction:
   $g \triangleleft e \rightsquigarrow (g', n) \implies g' \vdash n \simeq e$ 
  subgoal premises e using e
  proof (induction g e (g', n) arbitrary: g' n)
    case (ConstantNodeSame g' c n)

```

```

then have kind  $g' n = \text{ConstantNode } c$ 
  using find-exists-kind local.ConstantNodeSame by blast
then show ?case using ConstantNode by blast
next
case (ConstantNodeNew  $g c$ )
then show ?case
  using ConstantNode IRNode.distinct(683) add-node-lookup by presburger
next
case (ParameterNodeSame  $i s$ )
then show ?case
  by (metis ParameterNode find-exists-kind find-exists-stamp)
next
case (ParameterNodeNew  $g i s$ )
then show ?case
  by (metis IRNode.distinct(2447) ParameterNode add-node-lookup)
next
case (ConditionalNodeSame  $g ce g2 c te g3 t fe g4 f s' n$ )
then have  $k$ : kind  $g4 n = \text{ConditionalNode } c t f$ 
  using find-exists-kind by blast
have  $c$ :  $g4 \vdash c \simeq ce$  using local.ConditionalNodeSame unrep-unchanged
  using no-encoding by blast
have  $t$ :  $g4 \vdash t \simeq te$  using local.ConditionalNodeSame unrep-unchanged
  using no-encoding by blast
have  $f$ :  $g4 \vdash f \simeq fe$  using local.ConditionalNodeSame unrep-unchanged
  using no-encoding by blast
then show ?case using  $c t f$ 
  using ConditionalNode  $k$  by blast
next
case (ConditionalNodeNew  $g ce g2 c te g3 t fe g4 f s' n g'$ )
moreover have ConditionalNode  $c t f \neq \text{NoNode}$ 
  using unary-node.elims by blast
ultimately have  $k$ : kind  $g' n = \text{ConditionalNode } c t f$ 
  using find-new-kind local.ConditionalNodeNew
  by presburger
then have  $c$ :  $g' \vdash c \simeq ce$  using local.ConditionalNodeNew unrep-unchanged
  using no-encoding
  by (metis ConditionalNodeNew.hyps(9) fresh-node-preserves-other-nodes)
then have  $t$ :  $g' \vdash t \simeq te$  using local.ConditionalNodeNew unrep-unchanged
  using no-encoding fresh-node-preserves-other-nodes
  by metis
then have  $f$ :  $g' \vdash f \simeq fe$  using local.ConditionalNodeNew unrep-unchanged
  using no-encoding fresh-node-preserves-other-nodes
  by metis
then show ?case using  $c t f$ 
  using ConditionalNode  $k$  by blast
next
case (UnaryNodeSame  $g xe g' x s' op n$ )
then have  $k$ : kind  $g' n = \text{unary-node } op x$ 
  using find-exists-kind local.UnaryNodeSame by blast

```

```

then have  $g' \vdash x \simeq xe$  using local.UnaryNodeSame by blast
then show ?case using k
  apply (cases op)
  using AbsNode unary-node.simps(1) apply presburger
  using NegateNode unary-node.simps(3) apply presburger
  using NotNode unary-node.simps(2) apply presburger
  using LogicNegationNode unary-node.simps(4) apply presburger
  using NarrowNode unary-node.simps(5) apply presburger
  using SignExtendNode unary-node.simps(6) apply presburger
  using ZeroExtendNode unary-node.simps(7) by presburger
next
case (UnaryNodeNew g xe g2 x s' op n g')
moreover have unary-node op x  $\neq$  NoNode
  using unary-node.elims by blast
ultimately have k: kind g' n = unary-node op x
  using find-new-kind local.UnaryNodeNew
  by presburger
have  $x \in \text{ids } g2$  using local.UnaryNodeNew
  using eval-contains-id by blast
then have  $x \neq n$  using local.UnaryNodeNew(5) fresh-ids by blast
have  $g' \vdash x \simeq xe$  using local.UnaryNodeNew fresh-node-preserves-other-nodes
  using  $\langle x \in \text{ids } g2 \rangle$  by blast
then show ?case using k
  apply (cases op)
  using AbsNode unary-node.simps(1) apply presburger
  using NegateNode unary-node.simps(3) apply presburger
  using NotNode unary-node.simps(2) apply presburger
  using LogicNegationNode unary-node.simps(4) apply presburger
  using NarrowNode unary-node.simps(5) apply presburger
  using SignExtendNode unary-node.simps(6) apply presburger
  using ZeroExtendNode unary-node.simps(7) by presburger
next
case (BinaryNodeSame g xe g2 x ye g3 y s' op n)
then have k: kind g3 n = bin-node op x y
  using find-exists-kind by blast
have  $x: g3 \vdash x \simeq xe$  using local.BinaryNodeSame unrep-unchanged
  using no-encoding by blast
have  $y: g3 \vdash y \simeq ye$  using local.BinaryNodeSame unrep-unchanged
  using no-encoding by blast
then show ?case using  $x y k$  apply (cases op)
  using AddNode bin-node.simps(1) apply presburger
  using MulNode bin-node.simps(2) apply presburger
  using SubNode bin-node.simps(3) apply presburger
  using AndNode bin-node.simps(4) apply presburger
  using OrNode bin-node.simps(5) apply presburger
  using XorNode bin-node.simps(6) apply presburger
  using LeftShiftNode bin-node.simps(7) apply presburger
  using RightShiftNode bin-node.simps(8) apply presburger
  using UnsignedRightShiftNode bin-node.simps(9) apply presburger

```

```

    using IntegerEqualsNode bin-node.simps(10) apply presburger
    using IntegerLessThanNode bin-node.simps(11) apply presburger
    using IntegerBelowNode bin-node.simps(12) by presburger
next
case (BinaryNodeNew g xe g2 x ye g3 y s' op n g')
moreover have bin-node op x y  $\neq$  NoNode
  using bin-node.elims by blast
ultimately have k: kind g' n = bin-node op x y
  using find-new-kind local.BinaryNodeNew
  by presburger
then have k: kind g' n = bin-node op x y
  using find-exists-kind by blast
have x: g'  $\vdash$  x  $\simeq$  xe using local.BinaryNodeNew unrep-unchanged
  using no-encoding
  by (meson fresh-node-preserves-other-nodes)
have y: g'  $\vdash$  y  $\simeq$  ye using local.BinaryNodeNew unrep-unchanged
  using no-encoding
  by (meson fresh-node-preserves-other-nodes)
then show ?case using x y k apply (cases op)
  using AddNode bin-node.simps(1) apply presburger
  using MulNode bin-node.simps(2) apply presburger
  using SubNode bin-node.simps(3) apply presburger
  using AndNode bin-node.simps(4) apply presburger
  using OrNode bin-node.simps(5) apply presburger
  using XorNode bin-node.simps(6) apply presburger
  using LeftShiftNode bin-node.simps(7) apply presburger
  using RightShiftNode bin-node.simps(8) apply presburger
  using UnsignedRightShiftNode bin-node.simps(9) apply presburger
  using IntegerEqualsNode bin-node.simps(10) apply presburger
  using IntegerLessThanNode bin-node.simps(11) apply presburger
  using IntegerBelowNode bin-node.simps(12) by presburger
next
case (AllLeafNodes g n s)
then show ?case using rep.LeafNode by blast
qed
done

```

lemma *ref-refinement*:

```

assumes g  $\vdash$  n  $\simeq$  e1
assumes kind g n' = RefNode n
shows g  $\vdash$  n'  $\trianglelefteq$  e1
using assms RefNode
by (meson equal-refines graph-represents-expression-def)

```

lemma *unrep-refines*:

```

assumes g  $\triangleleft$  e  $\rightsquigarrow$  (g', n)
shows graph-refinement g g'
using assms
using graph-refinement-def subset-refines unrep-subset by blast

```

```

lemma add-new-node-refines:
  assumes  $n \notin \text{ids } g$ 
  assumes  $g' = \text{add-node } n \ (k, s) \ g$ 
  shows graph-refinement  $g \ g'$ 
  using assms unfolding graph-refinement
  using fresh-node-subset subset-refines by presburger

lemma add-node-as-set:
  assumes  $g' = \text{add-node } n \ (k, s) \ g$ 
  shows  $\{n\} \trianglelefteq \text{as-set } g \subseteq \text{as-set } g'$ 
  using assms unfolding as-set-def domain-subtraction-def
  using add-changed
  by (smt (z3) case-prodE changeonly.simps mem-Collect-eq prod.sel(1) subsetI)

```

end

7 Control-flow Semantics

```

theory IRStepObj
  imports
    TreeToGraph
begin

```

7.1 Object Heap

The heap model we introduce maps field references to object instances to runtime values. We use the $H[f][p]$ heap representation. See *\cite{heap-reps-2011}*. We also introduce the `DynamicHeap` type which allocates new object references sequentially storing the next free object reference as `'Free'`.

heapdef

```

type-synonym ('a, 'b) Heap = 'a  $\Rightarrow$  'b  $\Rightarrow$  Value
type-synonym Free = nat
type-synonym ('a, 'b) DynamicHeap = ('a, 'b) Heap  $\times$  Free

fun h-load-field :: 'a  $\Rightarrow$  'b  $\Rightarrow$  ('a, 'b) DynamicHeap  $\Rightarrow$  Value where
  h-load-field f r (h, n) = h f r

fun h-store-field :: 'a  $\Rightarrow$  'b  $\Rightarrow$  Value  $\Rightarrow$  ('a, 'b) DynamicHeap  $\Rightarrow$  ('a, 'b)
  DynamicHeap where
  h-store-field f r v (h, n) = (h(f := ((h f)(r := v))), n)

fun h-new-inst :: ('a, 'b) DynamicHeap  $\Rightarrow$  ('a, 'b) DynamicHeap  $\times$  Value
where
  h-new-inst (h, n) = ((h, n+1), (ObjRef (Some n)))

type-synonym FieldRefHeap = (string, objref) DynamicHeap

```

```

definition new-heap :: ('a, 'b) DynamicHeap where
  new-heap = (( $\lambda$ f.  $\lambda$ p. UndefVal), 0)

```

7.2 Intraprocedural Semantics

```

fun find-index :: 'a  $\Rightarrow$  'a list  $\Rightarrow$  nat where
  find-index - [] = 0 |
  find-index v (x # xs) = (if (x=v) then 0 else find-index v xs + 1)

fun phi-list :: IRGraph  $\Rightarrow$  ID  $\Rightarrow$  ID list where
  phi-list g n =
    (filter ( $\lambda$ x.(is-PhiNode (kind g x)))
     (sorted-list-of-set (usages g n)))

fun input-index :: IRGraph  $\Rightarrow$  ID  $\Rightarrow$  ID  $\Rightarrow$  nat where
  input-index g n n' = find-index n' (inputs-of (kind g n))

fun phi-inputs :: IRGraph  $\Rightarrow$  nat  $\Rightarrow$  ID list  $\Rightarrow$  ID list where
  phi-inputs g i nodes = (map ( $\lambda$ n. (inputs-of (kind g n))!(i + 1)) nodes)

fun set-phis :: ID list  $\Rightarrow$  Value list  $\Rightarrow$  MapState  $\Rightarrow$  MapState where
  set-phis [] [] m = m |
  set-phis (n # xs) (v # vs) m = (set-phis xs vs (m(n := v))) |
  set-phis [] (v # vs) m = m |
  set-phis (x # xs) [] m = m

```

Intraprocedural semantics are given as a small-step semantics.

Within the context of a graph, the configuration triple, (ID, MethodState, Heap), is related to the subsequent configuration.

```

inductive step :: IRGraph  $\Rightarrow$  Params  $\Rightarrow$  (ID  $\times$  MapState  $\times$  FieldRefHeap)  $\Rightarrow$  (ID

```

$\times \text{MapState} \times \text{FieldRefHeap}) \Rightarrow \text{bool}$
 $(-, - \vdash - \rightarrow - \text{ 55})$ **for** $g \ p$ **where**

SequentialNode:

$\llbracket \text{is-sequential-node } (kind \ g \ nid);$
 $\quad nid' = (\text{successors-of } (kind \ g \ nid))!0 \rrbracket$
 $\implies g, p \vdash (nid, m, h) \rightarrow (nid', m, h) \mid$

IfNode:

$\llbracket kind \ g \ nid = (\text{IfNode } cond \ tb \ fb);$
 $\quad g \vdash cond \simeq condE;$
 $\quad [m, p] \vdash condE \mapsto val;$
 $\quad nid' = (\text{if } val\text{-to-bool } val \text{ then } tb \text{ else } fb) \rrbracket$
 $\implies g, p \vdash (nid, m, h) \rightarrow (nid', m, h) \mid$

EndNodes:

$\llbracket \text{is-AbstractEndNode } (kind \ g \ nid);$
 $\quad merge = \text{any-usage } g \ nid;$
 $\quad \text{is-AbstractMergeNode } (kind \ g \ merge);$

 $\quad i = \text{find-index } nid \ (\text{inputs-of } (kind \ g \ merge));$
 $\quad phis = (\text{phi-list } g \ merge);$
 $\quad inps = (\text{phi-inputs } g \ i \ phis);$
 $\quad g \vdash inps \simeq_L inpsE;$
 $\quad [m, p] \vdash inpsE \mapsto_L vs;$

 $\quad m' = \text{set-phis } phis \ vs \ m \rrbracket$
 $\implies g, p \vdash (nid, m, h) \rightarrow (merge, m', h) \mid$

NewInstanceNode:

$\llbracket kind \ g \ nid = (\text{NewInstanceNode } nid \ f \ obj \ nid');$
 $\quad (h', ref) = h\text{-new-inst } h;$
 $\quad m' = m(nid := ref) \rrbracket$
 $\implies g, p \vdash (nid, m, h) \rightarrow (nid', m', h') \mid$

LoadFieldNode:

$\llbracket kind \ g \ nid = (\text{LoadFieldNode } nid \ f \ (\text{Some } obj) \ nid');$
 $\quad g \vdash obj \simeq objE;$
 $\quad [m, p] \vdash objE \mapsto \text{ObjRef } ref;$
 $\quad h\text{-load-field } f \ ref \ h = v;$
 $\quad m' = m(nid := v) \rrbracket$
 $\implies g, p \vdash (nid, m, h) \rightarrow (nid', m', h) \mid$

SignedDivNode:

$\llbracket kind \ g \ nid = (\text{SignedDivNode } nid \ x \ y \ zero \ sb \ nxt);$
 $\quad g \vdash x \simeq xe;$
 $\quad g \vdash y \simeq ye;$
 $\quad [m, p] \vdash xe \mapsto v1;$

$$\begin{aligned}
& [m, p] \vdash ye \mapsto v2; \\
& v = (\text{intval-div } v1 \ v2); \\
& m' = m(\text{nid} := v) \\
\implies & g, p \vdash (\text{nid}, m, h) \rightarrow (\text{nxt}, m', h) \mid
\end{aligned}$$

SignedRemNode:

$$\begin{aligned}
& \llbracket \text{kind } g \text{ nid} = (\text{SignedRemNode } \text{nid } x \ y \ \text{zero } sb \ \text{nxt}); \\
& \quad g \vdash x \simeq xe; \\
& \quad g \vdash y \simeq ye; \\
& \quad [m, p] \vdash xe \mapsto v1; \\
& \quad [m, p] \vdash ye \mapsto v2; \\
& \quad v = (\text{intval-mod } v1 \ v2); \\
& \quad m' = m(\text{nid} := v) \\
\implies & g, p \vdash (\text{nid}, m, h) \rightarrow (\text{nxt}, m', h) \mid
\end{aligned}$$

StaticLoadFieldNode:

$$\begin{aligned}
& \llbracket \text{kind } g \text{ nid} = (\text{LoadFieldNode } \text{nid } f \ \text{None } \text{nid}'); \\
& \quad h\text{-load-field } f \ \text{None } h = v; \\
& \quad m' = m(\text{nid} := v) \\
\implies & g, p \vdash (\text{nid}, m, h) \rightarrow (\text{nid}', m', h) \mid
\end{aligned}$$

StoreFieldNode:

$$\begin{aligned}
& \llbracket \text{kind } g \text{ nid} = (\text{StoreFieldNode } \text{nid } f \ \text{newval} - (\text{Some } \text{obj}) \ \text{nid}'); \\
& \quad g \vdash \text{newval} \simeq \text{newvalE}; \\
& \quad g \vdash \text{obj} \simeq \text{objE}; \\
& \quad [m, p] \vdash \text{newvalE} \mapsto \text{val}; \\
& \quad [m, p] \vdash \text{objE} \mapsto \text{ObjRef } \text{ref}; \\
& \quad h' = h\text{-store-field } f \ \text{ref } \text{val } h; \\
& \quad m' = m(\text{nid} := \text{val}) \\
\implies & g, p \vdash (\text{nid}, m, h) \rightarrow (\text{nid}', m', h') \mid
\end{aligned}$$

StaticStoreFieldNode:

$$\begin{aligned}
& \llbracket \text{kind } g \text{ nid} = (\text{StoreFieldNode } \text{nid } f \ \text{newval} - \text{None } \text{nid}'); \\
& \quad g \vdash \text{newval} \simeq \text{newvalE}; \\
& \quad [m, p] \vdash \text{newvalE} \mapsto \text{val}; \\
& \quad h' = h\text{-store-field } f \ \text{None } \text{val } h; \\
& \quad m' = m(\text{nid} := \text{val}) \\
\implies & g, p \vdash (\text{nid}, m, h) \rightarrow (\text{nid}', m', h')
\end{aligned}$$

code-pred (*modes*: $i \Rightarrow i \Rightarrow i * i * i \Rightarrow o * o * o \Rightarrow \text{bool}$) *step* .

7.3 Interprocedural Semantics

type-synonym *Signature* = *string*

type-synonym *Program* = *Signature* \rightarrow *IRGraph*

inductive *step-top* :: *Program* \Rightarrow (*IRGraph* \times *ID* \times *MapState* \times *Params*) *list* \times *FieldRefHeap* \Rightarrow (*IRGraph* \times *ID* \times *MapState* \times *Params*) *list* \times *FieldRefHeap* \Rightarrow

bool

$(- \vdash - \longrightarrow - \ 55)$

for P where

Lift:

$\llbracket g, p \vdash (nid, m, h) \rightarrow (nid', m', h') \rrbracket$
 $\implies P \vdash ((g, nid, m, p) \# stk, h) \longrightarrow ((g, nid', m', p) \# stk, h') \mid$

InvokeNodeStep:

$\llbracket is-Invoke \ (kind \ g \ nid);$

$callTarget = ir-callTarget \ (kind \ g \ nid);$

$kind \ g \ callTarget = (MethodCallTargetNode \ targetMethod \ arguments);$

$Some \ targetGraph = P \ targetMethod;$

$m' = new-map-state;$

$g \vdash arguments \simeq_L argsE;$

$[m, p] \vdash argsE \mapsto_L p \uparrow$

$\implies P \vdash ((g, nid, m, p) \# stk, h) \longrightarrow ((targetGraph, 0, m', p') \# (g, nid, m, p) \# stk, h)$

\mid

ReturnNode:

$\llbracket kind \ g \ nid = (ReturnNode \ (Some \ expr) \ -);$

$g \vdash expr \simeq e;$

$[m, p] \vdash e \mapsto v;$

$cm' = cm(cnid := v);$

$cnid' = (successors-of \ (kind \ cg \ cnid))!0 \uparrow$

$\implies P \vdash ((g, nid, m, p) \# (cg, cnid, cm, cp) \# stk, h) \longrightarrow ((cg, cnid', cm', cp) \# stk, h) \mid$

ReturnNodeVoid:

$\llbracket kind \ g \ nid = (ReturnNode \ None \ -);$

$cm' = cm(cnid := (ObjRef \ (Some \ (2048))));$

$cnid' = (successors-of \ (kind \ cg \ cnid))!0 \uparrow$

$\implies P \vdash ((g, nid, m, p) \# (cg, cnid, cm, cp) \# stk, h) \longrightarrow ((cg, cnid', cm', cp) \# stk, h) \mid$

UnwindNode:

$\llbracket kind \ g \ nid = (UnwindNode \ exception);$

$g \vdash exception \simeq exceptionE;$

$[m, p] \vdash exceptionE \mapsto e;$

$kind \ cg \ cnid = (InvokeWithExceptionNode \ - \ - \ - \ - \ - \ exEdge);$

$cm' = cm(cnid := e) \uparrow$

$\implies P \vdash ((g, nid, m, p) \# (cg, cnid, cm, cp) \# stk, h) \longrightarrow ((cg, exEdge, cm', cp) \# stk, h)$

code-pred (*modes*: $i \Rightarrow i \Rightarrow o \Rightarrow bool$) *step-top* .

7.4 Big-step Execution

type-synonym $Trace = (IRGraph \times ID \times MapState \times Params) \text{ list}$

fun $has\text{-}return :: MapState \Rightarrow bool$ **where**
 $has\text{-}return\ m = (m\ 0 \neq Undefined)$

inductive $exec :: Program$
 $\Rightarrow (IRGraph \times ID \times MapState \times Params) \text{ list} \times FieldRefHeap$
 $\Rightarrow Trace$
 $\Rightarrow (IRGraph \times ID \times MapState \times Params) \text{ list} \times FieldRefHeap$
 $\Rightarrow Trace$
 $\Rightarrow bool$
 $(- \vdash - \mid - \longrightarrow * - \mid -)$
for P
where
 $\llbracket P \vdash (((g, nid, m, p) \# xs), h) \longrightarrow (((g', nid', m', p') \# ys), h') ;$
 $\neg(has\text{-}return\ m') ;$
 $l' = (l @ [(g, nid, m, p)]) ;$
 $exec\ P\ (((g', nid', m', p') \# ys), h')\ l'\ next\text{-}state\ l'' \rrbracket$
 $\implies exec\ P\ (((g, nid, m, p) \# xs), h)\ l\ next\text{-}state\ l''$
 \mid
 $\llbracket P \vdash (((g, nid, m, p) \# xs), h) \longrightarrow (((g', nid', m', p') \# ys), h') ;$
 $has\text{-}return\ m' ;$
 $l' = (l @ [(g, nid, m, p)]) \rrbracket$
 $\implies exec\ P\ (((g, nid, m, p) \# xs), h)\ l\ (((g', nid', m', p') \# ys), h')\ l'$
code-pred $(modes: i \Rightarrow i \Rightarrow i \Rightarrow o \Rightarrow o \Rightarrow bool \text{ as } Exec)\ exec .$

inductive $exec\text{-}debug :: Program$
 $\Rightarrow (IRGraph \times ID \times MapState \times Params) \text{ list} \times FieldRefHeap$
 $\Rightarrow nat$
 $\Rightarrow (IRGraph \times ID \times MapState \times Params) \text{ list} \times FieldRefHeap$
 $\Rightarrow bool$
 $(\vdash \longrightarrow * - \mid -)$
where
 $\llbracket n > 0 ;$
 $p \vdash s \longrightarrow s' ;$
 $exec\text{-}debug\ p\ s'\ (n - 1)\ s' \rrbracket$
 $\implies exec\text{-}debug\ p\ s\ n\ s'' \mid$
 $\llbracket n = 0 \rrbracket$
 $\implies exec\text{-}debug\ p\ s\ n\ s$
code-pred $(modes: i \Rightarrow i \Rightarrow i \Rightarrow o \Rightarrow bool)\ exec\text{-}debug .$

7.4.1 Heap Testing

definition $p3 :: Params$ **where**

$p3 = [IntVal32\ 3]$

values $\{(prod.fst(prod.snd\ (prod.snd\ (hd\ (prod.fst\ res))))\ 0$
 $\mid res. (\lambda x. Some\ eg2-sq) \vdash [(eg2-sq, 0, new-map-state, p3), (eg2-sq, 0, new-map-state, p3)],$
 $new-heap) \rightarrow *2* res\}$

definition $field-sq :: string$ **where**

$field-sq = "sq"$

definition $eg3-sq :: IRGraph$ **where**

$eg3-sq = irgraph\ [$
 $(0, StartNode\ None\ 4, VoidStamp),$
 $(1, ParameterNode\ 0, default-stamp),$
 $(3, MulNode\ 1\ 1, default-stamp),$
 $(4, StoreFieldNode\ 4\ field-sq\ 3\ None\ None\ 5, VoidStamp),$
 $(5, ReturnNode\ (Some\ 3)\ None, default-stamp)$
 $]$

values $\{h-load-field\ field-sq\ None\ (prod.snd\ res)$
 $\mid res. (\lambda x. Some\ eg3-sq) \vdash [(eg3-sq, 0, new-map-state, p3), (eg3-sq, 0,$
 $new-map-state, p3)], new-heap) \rightarrow *3* res\}$

definition $eg4-sq :: IRGraph$ **where**

$eg4-sq = irgraph\ [$
 $(0, StartNode\ None\ 4, VoidStamp),$
 $(1, ParameterNode\ 0, default-stamp),$
 $(3, MulNode\ 1\ 1, default-stamp),$
 $(4, NewInstanceNode\ 4\ "obj-class"\ None\ 5, ObjectStamp\ "obj-class"\ True\ True$
 $True),$
 $(5, StoreFieldNode\ 5\ field-sq\ 3\ None\ (Some\ 4)\ 6, VoidStamp),$
 $(6, ReturnNode\ (Some\ 3)\ None, default-stamp)$
 $]$

values $\{h-load-field\ field-sq\ (Some\ 0)\ (prod.snd\ res) \mid res.$
 $(\lambda x. Some\ eg4-sq) \vdash [(eg4-sq, 0, new-map-state, p3), (eg4-sq, 0,$
 $new-map-state, p3)], new-heap) \rightarrow *4* res\}$

end

7.5 Control-flow Semantics Theorems

theory $IRStepThms$

imports

$IRStepObj$

begin

We prove that within the same graph, a configuration triple will always transition to the same subsequent configuration. Therefore, our step semantics is deterministic.

7.5.1 Control-flow Step is Deterministic

theorem *stepDet*:

$(g, p \vdash (nid, m, h) \rightarrow next) \implies$
 $(\forall next'. ((g, p \vdash (nid, m, h) \rightarrow next') \longrightarrow next = next'))$

proof (*induction rule: step.induct*)

case (*SequentialNode* *nid* *next* *m* *h*)

have *notif*: $\neg(is_IfNode\ (kind\ g\ nid))$

using *SequentialNode.hyps*(1) *is-sequential-node.simps*

by (*metis is-IfNode-def*)

have *notend*: $\neg(is_AbstractEndNode\ (kind\ g\ nid))$

using *SequentialNode.hyps*(1) *is-sequential-node.simps*

by (*metis is-AbstractEndNode.simps is-EndNode.elims*(2) *is-LoopEndNode-def*)

have *notnew*: $\neg(is_NewInstanceNode\ (kind\ g\ nid))$

using *SequentialNode.hyps*(1) *is-sequential-node.simps*

by (*metis is-NewInstanceNode-def*)

have *notload*: $\neg(is_LoadFieldNode\ (kind\ g\ nid))$

using *SequentialNode.hyps*(1) *is-sequential-node.simps*

by (*metis is-LoadFieldNode-def*)

have *notstore*: $\neg(is_StoreFieldNode\ (kind\ g\ nid))$

using *SequentialNode.hyps*(1) *is-sequential-node.simps*

by (*metis is-StoreFieldNode-def*)

have *notdivrem*: $\neg(is_IntegerDivRemNode\ (kind\ g\ nid))$

using *SequentialNode.hyps*(1) *is-sequential-node.simps is-SignedDivNode-def*

is-SignedRemNode-def

by (*metis is-IntegerDivRemNode.simps*)

from *notif notend notnew notload notstore notdivrem*

show ?*case* **using** *SequentialNode step.cases*

by (*smt* (z3) *IRNode.disc*(1028) *IRNode.disc*(2270) *IRNode.discI*(31) *Pair-inject*

is-sequential-node.simps(18) *is-sequential-node.simps*(43) *is-sequential-node.simps*(44))

next

case (*IfNode* *nid* *cond* *tb* *fb* *m* *val* *next* *h*)

then have *notseq*: $\neg(is_sequential-node\ (kind\ g\ nid))$

using *is-sequential-node.simps is-AbstractMergeNode.simps*

by (*simp add: IfNode.hyps*(1))

have *notend*: $\neg(is_AbstractEndNode\ (kind\ g\ nid))$

using *is-AbstractEndNode.simps*

by (*simp add: IfNode.hyps*(1))

have *notdivrem*: $\neg(is_IntegerDivRemNode\ (kind\ g\ nid))$

using *is-AbstractEndNode.simps*

by (*simp add: IfNode.hyps*(1))

from *notseq notend notdivrem* **show** ?*case* **using** *IfNode repDet evalDet IRN-*

```

ode.distinct IRNode.inject(11) Pair-inject step.simps
  by (smt (z3) IRNode.distinct IRNode.inject(12) Pair-inject step.simps)
next
case (EndNodes nid merge iphis inputs m vs m' h)
have notseq: ¬(is-sequential-node (kind g nid))
  using EndNodes.hyps(1) is-AbstractEndNode.simps is-sequential-node.simps
  by (metis is-EndNode.elims(2) is-LoopEndNode-def)
have notif: ¬(is-IfNode (kind g nid))
  using EndNodes.hyps(1) is-IfNode-def is-AbstractEndNode.elims
  by (metis IRNode.distinct-disc(1058) is-EndNode.simps(12))
have notref: ¬(is-RefNode (kind g nid))
  using EndNodes.hyps(1) is-sequential-node.simps
  using IRNode.disc(1899) IRNode.distinct(1473) is-AbstractEndNode.simps
is-EndNode.elims(2) is-LoopEndNode-def is-RefNode-def
  by metis
have notnew: ¬(is-NewInstanceNode (kind g nid))
  using EndNodes.hyps(1) is-AbstractEndNode.simps
  using IRNode.distinct-disc(1442) is-EndNode.simps(29) is-NewInstanceNode-def
  by (metis IRNode.distinct-disc(1901) is-EndNode.simps(32))
have notload: ¬(is-LoadFieldNode (kind g nid))
  using EndNodes.hyps(1) is-AbstractEndNode.simps
  using is-LoadFieldNode-def
  by (metis IRNode.distinct-disc(1706) is-EndNode.simps(21))
have notstore: ¬(is-StoreFieldNode (kind g nid))
  using EndNodes.hyps(1) is-AbstractEndNode.simps is-StoreFieldNode-def
  by (metis IRNode.distinct-disc(1926) is-EndNode.simps(44))
have notdivrem: ¬(is-IntegerDivRemNode (kind g nid))
  using EndNodes.hyps(1) is-AbstractEndNode.simps is-SignedDivNode-def is-SignedRemNode-def
  using IRNode.distinct-disc(1498) IRNode.distinct-disc(1500) is-IntegerDivRemNode.simps
is-EndNode.simps(36) is-EndNode.simps(37)
  by auto
from notseq notif notref notnew notload notstore notdivrem
show ?case using EndNodes repAllDet evalAllDet
  by (smt (z3) is-IfNode-def is-LoadFieldNode-def is-NewInstanceNode-def is-RefNode-def
is-StoreFieldNode-def is-SignedDivNode-def is-SignedRemNode-def Pair-inject is-IntegerDivRemNode.elims(3)
step.cases)
next
case (NewInstanceNode nid f obj nrt h' ref h m' m)
then have notseq: ¬(is-sequential-node (kind g nid))
  using is-sequential-node.simps is-AbstractMergeNode.simps
  by (simp add: NewInstanceNode.hyps(1))
have notend: ¬(is-AbstractEndNode (kind g nid))
  using is-AbstractMergeNode.simps
  by (simp add: NewInstanceNode.hyps(1))
have notif: ¬(is-IfNode (kind g nid))
  using is-AbstractMergeNode.simps
  by (simp add: NewInstanceNode.hyps(1))
have notref: ¬(is-RefNode (kind g nid))
  using is-AbstractMergeNode.simps

```

```

    by (simp add: NewInstanceNode.hyps(1))
  have notload:  $\neg(\text{is-LoadFieldNode } (\text{kind } g \text{ nid}))$ 
    using is-AbstractMergeNode.simps
  by (simp add: NewInstanceNode.hyps(1))
  have notstore:  $\neg(\text{is-StoreFieldNode } (\text{kind } g \text{ nid}))$ 
    using is-AbstractMergeNode.simps
  by (simp add: NewInstanceNode.hyps(1))
  have notdivrem:  $\neg(\text{is-IntegerDivRemNode } (\text{kind } g \text{ nid}))$ 
    using is-AbstractMergeNode.simps
  by (simp add: NewInstanceNode.hyps(1))
  from notseq notend notif notref notload notstore notdivrem
  show ?case using NewInstanceNode.step.cases
    by (smt (z3) IRNode.disc(1028) IRNode.disc(2270) IRNode.discI(11) IRNode.distinct(2311) IRNode.distinct(2313) IRNode.inject(31) Pair-inject)
next
  case (LoadFieldNode nid f obj nrt m ref h v m')
  then have notseq:  $\neg(\text{is-sequential-node } (\text{kind } g \text{ nid}))$ 
    using is-sequential-node.simps is-AbstractMergeNode.simps
  by (simp add: LoadFieldNode.hyps(1))
  have notend:  $\neg(\text{is-AbstractEndNode } (\text{kind } g \text{ nid}))$ 
    using is-AbstractEndNode.simps
  by (simp add: LoadFieldNode.hyps(1))
  have notdivrem:  $\neg(\text{is-IntegerDivRemNode } (\text{kind } g \text{ nid}))$ 
    using is-AbstractEndNode.simps
  by (simp add: LoadFieldNode.hyps(1))
  from notseq notend notdivrem
  show ?case using LoadFieldNode.step.cases repDet evalDet
    by (smt (z3) IRNode.distinct(1051) IRNode.distinct(1721) IRNode.distinct(1739) IRNode.distinct(1741) IRNode.distinct(1745) IRNode.inject(20) Pair-inject Value.inject(3) option.distinct(1) option.inject)
next
  case (StaticLoadFieldNode nid f nrt h v m' m)
  then have notseq:  $\neg(\text{is-sequential-node } (\text{kind } g \text{ nid}))$ 
    using is-sequential-node.simps is-AbstractMergeNode.simps
  by (simp add: StaticLoadFieldNode.hyps(1))
  have notend:  $\neg(\text{is-AbstractEndNode } (\text{kind } g \text{ nid}))$ 
    using is-AbstractEndNode.simps
  by (simp add: StaticLoadFieldNode.hyps(1))
  have notdivrem:  $\neg(\text{is-IntegerDivRemNode } (\text{kind } g \text{ nid}))$ 
    by (simp add: StaticLoadFieldNode.hyps(1))
  from notseq notend notdivrem
  show ?case using StaticLoadFieldNode.step.cases
    by (smt (z3) IRNode.distinct(1051) IRNode.distinct(1721) IRNode.distinct(1739) IRNode.distinct(1741) IRNode.distinct(1745) IRNode.inject(20) Pair-inject option.distinct(1))
next
  case (StoreFieldNode nid f newval uu obj nrt m val ref h' h m')
  then have notseq:  $\neg(\text{is-sequential-node } (\text{kind } g \text{ nid}))$ 
    using is-sequential-node.simps is-AbstractMergeNode.simps
  by (simp add: StoreFieldNode.hyps(1))

```

```

have notend: ¬(is-AbstractEndNode (kind g nid))
  using is-AbstractEndNode.simps
  by (simp add: StoreFieldNode.hyps(1))
have notdivrem: ¬(is-IntegerDivRemNode (kind g nid))
  by (simp add: StoreFieldNode.hyps(1))
from notseq notend notdivrem
show ?case using StoreFieldNode step.cases repDet evalDet
  by (smt (z3) IRNode.distinct(1097) IRNode.distinct(1745) IRNode.distinct(2317)
IRNode.distinct(2605) IRNode.distinct(2627) IRNode.inject(43) Pair-inject Value.inject(3)
option.distinct(1) option.inject)
next
case (StaticStoreFieldNode nid f newval uv nxt m val h' h m')
then have notseq: ¬(is-sequential-node (kind g nid))
  using is-sequential-node.simps is-AbstractMergeNode.simps
  by (simp add: StaticStoreFieldNode.hyps(1))
have notend: ¬(is-AbstractEndNode (kind g nid))
  using is-AbstractEndNode.simps
  by (simp add: StaticStoreFieldNode.hyps(1))
have notdivrem: ¬(is-IntegerDivRemNode (kind g nid))
  by (simp add: StaticStoreFieldNode.hyps(1))
from notseq notend notdivrem
show ?case using StoreFieldNode step.cases repDet evalDet
  by (smt (z3) IRNode.distinct(1097) IRNode.distinct(1745) IRNode.distinct(2317)
IRNode.distinct(2605) IRNode.distinct(2627) IRNode.inject(43) Pair-inject Static-
StoreFieldNode.hyps(1) StaticStoreFieldNode.hyps(2) StaticStoreFieldNode.hyps(3)
StaticStoreFieldNode.hyps(4) StaticStoreFieldNode.hyps(5) option.distinct(1))
next
case (SignedDivNode nid x y zero sb nxt m v1 v2 v m' h)
then have notseq: ¬(is-sequential-node (kind g nid))
  using is-sequential-node.simps is-AbstractMergeNode.simps
  by (simp add: SignedDivNode.hyps(1))
have notend: ¬(is-AbstractEndNode (kind g nid))
  using is-AbstractEndNode.simps
  by (simp add: SignedDivNode.hyps(1))
from notseq notend
show ?case using SignedDivNode step.cases repDet evalDet
  by (smt (z3) IRNode.distinct(1091) IRNode.distinct(1739) IRNode.distinct(2311)
IRNode.distinct(2601) IRNode.distinct(2605) IRNode.inject(40) Pair-inject)
next
case (SignedRemNode nid x y zero sb nxt m v1 v2 v m' h)
then have notseq: ¬(is-sequential-node (kind g nid))
  using is-sequential-node.simps is-AbstractMergeNode.simps
  by (simp add: SignedRemNode.hyps(1))
have notend: ¬(is-AbstractEndNode (kind g nid))
  using is-AbstractEndNode.simps
  by (simp add: SignedRemNode.hyps(1))
from notseq notend
show ?case using SignedRemNode step.cases repDet evalDet
  by (smt (z3) IRNode.distinct(1093) IRNode.distinct(1741) IRNode.distinct(2313)

```

IRNode.distinct(2601) IRNode.distinct(2627) IRNode.inject(41) Pair-inject
qed

lemma *stepRefNode*:

$\llbracket \text{kind } g \text{ nid} = \text{RefNode nid}' \rrbracket \implies g, p \vdash (\text{nid}, m, h) \rightarrow (\text{nid}', m, h)$

using *SequentialNode*

by (*metis IRNodes.successors-of-RefNode is-sequential-node.simps(7) nth-Cons-0*)

lemma *IfNodeStepCases*:

assumes *kind g nid = IfNode cond tb fb*

assumes $g \vdash \text{cond} \simeq \text{condE}$

assumes $[m, p] \vdash \text{condE} \mapsto v$

assumes $g, p \vdash (\text{nid}, m, h) \rightarrow (\text{nid}', m, h)$

shows $\text{nid}' \in \{\text{tb}, \text{fb}\}$

using *step.IfNode repDet stepDet assms*

by (*metis insert-iff old.prod.inject*)

lemma *IfNodeSeq*:

shows $\text{kind } g \text{ nid} = \text{IfNode cond tb fb} \longrightarrow \neg(\text{is-sequential-node } (\text{kind } g \text{ nid}))$

unfolding *is-sequential-node.simps*

using *is-sequential-node.simps(18) by presburger*

lemma *IfNodeCond*:

assumes *kind g nid = IfNode cond tb fb*

assumes $g, p \vdash (\text{nid}, m, h) \rightarrow (\text{nid}', m, h)$

shows $\exists \text{ condE } v. ((g \vdash \text{cond} \simeq \text{condE}) \wedge ([m, p] \vdash \text{condE} \mapsto v))$

using *assms(2,1) by (induct (nid,m,h) (nid',m,h) rule: step.induct; auto)*

lemma *step-in-ids*:

assumes $g, p \vdash (\text{nid}, m, h) \rightarrow (\text{nid}', m', h')$

shows $\text{nid} \in \text{ids } g$

using *assms apply (induct (nid, m, h) (nid', m', h') rule: step.induct)*

using *is-sequential-node.simps(45) not-in-g*

apply *simp*

apply (*metis is-sequential-node.simps(53)*)

using *ids-some*

using *IRNode.distinct(1113) apply presburger*

using *EndNodes(1) is-AbstractEndNode.simps is-EndNode.simps(45) ids-some*

apply (*metis IRNode.disc(1218) is-EndNode.simps(52)*)

by *simp+*

end

8 Proof Infrastructure

8.1 Bisimulation

theory *Bisimulation*

imports

Stuttering
begin

inductive *weak-bisimilar* :: $ID \Rightarrow IRGraph \Rightarrow IRGraph \Rightarrow bool$
 (- . - ~ -) **for** *nid* **where**
 $\llbracket \forall P'. (g \ m \ p \ h \vdash \textit{nid} \rightsquigarrow P') \longrightarrow (\exists Q'. (g' \ m \ p \ h \vdash \textit{nid} \rightsquigarrow Q') \wedge P' = Q');$
 $\forall Q'. (g' \ m \ p \ h \vdash \textit{nid} \rightsquigarrow Q') \longrightarrow (\exists P'. (g \ m \ p \ h \vdash \textit{nid} \rightsquigarrow P') \wedge P' = Q') \rrbracket$
 $\implies \textit{nid} . g \sim g'$

A strong bisimilution between no-op transitions

inductive *strong-noop-bisimilar* :: $ID \Rightarrow IRGraph \Rightarrow IRGraph \Rightarrow bool$
 (- | - ~ -) **for** *nid* **where**
 $\llbracket \forall P'. (g, p \vdash (\textit{nid}, m, h) \rightarrow P') \longrightarrow (\exists Q'. (g', p \vdash (\textit{nid}, m, h) \rightarrow Q') \wedge P' = Q');$
 $\forall Q'. (g', p \vdash (\textit{nid}, m, h) \rightarrow Q') \longrightarrow (\exists P'. (g, p \vdash (\textit{nid}, m, h) \rightarrow P') \wedge P' = Q') \rrbracket$
 $\implies \textit{nid} \mid g \sim g'$

lemma *lockstep-strong-bisimilulation*:
assumes $g' = \textit{replace-node} \ \textit{nid} \ \textit{node} \ g$
assumes $g, p \vdash (\textit{nid}, m, h) \rightarrow (\textit{nid}', m, h)$
assumes $g', p \vdash (\textit{nid}, m, h) \rightarrow (\textit{nid}', m, h)$
shows $\textit{nid} \mid g \sim g'$
using *assms(2) assms(3) stepDet strong-noop-bisimilar.simps by metis*

lemma *no-step-bisimulation*:
assumes $\forall m \ p \ h \ \textit{nid}' \ m' \ h'. \neg(g, p \vdash (\textit{nid}, m, h) \rightarrow (\textit{nid}', m', h'))$
assumes $\forall m \ p \ h \ \textit{nid}' \ m' \ h'. \neg(g', p \vdash (\textit{nid}, m, h) \rightarrow (\textit{nid}', m', h'))$
shows $\textit{nid} \mid g \sim g'$
using *assms*
by (*simp add: assms(1) assms(2) strong-noop-bisimilar.intros*)

end

8.2 Graph Rewriting

theory
Rewrites
imports
Semantics.IRGraphFrames
Stuttering
begin

fun *replace-usages* :: $ID \Rightarrow ID \Rightarrow IRGraph \Rightarrow IRGraph$ **where**
replace-usages *nid* *nid'* $g = \textit{replace-node} \ \textit{nid} \ (\textit{RefNode} \ \textit{nid}', \textit{stamp} \ g \ \textit{nid}') \ g$

lemma *replace-usages-effect*:

```

assumes  $g' = \text{replace-usages } nid \ nid' \ g$ 
shows  $\text{kind } g' \ nid = \text{RefNode } nid'$ 
using assms replace-node-lookup replace-usages.simps
by (metis IRNode.distinct(2755))

lemma replace-usages-changeonly:
assumes  $nid \in \text{ids } g$ 
assumes  $g' = \text{replace-usages } nid \ nid' \ g$ 
shows  $\text{changeonly } \{nid\} \ g \ g'$ 
using assms unfolding replace-usages.simps
by (metis add-changed add-node-def replace-node-def)

lemma replace-usages-unchanged:
assumes  $nid \in \text{ids } g$ 
assumes  $g' = \text{replace-usages } nid \ nid' \ g$ 
shows  $\text{unchanged } (\text{ids } g - \{nid\}) \ g \ g'$ 
using assms unfolding replace-usages.simps
using assms(2) disjoint-change replace-usages-changeonly by presburger

fun nextNid :: IRGraph  $\Rightarrow$  ID where
  nextNid  $g = (\text{Max } (\text{ids } g)) + 1$ 

lemma max-plus-one:
fixes  $c :: \text{ID set}$ 
shows  $\llbracket \text{finite } c; c \neq \{\} \rrbracket \Longrightarrow (\text{Max } c) + 1 \notin c$ 
by (meson Max-gr-iff less-add-one less-irrefl)

lemma ids-finite:
  finite (ids  $g$ )
by simp

lemma nextNidNotIn:
   $\text{ids } g \neq \{\} \longrightarrow \text{nextNid } g \notin \text{ids } g$ 
unfolding nextNid.simps
using ids-finite max-plus-one by blast

fun constantCondition :: bool  $\Rightarrow$  ID  $\Rightarrow$  IRNode  $\Rightarrow$  IRGraph  $\Rightarrow$  IRGraph where
  constantCondition  $\text{val } nid \ (\text{IfNode } \text{cond } t \ f) \ g =$ 
     $\text{replace-node } nid \ (\text{IfNode } (\text{nextNid } g) \ t \ f, \text{stamp } g \ nid)$ 
     $(\text{add-node } (\text{nextNid } g) \ ((\text{ConstantNode } (\text{bool-to-val } \text{val})), \text{constantAsStamp}$ 
     $(\text{bool-to-val } \text{val}))) \ g \mid$ 
     $\text{constantCondition } \text{cond } nid - g = g$ 

lemma constantConditionTrue:
assumes  $\text{kind } g \ \text{ifcond} = \text{IfNode } \text{cond } t \ f$ 
assumes  $g' = \text{constantCondition } \text{True } \text{ifcond} \ (\text{kind } g \ \text{ifcond}) \ g$ 
shows  $g', p \vdash (\text{ifcond}, m, h) \rightarrow (t, m, h)$ 

```

proof –
 have *ifn*: $\bigwedge c\ t\ f. \text{IfNode } c\ t\ f \neq \text{NoNode}$
 by *simp*
 then have *if'*: $\text{kind } g' \text{ ifcond} = \text{IfNode } (\text{nextNid } g) \ t\ f$
 using *assms*(1) *assms*(2) *constantCondition.simps*(1) *replace-node-lookup*
 by *presburger*
 have *truedef*: $\text{bool-to-val } \text{True} = (\text{IntVal32 } 1)$
 by *auto*
 from *ifn* have *ifcond* $\neq (\text{nextNid } g)$
 by (*metis* *assms*(1) *emptyE* *ids-some* *nextNidNotIn*)
 moreover have $\bigwedge c. \text{ConstantNode } c \neq \text{NoNode}$ by *simp*
 ultimately have $\text{kind } g' (\text{nextNid } g) = \text{ConstantNode } (\text{bool-to-val } \text{True})$
 using *add-changed* *add-node-def* *assms*(1) *assms*(2) *constantCondition.simps*(1)
not-in-g *other-node-unchanged* *replace-node-def* *replace-node-lookup* *singletonD*
 by (*smt* (z3) *DiffI* *add-node-lookup* *replace-node-unchanged*)
 then have *c'*: $\text{kind } g' (\text{nextNid } g) = \text{ConstantNode } (\text{IntVal32 } 1)$
 using *truedef* by *simp*
 have *valid-value* $(\text{IntVal32 } 1) (\text{constantAsStamp } (\text{IntVal32 } 1))$
 unfolding *constantAsStamp.simps* *valid-value.simps*
 using *nat-numeral* by *blast*
 then have $[g', m, p] \vdash \text{nextNid } g \mapsto \text{IntVal32 } 1$
 using *ConstantExpr* *ConstantNode* *Value.distinct*(1) $\langle \text{kind } g' (\text{nextNid } g) = \text{ConstantNode } (\text{bool-to-val } \text{True}) \rangle$ *encodeeval-def* *truedef*
 by *metis*
 from *if' c'* show ?thesis using *IfNode*
 by (*metis* (*no-types*, *opaque-lifting*) *val-to-bool.simps*(1) $\langle [g', m, p] \vdash \text{nextNid } g \mapsto \text{IntVal32 } 1 \rangle$ *encodeeval-def* *zero-neq-one*)
qed

lemma *constantConditionFalse*:

assumes $\text{kind } g \text{ ifcond} = \text{IfNode } \text{cond } t\ f$
 assumes $g' = \text{constantCondition } \text{False } \text{ifcond} (\text{kind } g \text{ ifcond})\ g$
 shows $g', p \vdash (\text{ifcond}, m, h) \rightarrow (f, m, h)$
proof –
 have *ifn*: $\bigwedge c\ t\ f. \text{IfNode } c\ t\ f \neq \text{NoNode}$
 by *simp*
 then have *if'*: $\text{kind } g' \text{ ifcond} = \text{IfNode } (\text{nextNid } g) \ t\ f$
 by (*metis* *assms*(1) *assms*(2) *constantCondition.simps*(1) *replace-node-lookup*)
 have *falsedef*: $\text{bool-to-val } \text{False} = (\text{IntVal32 } 0)$
 by *auto*
 from *ifn* have *ifcond* $\neq (\text{nextNid } g)$
 by (*metis* *assms*(1) *equals0D* *ids-some* *nextNidNotIn*)
 moreover have $\bigwedge c. \text{ConstantNode } c \neq \text{NoNode}$ by *simp*
 ultimately have $\text{kind } g' (\text{nextNid } g) = \text{ConstantNode } (\text{bool-to-val } \text{False})$
 by (*smt* (z3) *add-changed* *add-node-def* *assms*(1) *assms*(2) *constantCondition.simps*(1) *not-in-g* *other-node-unchanged* *replace-node-def* *replace-node-lookup* *singletonD*)
 then have *c'*: $\text{kind } g' (\text{nextNid } g) = \text{ConstantNode } (\text{IntVal32 } 0)$
 using *falsedef* by *simp*

have *valid-value* (*IntVal32* 0) (*constantAsStamp* (*IntVal32* 0))
unfolding *constantAsStamp.simps* *valid-value.simps*
using *nat-numeral* **by** *blast*
then have $[g', m, p] \vdash \text{nextNid } g \mapsto \text{IntVal32 } 0$
by (*metis* *ConstantExpr* *ConstantNode* $\langle \text{kind } g' (\text{nextNid } g) = \text{ConstantNode} (\text{bool-to-val } \text{False}) \rangle \text{ encodeeval-def falsedef}$)
from *if' c' show ?thesis using IfNode*
by (*metis* (*no-types, opaque-lifting*) *val-to-bool.simps*(1) $\langle [g', m, p] \vdash \text{nextNid } g \mapsto \text{IntVal32 } 0 \rangle \text{ encodeeval-def}$)
qed

lemma *diff-forall*:
assumes $\forall n \in \text{ids } g - \{nid\}. \text{ cond } n$
shows $\forall n. n \in \text{ids } g \wedge n \notin \{nid\} \longrightarrow \text{ cond } n$
by (*meson* *Diff-iff* *assms*)

lemma *replace-node-changeonly*:
assumes $g' = \text{replace-node } nid \text{ node } g$
shows *changeonly* $\{nid\} g g'$
using *assms* *replace-node-unchanged*
unfolding *changeonly.simps* **using** *diff-forall*
by (*metis* *add-changed* *add-node-def* *changeonly.simps* *replace-node-def*)

lemma *add-node-changeonly*:
assumes $g' = \text{add-node } nid \text{ node } g$
shows *changeonly* $\{nid\} g g'$
by (*metis* *Rep-IRGraph-inverse* *add-node.rep-eq* *assms* *replace-node.rep-eq* *replace-node-changeonly*)

lemma *constantConditionNoEffect*:
assumes $\neg(\text{is-IfNode } (\text{kind } g \text{ nid}))$
shows $g = \text{constantCondition } b \text{ nid } (\text{kind } g \text{ nid}) g$
using *assms* **apply** (*cases* *kind* *g* *nid*)
using *constantCondition.simps*
apply *presburger+*
apply (*metis* *is-IfNode-def*)
using *constantCondition.simps*
by *presburger+*

lemma *constantConditionIfNode*:
assumes $\text{kind } g \text{ nid} = \text{IfNode } \text{cond } t \text{ } f$
shows $\text{constantCondition } \text{val } nid (\text{kind } g \text{ nid}) g =$
 $\text{replace-node } nid (\text{IfNode } (\text{nextNid } g) t \text{ } f, \text{ stamp } g \text{ nid})$
 $(\text{add-node } (\text{nextNid } g) ((\text{ConstantNode } (\text{bool-to-val } \text{val})), \text{ constantAsStamp } (\text{bool-to-val } \text{val}))) g)$
using *constantCondition.simps*
by (*simp* *add: assms*)

lemma *constantCondition-changeonly*:

```

    assumes  $nid \in ids\ g$ 
    assumes  $g' = constantCondition\ b\ nid\ (kind\ g\ nid)\ g$ 
    shows  $changeonly\ \{nid\}\ g\ g'$ 
  proof (cases  $is\_IfNode\ (kind\ g\ nid)$ )
    case True
    have  $nextNid\ g \notin ids\ g$ 
    using  $nextNidNotIn$  by (metis  $emptyE$ )
    then show ?thesis using  $assms$ 
    using  $replace\_node\_changeonly\ add\_node\_changeonly\ unfolding\ changeonly.simps$ 
    using  $True\ constantCondition.simps(1)\ is\_IfNode\_def$ 
    by (metis ( $no\_types, lifting$ )  $insert\_iff$ )
  next
    case False
    have  $g = g'$ 
    using  $constantConditionNoEffect$ 
    using  $False\ assms(2)$  by blast
    then show ?thesis by simp
  qed

```

```

lemma  $constantConditionNoIf$ :
  assumes  $\forall\ cond\ t\ f.\ kind\ g\ ifcond \neq IfNode\ cond\ t\ f$ 
  assumes  $g' = constantCondition\ val\ ifcond\ (kind\ g\ ifcond)\ g$ 
  shows  $\exists\ nid'. (g\ m\ p\ h \vdash ifcond \rightsquigarrow nid') \longleftrightarrow (g'\ m\ p\ h \vdash ifcond \rightsquigarrow nid')$ 
  proof -
    have  $g' = g$ 
    using  $assms(2)\ assms(1)$ 
    using  $constantConditionNoEffect$ 
    by (metis  $IRNode.collapse(11)$ )
    then show ?thesis by simp
  qed

```

```

lemma  $constantConditionValid$ :
  assumes  $kind\ g\ ifcond = IfNode\ cond\ t\ f$ 
  assumes  $[g, m, p] \vdash cond \mapsto v$ 
  assumes  $const = val\_to\_bool\ v$ 
  assumes  $g' = constantCondition\ const\ ifcond\ (kind\ g\ ifcond)\ g$ 
  shows  $\exists\ nid'. (g\ m\ p\ h \vdash ifcond \rightsquigarrow nid') \longleftrightarrow (g'\ m\ p\ h \vdash ifcond \rightsquigarrow nid')$ 
  proof (cases  $const$ )
    case True
    have  $ifstep: g, p \vdash (ifcond, m, h) \rightarrow (t, m, h)$ 
    by (meson  $IfNode\ True\ assms(1)\ assms(2)\ assms(3)\ encodeeval\_def$ )
    have  $ifstep': g', p \vdash (ifcond, m, h) \rightarrow (t, m, h)$ 
    using  $constantConditionTrue$ 
    using  $True\ assms(1)\ assms(4)$  by presburger
    from  $ifstep\ ifstep'$  show ?thesis
    using  $StutterStep$  by blast
  next
    case False

```

```

have ifstep:  $g, p \vdash (\text{ifcond}, m, h) \rightarrow (f, m, h)$ 
  by (meson IfNode False assms(1) assms(2) assms(3) encodeeval-def)
have ifstep':  $g', p \vdash (\text{ifcond}, m, h) \rightarrow (f, m, h)$ 
  using constantConditionFalse
  using False assms(1) assms(4) by presburger
from ifstep ifstep' show ?thesis
  using StutterStep by blast
qed

end

```

8.3 Stuttering

```

theory Stuttering
  imports
    Semantics.IRStepThms
begin

```

```

inductive stutter:: IRGraph  $\Rightarrow$  MapState  $\Rightarrow$  Params  $\Rightarrow$  FieldRefHeap  $\Rightarrow$  ID  $\Rightarrow$ 
  ID  $\Rightarrow$  bool (- - -  $\vdash$  -  $\rightsquigarrow$  - 55)
  for g m p h where

```

```

  StutterStep:
   $\llbracket g, p \vdash (nid, m, h) \rightarrow (nid', m, h) \rrbracket$ 
   $\implies g \ m \ p \ h \vdash nid \rightsquigarrow nid' \mid$ 

```

```

  Transitive:
   $\llbracket g, p \vdash (nid, m, h) \rightarrow (nid'', m, h);$ 
   $g \ m \ p \ h \vdash nid'' \rightsquigarrow nid' \rrbracket$ 
   $\implies g \ m \ p \ h \vdash nid \rightsquigarrow nid'$ 

```

```

lemma stuttering-successor:
  assumes  $(g, p \vdash (nid, m, h) \rightarrow (nid', m, h))$ 
  shows  $\{P'. (g \ m \ p \ h \vdash nid \rightsquigarrow P')\} = \{nid'\} \cup \{nid''. (g \ m \ p \ h \vdash nid' \rightsquigarrow nid'')\}$ 
proof -
  have nextin:  $nid' \in \{P'. (g \ m \ p \ h \vdash nid \rightsquigarrow P')\}$ 
  using assms StutterStep by blast
  have nextsubset:  $\{nid''. (g \ m \ p \ h \vdash nid' \rightsquigarrow nid'')\} \subseteq \{P'. (g \ m \ p \ h \vdash nid \rightsquigarrow P')\}$ 
  by (metis Collect-mono assms stutter.Transitive)
  have  $\forall n \in \{P'. (g \ m \ p \ h \vdash nid \rightsquigarrow P')\}. n = nid' \vee n \in \{nid''. (g \ m \ p \ h \vdash nid' \rightsquigarrow nid'')\}$ 
  using stepDet
  by (metis (no-types, lifting) Pair-inject assms mem-Collect-eq stutter.simps)
  then show ?thesis
  using insert-absorb mk-disjoint-insert nextin nextsubset by auto
qed

end

```

8.4 Evaluation Stamp Theorems

```
theory StampEvalThms
  imports Semantics.IRTreeEvalThms
begin
```

8.4.1 Evaluated Value Satisfies Stamps

```
lemma size32: size v = 32 for v :: 32 word
  using size-word.rep-eq
  using One-nat-def add.right-neutral add-Suc-right len-of-numeral-defs(2) len-of-numeral-defs(3)
  mult.right-neutral mult-Suc-right numeral-2-eq-2 numeral-Bit0
  by (smt (verit, del-ists) mult.commute)

lemma size64: size v = 64 for v :: 64 word
  using size-word.rep-eq
  using One-nat-def add.right-neutral add-Suc-right len-of-numeral-defs(2) len-of-numeral-defs(3)
  mult.right-neutral mult-Suc-right numeral-2-eq-2 numeral-Bit0
  by (smt (verit, del-ists) mult.commute)

lemma signed-int-bottom32:  $-(((2::int) \wedge 31)) \leq \text{sint } (v::\text{int32})$ 
  using sint-range-size size32
  by (smt (verit, ccfv-SIG) One-nat-def Suc-pred add-Suc add-Suc-right eval-nat-numeral(3)
  nat.inject numeral-2-eq-2 numeral-Bit0 numeral-Bit1 zero-less-numeral)

lemma signed-int-top32:  $(2 \wedge 31) - 1 \geq \text{sint } (v::\text{int32})$ 
  using sint-range-size size32
  by (smt (verit, ccfv-SIG) One-nat-def Suc-pred add-Suc add-Suc-right eval-nat-numeral(3)
  nat.inject numeral-2-eq-2 numeral-Bit0 numeral-Bit1 zero-less-numeral)

lemma lower-bounds-equiv32:  $-(((2::int) \wedge 31)) = (2::int) \wedge 32 \text{ div } 2 * - 1$ 
  by fastforce

lemma upper-bounds-equiv32:  $(2::int) \wedge 31 = (2::int) \wedge 32 \text{ div } 2$ 
  by simp

lemma bit-bounds-min32:  $((\text{fst } (\text{bit-bounds } 32))) \leq (\text{sint } (v::\text{int32}))$ 
  unfolding bit-bounds.simps fst-def using signed-int-bottom32 lower-bounds-equiv32
  by auto

lemma bit-bounds-max32:  $((\text{snd } (\text{bit-bounds } 32))) \geq (\text{sint } (v::\text{int32}))$ 
  unfolding bit-bounds.simps fst-def using signed-int-top32 upper-bounds-equiv32
  by auto

lemma signed-int-bottom64:  $-(((2::int) \wedge 63)) \leq \text{sint } (v::\text{int64})$ 
  using sint-range-size size64
  by (smt (verit, ccfv-SIG) One-nat-def Suc-pred add-Suc add-Suc-right eval-nat-numeral(3)
  nat.inject numeral-2-eq-2 numeral-Bit0 numeral-Bit1 zero-less-numeral)

lemma signed-int-top64:  $(2 \wedge 63) - 1 \geq \text{sint } (v::\text{int64})$ 
```

```

using sint-range-size size64
by (smt (verit, ccfv-SIG) One-nat-def Suc-pred add-Suc add-Suc-right eval-nat-numeral(3)
nat.inject numeral-2-eq-2 numeral-Bit0 numeral-Bit1 zero-less-numeral)

lemma lower-bounds-equiv64:  $-(((2::int) \wedge 63)) = (2::int) \wedge 64 \text{ div } 2 * - 1$ 
by fastforce

lemma upper-bounds-equiv64:  $(2::int) \wedge 63 = (2::int) \wedge 64 \text{ div } 2$ 
by simp

lemma bit-bounds-min64:  $((fst (bit-bounds 64))) \leq (sint (v::int64))$ 
unfolding bit-bounds.simps fst-def using signed-int-bottom64 lower-bounds-equiv64
by auto

lemma bit-bounds-max64:  $((snd (bit-bounds 64))) \geq (sint (v::int64))$ 
unfolding bit-bounds.simps fst-def using signed-int-top64 upper-bounds-equiv64
by auto

lemma unrestricted-32bit-always-valid:
  valid-value (IntVal32 v) (unrestricted-stamp (IntegerStamp 32 lo hi))
using valid-value.simps(1) bit-bounds-min32 bit-bounds-max32
using unrestricted-stamp.simps(2) by presburger

lemma unrestricted-64bit-always-valid:
  valid-value (IntVal64 v) (unrestricted-stamp (IntegerStamp 64 lo hi))
using valid-value.simps(2) bit-bounds-min64 bit-bounds-max64
using unrestricted-stamp.simps(2) by presburger

lemma unary-undef:  $val = \text{UndefVal} \implies \text{unary-eval } op \text{ } val = \text{UndefVal}$ 
by (cases op; auto)

lemma unary-obj:  $val = \text{ObjRef } x \implies \text{unary-eval } op \text{ } val = \text{UndefVal}$ 
by (cases op; auto)

lemma unary-eval-implies-valid-value:
  assumes  $[m,p] \vdash expr \mapsto val$ 
  assumes  $result = \text{unary-eval } op \text{ } val$ 
  assumes  $result \neq \text{UndefVal}$ 
  assumes valid-value val (stamp-expr expr)
  shows valid-value result (stamp-expr (UnaryExpr op expr))
proof –
  have is-IntVal:  $\exists x y. result = \text{IntVal32 } x \vee result = \text{IntVal64 } y$ 
    using asms(2,3) apply (cases op; auto; cases val; auto)
    applymetis
    bymetis
  then have is-IntegerStamp (stamp-expr expr)
    using asms(2,3,4) apply (cases (stamp-expr expr); auto)
    using valid-VoidStamp unary-undef apply simp
    using valid-VoidStamp unary-undef apply simp

```



```

    using valid-ObjStamp unary-obj apply fastforce
    using valid-ObjStamp unary-obj by fastforce
    then obtain b lo hi where stamp-expr-def: stamp-expr expr = (IntegerStamp b
lo hi)
    using is-IntegerStamp-def by auto
    then have stamp-expr (UnaryExpr op expr) = unrestricted-stamp (IntegerStamp
b lo hi)
    using stamp-expr.simps(1) stamp-unary.simps(1) by presburger
    from stamp-expr-def have bit32: b = 32  $\implies \exists x. \text{result} = \text{IntVal32 } x$ 
    using assms(2,3,4) by (cases op; auto; cases val; auto)
    from stamp-expr-def have bit64: b = 64  $\implies \exists x. \text{result} = \text{IntVal64 } x$ 
    using assms(2,3,4) by (cases op; auto; cases val; auto)

    show ?thesis using valid-value.simps(1,2)
    unrestricted-32bit-always-valid unrestricted-64bit-always-valid stamp-expr-def
    bit32 bit64
    by (metis <stamp-expr (UnaryExpr op expr) = unrestricted-stamp (IntegerStamp
b lo hi)> assms(4) valid32or64-both)
qed

```

```

lemma binary-undef: v1 = UndefVal  $\vee$  v2 = UndefVal  $\implies \text{bin-eval op v1 v2} =$ 
UndefVal
  by (cases op; auto)

```

```

lemma binary-obj: v1 = ObjRef x  $\vee$  v2 = ObjRef y  $\implies \text{bin-eval op v1 v2} =$ 
UndefVal
  by (cases op; auto)

```

```

lemma binary-eval-bits-equal:
  assumes result = bin-eval op val1 val2
  assumes result  $\neq$  UndefVal
  assumes valid-value val1 (IntegerStamp b1 lo1 hi1)
  assumes valid-value val2 (IntegerStamp b2 lo2 hi2)
  shows b1 = b2
  using assms
  by (cases op; cases val1; cases val2; auto)

```

```

lemma binary-eval-values:
  assumes  $\exists x y. \text{result} = \text{IntVal32 } x \vee \text{result} = \text{IntVal64 } y$ 
  assumes result = bin-eval op val1 val2
  shows  $\exists x32 x64 y32 y64. \text{val1} = \text{IntVal32 } x32 \wedge \text{val2} = \text{IntVal32 } y32 \vee \text{val1} =$ 
IntVal64 x64  $\wedge \text{val2} = \text{IntVal64 } y64$ 
  using assms apply (cases result)
  apply simp apply (cases op; cases val1; cases val2; auto)
  apply (cases op; cases val1; cases val2; auto) by auto+

```

```

lemma binary-eval-implies-valid-value:
  assumes [m,p]  $\vdash \text{expr1} \mapsto \text{val1}$ 
  assumes [m,p]  $\vdash \text{expr2} \mapsto \text{val2}$ 

```

```

assumes result = bin-eval op val1 val2
assumes result ≠ UndefVal
assumes valid-value val1 (stamp-expr expr1)
assumes valid-value val2 (stamp-expr expr2)
shows valid-value result (stamp-expr (BinaryExpr op expr1 expr2))
proof –
  have is-IntVal:  $\exists x y. \text{result} = \text{IntVal32 } x \vee \text{result} = \text{IntVal64 } y$ 
    using assms(1,2,3,4) apply (cases op; auto; cases val1; auto; cases val2; auto)
    by (meson Values.bool-to-val.elims)+
  then have expr1-intstamp: is-IntegerStamp (stamp-expr expr1)
    using assms(1,3,4,5) apply (cases (stamp-expr expr1); auto simp: valid-VoidStamp
binary-undef)
    using valid-ObjStamp binary-obj apply (metis assms(4))
    using valid-ObjStamp binary-obj by (metis assms(4))
  from is-IntVal have expr2-intstamp: is-IntegerStamp (stamp-expr expr2)
    using assms(2,3,4,6) apply (cases (stamp-expr expr2); auto simp: valid-VoidStamp
binary-undef)
    using valid-ObjStamp binary-obj apply (metis assms(4))
    using valid-ObjStamp binary-obj by (metis assms(4))
  from expr1-intstamp obtain b1 lo1 hi1 where stamp-expr1-def: stamp-expr expr1
= (IntegerStamp b1 lo1 hi1)
    using is-IntegerStamp-def by auto
  from expr2-intstamp obtain b2 lo2 hi2 where stamp-expr2-def: stamp-expr
expr2 = (IntegerStamp b2 lo2 hi2)
    using is-IntegerStamp-def by auto

  have  $\exists x32\ x64\ y32\ y64. (\text{val1} = \text{IntVal32 } x32 \wedge \text{val2} = \text{IntVal32 } y32) \vee (\text{val1}$ 
= IntVal64 x64  $\wedge \text{val2} = \text{IntVal64 } y64)$ 
    using is-IntVal assms(3) binary-eval-values
    by presburger

  have b1 = b2
    using assms(3,4,5,6) stamp-expr1-def stamp-expr2-def
    using binary-eval-bits-equal
    by auto
  then have stamp-def: stamp-expr (BinaryExpr op expr1 expr2) =
    (case op ∈ fixed-32 of True ⇒ unrestricted-stamp (IntegerStamp 32 lo1 hi1)|
False ⇒ unrestricted-stamp (IntegerStamp b1 lo1 hi1))
    using stamp-expr.simps(2) stamp-binary.simps(1)
    using stamp-expr1-def stamp-expr2-def by presburger
  from stamp-expr1-def have bit32: b1 = 32  $\implies \exists x. \text{result} = \text{IntVal32 } x$ 
    using assms apply (cases op; cases val1; cases val2; auto)
    by (meson Values.bool-to-val.elims)+
  from stamp-expr1-def have bit64: b1 = 64  $\wedge \text{op} \notin \text{fixed-32} \implies \exists x y. \text{result} =$ 
IntVal64 x
    using assms apply (cases op; cases val1; cases val2; simp)
    using fixed-32-def by auto+
  from stamp-expr1-def have fixed: op ∈ fixed-32  $\implies \exists x y. \text{result} = \text{IntVal32 } x$ 
    using assms unfolding fixed-32-def apply (cases op; auto)

```

```

apply (cases val1; cases val2; auto)
using bit32 apply fastforce
  apply (meson Values.bool-to-val.elims)
apply (cases val1; cases val2; auto)
using bit32 apply fastforce
  apply (meson Values.bool-to-val.elims)
  apply (cases val1; cases val2; auto)
using bit32 apply fastforce
by (meson Values.bool-to-val.elims)

show ?thesis apply (cases op ∈ fixed-32) defer using valid-value.simps(1,2)
  unrestricted-32bit-always-valid unrestricted-64bit-always-valid stamp-expr1-def
  bit32 bit64 stamp-def apply auto
  using ⟨∃ x32 x64 y32 y64. val1 = IntVal32 x32 ∧ val2 = IntVal32 y32 ∨ val1
= IntVal64 x64 ∧ val2 = IntVal64 y64⟩ assms(5) apply auto[1]
  using fixed by force
qed

lemma stamp-meet-is-valid:
  assumes valid-value val stamp1 ∨ valid-value val stamp2
  assumes meet stamp1 stamp2 ≠ IllegalStamp
  shows valid-value val (meet stamp1 stamp2)
  using assms proof (cases stamp1)
  case VoidStamp
  then show ?thesis
    by (metis Stamp.exhaust assms(1) assms(2) meet.simps(1) meet.simps(37)
meet.simps(44) meet.simps(51) meet.simps(58) meet.simps(65) meet.simps(66) meet.simps(67))
  next
  case (IntegerStamp b lo hi)
  obtain b2 lo2 hi2 where stamp2-def: stamp2 = IntegerStamp b2 lo2 hi2
  by (metis IntegerStamp assms(2) meet.simps(45) meet.simps(52) meet.simps(59)
meet.simps(6) meet.simps(65) meet.simps(66) meet.simps(67) unrestricted-stamp.cases)
  then have b = b2 using meet.simps(2) assms(2)
  by (metis IntegerStamp)
  then have meet-def: meet stamp1 stamp2 = (IntegerStamp b (min lo lo2) (max
hi hi2))
  by (simp add: IntegerStamp stamp2-def)
  then show ?thesis proof (cases b = 32)
  case True
  then obtain x where val-def: val = IntVal32 x
  using IntegerStamp assms(1) valid32
  using ⟨b = b2⟩ stamp2-def by blast
  have min: sint x ≥ min lo lo2
  using val-def
  using IntegerStamp assms(1)
  using stamp2-def by force
  have max: sint x ≤ max hi hi2
  using val-def
  using IntegerStamp assms(1)

```

```

    using stamp2-def by force
  from min max show ?thesis
    by (simp add: True meet-def val-def)
next
  case False
  then have bit64: b = 64
    using assms(1) IntegerStamp valid-value.simps
    valid32or64-both
    by (metis ⟨b = b2⟩ stamp2-def)
  then obtain x where val-def: val = IntVal64 x
    using IntegerStamp assms(1) valid64
    using ⟨b = b2⟩ stamp2-def by blast
  have min: sint x ≥ min lo lo2
    using val-def
    using IntegerStamp assms(1)
    using stamp2-def by force
  have max: sint x ≤ max hi hi2
    using val-def
    using IntegerStamp assms(1)
    using stamp2-def by force
  from min max show ?thesis
    by (simp add: bit64 meet-def val-def)
qed
next
  case (KlassPointerStamp x31 x32)
  then show ?thesis using assms valid-value.elims(2)
    by (metis meet.simps(14) valid-value.simps(21))
next
  case (MethodCountersPointerStamp x41 x42)
  then show ?thesis using assms valid-value.elims(2)
    by (metis meet.simps(39) valid-value.simps(22))
next
  case (MethodPointersStamp x51 x52)
  then show ?thesis using assms valid-value.elims(2)
    by (metis meet.simps(40) valid-value.simps(23))
next
  case (ObjectStamp x61 x62 x63 x64)
  then show ?thesis using assms
    using meet.simps(34) by blast
next
  case (RawPointerStamp x71 x72)
  then show ?thesis using assms
    using meet.simps(35) by blast
next
  case IllegalStamp
  then show ?thesis using assms
    using meet.simps(36) by blast
qed

```

```

lemma conditional-eval-implies-valid-value:
  assumes  $[m, p] \vdash \text{cond} \mapsto \text{condv}$ 
  assumes  $\text{expr} = (\text{if } \text{val-to-bool } \text{condv} \text{ then } \text{expr1} \text{ else } \text{expr2})$ 
  assumes  $[m, p] \vdash \text{expr} \mapsto \text{val}$ 
  assumes  $\text{val} \neq \text{UndefVal}$ 
  assumes valid-value  $\text{condv}$  (stamp-expr  $\text{cond}$ )
  assumes valid-value  $\text{val}$  (stamp-expr  $\text{expr}$ )
  assumes compatible (stamp-expr  $\text{expr1}$ ) (stamp-expr  $\text{expr2}$ )
  shows valid-value  $\text{val}$  (stamp-expr (ConditionalExpr  $\text{cond}$   $\text{expr1}$   $\text{expr2}$ ))
proof –
  have meet (stamp-expr  $\text{expr1}$ ) (stamp-expr  $\text{expr2}$ )  $\neq \text{IllegalStamp}$ 
    using assms
    by (metis Stamp.distinct(13) Stamp.distinct(25) compatible.elims(2) meet.simps(1)
meet.simps(2))
    then show ?thesis using stamp-meet-is-valid using stamp-expr.simps(6)
      using assms(2) assms(6) by presburger
qed

experiment begin
lemma stamp-implies-valid-value:
  assumes  $[m, p] \vdash \text{expr} \mapsto \text{val}$ 
  shows valid-value  $\text{val}$  (stamp-expr  $\text{expr}$ )
  using assms proof (induction  $\text{expr}$   $\text{val}$ )
case (UnaryExpr  $\text{expr}$   $\text{val}$   $\text{result}$   $\text{op}$ )
  then show ?case using unary-eval-implies-valid-value by simp
next
  case (BinaryExpr  $\text{expr1}$   $\text{val1}$   $\text{expr2}$   $\text{val2}$   $\text{result}$   $\text{op}$ )
  then show ?case using binary-eval-implies-valid-value by simp
next
  case (ConditionalExpr  $\text{cond}$   $\text{condv}$   $\text{expr}$   $\text{expr1}$   $\text{expr2}$   $\text{val}$ )
  then show ?case using conditional-eval-implies-valid-value sorry
next
  case (ParameterExpr  $x1$   $x2$ )
  then show ?case by auto
next
  case (LeafExpr  $x1$   $x2$ )
  then show ?case by auto
next
  case (ConstantExpr  $x$ )
  then show ?case by auto
qed

lemma value-range:
  assumes  $[m, p] \vdash e \mapsto v$ 
  shows  $v \in \{\text{val} . \text{valid-value } \text{val} \text{ (stamp-expr } e)\}$ 
  using assms sorry
end

```

lemma *upper-bound-32*:

assumes $val = IntVal32\ v$
assumes $\exists\ l\ h. s = (IntegerStamp\ 32\ l\ h)$
shows $valid_value\ val\ s \implies sint\ v \leq (stpi_upper\ s)$
using *assms* **by** *force*

lemma *upper-bound-64*:

assumes $val = IntVal64\ v$
assumes $\exists\ l\ h. s = (IntegerStamp\ 64\ l\ h)$
shows $valid_value\ val\ s \implies sint\ v \leq (stpi_upper\ s)$
using *assms* **by** *force*

lemma *lower-bound-32*:

assumes $val = IntVal32\ v$
assumes $\exists\ l\ h. s = (IntegerStamp\ 32\ l\ h)$
shows $valid_value\ val\ s \implies sint\ v \geq (stpi_lower\ s)$
using *assms* **by** *force*

lemma *lower-bound-64*:

assumes $val = IntVal64\ v$
assumes $\exists\ l\ h. s = (IntegerStamp\ 64\ l\ h)$
shows $valid_value\ val\ s \implies sint\ v \geq (stpi_lower\ s)$
using *assms*
by *force*

lemma *stamp-under-semantics*:

assumes $stamp_under\ (stamp_expr\ x)\ (stamp_expr\ y)$
assumes $[m, p] \vdash (BinaryExpr\ BinIntegerLessThan\ x\ y) \mapsto v$
assumes $xvalid: (\forall m\ p\ v. ([m, p] \vdash x \mapsto v) \longrightarrow valid_value\ v\ (stamp_expr\ x))$
assumes $yvalid: (\forall m\ p\ v. ([m, p] \vdash y \mapsto v) \longrightarrow valid_value\ v\ (stamp_expr\ y))$
shows $val_to_bool\ v$

proof –

obtain $xval$ **where** $xval_def: [m, p] \vdash x \mapsto xval$

using *assms*(2) **by** *blast*

obtain $yval$ **where** $yval_def: [m, p] \vdash y \mapsto yval$

using *assms*(2) **by** *blast*

have $is_IntVal32\ xval \vee is_IntVal64\ xval$

by (*metis* *BinaryExprE* *Value.exhaust-disc* *assms*(2) *bin-eval.simps*(11) *binary-obj* *binary-undef* *evalDet* *intval-less-than.simps*(9) *is-ObjRef-def* *is-ObjStr-def* *xval-def*)

have $is_IntVal32\ yval \vee is_IntVal64\ yval$

by (*metis* *BinaryExprE* *Value.exhaust-disc* *assms*(2) *bin-eval.simps*(11) *binary-obj* *binary-undef* *evalDet* *intval-less-than.simps*(16) *is-ObjRef-def* *is-ObjStr-def* *yval-def*)

have $is_IntVal32\ xval = is_IntVal32\ yval$

by (*metis* *BinaryExprE* *Value.collapse*(2) $\langle is_IntVal32\ xval \vee is_IntVal64\ xval \rangle$ $\langle is_IntVal32\ yval \vee is_IntVal64\ yval \rangle$ *assms*(2) *bin-eval.simps*(11) *evalDet* *intval-less-than.simps*(12) *intval-less-than.simps*(5) *is-IntVal32-def* *xval-def* *yval-def*)

```

have is-IntVal64 xval = is-IntVal64 yval
using  $\langle is-IntVal32\ xval = is-IntVal32\ yval \rangle \langle is-IntVal32\ xval \vee is-IntVal64\ xval \rangle$ 
 $\langle is-IntVal32\ yval \vee is-IntVal64\ yval \rangle$  by blast
have (intval-less-than xval yval)  $\neq$  UndefVal
using assms(2)
by (metis BinaryExprE bin-eval.simps(11) evalDet xval-def yval-def)
have is-IntVal32 xval  $\implies$  ( $\exists$  lo hi. stamp-expr x = IntegerStamp 32 lo hi)  $\wedge$ 
( $\exists$  lo hi. stamp-expr y = IntegerStamp 32 lo hi)
using assms(2) binary-eval-bits-equal valid-value.elims(2) xval-def
by (metis Value.distinct(9) Value.distinct-disc(9)  $\langle is-IntVal32\ yval \vee is-IntVal64\ yval \rangle$ 
 $\langle is-IntVal64\ xval = is-IntVal64\ yval \rangle$  is-IntVal32-def xvalid yval-def yvalid)
have is-IntVal64 xval  $\implies$  ( $\exists$  lo hi. stamp-expr x = IntegerStamp 64 lo hi)  $\wedge$ 
( $\exists$  lo hi. stamp-expr y = IntegerStamp 64 lo hi)
by (metis (full-types)  $\langle is-IntVal64\ xval = is-IntVal64\ yval \rangle$  is-IntVal64-def
stamprange valid-value.simps(2) xval-def xvalid yval-def yvalid)
have xvalid: valid-value xval (stamp-expr x)
using xvalid xval-def by auto
have yvalid: valid-value yval (stamp-expr y)
using yvalid yval-def by auto
{ assume c: is-IntVal32 xval
obtain xxval where x32: xval = IntVal32 xxval
using c is-IntVal32-def by blast
obtain yyval where y32: yval = IntVal32 yyval
using  $\langle is-IntVal32\ xval = is-IntVal32\ yval \rangle$  c is-IntVal32-def by auto
have xs:  $\exists$  lo hi. stamp-expr x = IntegerStamp 32 lo hi
by (simp add:  $\langle is-IntVal32\ xval \implies (\exists$  lo hi. stamp-expr x = IntegerStamp 32
lo hi)  $\wedge (\exists$  lo hi. stamp-expr y = IntegerStamp 32 lo hi) $\rangle$  c)
have ys:  $\exists$  lo hi. stamp-expr y = IntegerStamp 32 lo hi
using  $\langle is-IntVal32\ xval \implies (\exists$  lo hi. stamp-expr x = IntegerStamp 32 lo hi)
 $\wedge (\exists$  lo hi. stamp-expr y = IntegerStamp 32 lo hi) $\rangle$  c by blast
have sint xxval  $\leq$  stpi-upper (stamp-expr x)
using upper-bound-32 x32 xs xvalid by presburger
have stpi-lower (stamp-expr y)  $\leq$  sint yyval
using lower-bound-32 y32 ys yvalid by presburger
have stpi-upper (stamp-expr x) < stpi-lower (stamp-expr y)
using assms(1) unfolding stamp-under.simps
by auto
then have xxval <s yyval
using assms(1) unfolding stamp-under.simps
using  $\langle sint\ xxval \sqsubseteq stpi-upper\ (stamp-expr\ x) \rangle \langle stpi-lower\ (stamp-expr\ y) \sqsubseteq$ 
sint yyval $\rangle$  word-sless-alt by fastforce
then have (intval-less-than xval yval) = IntVal32 1
by (simp add: x32 y32)
}
note case32 = this
{ assume c: is-IntVal64 xval
obtain xxval where x64: xval = IntVal64 xxval
using c is-IntVal64-def by blast
obtain yyval where y64: yval = IntVal64 yyval

```

```

    using ‹is-IntVal64 xval = is-IntVal64 yval› c is-IntVal64-def by auto
  have xs:  $\exists$  lo hi. stamp-expr x = IntegerStamp 64 lo hi
    by (simp add: ‹is-IntVal64 xval  $\implies$  ( $\exists$  lo hi. stamp-expr x = IntegerStamp 64 lo hi)› c)
  have ys:  $\exists$  lo hi. stamp-expr y = IntegerStamp 64 lo hi
    using ‹is-IntVal64 xval  $\implies$  ( $\exists$  lo hi. stamp-expr x = IntegerStamp 64 lo hi)
   $\wedge$  ( $\exists$  lo hi. stamp-expr y = IntegerStamp 64 lo hi)› c by blast
  have sint xval  $\leq$  stpi-upper (stamp-expr x)
    using upper-bound-64 x64 xs xvalid by presburger
  have stpi-lower (stamp-expr y)  $\leq$  sint yyval
    using lower-bound-64 y64 ys yvalid by presburger
  have stpi-upper (stamp-expr x) < stpi-lower (stamp-expr y)
    using assms(1) unfolding stamp-under.simps
    by auto
  then have xval < s yyval
    using assms(1) unfolding stamp-under.simps
    using ‹sint xval  $\sqsubseteq$  stpi-upper (stamp-expr x)› ‹stpi-lower (stamp-expr y)  $\sqsubseteq$ 
sint yyval› word-sless-alt by fastforce
  then have (intval-less-than xval yval) = IntVal32 1
    by (simp add: x64 y64)
}
note case64 = this
have (intval-less-than xval yval) = IntVal32 1
  using ‹is-IntVal32 xval  $\vee$  is-IntVal64 xval› case32 case64 by fastforce
then show ?thesis
  by (metis BinaryExprE assms(2) bin-eval.simps(11) evalDet val-to-bool.simps(1)
xval-def yval-def zero-neq-one)
qed

```

lemma stamp-under-semantics-inversed:

```

  assumes stamp-under (stamp-expr y) (stamp-expr x)
  assumes [m, p]  $\vdash$  (BinaryExpr BinIntegerLessThan x y)  $\mapsto$  v
  assumes xvalid: ( $\forall$  m p v. ([m, p]  $\vdash$  x  $\mapsto$  v)  $\longrightarrow$  valid-value v (stamp-expr x))
  assumes yvalid: ( $\forall$  m p v. ([m, p]  $\vdash$  y  $\mapsto$  v)  $\longrightarrow$  valid-value v (stamp-expr y))
  shows  $\neg$ (val-to-bool v)
proof –
  obtain xval where xval-def: [m, p]  $\vdash$  x  $\mapsto$  xval
    using assms(2) by blast
  obtain yval where yval-def: [m, p]  $\vdash$  y  $\mapsto$  yval
    using assms(2) by blast
  have is-IntVal32 xval  $\vee$  is-IntVal64 xval
    by (metis is-IntVal32-def is-IntVal64-def xvalid valid-value.elims(2) xval-def)
  have is-IntVal32 yval  $\vee$  is-IntVal64 yval
    by (metis is-IntVal32-def is-IntVal64-def yvalid valid-value.elims(2) yval-def)
  have is-IntVal32 xval = is-IntVal32 yval
    by (metis BinaryExprE Value.collapse(2) ‹is-IntVal32 xval  $\vee$  is-IntVal64 xval›
‹is-IntVal32 yval  $\vee$  is-IntVal64 yval› assms(2) bin-eval.simps(11) evalDet int-
val-less-than.simps(12) intval-less-than.simps(5) is-IntVal32-def xval-def yval-def)
  have is-IntVal64 xval = is-IntVal64 yval

```



```

using ⟨is-IntVal32 xval = is-IntVal32 yval⟩ ⟨is-IntVal32 xval ∨ is-IntVal64 xval⟩
⟨is-IntVal32 yval ∨ is-IntVal64 yval⟩ by blast
have (intval-less-than xval yval) ≠ UndefVal
using assms(2)
by (metis BinaryExprE bin-eval.simps(11) evalDet xval-def yval-def)
have is-IntVal32 xval ⇒ ((∃ lo hi. stamp-expr x = IntegerStamp 32 lo hi) ∧
(∃ lo hi. stamp-expr y = IntegerStamp 32 lo hi))
by (smt (verit) BinaryExprE Value.discI(2) Value.distinct-disc(9) assms(2)
binary-eval-bits-equal xvalid yvalid valid-value.elims(2) xval-def)
have is-IntVal64 xval ⇒ ((∃ lo hi. stamp-expr x = IntegerStamp 64 lo hi) ∧
(∃ lo hi. stamp-expr y = IntegerStamp 64 lo hi))
by (smt (verit, best) BinaryExprE ⟨intval-less-than xval yval ≠ UndefVal⟩
assms(2) binary-eval-bits-equal intval-less-than.simps(5) is-IntVal64-def xvalid yvalid
valid-value.elims(2) yval-def)
have xvalid: valid-value xval (stamp-expr x)
using xvalid xval-def by auto
have yvalid: valid-value yval (stamp-expr y)
using yvalid yval-def by auto
{ assume c: is-IntVal32 xval
obtain xxval where x32: xval = IntVal32 xxval
using c is-IntVal32-def by blast
obtain yyval where y32: yval = IntVal32 yyval
using ⟨is-IntVal32 xval = is-IntVal32 yval⟩ c is-IntVal32-def by auto
have xs: ∃ lo hi. stamp-expr x = IntegerStamp 32 lo hi
by (simp add: ⟨is-IntVal32 xval ⇒ (∃ lo hi. stamp-expr x = IntegerStamp 32
lo hi) ∧ (∃ lo hi. stamp-expr y = IntegerStamp 32 lo hi)⟩ c)
have ys: ∃ lo hi. stamp-expr y = IntegerStamp 32 lo hi
using ⟨is-IntVal32 xval ⇒ (∃ lo hi. stamp-expr x = IntegerStamp 32 lo hi)
∧ (∃ lo hi. stamp-expr y = IntegerStamp 32 lo hi)⟩ c by blast
have sint yyval ≤ stpi-upper (stamp-expr y)
using y32 ys yvalid by force
have stpi-lower (stamp-expr x) ≤ sint xxval
using x32 xs xvalid by force
have stpi-upper (stamp-expr y) < stpi-lower (stamp-expr x)
using assms(1) unfolding stamp-under.simps
by auto
then have yyval < s xxval
using assms(1) unfolding stamp-under.simps
using ⟨sint yyval ⊆ stpi-upper (stamp-expr y)⟩ ⟨stpi-lower (stamp-expr x) ⊆
sint xxval⟩ word-sless-alt by fastforce
then have (intval-less-than xval yval) = IntVal32 0
using signed.less-not-sym x32 y32 by fastforce
}
note case32 = this
{ assume c: is-IntVal64 xval
obtain xxval where x64: xval = IntVal64 xxval
using c is-IntVal64-def by blast
obtain yyval where y64: yval = IntVal64 yyval
using ⟨is-IntVal64 xval = is-IntVal64 yval⟩ c is-IntVal64-def by auto

```

```

    have xs:  $\exists$  lo hi. stamp-expr x = IntegerStamp 64 lo hi
    by (simp add:  $\langle$ is-IntVal64 xval  $\implies$  ( $\exists$  lo hi. stamp-expr x = IntegerStamp 64 lo hi) $\rangle$  c)
    have ys:  $\exists$  lo hi. stamp-expr y = IntegerStamp 64 lo hi
    using  $\langle$ is-IntVal64 xval  $\implies$  ( $\exists$  lo hi. stamp-expr x = IntegerStamp 64 lo hi) $\rangle$ 
 $\wedge$  ( $\exists$  lo hi. stamp-expr y = IntegerStamp 64 lo hi) $\rangle$  c by blast
    have sint yyval  $\leq$  stpi-upper (stamp-expr y)
    using y64 ys yvalid by force
    have stpi-lower (stamp-expr x)  $\leq$  sint xxval
    using x64 xs xvalid by force
    have stpi-upper (stamp-expr y)  $<$  stpi-lower (stamp-expr x)
    using assms(1) unfolding stamp-under.simps
    by auto
    then have yyval  $<_s$  xxval
    using assms(1) unfolding stamp-under.simps
    using  $\langle$ sint yyval  $\sqsubseteq$  stpi-upper (stamp-expr y) $\rangle$   $\langle$ stpi-lower (stamp-expr x)  $\sqsubseteq$ 
sint xxval $\rangle$  word-sless-alt by fastforce
    then have (intval-less-than xval yval) = IntVal32 0
    using signed.less-imp-triv x64 y64 by fastforce
  }
  note case64 = this
  have (intval-less-than xval yval) = IntVal32 0
  using  $\langle$ is-IntVal32 xval  $\vee$  is-IntVal64 xval $\rangle$  case32 case64 by fastforce
  then show ?thesis
  by (metis BinaryExprE assms(2) bin-eval.simps(11) evalDet val-to-bool.simps(1)
xval-def yval-def)
qed

end

```

9 Optimization DSLs

```

theory Markup
  imports Semantics.IRTreeEval Snippets.Snipping
begin

```

```

datatype 'a Rewrite =
  Transform 'a 'a (-  $\mapsto$  - 10) |
  Conditional 'a 'a bool (-  $\mapsto$  - when - 70) |
  Sequential 'a Rewrite 'a Rewrite |
  Transitive 'a Rewrite

```

```

datatype 'a ExtraNotation =
  ConditionalNotation 'a 'a 'a (- ? - : -) |
  EqualsNotation 'a 'a (- eq -) |
  ConstantNotation 'a (const - 120) |
  TrueNotation (true) |
  FalseNotation (false)

```

ML-file *<markup.ML>*

ML *<*

```
structure IRExprTranslator : DSL-TRANSLATION =
struct
  fun markup DSL-Tokens.Add = @{term BinaryExpr} $ @{term BinAdd}
    | markup DSL-Tokens.Sub = @{term BinaryExpr} $ @{term BinSub}
    | markup DSL-Tokens.Mul = @{term BinaryExpr} $ @{term BinMul}
    | markup DSL-Tokens.And = @{term BinaryExpr} $ @{term BinAnd}
    | markup DSL-Tokens.Abs = @{term UnaryExpr} $ @{term UnaryAbs}
    | markup DSL-Tokens.Less = @{term BinaryExpr} $ @{term BinIntegerLessThan}
    | markup DSL-Tokens.Equals = @{term BinaryExpr} $ @{term BinIntegerEquals}
    | markup DSL-Tokens.Not = @{term UnaryExpr} $ @{term UnaryLogicNegation}
    | markup DSL-Tokens.Negate = @{term UnaryExpr} $ @{term UnaryNeg}
    | markup DSL-Tokens.LeftShift = @{term BinaryExpr} $ @{term BinLeftShift}
    | markup DSL-Tokens.RightShift = @{term BinaryExpr} $ @{term BinRightShift}
    | markup DSL-Tokens.UnsignedRightShift = @{term BinaryExpr} $ @{term Bin-
URightShift}
    | markup DSL-Tokens.Conditional = @{term ConditionalExpr}
    | markup DSL-Tokens.Constant = @{term ConstantExpr}
    | markup DSL-Tokens.TrueConstant = @{term ConstantExpr (IntVal32 1)}
    | markup DSL-Tokens.FalseConstant = @{term ConstantExpr (IntVal32 0)}
end

structure IntValTranslator : DSL-TRANSLATION =
struct
  fun markup DSL-Tokens.Add = @{term intval-add}
    | markup DSL-Tokens.Sub = @{term intval-sub}
    | markup DSL-Tokens.Mul = @{term intval-mul}
    | markup DSL-Tokens.And = @{term intval-and}
    | markup DSL-Tokens.Abs = @{term intval-abs}
    | markup DSL-Tokens.Less = @{term intval-less-than}
    | markup DSL-Tokens.Equals = @{term intval-equals}
    | markup DSL-Tokens.Not = @{term intval-logic-negation}
    | markup DSL-Tokens.Negate = @{term intval-negate}
    | markup DSL-Tokens.LeftShift = @{term intval-left-shift}
    | markup DSL-Tokens.RightShift = @{term intval-right-shift}
    | markup DSL-Tokens.UnsignedRightShift = @{term intval-uright-shift}
    | markup DSL-Tokens.Conditional = @{term intval-conditional}
    | markup DSL-Tokens.Constant = @{term IntVal32}
    | markup DSL-Tokens.TrueConstant = @{term IntVal32 1}
    | markup DSL-Tokens.FalseConstant = @{term IntVal32 0}
end

structure IRExprMarkup = DSL-Markup(IRExprTranslator);
structure IntValMarkup = DSL-Markup(IntValTranslator);
>
```

ir expression translation

```
syntax -expandExpr :: term ⇒ term (exp[-])
parse-translation < [( @ {syntax-const -expandExpr} , IRExprMarkup.markup-expr)] >
```

value expression translation

```
syntax -expandIntVal :: term ⇒ term (val[-])
parse-translation < [( @ {syntax-const -expandIntVal} , IntValMarkup.markup-expr)] >
```

ir expression example

```
value exp[(e1 < e2) ? e1 : e2]

ConditionalExpr (BinaryExpr BinIntegerLessThan e1 e2) e1 e2
```

value expression example

```
value val[(e1 < e2) ? e1 : e2]

intval-conditional (intval-less-than e1 e2) e1 e2
```

```
value exp[((e1 - e2) + (const (IntVal32 0)) + e2) ↦ e1 when True]
value val[((e1 - e2) + (const 0) + e2) ↦ e1 when True]
```

```
end
theory Phase
  imports Main
begin
```

```
ML-file map.ML
ML-file phase.ML
```

```
end
```

9.1 Canonicalization DSL

```
theory Canonicalization
  imports
    Markup
    Phase
  keywords
    phase :: thy-decl and
    terminating :: quasi-command and
    print-phases :: diag and
    optimization :: thy-goal-defn
```

begin

ML <

```
datatype 'a Rewrite =  
  Transform of 'a * 'a |  
  Conditional of 'a * 'a * term |  
  Sequential of 'a Rewrite * 'a Rewrite |  
  Transitive of 'a Rewrite
```

```
type rewrite = {name: string, rewrite: term Rewrite}
```

```
structure RewriteRule : Rule =  
struct  
  type T = rewrite;
```

```
fun pretty-rewrite ctxt (Transform (from, to)) =  
  Pretty.block [  
    Syntax.pretty-term ctxt from,  
    Pretty.str  $\mapsto$  ,  
    Syntax.pretty-term ctxt to  
  ]  
| pretty-rewrite ctxt (Conditional (from, to, cond)) =  
  Pretty.block [  
    Syntax.pretty-term ctxt from,  
    Pretty.str  $\mapsto$  ,  
    Syntax.pretty-term ctxt to,  
    Pretty.str when ,  
    Syntax.pretty-term ctxt cond  
  ]  
| pretty-rewrite - - = Pretty.str not implemented
```

```
fun pretty ctxt t =  
  Pretty.block [  
    Pretty.str ((#name t) ^: ),  
    pretty-rewrite ctxt (#rewrite t)  
  ]  
end
```

```
structure RewritePhase = DSL-Phase(RewriteRule);
```

```
val - =  
  Outer-Syntax.command command-keyword <phase> enter an optimization phase  
  (Parse.binding --| Parse.$$$ terminating -- Parse.const --| Parse.begin  
   >> (Toplevel.begin-main-target true o RewritePhase.setup));
```

```
fun print-phases ctxt =  
  let  
    val thy = Proof-Context.theory-of ctxt;  
    fun print phase = RewritePhase.pretty phase ctxt
```

```

in
  map print (RewritePhase.phases thy)
end

fun print-optimizations thy =
  print-phases thy |> Pretty.writeln-chunks

val - =
  Outer-Syntax.command command-keyword ⟨print-phases⟩
  print debug information for optimizations
  (Scan.succeed
    (Toplevel.keep (print-optimizations o Toplevel.context-of)));
  >

```

ML-file *rewrites.ML*

```

fun rewrite-preservation :: IRExp Rewrite ⇒ bool where
  rewrite-preservation (Transform x y) = (y ≤ x) |
  rewrite-preservation (Conditional x y cond) = (cond ⟶ (y ≤ x)) |
  rewrite-preservation (Sequential x y) = (rewrite-preservation x ∧ rewrite-preservation
y) |
  rewrite-preservation (Transitive x) = rewrite-preservation x

fun rewrite-termination :: IRExp Rewrite ⇒ (IRExp ⇒ nat) ⇒ bool where
  rewrite-termination (Transform x y) trm = (trm x > trm y) |
  rewrite-termination (Conditional x y cond) trm = (cond ⟶ (trm x > trm y)) |
  rewrite-termination (Sequential x y) trm = (rewrite-termination x trm ∧ rewrite-termination
y trm) |
  rewrite-termination (Transitive x) trm = rewrite-termination x trm

fun intval :: Value Rewrite ⇒ bool where
  intval (Transform x y) = (x ≠ UndefVal ∧ y ≠ UndefVal ⟶ x = y) |
  intval (Conditional x y cond) = (cond ⟶ (x = y)) |
  intval (Sequential x y) = (intval x ∧ intval y) |
  intval (Transitive x) = intval x

```

```

ML <
structure System : RewriteSystem =
struct
  val preservation = @{const rewrite-preservation};
  val termination = @{const rewrite-termination};
  val intval = @{const intval};
end

```

```

structure DSL = DSL-Rewrites(System);

```

```

val - =
  Outer-Syntax.local-theory-to-proof command-keyword ⟨optimization⟩
  define an optimization and open proof obligation

```

```

    (Parse-Spec.thm-name : -- Parse.term
      >> DSL.rewrite-cmd);
  >

end

```

10 Canonicalization Phase

```

theory Common
  imports
    OptimizationDSL.Canonicalization
    HOL-Eisbach.Eisbach
begin

fun size :: IRExpr ⇒ nat where
  size (UnaryExpr op e) = (size e) + 1 |
  size (BinaryExpr BinAdd x y) = (size x) + ((size y) * 2) |
  size (BinaryExpr op x y) = (size x) + (size y) |
  size (ConditionalExpr cond t f) = (size cond) + (size t) + (size f) + 2 |
  size (ConstantExpr c) = 1 |
  size (ParameterExpr ind s) = 2 |
  size (LeafExpr nid s) = 2 |
  size (ConstantVar c) = 2 |
  size (VariableExpr x s) = 2

method unfold-optimization =
  (unfold rewrite-preservation.simps, unfold rewrite-termination.simps,
   unfold intval.simps,
   rule conjE, simp, simp del: le-expr-def)
| (unfold rewrite-preservation.simps, unfold rewrite-termination.simps,
   rule conjE, simp, simp del: le-expr-def)

end

```

10.1 Conditional Expression

```

theory ConditionalPhase
  imports
    Common
    Proofs.StampEvalThms
begin

phase Conditional
  terminating size
begin

lemma negates: is-IntVal32 e ∨ is-IntVal64 e ⇒ val-to-bool (val[e]) ≡ ¬(val-to-bool
(val[¬e]))
  by (smt (verit, best) Value.disc(1) Value.disc(10) Value.disc(4) Value.disc(5))

```

Value.disc(6) Value.disc(9) intval-logic-negation.elims val-to-bool.simps(1) val-to-bool.simps(2)
zero-neq-one)

optimization *negate-condition*: $((\neg e) \text{ ? } x : y) \mapsto (e \text{ ? } y : x)$
 apply *unfold-optimization* apply *simp* using *negates*
 using *ConditionalExprE UnaryExprE intval-logic-negation.elims unary-eval.simps(4)*
val-to-bool.simps(1) val-to-bool.simps(2) zero-neq-one
 apply (*smt (verit) ConditionalExpr*)
 unfolding *size.simps* by *simp*

optimization *const-true*: $(\text{true} \text{ ? } x : y) \mapsto x$
 apply *unfold-optimization*
 apply *force*
 unfolding *size.simps* by *simp*

optimization *const-false*: $(\text{false} \text{ ? } x : y) \mapsto y$
 apply *unfold-optimization*
 apply *force*
 unfolding *size.simps* by *simp*

optimization *equal-branches*: $(e \text{ ? } x : x) \mapsto x$
 apply *unfold-optimization*
 apply *force*
 unfolding *size.simps* by *auto*

definition *wff-stamps* :: *bool* **where**
wff-stamps = $(\forall m \ p \ \text{expr} \ \text{val} . ([m, p] \vdash \text{expr} \mapsto \text{val}) \longrightarrow \text{valid-value} \ \text{val} \ (\text{stamp-expr} \ \text{expr}))$

definition *wf-stamp* :: *IRExpr* \Rightarrow *bool* **where**
wf-stamp *e* = $(\forall m \ p \ v . ([m, p] \vdash e \mapsto v) \longrightarrow \text{valid-value} \ v \ (\text{stamp-expr} \ e))$

optimization *condition-bounds-x*: $((x < y) \text{ ? } x : y) \mapsto x$
 when (*stamp-under (stamp-expr x) (stamp-expr y) \wedge wf-stamp x \wedge wf-stamp y*)
 apply *unfold-optimization*
 using *stamp-under-semantics*
 using *wf-stamp-def*
 apply (*smt (verit, best) ConditionalExprE le-expr-def stamp-under.simps*)
 unfolding *size.simps* by *simp*

optimization *condition-bounds-y*: $((x < y) \text{ ? } x : y) \mapsto y$
 when (*stamp-under (stamp-expr y) (stamp-expr x) \wedge wf-stamp x \wedge wf-stamp y*)
 apply *unfold-optimization*
 using *stamp-under-semantics-inversed*
 using *wf-stamp-def*
 apply (*smt (verit, best) ConditionalExprE le-expr-def stamp-under.simps*)
 unfolding *size.simps* by *simp*


```

optimization b[intval]: ((x eq y) ? x : y)  $\mapsto$  y
  apply unfold-optimization
    apply (smt (z3) bool-to-val.simps(2) intval-equals.elims val-to-bool.simps(1)
val-to-bool.simps(3))
    unfolding intval.simps
    apply (smt (z3) BinaryExprE ConditionalExprE Value.inject(1) Value.inject(2)
bin-eval.simps(10) bool-to-val.simps(2) evalDet intval-equals.simps(1) intval-equals.simps(10)
intval-equals.simps(12) intval-equals.simps(15) intval-equals.simps(16) intval-equals.simps(2)
intval-equals.simps(5) intval-equals.simps(8) intval-equals.simps(9) le-expr-def val-to-bool.cases
val-to-bool.elims(2))
    unfolding size.simps by auto

end

end

```

11 Conditional Elimination Phase

```

theory ConditionalElimination
  imports
    Semantics.IRGraphFrames
    Proofs.Stuttering
    Proofs.Rewrites
    Proofs.Bisimulation
begin

```

11.1 Individual Elimination Rules

We introduce a *TriState* as in the Graal compiler to represent when static analysis can tell us information about the value of a boolean expression. Unknown = No information can be inferred KnownTrue/KnownFalse = We can infer the expression will always be true or false.

```

datatype TriState = Unknown | KnownTrue | KnownFalse

```

The *implies* relation corresponds to the *LogicNode.implies* method from the compiler which attempts to infer when one logic nodes value can be inferred from a known logic node.

```

inductive implies :: IRGraph  $\Rightarrow$  IRNode  $\Rightarrow$  IRNode  $\Rightarrow$  TriState  $\Rightarrow$  bool
  (-  $\vdash$  - & -  $\hookrightarrow$  -) for g where
    eq-imp-less:
      g  $\vdash$  (IntegerEqualsNode x y) & (IntegerLessThanNode x y)  $\hookrightarrow$  KnownFalse |
    eq-imp-less-rev:
      g  $\vdash$  (IntegerEqualsNode x y) & (IntegerLessThanNode y x)  $\hookrightarrow$  KnownFalse |
    less-imp-rev-less:
      g  $\vdash$  (IntegerLessThanNode x y) & (IntegerLessThanNode y x)  $\hookrightarrow$  KnownFalse |
    less-imp-not-eq:

```

$g \vdash (\text{IntegerLessThanNode } x \ y) \ \& \ (\text{IntegerEqualsNode } x \ y) \hookrightarrow \text{KnownFalse} \mid$
less-imp-not-eq-rev:
 $g \vdash (\text{IntegerLessThanNode } x \ y) \ \& \ (\text{IntegerEqualsNode } y \ x) \hookrightarrow \text{KnownFalse} \mid$

x-imp-x:
 $g \vdash x \ \& \ x \hookrightarrow \text{KnownTrue} \mid$

negate-false:
 $\llbracket g \vdash x \ \& \ (\text{kind } g \ y) \hookrightarrow \text{KnownTrue} \rrbracket \implies g \vdash x \ \& \ (\text{LogicNegationNode } y) \hookrightarrow \text{KnownFalse} \mid$
negate-true:
 $\llbracket g \vdash x \ \& \ (\text{kind } g \ y) \hookrightarrow \text{KnownFalse} \rrbracket \implies g \vdash x \ \& \ (\text{LogicNegationNode } y) \hookrightarrow \text{KnownTrue}$

Total relation over partial implies relation

inductive *condition-implies* :: $\text{IRGraph} \Rightarrow \text{IRNode} \Rightarrow \text{IRNode} \Rightarrow \text{TriState} \Rightarrow \text{bool}$
 $(- \vdash - \ \& \ - \hookrightarrow -)$ **for** g **where**
 $\llbracket \neg(g \vdash a \ \& \ b \hookrightarrow \text{imp}) \rrbracket \implies (g \vdash a \ \& \ b \hookrightarrow \text{Unknown}) \mid$
 $\llbracket (g \vdash a \ \& \ b \hookrightarrow \text{imp}) \rrbracket \implies (g \vdash a \ \& \ b \hookrightarrow \text{imp})$

inductive *implies-tree* :: $\text{IRExpr} \Rightarrow \text{IRExpr} \Rightarrow \text{bool} \Rightarrow \text{bool}$
 $(- \ \& \ - \hookrightarrow -)$ **where**
eq-imp-less:
 $(\text{BinaryExpr } \text{BinIntegerEquals } x \ y) \ \& \ (\text{BinaryExpr } \text{BinIntegerLessThan } x \ y) \hookrightarrow \text{False} \mid$
eq-imp-less-rev:
 $(\text{BinaryExpr } \text{BinIntegerEquals } x \ y) \ \& \ (\text{BinaryExpr } \text{BinIntegerLessThan } y \ x) \hookrightarrow \text{False} \mid$
less-imp-rev-less:
 $(\text{BinaryExpr } \text{BinIntegerLessThan } x \ y) \ \& \ (\text{BinaryExpr } \text{BinIntegerLessThan } y \ x) \hookrightarrow \text{False} \mid$
less-imp-not-eq:
 $(\text{BinaryExpr } \text{BinIntegerLessThan } x \ y) \ \& \ (\text{BinaryExpr } \text{BinIntegerEquals } x \ y) \hookrightarrow \text{False} \mid$
less-imp-not-eq-rev:
 $(\text{BinaryExpr } \text{BinIntegerLessThan } x \ y) \ \& \ (\text{BinaryExpr } \text{BinIntegerEquals } y \ x) \hookrightarrow \text{False} \mid$

x-imp-x:
 $x \ \& \ x \hookrightarrow \text{True} \mid$

negate-false:
 $\llbracket x \ \& \ y \hookrightarrow \text{True} \rrbracket \implies x \ \& \ (\text{UnaryExpr } \text{UnaryLogicNegation } y) \hookrightarrow \text{False} \mid$
negate-true:
 $\llbracket x \ \& \ y \hookrightarrow \text{False} \rrbracket \implies x \ \& \ (\text{UnaryExpr } \text{UnaryLogicNegation } y) \hookrightarrow \text{True}$

Proofs that the implies relation is correct with respect to the existing eval-

uation semantics.

experiment begin

lemma *logic-negate-type*:

assumes $[m, p] \vdash \text{UnaryExpr } \text{UnaryLogicNegation } x \mapsto v$

assumes $v \neq \text{UndefVal}$

shows $\exists v2. [m, p] \vdash x \mapsto \text{IntVal32 } v2$

proof –

obtain ve **where** $ve: [m, p] \vdash x \mapsto ve$

using *assms(1)* **by** *blast*

then have $[m, p] \vdash \text{UnaryExpr } \text{UnaryLogicNegation } x \mapsto \text{unary-eval } \text{UnaryLogicNegation } ve$

by (*metis* *UnaryExprE* *assms(1)* *evalDet*)

then show *?thesis* **using** *assms* *unary-eval.elims* *evalDet* *ve* *IRUnaryOp.distinct*

sorry

qed

lemma *logic-negation-relation-tree*:

assumes $[m, p] \vdash y \mapsto val$

assumes $[m, p] \vdash \text{UnaryExpr } \text{UnaryLogicNegation } y \mapsto invval$

assumes $intval \neq \text{UndefVal}$

shows $\text{val-to-bool } val \longleftrightarrow \neg(\text{val-to-bool } invval)$

proof –

obtain v **where** $invval = \text{unary-eval } \text{UnaryLogicNegation } v$

using *assms(2)* **by** *blast*

then have $[m, p] \vdash y \mapsto v$ **using** *UnaryExprE* *assms(1,2)* **sorry**

then show *?thesis* **sorry**

qed

lemma *logic-negation-relation*:

assumes $[g, m, p] \vdash y \mapsto val$

assumes $\text{kind } g \text{ neg} = \text{LogicNegationNode } y$

assumes $[g, m, p] \vdash \text{neg} \mapsto invval$

assumes $intval \neq \text{UndefVal}$

shows $\text{val-to-bool } val \longleftrightarrow \neg(\text{val-to-bool } invval)$

proof –

obtain $yencode$ **where** $g \vdash y \simeq yencode$

using *assms(1)* *encodeeval-def* **by** *auto*

then have $g \vdash \text{neg} \simeq \text{UnaryExpr } \text{UnaryLogicNegation } yencode$

using *rep.intros(7)* *assms(2)* **by** *simp*

then have $[m, p] \vdash \text{UnaryExpr } \text{UnaryLogicNegation } yencode \mapsto invval$

using *assms(3)* *encodeeval-def*

by (*metis* *repDet*)

obtain $v1$ **where** $[g, m, p] \vdash y \mapsto \text{IntVal32 } v1$

using *assms(1,2,3,4)* **using** *logic-negate-type* **sorry**

have $invval = \text{bool-to-val } (\neg(\text{val-to-bool } val))$

using *assms(1,2,3)* *evalDet* *unary-eval.simps(4)*

by (*smt* (*verit*, *ccfv-SIG*) *UnaryExprE* $\langle [m, p] \vdash \text{UnaryExpr } \text{UnaryLogicNegation } yencode \mapsto invval \rangle \langle g \vdash y \simeq yencode \rangle \text{bool-to-val.simps(1)} \text{bool-to-val.simps(2)} \text{en-}$

```

codeeval-def intval-logic-negation.simps(1) logic-negate-type repDet val-to-bool.simps(1))
  have val-to-bool invval  $\longleftrightarrow \neg(\text{val-to-bool val})$ 
    using  $\langle \text{invval} = \text{bool-to-val } (\neg \text{ val-to-bool val}) \rangle$  by force
  then show ?thesis
    by simp
qed
end

```

lemma *implies-valid*:

```

  assumes  $x \ \& \ y \hookrightarrow \text{imp}$ 
  assumes  $[m, p] \vdash x \mapsto v1$ 
  assumes  $[m, p] \vdash y \mapsto v2$ 
  assumes  $v1 \neq \text{UndefVal} \wedge v2 \neq \text{UndefVal}$ 
  shows  $(\text{imp} \longrightarrow (\text{val-to-bool } v1 \longrightarrow \text{val-to-bool } v2)) \wedge$ 
     $(\neg \text{imp} \longrightarrow (\text{val-to-bool } v1 \longrightarrow \neg(\text{val-to-bool } v2)))$ 
    (is  $(?TP \longrightarrow ?TC) \wedge (?FP \longrightarrow ?FC)$ )
  apply (intro conjI; rule impI)
proof -
  assume KnownTrue: ?TP
  show ?TC
  using assms(1) KnownTrue assms(2-) proof (induct x y imp rule: implies-tree.induct)
    case (eq-imp-less x y)
    then show ?case by simp
  next
    case (eq-imp-less-rev x y)
    then show ?case by simp
  next
    case (less-imp-rev-less x y)
    then show ?case by simp
  next
    case (less-imp-not-eq x y)
    then show ?case by simp
  next
    case (less-imp-not-eq-rev x y)
    then show ?case by simp
  next
    case (x-imp-x)
    then show ?case
      by (metis evalDet)
  next
    case (negate-false x1)
    then show ?case using evalDet
      using assms(2,3) by blast
  next
    case (negate-true y)
    then show ?case
      sorry
  qed
next

```

```

assume KnownFalse: ?FP
show ?FC using assms KnownFalse proof (induct x y imp rule: implies-tree.induct)
  case (eq-imp-less x y)
  obtain xval where xval: [m, p] ⊢ x ↦ xval
    using eq-imp-less(1) eq-imp-less.prem(3)
    by blast
  then obtain yval where yval: [m, p] ⊢ y ↦ yval
    using eq-imp-less.prem(3)
    using eq-imp-less.prem(2) by blast
  have egeval: [m, p] ⊢ (BinaryExpr BinIntegerEquals x y) ↦ intval-equals xval
yval
    using xval yval evaltree.BinaryExpr
    by (metis BinaryExprE bin-eval.simp(10) eq-imp-less.prem(1) evalDet)
  have lesseval: [m, p] ⊢ (BinaryExpr BinIntegerLessThan x y) ↦ intval-less-than
xval yval
    using xval yval evaltree.BinaryExpr
    by (metis BinaryExprE bin-eval.simp(11) eq-imp-less.prem(2) evalDet)
  have val-to-bool (intval-equals xval yval) ⟶ ¬(val-to-bool (intval-less-than xval
yval))
    using assms(4) apply (cases xval; cases yval; auto)
    apply (metis (full-types) val-to-bool.simp(1) Values.bool-to-val.simp(2)
signed.less-irrefl)
  by (metis (mono-tags) val-to-bool.simp(1) Values.bool-to-val.elims signed.order.strict-implies-not-eq)
  then show ?case
    using egeval lesseval
    by (metis eq-imp-less.prem(1) eq-imp-less.prem(2) evalDet)
next
  case (eq-imp-less-rev x y)
  obtain xval where xval: [m, p] ⊢ x ↦ xval
    using eq-imp-less-rev.prem(3)
    using eq-imp-less-rev.prem(2) by blast
  obtain yval where yval: [m, p] ⊢ y ↦ yval
    using eq-imp-less-rev.prem(3)
    using eq-imp-less-rev.prem(2) by blast
  have egeval: [m, p] ⊢ (BinaryExpr BinIntegerEquals x y) ↦ intval-equals xval
yval
    using xval yval evaltree.BinaryExpr
    by (metis BinaryExprE bin-eval.simp(10) eq-imp-less-rev.prem(1) evalDet)
  have lesseval: [m, p] ⊢ (BinaryExpr BinIntegerLessThan y x) ↦ intval-less-than
yval xval
    using xval yval evaltree.BinaryExpr
    by (metis BinaryExprE bin-eval.simp(11) eq-imp-less-rev.prem(2) evalDet)
  have val-to-bool (intval-equals xval yval) ⟶ ¬(val-to-bool (intval-less-than yval
xval))
    using assms(4) apply (cases xval; cases yval; auto)
    apply (metis (full-types) val-to-bool.simp(1) Values.bool-to-val.simp(2)
signed.less-irrefl)
  by (metis (full-types) val-to-bool.simp(1) Values.bool-to-val.elims signed.order.strict-implies-not-eq)
  then show ?case

```

```

    using egeval lesseval
    by (metis eq-imp-less-rev.prem(1) eq-imp-less-rev.prem(2) evalDet)
next
case (less-imp-rev-less x y)
obtain xval where xval: [m, p] ⊢ x ↦ xval
    using less-imp-rev-less.prem(3)
    using less-imp-rev-less.prem(2) by blast
obtain yval where yval: [m, p] ⊢ y ↦ yval
    using less-imp-rev-less.prem(3)
    using less-imp-rev-less.prem(2) by blast
have lesseval: [m, p] ⊢ (BinaryExpr BinIntegerLessThan x y) ↦ intval-less-than
xval yval
    using xval yval evaltree.BinaryExpr
    by (metis BinaryExprE bin-eval.simp(11) evalDet less-imp-rev-less.prem(1))
    have revlesseval: [m, p] ⊢ (BinaryExpr BinIntegerLessThan y x) ↦ int-
val-less-than yval xval
        using xval yval evaltree.BinaryExpr
        by (metis BinaryExprE bin-eval.simp(11) evalDet less-imp-rev-less.prem(2))
    have val-to-bool (intval-less-than xval yval) ⟶ ¬(val-to-bool (intval-less-than
yval xval))
        using assms(4) apply (cases xval; cases yval; auto)
    apply (metis val-to-bool.simp(1) Values.bool-to-val.elims signed.not-less-iff-gr-or-eq)
        by (metis val-to-bool.simp(1) Values.bool-to-val.elims signed.less-asym')
    then show ?case
    by (metis evalDet less-imp-rev-less.prem(1) less-imp-rev-less.prem(2) lesseval
revlesseval)
next
case (less-imp-not-eq x y)
obtain xval where xval: [m, p] ⊢ x ↦ xval
    using less-imp-not-eq.prem(3)
    using less-imp-not-eq.prem(1) by blast
obtain yval where yval: [m, p] ⊢ y ↦ yval
    using less-imp-not-eq.prem(3)
    using less-imp-not-eq.prem(1) by blast
have egeval: [m, p] ⊢ (BinaryExpr BinIntegerEquals x y) ↦ intval-equals xval
yval
    using xval yval evaltree.BinaryExpr
    by (metis BinaryExprE bin-eval.simp(10) evalDet less-imp-not-eq.prem(2))
    have lesseval: [m, p] ⊢ (BinaryExpr BinIntegerLessThan x y) ↦ intval-less-than
xval yval
        using xval yval evaltree.BinaryExpr
        by (metis BinaryExprE bin-eval.simp(11) evalDet less-imp-not-eq.prem(1))
    have val-to-bool (intval-less-than xval yval) ⟶ ¬(val-to-bool (intval-equals xval
yval))
        using assms(4) apply (cases xval; cases yval; auto)
    apply (metis (full-types) bool-to-val.simp(2) signed.less-imp-not-eq val-to-bool.simp(1))
    by (metis (full-types) bool-to-val.simp(2) signed.less-imp-not-eq2 val-to-bool.simp(1))
    then show ?case
    by (metis egeval evalDet less-imp-not-eq.prem(1) less-imp-not-eq.prem(2))

```

```

lesseval)
next
  case (less-imp-not-eq-rev x y)
  obtain xval where xval: [m, p] ⊢ x ↦ xval
  using less-imp-not-eq-rev.prem(3)
  using less-imp-not-eq-rev.prem(1) by blast
  obtain yval where yval: [m, p] ⊢ y ↦ yval
  using less-imp-not-eq-rev.prem(3)
  using less-imp-not-eq-rev.prem(1) by blast
  have egeval: [m, p] ⊢ (BinaryExpr BinIntegerEquals y x) ↦ intval-equals yval
xval
  using xval yval evaltree.BinaryExpr
  by (metis BinaryExprE bin-eval.simp(10) evalDet less-imp-not-eq-rev.prem(2))
  have lesseval: [m, p] ⊢ (BinaryExpr BinIntegerLessThan x y) ↦ intval-less-than
xval yval
  using xval yval evaltree.BinaryExpr
  by (metis BinaryExprE bin-eval.simp(11) evalDet less-imp-not-eq-rev.prem(1))
  have val-to-bool (intval-less-than xval yval) ⟶ ¬(val-to-bool (intval-equals yval
xval))
  using assms(4) apply (cases xval; cases yval; auto)
  apply (metis (full-types) bool-to-val.simp(2) signed.less-imp-not-eq2 val-to-bool.simp(1))
  by (metis (full-types, opaque-lifting) val-to-bool.simp(1) Values.bool-to-val.elims
signed.dual-order.strict-implies-not-eq)
  then show ?case
  by (metis egeval evalDet less-imp-not-eq-rev.prem(1) less-imp-not-eq-rev.prem(2))
lesseval)
next
  case (x-imp-x x1)
  then show ?case by simp
next
  case (negate-false x y)
  then show ?case sorry
next
  case (negate-true x1)
  then show ?case by simp
qed
qed

lemma implies-true-valid:
  assumes x & y ⟷ imp
  assumes imp
  assumes [m, p] ⊢ x ↦ v1
  assumes [m, p] ⊢ y ↦ v2
  assumes v1 ≠ UndefVal ∧ v2 ≠ UndefVal
  shows val-to-bool v1 ⟶ val-to-bool v2
  using assms implies-valid
  by blast

lemma implies-false-valid:

```

```

assumes  $x \& y \hookrightarrow imp$ 
assumes  $\neg imp$ 
assumes  $[m, p] \vdash x \mapsto v1$ 
assumes  $[m, p] \vdash y \mapsto v2$ 
assumes  $v1 \neq UndefinedVal \wedge v2 \neq UndefinedVal$ 
shows  $val\text{-}to\text{-}bool\ v1 \longrightarrow \neg(val\text{-}to\text{-}bool\ v2)$ 
using assms implies-valid by blast

```

The following relation corresponds to the `UnaryOpLogicNode.tryFold` and `BinaryOpLogicNode.tryFold` methods and their associated concrete implementations.

The relation determines if a logic operation can be shown true or false through the stamp typing information.

```

inductive tryFold :: IRNode  $\Rightarrow$  (ID  $\Rightarrow$  Stamp)  $\Rightarrow$  bool  $\Rightarrow$  bool
where
   $\llbracket alwaysDistinct\ (stamps\ x)\ (stamps\ y) \rrbracket$ 
     $\implies tryFold\ (IntegerEqualsNode\ x\ y)\ stamps\ False\ |$ 
   $\llbracket neverDistinct\ (stamps\ x)\ (stamps\ y) \rrbracket$ 
     $\implies tryFold\ (IntegerEqualsNode\ x\ y)\ stamps\ True\ |$ 
   $\llbracket isIntegerStamp\ (stamps\ x);$ 
     $isIntegerStamp\ (stamps\ y);$ 
     $stpi\_upper\ (stamps\ x) < stpi\_lower\ (stamps\ y) \rrbracket$ 
     $\implies tryFold\ (IntegerLessThanNode\ x\ y)\ stamps\ True\ |$ 
   $\llbracket isIntegerStamp\ (stamps\ x);$ 
     $isIntegerStamp\ (stamps\ y);$ 
     $stpi\_lower\ (stamps\ x) \geq stpi\_upper\ (stamps\ y) \rrbracket$ 
     $\implies tryFold\ (IntegerLessThanNode\ x\ y)\ stamps\ False$ 

```

Proofs that show that when the stamp lookup function is well-formed, the `tryFold` relation correctly predicts the output value with respect to our evaluation semantics.

lemma

```

assumes  $kind\ g\ nid = IntegerEqualsNode\ x\ y$ 
assumes  $[g, m, p] \vdash nid \mapsto v$ 
assumes  $v \neq UndefinedVal$ 
assumes  $([g, m, p] \vdash x \mapsto xval) \wedge ([g, m, p] \vdash y \mapsto yval)$ 
shows  $val\text{-}to\text{-}bool\ (intval\text{-}equals\ xval\ yval) \longleftrightarrow v = IntVal32\ 1$ 

```

proof –

```

have  $v = intval\text{-}equals\ xval\ yval$ 
using assms(1, 2, 3, 4) BinaryExprE IntegerEqualsNode bin-eval.simps(7)
by (smt (verit) bin-eval.simps(10) encodeeval-def evalDet repDet)
then show ?thesis using intval-equals.simps val-to-bool.simps sorry

```

qed

lemma *tryFoldIntegerEqualsAlwaysDistinct*:

```

assumes wf-stamp g stamps
assumes  $kind\ g\ nid = (IntegerEqualsNode\ x\ y)$ 
assumes  $[g, m, p] \vdash nid \mapsto v$ 

```



```

assumes alwaysDistinct (stamps x) (stamps y)
shows v = IntVal32 0
proof –
  have  $\forall$  val.  $\neg(\text{valid-value } \text{val } (\text{join } (\text{stamps } x) (\text{stamps } y)))$ 
    using assms(1,4) unfolding alwaysDistinct.simps
  by (metis is-stamp-empty.elims(2) le-less-trans not-less valid32or64 valid-value.simps(1)
valid-value.simps(2))
  have  $\neg(\exists \text{ val} . ([g, m, p] \vdash x \mapsto \text{val}) \wedge ([g, m, p] \vdash y \mapsto \text{val}))$ 
    using assms(1,4) unfolding alwaysDistinct.simps wf-stamp.simps encodee-
val-def sorry
  then show ?thesis sorry
qed

```

```

lemma tryFoldIntegerEqualsNeverDistinct:
  assumes wf-stamp g stamps
  assumes kind g nid = (IntegerEqualsNode x y)
  assumes  $[g, m, p] \vdash \text{nid} \mapsto v$ 
  assumes neverDistinct (stamps x) (stamps y)
  shows v = IntVal32 1
  using assms IntegerEqualsNodeE sorry

```

```

lemma tryFoldIntegerLessThanTrue:
  assumes wf-stamp g stamps
  assumes kind g nid = (IntegerLessThanNode x y)
  assumes  $[g, m, p] \vdash \text{nid} \mapsto v$ 
  assumes stpi-upper (stamps x) < stpi-lower (stamps y)
  shows v = IntVal32 1
proof –
  have stamp-type: is-IntegerStamp (stamps x)
    using assms
  sorry
  obtain xval where xval:  $[g, m, p] \vdash x \mapsto xval$ 
    using assms(2,3) sorry
  obtain yval where yval:  $[g, m, p] \vdash y \mapsto yval$ 
    using assms(2,3) sorry
  have is-IntegerStamp (stamps x)  $\wedge$  is-IntegerStamp (stamps y)
    using assms(4)
  sorry
  then have val-to-bool (intval-less-than xval yval)
  sorry
  then show ?thesis
  sorry
qed

```

```

lemma tryFoldIntegerLessThanFalse:
  assumes wf-stamp g stamps
  assumes kind g nid = (IntegerLessThanNode x y)
  assumes  $[g, m, p] \vdash \text{nid} \mapsto v$ 
  assumes stpi-lower (stamps x)  $\geq$  stpi-upper (stamps y)

```

```

shows  $v = \text{IntVal32 } 0$ 
proof -
have stamp-type: is-IntegerStamp (stamps  $x$ )
  using assms
  sorry
obtain  $xval$  where  $xval: [g, m, p] \vdash x \mapsto xval$ 
  using assms(2,3) sorry
obtain  $yval$  where  $yval: [g, m, p] \vdash y \mapsto yval$ 
  using assms(2,3) sorry
have is-IntegerStamp (stamps  $x$ )  $\wedge$  is-IntegerStamp (stamps  $y$ )
  using assms(4)
  sorry
then have  $\neg(\text{val-to-bool } (\text{intval-less-than } xval \ yval))$ 
  sorry
then show ?thesis
  sorry
qed

theorem tryFoldProofTrue:
  assumes wf-stamp  $g$  stamps
  assumes tryFold (kind  $g$  nid) stamps True
  assumes  $[g, m, p] \vdash \textit{nid} \mapsto v$ 
  shows val-to-bool  $v$ 
  using assms(2) proof (induction kind  $g$  nid stamps True rule: tryFold.induct)
case (1 stamps  $x$   $y$ )
  then show ?case using tryFoldIntegerEqualsAlwaysDistinct assms sorry
next
case (2 stamps  $x$   $y$ )
  then show ?case using tryFoldIntegerEqualsAlwaysDistinct assms sorry
next
case (3 stamps  $x$   $y$ )
  then show ?case using tryFoldIntegerLessThanTrue assms sorry
next
case (4 stamps  $x$   $y$ )
  then show ?case using tryFoldIntegerLessThanFalse assms sorry
qed

theorem tryFoldProofFalse:
  assumes wf-stamp  $g$  stamps
  assumes tryFold (kind  $g$  nid) stamps False
  assumes  $[g, m, p] \vdash \textit{nid} \mapsto v$ 
  shows  $\neg(\text{val-to-bool } v)$ 
  using assms(2) proof (induction kind  $g$  nid stamps False rule: tryFold.induct)
case (1 stamps  $x$   $y$ )
  then show ?case using tryFoldIntegerEqualsAlwaysDistinct assms sorry
next
case (2 stamps  $x$   $y$ )
  then show ?case using tryFoldIntegerEqualsNeverDistinct assms sorry
next

```

```

case (3 stamps x y)
then show ?case using tryFoldIntegerLessThanTrue assms sorry
next
case (4 stamps x y)
then show ?case using tryFoldIntegerLessThanFalse assms sorry

qed

```

inductive-cases *StepE*:

$g, p \vdash (nid, m, h) \rightarrow (nid', m', h)$

Perform conditional elimination rewrites on the graph for a particular node. In order to determine conditional eliminations appropriately the rule needs two data structures produced by static analysis. The first parameter is the set of IRNodes that we know result in a true value when evaluated. The second parameter is a mapping from node identifiers to the flow-sensitive stamp.

The relation transforms the third parameter to the fifth parameter for a node identifier which represents the fourth parameter.

inductive *ConditionalEliminationStep* ::

$IRExpr \text{ set} \Rightarrow (ID \Rightarrow Stamp) \Rightarrow IRGraph \Rightarrow ID \Rightarrow IRGraph \Rightarrow bool$ **where**
impliesTrue:

$\llbracket kind\ g\ ifcond = (IfNode\ cid\ t\ f);$
 $g \vdash cid \simeq cond;$
 $\exists\ ce \in conds . (ce \ \&\ cond \hookrightarrow True);$
 $g' = constantCondition\ True\ ifcond\ (kind\ g\ ifcond)\ g$
 $\rrbracket \implies ConditionalEliminationStep\ conds\ stamps\ g\ ifcond\ g' \mid$

impliesFalse:

$\llbracket kind\ g\ ifcond = (IfNode\ cid\ t\ f);$
 $g \vdash cid \simeq cond;$
 $\exists\ ce \in conds . (ce \ \&\ cond \hookrightarrow False);$
 $g' = constantCondition\ False\ ifcond\ (kind\ g\ ifcond)\ g$
 $\rrbracket \implies ConditionalEliminationStep\ conds\ stamps\ g\ ifcond\ g' \mid$

tryFoldTrue:

$\llbracket kind\ g\ ifcond = (IfNode\ cid\ t\ f);$
 $cond = kind\ g\ cid;$
 $tryFold\ (kind\ g\ cid)\ stamps\ True;$
 $g' = constantCondition\ True\ ifcond\ (kind\ g\ ifcond)\ g$
 $\rrbracket \implies ConditionalEliminationStep\ conds\ stamps\ g\ ifcond\ g' \mid$

tryFoldFalse:

$\llbracket kind\ g\ ifcond = (IfNode\ cid\ t\ f);$
 $cond = kind\ g\ cid;$
 $tryFold\ (kind\ g\ cid)\ stamps\ False;$

$g' = \text{constantCondition False ifcond (kind g ifcond) g}$
 $\mathbb{I} \Rightarrow \text{ConditionalEliminationStep conds stamps g ifcond g'}$

code-pred (modes: $i \Rightarrow i \Rightarrow i \Rightarrow i \Rightarrow o \Rightarrow \text{bool}$) *ConditionalEliminationStep* .

thm *ConditionalEliminationStep.equation*

11.2 Control-flow Graph Traversal

type-synonym *Seen* = *ID set*

type-synonym *Condition* = *IRNode*

type-synonym *Conditions* = *Condition list*

type-synonym *StampFlow* = (*ID* \Rightarrow *Stamp*) *list*

nextEdge helps determine which node to traverse next by returning the first successor edge that isn't in the set of already visited nodes. If there is not an appropriate successor, *None* is returned instead.

fun *nextEdge* :: *Seen* \Rightarrow *ID* \Rightarrow *IRGraph* \Rightarrow *ID option* **where**
nextEdge *seen* *nid* *g* =
 (let *nids* = (filter ($\lambda \text{nid}'$. *nid'* \notin *seen*) (successors-of (kind *g* *nid*))) in
 (if length *nids* > 0 then Some (hd *nids*) else None))

pred determines which node, if any, acts as the predecessor of another.

Merge nodes represent a special case where-in the predecessor exists as an input edge of the merge node, to simplify the traversal we treat only the first input end node as the predecessor, ignoring that multiple nodes may act as a successor.

For all other nodes, the predecessor is the first element of the predecessors set. Note that in a well-formed graph there should only be one element in the predecessor set.

fun *pred* :: *IRGraph* \Rightarrow *ID* \Rightarrow *ID option* **where**
pred *g* *nid* = (case kind *g* *nid* of
 (MergeNode *ends* -) \Rightarrow Some (hd *ends*) |
 - \Rightarrow
 (if *IRGraph.predecessors* *g* *nid* = {}
 then None else
 Some (hd (sorted-list-of-set (*IRGraph.predecessors* *g* *nid*)))
)
)

When the basic block of an if statement is entered, we know that the condition of the preceding if statement must be true. As in the GraalVM compiler, we introduce the *registerNewCondition* function which roughly corresponds to the *ConditionalEliminationPhase.registerNewCondition*. This method updates the flow-sensitive stamp information based on the condition which we know must be true.

```

fun clip-upper :: Stamp  $\Rightarrow$  int  $\Rightarrow$  Stamp where
  clip-upper (IntegerStamp b l h) c = (IntegerStamp b l c) |
  clip-upper s c = s
fun clip-lower :: Stamp  $\Rightarrow$  int  $\Rightarrow$  Stamp where
  clip-lower (IntegerStamp b l h) c = (IntegerStamp b c h) |
  clip-lower s c = s

fun registerNewCondition :: IRGraph  $\Rightarrow$  Condition  $\Rightarrow$  (ID  $\Rightarrow$  Stamp)  $\Rightarrow$  (ID  $\Rightarrow$  Stamp) where

  registerNewCondition g (IntegerEqualsNode x y) stamps =
    (stamps(x := join (stamps x) (stamps y)))(y := join (stamps x) (stamps y)) |

  registerNewCondition g (IntegerLessThanNode x y) stamps =
    (stamps
      (x := clip-upper (stamps x) (stpi-lower (stamps y)))
      (y := clip-lower (stamps y) (stpi-upper (stamps x)))) |
  registerNewCondition g - stamps = stamps

fun hdOr :: 'a list  $\Rightarrow$  'a  $\Rightarrow$  'a where
  hdOr (x # xs) de = x |
  hdOr [] de = de

The Step relation is a small-step traversal of the graph which handles transitions between individual nodes of the graph.

It relates a pairs of tuple of the current node, the set of seen nodes, the always true stack of IfNode conditions, and the flow-sensitive stamp information.

inductive Step
  :: IRGraph  $\Rightarrow$  (ID  $\times$  Seen  $\times$  Conditions  $\times$  StampFlow)  $\Rightarrow$  (ID  $\times$  Seen  $\times$  Conditions  $\times$  StampFlow) option  $\Rightarrow$  bool
  for g where
    — Hit a BeginNode with an IfNode predecessor which represents the start of a basic block for the IfNode. 1. nid' will be the successor of the begin node. 2. Find the first and only predecessor. 3. Extract condition from the preceding IfNode. 4. Negate condition if the begin node is second branch (we've taken the else branch of the condition) 5. Add the condition or the negated condition to stack 6. Perform any stamp updates based on the condition using the registerNewCondition function and place them on the top of the stack of stamp information
     $\llbracket$ kind g nid = BeginNode nid';

    nid  $\notin$  seen;
    seen' = {nid}  $\cup$  seen;

    Some ifcond = pred g nid;
    kind g ifcond = IfNode cond t f;

    i = find-index nid (successors-of (kind g ifcond));
    c = (if i = 0 then kind g cond else LogicNegationNode cond);
    conds' = c # conds;

```

$flow' = registerNewCondition\ g\ c\ (hdOr\ flow\ (stamp\ g))$
 $\implies Step\ g\ (nid,\ seen,\ conds,\ flow)\ (Some\ (nid',\ seen',\ conds',\ flow'\ \# \ flow))\ |$

— Hit an EndNode 1. nid' will be the usage of EndNode 2. pop the conditions and stamp stack

$\llbracket kind\ g\ nid = EndNode;$

$nid \notin seen;$
 $seen' = \{nid\} \cup seen;$

$nid' = any-usage\ g\ nid;$

$conds' = tl\ conds;$

$flow' = tl\ flow$

$\implies Step\ g\ (nid,\ seen,\ conds,\ flow)\ (Some\ (nid',\ seen',\ conds',\ flow'))\ |$

— We can find a successor edge that is not in seen, go there

$\llbracket \neg(is-EndNode\ (kind\ g\ nid));$
 $\neg(is-BeginNode\ (kind\ g\ nid));$

$nid \notin seen;$
 $seen' = \{nid\} \cup seen;$

$Some\ nid' = nextEdge\ seen'\ nid\ g$

$\implies Step\ g\ (nid,\ seen,\ conds,\ flow)\ (Some\ (nid',\ seen',\ conds,\ flow))\ |$

— We can cannot find a successor edge that is not in seen, give back None

$\llbracket \neg(is-EndNode\ (kind\ g\ nid));$
 $\neg(is-BeginNode\ (kind\ g\ nid));$

$nid \notin seen;$
 $seen' = \{nid\} \cup seen;$

$None = nextEdge\ seen'\ nid\ g$

$\implies Step\ g\ (nid,\ seen,\ conds,\ flow)\ None\ |$

— We've already seen this node, give back None

$\llbracket nid \in seen \rrbracket \implies Step\ g\ (nid,\ seen,\ conds,\ flow)\ None$

code-pred (*modes*: $i \Rightarrow i \Rightarrow o \Rightarrow bool$) *Step* .

The ConditionalEliminationPhase relation is responsible for combining the individual traversal steps from the Step relation and the optimizations from the ConditionalEliminationStep relation to perform a transformation of the whole graph.

end