

Create/Drop/Describe Table

```
create table department (id number(7) primary key, dept_name varchar2(50) unique, regi_date date default sysdate);
```

```
create table contact (id number(7) primary key, mobile number(15) unique, country varchar2(50) default 'Bangladesh')
```

```
create table employee (id number(7) primary key, emp_name varchar2(20) not null, salary number(7,2) check(salary>=25000), joining_date date check(joining_date<='01-Jan-2000'), dept_id number(7) not null, con_id number(7), foreign key (dept_id) references department(id), foreign key (con_id) references contact(id));
```

```
create table department_backup as select * from department;
```

```
drop table dhaka;
```

```
desc dhaka;
```

Create/Drop Role/User

```
create role super_user;
```

```
create user shuvo identified by shuvo;
```

```
drop user hasina;
```

```
drop user hasina cascade;
```

Grant/Revoke Privilege

```
grant create session, create table, create view, create sequence, create procedure, create synonym, create trigger to super_user;
```

```
grant super_user to shuvo;
```

```
grant dba to shuvo;
```

```
grant all privileges to shuvo;
```

```
revoke all privileges from shuvo;
```

Grant Tablespace to User

```
grant unlimited tablespace to shuvo;
```

```
alter user olive quota 500m on system;
```

Insert Data

```
insert into department values (dept_seq.nextval, 'Administration');
```

```
insert into contact (con_id, mobile, country) values(con_seq.nextval, 01712345678, 'Japan');
```

```
insert into employee (id, emp_name, salary, joining_date, dept_id, con_id) values(emp_seq.nextval, 'AAA', 25000, '01-Feb-1998', 10, 10);
```

Table Privilege/Add Constraints

```
ALTER TABLE dhaka READ ONLY;
```

```
ALTER TABLE dhaka READ WRITE;
```

```
ALTER TABLE department ADD job_id VARCHAR2(9);
```

```
ALTER TABLE department DROP COLUMN job_id;
```

```
ALTER TABLE customer ADD (city varchar2(15), code number(5));
```

```
ALTER TABLE customer drop (city, code);
```

```
alter table department modify (dept_name varchar2(55));
```

```
alter table employee add constraint emp_dept_id unique (con_id);
```

```
alter table customer drop constraint cus_mob;
```

Update Data

```
update dhaka set name='C' where income = 30000;
```

```
update employee set salary=35000, emp_name='BBB' where con_id=15;
```

```
update company set brand_id = (select brand_id from company where name='Google Inc.') where id=03;
```

Create View/Sequence/Synonym/Index

```
create sequence dept_seq increment by 10 start with 10 maxvalue 5000 nocache nocycle;
```

```
create sequence con_seq increment by 5 start with 5 nocache nocycle;
```

```
create sequence emp_seq increment by 1 start with 1 nocache nocycle;
```

```
create view dha_view1 as select id, name, email from dhaka;
```

```
create or replace view empvu80 (id_number, name, sal, department_id) as select employee_id, first_name|| ' ' || last_name, salary, department_id from employees;
```

```
CREATE OR REPLACE VIEW dept_sum_vu (name, minsal, maxsal, avgsal) AS SELECT  
d.department_name, MIN(e.salary), MAX(e.salary), AVG(e.salary) FROM employees e JOIN departments d  
ON (e.department_id = d.department_id) GROUP BY d.department_name;
```

```
CREATE INDEX emp_last_name_idx ON employees(last_name);
```

```
create synonym e20 for empvu80;
```

Show View/Table/Sequence/Username

```
select view_name from user_views;
```

```
select table_name from user_tables;
```

```
select sequence_name from user_sequences;
```

```
select USERNAME from DBA_USERS;
```

```
SELECT INDEX_NAME FROM USER_INDEXES;
```

```
SELECT SYNONYM_NAME FROM USER_SYNONYMS;
```

```
SELECT TRIGGER_NAME FROM USER_TRIGGERS;
```

Autocommit

```
show autocommit;
```

```
set autocommit on;
```

Delete Data

```
delete brand where id=04;
```

```
delete from department;
```

```
truncate table brand; (Works with DDL Statement)
```

Spool On/Off

```
spool E:/quiz.txt;
```

```
spool off;
```

Create Trigger for Insert

Step-1: Create Two Tables

```
create table usa (id number (5), fname varchar2(55), lname varchar2(55));  
create table usa_backup as select * from usa;
```

Step-2: Create Trigger:

```
CREATE OR REPLACE TRIGGER usa_trigger AFTER insert ON usa (NB: after update/before delete)  
FOR EACH ROW  
DECLARE  
BEGIN  
insert into usa_backup values (:new.id, :new.fname, :new.lname);  
dbms_output.put_line ('Data inserted successfully on usa_backup table');  
END;  
/
```

Step-3: Insert Data & View from Backup Table

```
insert into usa values (01,'Mehedi','Hasan');  
select * from usa_backup;
```

Create Trigger for Update

Step-1: Create Trigger

```
CREATE OR REPLACE TRIGGER usa_trigger_update AFTER update ON usa  
FOR EACH ROW  
DECLARE  
BEGIN  
UPDATE usa_backup  
set id = :new.id, name = :new.name, lname = :new.lname  
where id = :old.id or name = :old.name or lname = :old.lname;  
dbms_output.put_line ('Data successfully updated into usa_backup table');  
END;
```

Step-2: Update Main Table & View from Backup Table

```
update usa set name = 'Hollywood' where id = 5010;  
update usa set id = 5010 where name = 'Hollywood';  
select * from usa_backup;
```

Create Trigger for Delete

Step-1: Create Trigger

```
CREATE OR REPLACE TRIGGER usa_trigger_delete AFTER delete ON usa  
FOR EACH ROW
```

DECLARE

BEGIN

DELETE from usa_backup

where id = :old.id or name = :old.name;

dbms_output.put_line ('Data successfully deleted from usa_backup table');

END;

Step-2: Delete from Main Table & View from Backup Table

delete from usa where name = 'Los Angeles';

delete from usa where id = 5010;

select * from usa_backup;

Create Procedure for Insert

Step-1: Create Table

Create Table customer (id number(5) primary key, name varchar2(55) not null, mobile varchar2(55), country varchar2(55));

Step-2: Create Insert Procedure

CREATE OR REPLACE PROCEDURE insertCustomer(

p_id IN customer.id%TYPE,

p_name IN customer.name%TYPE,

p_mobile IN customer.mobile%TYPE,

p_country IN customer.country%TYPE)

IS

BEGIN

INSERT into customer (id, name, mobile, country)

VALUES (p_id, p_name, p_mobile, p_country);

COMMIT;

END;

/

Step-3: Calling Insert Procedure

❖ BEGIN

insertCustomer(101, 'Shuvo', 01711000001, 'Bangladesh');

END;

/

❖ EXECUTE insertCustomer(101, 'Shuvo', 01711000001, 'Bangladesh');

Create Procedure for Update

Step-1: Create Update Procedure

```
CREATE OR REPLACE PROCEDURE updateCustomer(  
p_id IN customer.id%TYPE,  
p_name IN customer.name%TYPE,  
p_mobile IN customer.mobile%TYPE,  
p_country IN customer.country%TYPE)  
IS  
BEGIN  
UPDATE customer SET name = p_name, mobile = P_mobile, country = p_country where id = p_id or name  
= p_name;  
COMMIT;  
END;  
/
```

Step-2: Calling Update Procedure

```
❖ BEGIN  
    updateCustomer(102, 'Masud', 01711000002, 'France');  
END;  
/  
❖ EXECUTE updateCustomer(102, 'Masud', 01711000002, 'France');
```

Create procedure for delete

Step-1: Create Update Procedure

```
CREATE OR REPLACE PROCEDURE deleteCustomer(  
p_id IN customer.id%TYPE,  
p_name IN customer.name%TYPE)  
IS  
BEGIN  
DELETE from customer where id = p_id or name = p_name;  
COMMIT;  
END;  
/
```

Step-2: Calling Delete Procedure

```
❖ BEGIN  
    deleteCustomer(103, 'Mehedi');  
END;
```

/

❖ EXECUTE deleteCustomer(103, 'Mehedi');