

Spatial Signatures

Dynamically building the built environment

Daniel Arribas-Bel^{*†‡}
Martin Fleischmann^{*†§}

Geographic Data Science Lab, University of Liverpool

September 2019

ABSTRACT: Blah blah blah

Key words: blah, blah, blah

*THANKS.

†Geographic Data Science Lab, Department of Geography and Planning, University of Liverpool, Roxby Building ,
74 Bedford St S , Liverpool , L69 7ZT, United Kingdom

‡E-mail: D.Arribas-Bel@liverpool.ac.uk; phone: +44 (0)151 795 9727; website: <http://darribas.org>.

§E-mail: M.Fleischmann@liverpool.ac.uk; website: <https://martinfleischmann.net/>.

1. Introduction

Fleischmann et al. (2020a) is king.

2. (Urban) form and function

Research studying urban form has a long tradition (Geddes, 1915, Trewartha, 1934), whilst urban morphology as an independent area of research has established in the 1960s. It originated independently in geography (Conzen, 1960) and architecture (Muratori, 1959), reflecting its inherently multi-disciplinary nature, which was later reinforced by the inclusion of socio-economic component in works of Panerai et al. (1997). The original methods are predominantly qualitative, and this tendency persists (Dibble, 2016). First notable quantitative approaches date to the late 1980s and 1990s, reflecting advancements in computer science and newly available data capturing built environment. Two strains of research have emerged, one based on cartographic (vector) representation of the urban environment, assessing its boundaries (Batty and Longley, 1987), street networks (Hillier, 1996, Porta et al., 2006) and other elements (Pivo, 1993). The other one based on earth observation exploiting remotely sensed data to capture the change of footprints of urban areas (Howarth and Boasson, 1983) or classification of land cover (European Environment Agency, 1990).

The distinction between two approaches based on their primary source of data can also be applied to the recent literature reflecting the state of the art of characterization of urban form. A quantitative branch of urban morphology, or urban morphometrics, working predominantly with vector representation of elements of urban form has rapidly grown and offers an abundant selection of measurable characters describing different aspects of form (Fleischmann et al., 2020b). Methods focusing on a single aspect (Porta et al., 2006) were replaced by others aiming to better reflect the complexity of urban form by combining multiple morphometric characters into a single model, often leading to a classification of some sort (Song and Knaap, 2007). The focus on classification is becoming more present in recent years, starting from small-scale studies classifying blocks and streets (Gil et al., 2012) to larger areas and higher granularity (Schirmer and Axhausen, 2015, Araldi and Fusco, 2019, Bobkova et al., 2019, Dibble et al., 2019, Jochem et al., 2020).

In parallel, advancements in remote sensing led to a range of classification frameworks based on various conceptualizations of the urban fabric. However, there is one significant difference between classification derived via morphometric characterization and the one of remote sensing origin. Where the former is mostly unsupervised (Araldi and Fusco, 2019, Schirmer and Axhausen, 2015), the latter tends towards supervised techniques, capturing classes defined prior to the analysis (Pauleit and Duhme, 2000). Two most prominent classification models used as an input (i.e. training set) are Local Climate Zones (Stewart and Oke, 2012) defining ten built-form types and seven land cover types, used by Koc et al. (2017) or Taubenböck et al. (2020), and Urban Structural Type, a generic typology based on the notion of internal homogeneity of types (Lehner and Blaschke, 2019).

However, all the methods above have certain limits, mostly related to detail, comprehensiveness and scalability, lacking at least on them. Detail reflects spatial granularity of resulting classification, where more granular, i.e. more detailed, unit has the ability to capture smaller nuances of the urban environment and better reflect local characters or a place. Methods based on a unit which can be further subdivided (Dibble et al., 2019, Jochem et al., 2020, Araldi and Fusco, 2019, Gil et al., 2012), therefore does not ensure internal homogeneity, can result in classes driven by the heterogeneity instead of the unit instead of the actual pattern of urban form. Comprehensiveness refers to the number of characters (variables) used in the classification procedure. Small sets of characters as in Bobkova et al. (2019) or Serra et al. (2018) are prone to a selection bias and will less likely reflect the complexity of the urban environment. Finally, scalability reflects the ability of the proposed method to scale up to large extents of metropolitan areas or national-level studies. While some works illustrate such a potential (Jochem et al., 2020, Schirmer and Axhausen, 2015, Bobkova et al., 2019, Araldi and Fusco, 2019), others which may overcome other issues are less likely to scale from their original limits (Dibble et al., 2019). Furthermore, computational scalability can be limited by data availability. Methods dependent on a high amount of detailed vector data (Bobkova et al., 2019) can be hardly applied in other contexts where such input is not available.

3. Spatial Signatures

3.1 Definition

3.2 Building blocks: the Enclosed Tessellation

This section proposes a novel and theoretically-informed delineation of space to support the development of spatial signatures. Since spatial signatures are conceptualised as highly granular in space, considering the ideal unit of analysis at which to measure them is of utmost importance. This process involves identifying the fundamental building block that partitions space in a way that may later be meaningfully aggregated into organic delineations of spatial signatures. This step is worth spending energy and effort for two main reasons. First, if ignored, there is an important risk of incurring the modifiable areal unit problem (MAUP, Openshaw, 1981). The urban fabric is not a spatially smooth phenomenon; rather, it is lumpy, irregular and operates at very small scales. Choosing a spatial unit that does not closely match its distribution will subsume interesting variation and will hide features that are at the very heart of what we are trying to capture with spatial signatures. Second, and conversely, we see adopting a meaningful unit a step of analysis itself. Rather than selecting an imperfect but existing unit to try to characterise spatial signatures, delineating our own is an opportunity in itself to learn about the nature of urban tissue and better understand issues about distribution and composition within urban areas.

Let us first focus on what is required from an ideal unit of analysis for spatial signatures. We need a partition of space into sections of built *and* lived environment that can later be pieced together based on their characteristics. The result will feed into an organic delineation that captures variation in the appearance and character of urban fabric as it unfolds over space. To

be more specific, a successful candidate for this task will need to fulfill at least three features: indivisibility, internal consistency, and exhaustivity. An ideal unit will need to be *indivisible* in the sense that if it were to be broken into smaller components, none of them would be enough to capture the notion of spatial signature. Similarly, every unit needs to be *internally consistent*: one and only one type of signature should be represented in each observation. Finally, the resulting delineation needs to be geographically *exhaustive*. In other words, it should assign every location within the area of interest (e.g. a region or a country) to one and only one class. A unit that is indivisible, consistent, and exhaustive can thus form the basis of meaningful aggregation of space into spatial signatures.

The existing literature does not appear to have a satisfying candidate to act as the building block of spatial signatures. Without attempting an exhaustive review, an endeavour beyond the scope of this article, the vast majority of existing approaches to delineate meaningful units of urban form and function fall within one of the following three categories. The first group relies on *administrative* units such as postcodes, census geographies or municipal boundaries (e.g. XXXrefsXXX). These are practical as they usually are exhaustive of the geography and readily available. However, their partition of space is usually driven by different needs that rarely align with the measurement of spatial signatures, or indeed those of any morphological or functional urban process. For example, Puente-Ajovín et al. (2020) compare the size distribution of urban areas in Spain across several definitions and conclude they are fundamentally different; similarly, Taubenböck et al. (2019) rank world's largest cities based on their administrative size and on an alternative methods they proposed following built-up area, reaching similar conclusions and even going on to argue that "administrative units obscure morphologic reality". An emerging body of work relies on granular, *uniform grids* as the main unit of analysis. The building blocks may be squares (e.g. Jochem et al., 2020) or hexagons, as in the case of the H3 spatial indexing system (Brodsky, 2018). This choice is usually explicitly or implicitly motivated by the lack of a better, bespoke partitioning; the use of input data distributed in grids (e.g. satellite imagery); and the assumption that, with enough resolution, grids can be organically aggregated into units that match the processes of interest. XXXmf to fill in here A third approach followed mostly by the literature on urban morphology relies on the definition of morphometric units. These include street segments (Araldi and Fusco, 2019), building footprints (Fleischmann et al., 2020a), or constructs such as the sactuary area (Mehaffy et al., 2010, Dibble et al., 2019). XXX In all these cases, the choice of an administrative, uniform or morphometric choice is justified by the particular application in which it take place. However none of these approaches meet the three characteristics we require for spatial signatures. Administrative boundaries are exhaustive but rarely indivisible or consistent when it comes to urban form, usually grouping very different types of fabric within a single area. Uniform grids are also exhaustive but, similarly to administrative definition, the arbitrariness of their delineation with respect to urban form usually leaves them divisible and internally inconsistent. Morphometric units are the most theoretically appealing since they are built to match the distribution of urban features and are usually granular enough to warrant internal consistency and indivisibility. Most of them are however not exhaustive as they are anchored to particular elements of the build environment,

such as streets or building footprints, which do not provide full coverage. [Martin: \[You could argue that plot is all indivisible, consistent and exhaustive entity.\]](#)

We propose the development of a new spatial unit that we term the *enclosed tessellation* (ET). An ET is defined as:

The portion of space that results from growing a morphological tessellation within an enclosure delineated by a series of natural or built barriers identified from the literature on urban form, function and perception.

[Martin: \[We should fix terminology. What is tessellation \(mesh, process, unit\) and what is cell etc.\]](#) Let us unpack this concept a bit further. ETs result from the combination of three sequential steps. First, they rely on a set of enclosing components: features of the landscape that divide it in smaller, fully delimited portions. The list of what should be counted as enclosing is informed by theory and, as we will see below, may vary by context. But, as an illustration, it includes elements such as the street network, rivers and coastlines, or railways. Second, these enclosing features are integrated into a single set of boundaries that partition the geography into smaller areas. In some cases, they will be small, as with urban blocks in dense city centres; in others, they will be larger in size, as in rural sections with lower density of enclosing features. We call each of this fully delimited areas an enclosure. Third, enclosures are further subdivided using a morphological tessellation. Originally proposed by ([Fleischmann et al., 2020a](#)), morphological tessellations exhaustively partition space based on a set of building footprints, which are used in this context as anchors to draw catchment polygons. This process generates geographical boundaries for a given area that result in a new spatial unit. This unit provides full geographical coverage without any overlap. Since the essence of the approach resides in growing a tessellation inside a set of enclosing features, we call the resulting areas “enclosed tessellations”.

The ET intersects two perspectives of how space can be understood and organised. The first relies on the use of features that *delimit* the landscape and partition it into smaller, fully enclosed portions. These include the road and street networks, but also others such as railways or rivers. Each feature is conceptualised as a line that acts as a boundary, dividing space into what falls within each of its sides. A long tradition in the literature on urban morphology and perception relies on variations of these delimiters to parse through the urban fabric. Prominent early examples include the edges and paths highlighted by [Lynch \(1960\)](#) as two of the five core elements that define legibility and imageability of a city; as well as the large amount of work inspired by this framework that continues to contribute new understandings of how the internal structure of cities is spatially arranged and perceived by humans (e.g. [Filomena et al., 2019](#)).

The second perspective that ETs integrate is a vision organised around *anchors*. In this view, space is best understood as the area in between a discrete set of relevant features. Unlike delimiters, these elements do not partition space per se, but instead act as origins to which the rest can be “attached”. The choice of anchors might vary by context but, in this case, the literature on morphometrics has extensive evidence to support the use of buildings as the primary feature ([Hamaina et al., 2012](#), [Usui and Asami, 2013](#), [Schirmer and Axhausen, 2015](#)). Tessellations grow areas around a point of focus. In our case, we use the morphological tessellation ([Fleischmann et al., 2020a](#)), which has been shown to be an efficient proxy for cadastral plots, the gold standard in morphometric analysis.

The combination of delimiters and anchors as the parsers of space make ETs an ideal spatial unit to study spatial signatures. Building on recent morphometric advances and integrating them with well-established understandings of how cities are read and perceived, the ETs meet the three requirements we outlined above. They are indivisible in that a single ET will contain no delimiters, at most a single anchor, and potentially none. They are also internally consistent because they are delineated as the area within the delimiters that contain at most one anchor. And finally ETs are exhaustive in that every location within the area of interest is assigned to one and only one ET, providing full geographical coverage without any overlap.

3.3 Embedding form and function into Spatial Signatures

4. Illustration

5. Conclusions

References

- Araldi, A. and Fusco, G. (2019). From the street to the metropolitan region: Pedestrian perspective in urban fabric analysis. *Environment and Planning B: Urban Analytics and City Science*, 46(7):1243–1263.
- Batty, M. and Longley, P. A. (1987). Fractal-based description of urban form. *Environment and Planning B: Planning and Design*, 14(1961):123–134.
- Bobkova, E., Berghauser Pont, M., and Marcus, L. (2019). Towards analytical typologies of plot systems: Quantitative profile of five European cities. *Environment and Planning B: Urban Analytics and City Science*, page 239980831988090.
- Brodsky, I. (2018). H3: Uber’s hexagonal hierarchical spatial index. Available from Uber Engineering website: <https://eng.uber.com/h3/>[22 June 2019].
- Conzen, M. R. G. (1960). Alnwick, northumberland: a study in town-plan analysis. *Transactions and Papers (Institute of British Geographers)*, (27):iii–122.
- Dibble, J., Prelorendjos, A., Romice, O., Zanella, M., Strano, E., Pagel, M., and Porta, S. (2019). On the origin of spaces: Morphometric foundations of urban form evolution. *Environment and Planning B: Urban Analytics and City Science*, 46(4):707–730.
- Dibble, J. L. (2016). *Urban morphometrics: towards a quantitative science of urban form*. PhD thesis, University of Strathclyde.
- European Environment Agency (1990). CORINE Land Cover. pages 1–163.
- Filomena, G., Verstegen, J. A., and Manley, E. (2019). A computational approach to ‘The Image of the City’. *Cities*, 89:14–25.
- Fleischmann, M., Feliciotti, A., Romice, O., and Porta, S. (2020a). Morphological tessellation as a way of partitioning space: Improving consistency in urban morphology at the plot scale. *Computers, Environment and Urban Systems*, 80:101441.
- Fleischmann, M., Romice, O., and Porta, S. (2020b). Measuring urban form: Overcoming terminological inconsistencies for a quantitative and comprehensive morphologic analysis of cities. *Environment and Planning B: Urban Analytics and City Science*, page 2399808320910444.
- Geddes, P. (1915). *Cities in evolution: an introduction to the town planning movement and to the study of civics*. London, Williams.
- Gil, J., Montenegro, N., Beirão, J. N., and Duarte, J. P. (2012). On the Discovery of Urban Typologies: Data Mining the Multi-dimensional Character of Neighbourhoods. *Urban Morphology*, 16(1):27–40.
- Hamaina, R., Leduc, T., and Moreau, G. (2012). Towards Urban Fabrics Characterization Based on Buildings Footprints. In *Bridging the Geographic Information Sciences*, volume 2, pages 327–346. Springer, Berlin, Heidelberg, Berlin, Heidelberg.
- Hillier, B. (1996). *Space is the machine : a configurational theory of architecture*. Cambridge University Press, Cambridge.
- Howarth, P. J. and Boasson, E. (1983). Landsat digital enhancements for change detection in urban environments. *Remote sensing of environment*, 13(2):149–160.

- Jochem, W. C., Leasure, D. R., Pannell, O., Chamberlain, H. R., Jones, P., and Tatem, A. J. (2020). Classifying settlement types from multi-scale spatial patterns of building footprints. *Environment and Planning B: Urban Analytics and City Science*, page 239980832092120.
- Koc, C. B., Osmond, P., Peters, A., and Irger, M. (2017). Mapping local climate zones for urban morphology classification based on airborne remote sensing data. In *2017 Joint Urban Remote Sensing Event (JURSE)*, pages 1–4. IEEE.
- Lehner, A. and Blaschke, T. (2019). A Generic Classification Scheme for Urban Structure Types. *Remote Sensing*, 11(2):173.
- Lynch, K. (1960). *The Image of the City*, volume 11. MIT press.
- Mehaffy, M., Porta, S., Rofo, Y., and Salingaros, N. (2010). Urban nuclei and the geometry of streets: The ‘emergent neighborhoods’ model. *Urban Design International*, 15(1):22–46.
- Muratori, S. (1959). Studi per una operante storia urbana di venezia. *Palladio*, 1959:1–113.
- Openshaw, S. (1981). The modifiable areal unit problem. *Quantitative geography: A British view*, pages 60–69.
- Panerai, P., Castex, J., and Depaule, J.-C. (1997). *Formes urbaines: de l’ilot à la barre*. Editions Parentheses.
- Pauleit, S. and Duhme, F. (2000). Assessing the environmental performance of land cover types for urban planning. *Landscape and urban planning*, 52(1):1–20.
- Pivo, G. (1993). A taxonomy of suburban office clusters: the case of toronto. *Urban Studies*, 30(1):31–49.
- Porta, S., Crucitti, P., and Latora, V. (2006). The network analysis of urban streets: A primal approach. *Environment and Planning B: Planning and Design*, 33(5):705–725.
- Puente-Ajovín, M., Ramos, A., Sanz-Gracia, F., and Arribas-Bel, D. (2020). How sensitive is city size distribution to the definition of city? the case of spain. *Economics Letters*, page 109643.
- Schirmer, P. M. and Axhausen, K. W. (2015). A multiscale classification of urban morphology. *Journal of Transport and Land Use*, 9(1):101–130.
- Serra, M., Psarra, S., and O’Brien, J. (2018). Social and Physical Characterization of Urban Contexts: Techniques and Methods for Quantification, Classification and Purposive Sampling. *Urban Planning*, 3(1):58–74.
- Song, Y. and Knaap, G.-J. (2007). Quantitative Classification of Neighbourhoods: The Neighbourhoods of New Single-family Homes in the Portland Metropolitan Area. *Journal of Urban Design*, 12(1):1–24.
- Stewart, I. D. and Oke, T. R. (2012). Local Climate Zones for Urban Temperature Studies. *Bulletin of the American Meteorological Society*, 93(12):1879–1900.
- Taubenböck, H., Debray, H., Qiu, C., Schmitt, M., Wang, Y., and Zhu, X. (2020). Seven city types representing morphologic configurations of cities across the globe. *Cities*, 105:102814.
- Taubenböck, H., Weigand, M., Esch, T., Staab, J., Wurm, M., Mast, J., and Dech, S. (2019). A new ranking of the world’s largest cities—do administrative units obscure morphological realities? *Remote Sensing of Environment*, 232:111353.

- Trewartha, G. T. (1934). Japanese cities distribution and morphology. *Geographical Review*, 24(3):404-417.
- Usui, H. and Asami, Y. (2013). Estimation of mean lot depth and its accuracy. *Journal of City Planning Institute of Japan*, 48(3):357-362.