




輸出端(output)



輸入端(input)



A

A

B

B

C

C

D

D

急停扭矩 (Emergency Stop Torque)	2倍額定輸出力矩 (3 times rated output torque)
額定輸入轉速 (Rated input speed)	3000rpm
最大輸入轉速 (Maximum input speed)	6000rpm
背隙 (Dorsal gap)	≤6arcmin
容許徑向力 (Allowable radial force)	700N
容許軸向力 (Allowable axial force)	610N
使用壽命 (Service life)	20000hr
效率 (Efficiency)	≥95%
使用溫度範圍 (Operating temperature range)	-15°C~90°C
防護等級 (protection class)	IP65
噪音值 (Noise value)	≤60dB
安裝方式 (Installation DIRECTION)	任意(Arbitrarily)

減速比 (Speed ratio)	3	4	5	7	10
額定輸出力矩 (Rated output torque)	19Nm	20Nm	20Nm	19Nm	14Nm

---	2018-12-26	00初版	陳國棟	
改版 SYM	年月日 DATE	變更事項 REVISIONS	設計 BY	備注 NOTE

制圖 PRAWN	設計 DESIGNED	品名: TITLE	精密行星減速機 Precision Planetary Gear Reducer	
		規格: SPEC	GPBR042-L1-(8-30-45-M3)	
 吉嘉精密科技有限公司 GIGA Precision Technology Co., Ltd			A4	