




A



輸出端(output)



輸入端(input)



B



C

急停扭矩 (Emergency Stop Torque)	2倍額定輸出力矩 (2 times rated output torque)
額定輸入轉速 (Rated input speed)	3000rpm
背隙 (Dorsal gap)	≤10arcmin
容許徑向力 (Allowable radial force)	500N
容許軸向力 (Allowable axial force)	390N
使用壽命 (Service life)	20000h
效率 (Efficiency)	≥94%
使用溫度範圍 (Operating temperature range)	-25°C~80°C
防護等級 (protection class)	IP65
安裝方式 (Installation DIRECTION)	任意(Arbitrarily)

減速比 (Speed ratio)	12	16	20	25	28	35	40	50	70
額定輸出力矩 (Rated output torque)	28Nm	29.5Nm	29.5Nm	31.5Nm	29.5Nm	31.5Nm	29.5Nm	31.5Nm	22.5Nm

---	2018-12-26	00初版	陳國棟	
改版 SYM	年月日 DATE	變更事項 REVISIONS	設計 BY	備注 NOTE
制圖 PRAWN		設計 DESIGNED	品名: TITLE	精密行星減速機 Precision Planetary Gear Reducer

規格: SPEC	GPL060-L2-(14-50-70-M5)
	G+® 吉嘉精密科技有限公司 GIGA Precision Technology Co., Ltd