


急停扭矩 (Emergency Stop Torque)	3倍額定輸出力矩 (3 times rated output torque)	
額定輸入轉速 (Rated input speed)	3000rpm	
最大輸入轉速 (Maximum input speed)	6000rpm	
背隙 (Dorsal gap)	P1	≤5arcmin
	P2	≤8arcmin
容許徑向力 (Allowable radial force)	14500N	
容許軸向力 (Allowable axial force)	7250N	
使用壽命 (Service life)	20000hr	
效率 (Efficiency)	≥94%	
使用溫度範圍 (Operating temperature range)	-10℃～90℃	
防護等級 (protection class)	IP65	
噪音值 (Noise value)	≤67dB	
安裝方式 (Installation DIRECTION)	任意(Arbitrarily)	

減速比 (Speed ratio)	3	4	5	7	10
額定輸出力矩 (Rated output torque)	588Nm	1050Nm	1200Nm	1100Nm	900Nm

---		2018-12-26		00初版		陳國棟	
改版 SYM		年 月 日 DATE		變更事項 REVISIONS		設計 BY	
						備 注 NOTE	
制圖 PRAWN		設計 DESIGNED		品名: TITLE		精密行星減速機 Precision Planetary Gear Reducer	
				規格: SPEC		GPB180-L1-(42-114.3-200-M12)	
				 吉嘉精密科技有限公司 GIGA Precision Technology Co., Ltd		A4	
4				比例SCALE:1:5		圖紙 1 (共1)	