



C	急停扭矩 (Emergency Stop Torque)	3倍額定輸出力矩 (3 times rated output torque)	
	額定輸入轉速 (Rated input speed)	5000rpm	
	最大輸入轉速 (Maximum input speed)	10000rpm	
	背隙 (Dorsal gap)	P1	≤9arcmin
		P2	≤11arcmin
	容許徑向力 (Allowable radial force)	1530N	
D	容許軸向力 (Allowable axial force)	765N	
	使用壽命 (Service life)	20000hr	
	效率 (Efficiency)	≥92%	
	使用溫度範圍 (Operating temperature range)	-10℃～90℃	
	防護等級 (protection class)	IP65	
	噪音值 (Noise value)	≤63dB	
	安裝方式 (Installation DIRECTION)	任意(Arbitrarily)	

減速比 (Speed ratio)	15	25	30	35	40	50	60	70	80	100	140	200
額定出力矩 (Rated output torque)	60Nm	60Nm	55Nm	50Nm	45Nm	60Nm	55Nm	50Nm	45Nm	40Nm	50Nm	40Nm

---	2018-12-26	00初版	陳國棟	
改版 SYM	年 月 日 DATE	變更事項 REVISIONS	設計 BY	備 注 NOTE
制圖 PRAWN		設計 DESIGNED	品名: TITLE	精密行星減速機 Precision Planetary Gear Reducer
			規格: SPEC	GPER070-L2-(14-50-70-M5)
			<div>G+[®] 吉嘉精密科技有限公司 GIGA Precision Technology Co., Ltd</div> <div>A4</div>	