


C	急停扭矩 (Emergency Stop Torque)	3倍額定輸出力矩 (3 times rated output torque)
	額定輸入轉速 (Rated input speed)	3500rpm
	背隙 (Dorsal gap)	≤12arcmin
	容許徑向力 (Allowable radial force)	400N
D	容許軸向力 (Allowable axial force)	420N
	使用壽命 (Service life)	10000hr
	效率 (Efficiency)	≥93%
	使用溫度範圍 (Operating temperature range)	-10℃～80℃
	防護等級 (protection class)	IP65
	噪音值 (Noise value)	≤63dB
	安裝方式 (Installation DIRECTION)	任意(Arbitrarily)

減速比 (Speed ratio)	15	20	25	30	35	40	50	70	100	140	200
額定輸出力矩 (Rated output torque)	90Nm	90Nm	90Nm	90Nm	90Nm	90Nm	125Nm	90Nm	90Nm	55Nm	22Nm

---	2018-12-26	00初版	陳國棟	
改版 SYM	年 月 日 DATE	變更事項 REVISIONS	設計 BY	備 注 NOTE
制圖 PRAWN		設計 DESIGNED	精密行星減速機 Precision Planetary Gear Reducer	
		品名: TITLE	GPFR090-L2- ( 19-70-90-M6 )	
		規格: SPEC	 吉嘉精密科技有限公司 GIGA Precision Technology Co., Ltd	
			A4	