


急停扭矩 (Emergency Stop Torque)	3倍額定輸出力矩 (3 times rated output torque)	
額定輸入轉速 (Rated input speed)	5000rpm	
最大輸入轉速 (Maximum input speed)	10000rpm	
背隙 (Dorsal gap)	P2	≤5arcmin
最大彎曲力矩 (maxi bending torque)	42.5Nm	
容許軸向力 (Allowable axial force)	990N	
使用壽命 (Service life)	20000hr	
效率 (Efficiency)	≥97%	
使用溫度範圍 (Operating temperature range)	-10℃～90℃	
防護等級 (protection class)	IP65	
噪音值 (Noise value)	≤56dB	
安裝方式 (Installation DIRECTION)	任意(Arbitrarily)	

減速比 (Speed ratio)	4	5	7	10
額定輸出力矩 (Rated output torque)	19Nm	22Nm	19Nm	14Nm

---	2021-2-1	00初版		陳國棟	
改版 SYM	年 月 日 DATE	變更事項 REVISIONS		設計 BY	備 注 NOTE
制圖 PRAWN		設計 DESIGNED	品名: TITLE	精密行星減速機 Precision Planetary Gear Reducer	
			規格: SPEC	GPD047-L1-(8-30-45-M3)	
			 吉嘉精密科技有限公司 GIGA Precision Technology Co., Ltd		A4