




輸出端(output)



急停扭矩 (Emergency Stop Torque)	3倍額定輸出力矩 (3 times rated output torque)	
額定輸入轉速 (Rated input speed)	5000rpm	
最大輸入轉速 (Maximum input speed)	10000rpm	
背隙 (Dorsal gap)	P1	≤6arcmin
	P2	≤9arcmin
容許徑向力 (Allowable radial force)	1530N	
容許軸向力 (Allowable axial force)	765N	
使用壽命 (Service life)	20000hr	
效率 (Efficiency)	≥95%	
使用溫度範圍 Operating temperature range)	-10°C ~ 90°C	
防護等級 (protection class)	IP65	
噪音值 (Noise value)	≤63dB	
安裝方式 (Installation DIRECTION)	任意(Arbitrarily)	

減速比 (Speed ratio)	3	4	5	7	10	14	20
額定輸出力矩 (Rated output torque)	36Nm	48Nm	60Nm	50Nm	40Nm	50Nm	40Nm

2021-2

變更事項
REVISIONS

設計 BY 備註 NOTE

制圖
PRAWN

設計
DESIGNED

品名:
TITLE

精密行星減速機
Precision Planetary Gear Reducer

G+

吉嘉精密科技有限公司
GIGA Precision Technology Co., Ltd

A4