


| | | | |
|---|---|---|----------|
| C | 急停扭矩 (Emergency Stop Torque) | 3倍額定輸出力矩 (3 times rated output torque) | |
| | 額定輸入轉速 (Rated input speed) | 5000rpm | |
| | 最大輸入轉速 (Maximum input speed) | 10000rpm | |
| | 背隙 (Dorsal gap) | P1 | ≤6arcmin |
| | | P2 | ≤9arcmin |
| | 容許徑向力 (Allowable radial force) | 1530N | |
| D | 容許軸向力 (Allowable axial force) | 765N | |
| | 使用壽命 (Service life) | 20000hr | |
| | 效率 (Efficiency) | ≥95% | |
| | 使用溫度範圍 (Operating temperature range) | -10℃～90℃ | |
| | 防護等級 (protection class) | IP65 | |
| | 噪音值 (Noise value) | ≤63dB | |
| | 安裝方式 (Installation DIRECTION) | 任意(Arbitrarily) | |

| | | | | | | | |
|---------------------------------|---------------|-------------------|------|--|---|-------------|------|
| 減速比 (Speed ratio) | 3 | 4 | 5 | 7 | 10 | 14 | 20 |
| 額定輸出力矩 (Rated output torque) | 36Nm | 48Nm | 60Nm | 50Nm | 40Nm | 50Nm | 40Nm |
| | | | | | | | |
| | | | | | | | |
| --- | 2018-12-26 | 00初版 | | | 陳國棟 | | |
| 改版 SYM | 年 月 日 DATE | 變更事項 REVISIONS | | | 設計 BY | 備 注 NOTE | |
| 制圖 PRAWN | | 設計 DESIGNED | | 品名: TITLE | 精密行星減速機 Precision Planetary Gear Reducer | | |
| | | | | 規格: SPEC | GPVR060-L1-(14-50-70-M4) | | |
| | | | |  吉嘉精密科技有限公司 GIGA Precision Technology Co., Ltd | | | A4 |