




輸出端(output)



輸入端(input)



急停扭矩 (Emergency Stop Torque)	3倍額定輸出力矩 (3 times rated output torque)	
額定輸入轉速 (Rated input speed)	4000rpm	
最大輸入轉速 (Maximum input speed)	8000rpm	

背隙 (Dorsal gap)	P1	≤5arcmin
	P2	≤8arcmin

容許徑向力 (Allowable radial force)	3250N	
容許軸向力 (Allowable axial force)	1625N	
使用壽命 (Service life)	20000hr	
效率 (Efficiency)	≥94%	

使用溫度範圍 (Operating temperature range)	-10°C~90°C	
防護等級 (protection class)	IP65	
噪音值 (Noise value)	≤60dB	
安裝方式 (Installation DIRECTION)	任意(Arbitrarily)	

減速比 (Speed ratio)	15	20	25	30	35	40	50	70	100
額定輸出力矩 (Rated output torque)	130Nm	140Nm	160Nm	150Nm	140Nm	120Nm	160Nm	140Nm	100Nm

---	2021-2-1	00初版	陳國棟	
改版 SYM	年月日 DATE	變更事項 REVISIONS	設計 BY	備注 NOTE

制圖
PRAWN 設計
DESIGNED 品名:
TITLE 精密行星減速機
Precision Planetary Gear Reducer

規格:
SPEC GPB090-L2-(19-70-90-M5)
G+® 吉嘉精密科技有限公司
GIGA Precision Technology Co., Ltd A4