




輸出端(output)




輸入端(input)



急停扭矩 (Emergency Stop Torque)	3倍額定輸出力矩 (3 times rated output torque)	
額定輸入轉速 (Rated input speed)	4000rpm	
最大輸入轉速 (Maximum input speed)	8000rpm	
背隙 (Dorsal gap)	P1	≤5arcmin
	P2	≤8arcmin
最大彎曲力矩 (maxi bending torque)	235Nm	
容許軸向力 (Allowable axial force)	2850N	
使用壽命 (Service life)	20000hr	
效率 (Efficiency)	≥94%	
使用溫度範圍 (operating temperature range)	-10°C ~ 90°C	
防護等級 (protection class)	IP65	
噪音值 (Noise value)	≤60dB	
安裝方式 (Installation DIRECTION)	任意(Arbitrarily)	

減速比 (Speed ratio)	20	25	35	40	50	70	100	C
額定輸出力矩 (Rated output torque)	130Nm	160Nm	140Nm	130Nm	160Nm	140Nm	100Nm	

---	2021-2-1	00初版	陳國棟
改版 SYM	年月日 DATE	變更事項 REVISIONS	設計 BY

制圖 PRAWN	設計 DESIGNED	品名: TITLE	精密行星減速機 Precision Planetary Gear Reducer
		規格: SPEC	GPD090-L2-(14-73-□69.6-M5)
		 吉嘉精密科技有限公司 GIGA Precision Technology Co., Ltd	A4