



急停扭矩 (Emergency Stop Torque)	3倍額定輸出力矩 (3 times rated output torque)
額定輸入轉速 (Rated input speed)	4000rpm
背隙 (Dorsal gap)	≤10arcmin
容許徑向力 (Allowable radial force)	220N
容許軸向力 (Allowable axial force)	240N
使用壽命 (Service life)	10000hr
效率 (Efficiency)	≥96%
使用溫度範圍 (Operating temperature range)	-10°C~80°C
防護等級 (protection class)	IP65
噪音值 (Noise value)	≤61dB
安裝方式 (Installation DIRECTION)	任意(Arbitrarily)

減速比 (Speed ratio)	3	4	5	7	10
額定輸出力矩 (Rated output torque)	18Nm	36Nm	40Nm	20Nm	12Nm
-----	2018-12-26	00初版	陳國棟		
改版 SYM	年月日 DATE	變更事項 REVISIONS	設計 BY	備注 NOTE	
制圖 PRAWN	設計 DESIGNED	品名: TITLE	精密行星減速機 Precision Planetary Gear Reducer		
		規格: SPEC	GPLR060-L1- (14-50-70-M4)		
		G+®	吉嘉精密科技有限公司 GIGA Precision Technology Co., Ltd	A4	