



A


輸出端(output)



B



輸入端(input)



C

急停扭矩 (Emergency Stop Torque)	3倍額定輸出力矩 (3 times rated output torque)
額定輸入轉速 (Rated input speed)	3000rpm
背隙 (Dorsal gap)	$\leq 8\text{arcmin}$
容許徑向力 (Allowable radial force)	280N
容許軸向力 (Allowable axial force)	200N
使用壽命 (Service life)	20000hr
效率 (Efficiency)	$\geq 94\%$
使用溫度範圍 (Operating temperature range)	-25°C ~ 90°C
防護等級 (protection class)	IP65
安裝方式 (Installation DIRECTION)	任意(Arbitrarily)

減速比 (Speed ratio)	16	20	25	32	40
額定輸出力矩 (Rated output torque)	12Nm	12Nm	10.5Nm	12Nm	10.5Nm
---	2018-12-26	00初版	陳國棟		
改版 SYM	年月日 DATE	變更事項 REVISIONS	設計 BY	備注 NOTE	
制圖 PRAWN	設計 DESIGNED	品名: TITLE	精密行星減速機 Precision Planetary Gear Reducer		
		規格: SPEC	GPL042-L2-(8-30-45-M3)		
			GIGA	吉嘉精密科技有限公司 GIGA Precision Technology Co., Ltd	A4