


急停扭矩 (Emergency Stop Torque)	3倍額定輸出力矩 (3 times rated output torque)	
額定輸入轉速 (Rated input speed)	4000rpm	
最大輸入轉速 (Maximum input speed)	8000rpm	
背隙 (Dorsal gap)	P1	≤5arcmin
	P2	≤8arcmin
容許徑向力 (Allowable radial force)	3250N	
容許軸向力 (Allowable axial force)	1625N	
使用壽命 (Service life)	20000hr	
效率 (Efficiency)	≥94%	
使用溫度範圍 (Operating temperature range)	-10℃～90℃	
防護等級 (protection class)	IP65	
噪音值 (Noise value)	≤60dB	
安裝方式 (Installation DIRECTION)	任意(Arbitrarily)	

減速比 (Speed ratio)	15	20	25	30	35	40	50	70	100
額定輸出力矩 (Rated output torque)	130Nm	140Nm	160Nm	150Nm	140Nm	120Nm	160Nm	140Nm	100Nm

---	2021-2-1	00初版	陳國棟	
改版 SYM	年 月 日 DATE	變更事項 REVISIONS	設計 BY	備 注 NOTE
制圖 PRAWN	設計 DESIGNED	品 名: TITLE	精密行星減速機 Precision Planetary Gear Reducer	
		規格: SPEC	GPB090-L2-(19-70-90-M6)	
		 吉嘉精密科技有限公司 GIGA Precision Technology Co., Ltd		
		A4		
	4	比例SCALE:1:5		圖紙 1 (共1)