



輸出端(output)




輸入端(input)



急停扭矩 (Emergency Stop Torque)	3倍額定輸出力矩 (3 times rated output torque)	
額定輸入轉速 (Rated input speed)	2000rpm	
最大輸入轉速 (Maximum input speed)	4000rpm	
背隙 (Dorsal gap)	P1	≤3arcmin
	P2	≤5arcmin
容許徑向力 (Allowable radial force)	50000N	
容許軸向力 (Allowable axial force)	25000N	
使用壽命 (Service life)	20000hr	
效率 (Efficiency)	≥97%	
使用溫度範圍 (Operating temperature range)	-10℃～90℃	
防護等級 (protection class)	IP65	
噪音值 (Noise value)	≤70dB	
安裝方式 (Installation DIRECTION)	任意(Arbitrarily)	

減速比 (Speed ratio)	3	4	5	7	10
額定輸出力矩 (Rated output torque)	1140Nm	1700Nm	2000Nm	1800Nm	1500Nm

---	2018-12-26	00初版	陳國棟	
改版 SYM	年 月 日 DATE	變更事項 REVISIONS	設計 BY	備 注 NOTE
制圖 PRAWN	設計 DESIGNED	品名: TITLE	精密行星減速機 Precision Planetary Gear Reducer	
		規格: SPEC	GPB220-L1-(42-114.3-200-M12)	
		 吉嘉精密科技有限公司 GIGA Precision Technology Co., Ltd		
		A4		