



C	急停扭矩 (Emergency Stop Torque)	3倍額定輸出力矩 (3 times rated output torque)
	額定輸入轉速 (Rated input speed)	4000rpm
D	背隙 (Dorsal gap)	≤12arcmin
	容許徑向力 (Allowable radial force)	220N
	容許軸向力 (Allowable axial force)	240N
	使用壽命 (Service life)	10000hr
	效率 (Efficiency)	≥93%
	使用溫度範圍 (Operating temperature range)	-10℃~80℃
	防護等級 (protection class)	IP65
	噪音值 (Noise value)	≤61dB
	安裝方式 (Installation DIRECTION)	任意(Arbitrarily)

減速比 (Speed ratio)	15	20	25	30	35	40	50	70	100
額定輸出力矩 (Rated output torque)	36Nm	36Nm	36Nm	36Nm	36Nm	36Nm	36Nm	36Nm	36Nm

---	2018-12-26	00初版	陳國棟
改版 SYM	年 月 日 DATE	變更事項 REVISIONS	設計 BY
制圖 PRAWN	設計 DESIGNED	品名: TITLE	精密行星減速機 Precision Planetary Gear Reducer
		規格: SPEC	GPLR060-L2- ( 14-50-70-M4 )
		G+ <sup>®</sup> 吉嘉精密科技有限公司 GIGA Precision Technology Co., Ltd	
			A4