


C	急停扭矩 (Emergency Stop Torque)	3倍額定輸出力矩 (3 times rated output torque)
	額定輸入轉速 (Rated input speed)	3500rpm
	背隙 (Dorsal gap)	≤10arcmin
	容許徑向力 (Allowable radial force)	400N
D	容許軸向力 (Allowable axial force)	420N
	使用壽命 (Service life)	10000hr
	效率 (Efficiency)	≥96%
	使用溫度範圍 (Operating temperature range)	-10℃～80℃
	防護等級 (protection class)	IP65
	噪音值 (Noise value)	≤63dB
	安裝方式 (Installation DIRECTION)	任意(Arbitrarily)

減速比 (Speed ratio)	3	4	5	7	10
額定輸出力矩 (Rated output torque)	40Nm	900Nm	110Nm	40Nm	22Nm

---		2018-12-26		00初版		陳國棟	
改版 SYM		年 月 日 DATE		變更事項 REVISIONS		設計 BY 備 注 NOTE	
制圖 PRAWN		設計 DESIGNED		品名: TITLE		精密行星減速機 Precision Planetary Gear Reducer	
				規格: SPEC		GPLR090-L1- (19-70-90-M6)	
				 吉嘉精密科技有限公司 GIGA Precision Technology Co., Ltd		A4	
		4		比例SCALE:1:5		圖紙 1 (共1)	