


C	急停扭矩 (Emergency Stop Torque)	3倍額定輸出力矩 (3 times rated output torque)	
	額定輸入轉速 (Rated input speed)	4000rpm	
	最大輸入轉速 (Maximum input speed)	8000rpm	
	背隙 (Dorsal gap)	P1	≤9arcmin
		P2	≤11arcmin
	容許徑向力 (Allowable radial force)	6700N	
D	容許軸向力 (Allowable axial force)	3350N	
	使用壽命 (Service life)	20000hr	
	效率 (Efficiency)	≥92%	
	使用溫度範圍 (Operating temperature range)	-10℃～90℃	
	防護等級 (protection class)	IP65	
	噪音值 (Noise value)	≤68dB	
	安裝方式 (Installation DIRECTION)	任意(Arbitrarily)	

減速比 (Speed ratio)	15	25	30	35	40	50	60	70	80	100	140	200	C
額定輸出力矩 (Rated output torque)	325Nm	325Nm	310Nm	300Nm	260Nm	230Nm	310Nm	300Nm	260Nm	230Nm	300Nm	230Nm	
---	2021-2-1	00初版							陳國棟				
改版 SYM	年 月 日 DATE	變更事項 REVISIONS							設計 BY	備 注 NOTE			
制圖 PRAWN		設計 DESIGNED		品名: TITLE		精密行星減速機 Precision Planetary Gear Reducer							
				規格: SPEC		GPBR115-L2-(22-110-145-M8)							
				<div> 吉嘉精密科技有限公司 GIGA Precision Technology Co., Ltd</div>								A4	