




輸出端(output)



輸入端(input)



A

A

B

B

C

C

D

D

急停扭矩 (Emergency Stop Torque)	3倍額定輸出力矩 (3 times rated output torque)	
額定輸入轉速 (Rated input speed)	3000rpm	
最大輸入轉速 (Maximum input speed)	6000rpm	
背隙 (Dorsal gap)	P1	≤5arcmin
	P2	≤8arcmin
最大彎曲力矩 (maxi bending torque)	3064Nm	
容許軸向力 (Allowable axial force)	16660N	
使用壽命 (Service life)	20000hr	
效率 (Efficiency)	≥97%	
使用溫度範圍 (Operating temperature range)	-10°C~90°C	
防護等級 (protection class)	IP65	
噪音值 (Noise value)	≤67dB	
安裝方式 (Installation DIRECTION)	任意(Arbitrarily)	

減速比 (Speed ratio)	4	5	7	10
額定輸出力矩 (Rated output torque)	1100Nm	1200Nm	1100Nm	900Nm

改版 SYM	年月日 DATE	變更事項 REVISIONS	設計 BY	備註 NOTE

制圖 PRAWN	設計 DESIGNED	品名: TITLE	精密行星減速機 Precision Planetary Gear Reducer
		規格: SPEC	GPD200-L1-(42-114.3-200-M12)
G+ ® 吉嘉精密科技有限公司 GIGA Precision Technology Co., Ltd			A4