





Dresser™ MRD0160B4C Rotary Meter

Temperature Range	deg.C	-40 to +70	Displaced Volume/Revolution	dm ³	1.05
Base Rating (Qmax)	m ³ /h	160	Drive Rate	m ³ /rev	1.0
Max. Operating Pressure	bar	16	Min. Odometer Reading	m ³ /h	0.02
Leak Test (1.1 x MOP)	bar	17.6	Odometer Turnover	hrs	7.13
Static Test (1.5 x MOP)	bar	24	Nominal Pipe Size	mm	80
Rangeability +/- 1%	ratio	120:1	Flange to Flange	mm	171
Rangeability +/- 2%	ratio	160:1	Flange Connection	DIN	DN80 PN16
Start Rate	m ³ /h	0.0340	Bolts per Flange	Qty	8
Stop Rate	m ³ /h	0.0230	Bolt Size	mm	M16 x 40
Flow Rate @ 1.25mbar	m ³ /h	130	Flange Bolt Hole Depth	mm	24.0
Avg. Differential, 100% Flow	mbar	1.45	Bolt Torque: Lubricated/Non-Lub.	N-m	74/81
Max. Pressurisation Rate	kPa/sec	35	Oil Capacity (Side Inlet)	ml	47
Max. Operating Speed	rpm	1667	Oil Capacity (Top Inlet)	ml	225
Gear Ratio	ratio	952.32			



Meter	C mm	L mm	M mm	O mm	P mm	R mm	Z	Flange	Weight Kg
5M	460	195	265	177	171	89	8	DN80	16