





Dresser™ MRD0250B4C Rotary Meter

Temperature Range	deg.C	-40 to +70	Displaced Volume/Revolution	dm ³	2.77
Base Rating (Qmax)	m ³ /h	250	Drive Rate	m ³ /rev	1.0
Max. Operating Pressure	bar	16	Min. Odometer Reading	m ³ /h	0.02
Leak Test (1.1 x MOP)	bar	17.6	Odometer Turnover	yrs	4.57
Static Test (1.5 x MOP)	bar	24	Nominal Pipe Size	mm	80
Rangeability +/- 1%	ratio	70:1	Flange to Flange	mm	241
Rangeability +/- 2%	ratio	125:1	Flange Connection	DIN	DN80 PN16
Start Rate	m ³ /h	0.1510	Bolts per Flange	Qty	8
Stop Rate	m ³ /h	0.0960	Bolt Size	mm	M16 x 40
Flow Rate @ 1.25mbar	m ³ /h	230	Flange Bolt Hole Depth	mm	24
Avg. Differential, 100% Flow	mbar	1.73	Bolt Torque: Lubricated/Non-Lub.	N-m	74/81
Max. Pressurisation Rate	kPa/sec	35	Oil Capacity (Side Inlet)	ml	100
Max. Operating Speed	rpm	1500	Oil Capacity (Top Inlet)	ml	645
Gear Ratio	ratio	360.64			



Meter	C	L	M	O	P	R	Z	Flange	Weight
	mm	mm	mm	mm	mm	mm			Kg
9M-3"	485	205	280	226	241	113	8	DN80	30