Results on PBM-driven ODE discovery and ODE parameter estimation

Urh Primožič, IJS

ODE discovery with Probmot

- processes between entities (predator-prey models,...)
- build a list of possible models $[\vec{x}'(t) = \vec{F}_i(\vec{x}(t), t, \theta^{(i)})]_i$
- **estimate model parameters** $\theta^{(i)}$
- evaluate all possible models

Structure changes

- migration from Java to Python
- gradient opt instead of EA
- magnitutes faster parameter estimation
- conditional statemets support

$$x'(t) = \begin{cases} f(x,t,\theta) & \phi(x,t,\theta) > 0 \\ g(x,t,\theta) & \text{otherwise} \end{cases}$$


Other possible solutions

- JIT compiled $F(x, t, \theta)$
- clever structure search
- precise estimation just for best candidates

Relaxed conditionals

$$F = \begin{cases} f & \theta \geq 0 \\ g & \text{otherwise} \end{cases}$$

$$\tilde{F} = \frac{f+g}{2} + \frac{f-g}{2} \tanh \frac{\theta}{\varepsilon}$$



Parameter estimation

- $x\colon [t_0, t_1] \to \mathbb{R}^n$
- $x_{\text{obs}} = (x_{o_1}, x_{o_2}, \ldots, x_{o_{n_{\text{obs}}}}) \in \mathbb{R}^{n_{\text{obs}}}$

Given

- ODE $x'(t) = F(x(t), t, \theta)$
- measurments $(t_i, x_{\text{obs}}(t_i) + \epsilon_i)$, $\epsilon_i \sim N(\mu, \sigma^2)$


estimate θ.

Integration using multishooting[1]

- integration: pick $x(t_0)$, solve ODE for $x_\theta(t)$, min discrepancy $\mathcal{L}(x_\theta)$ on data
- problem: caotic system
- solution: integrate shorter intervals, join trajectories

[1] Ozgur Aydogmus and Ali Hakan Tor (2020). *A Modified Multiple Shooting Algorithm for Parameter Estimation in ODEs Using Adjoint Sensitivity Analysis*. arXiv: 2006.15740 [math.OC].

Integration using multishooting



Multiple shooting for $x(t) = \sin(\theta t)/t$ on $[1, 5]$, $\theta_{\text{true}} = 1$, evaluated at $\theta = 0.7$ with 10 intervals. Data: 16 points with noise $\mathcal{N}(0, 0.05^2)$; initial values perturbed by $\mathcal{U}(-0.1, 0.1)$.

Integration using multishooting[2]

Multishooting

minimize discrepancy on data

$$\sum_i \mathcal{L}(x_i), \quad \text{where } x_i' = F(x_i, t, \theta), x_i(t_i) = s_i$$

on

$$x_i(t_{i+1}) = s_i \quad \forall i = 0, 1, \ldots N_{\text{subintervals}}$$

[2] Ozgur Aydogmus and Ali Hakan Tor (2020). *A Modified Multiple Shooting Algorithm for Parameter Estimation in ODEs Using Adjoint Sensitivity Analysis*. arXiv: 2006.15740 [math.OC].

Gradient matching for fully-observed systems

- $\hat{x}(t)$ - interpolant of the data
- interpolation: gaussian processes[3], cubic splines[4]

Least squares formulation

Find $\operatorname{argmin} \|\hat{x}'(t) - F(\hat{x}(t), t, \theta)\|$

[3] Philippe Wenk et al. (2019). *Fast Gaussian Process Based Gradient Matching for Parameter Identification in Systems of Nonlinear ODEs*. arXiv: 1804.04378 [stat.ML].

[4] J. M. Varah (1982). "A Spline Least Squares Method for Numerical Parameter Estimation in Differential Equations". In: *SIAM Journal on Scientific and Statistical Computing* 3.1, pp. 28–46. DOI: 10.1137/0903003. eprint: https://doi.org/10.1137/0903003.

Integral matching[5]

Derivatives are noisy $\propto \frac{1}{|t_{i+1}-t_i|}$!

Minimize

$$\int_{t_0}^{t_1} \left\| \hat{x}(t) - \hat{x}(\phi(t)) - \int_{\phi(t)}^{t} F(\hat{x}(\tau), \tau, \theta) d\tau \right\| dt$$

[5] Baptiste T Rossi (2025). *ODE Parameter Identification: An Integral Matching Approach.*

Design choiches and challanges

- bayesian vs least squares
- two-step approach vs joint estimation
- choose integration interval
- kernel choice
- caotic loss surface -**homotopic approaches**[6]

[6] Chandrika Vyasarayani et al. (Mar. 2012). "Single-shooting homotopy method for parameter identification in dynamical systems". In: *Physical Review E* 85, p. 036201. DOI: 10.1103/PhysRevE.85.036201.

Collocation[7]

- $x\colon I \to R^n$ partially observed
- choose l *collocation* points
  $(\tau_1, s_1), (\tau_2, s_2), \cdots, (\tau_l, s_l) \in I \times R^n$
- $\hat{x}(t)$: interpolant of $(\tau_i, s_i)_i$, hyperparameters ϕ
- choose such $s = (s_1, \cdots, s_l), \phi$ that $\hat{x}(t)$ solves ODE and matches data

[7] Samuel W. K. Wong et al. (2023). *MAGI: A Package for Inference of Dynamic Systems from Noisy and Sparse Data via Manifold-constrained Gaussian Processes.* arXiv: 2203.06066 [stat.CO].

Collocation

Let $\hat{x}(t)$ interpolant of (τ_i, s_i) with hyperparameters ϕ and collocation points $s = (s_1, \cdots, s_l)$. Let (t_i, y_i) be a noisy set of measurments.

Find s, θ, phi, minimizing[a]

$$||\hat{x}(t_i) - y_i||$$

such that[b]

$$\hat{x}'(t) = F(\hat{x}(t), t, \theta).$$

[a] Wong et al. 2023 use bayesian approach

[b] Gradient matching. Integral matching can be used as well.


Collocation vs integration

multishooting	collocation
Freezes θ, solves ODE	Changes both θ and s until trajectory satisfies ODE
Additional parameters are initial values	Additional parameters are collocation points of the interpolant

Desing choices and hyperparameters

- bayesian, least squares, *constrained problem*
- gradient vs integral matching
- collocation points, manifold points, discrepancy points

Lotka–Volterra




numbers at the line ends: nRMSE against the truth (RMSE / std of the true component), training / test range

truth training data test data


$$x_1' = \theta_1 x_1 - \theta_2 x_1 x_2, \quad x_2' = -\theta_3 x_2 + \theta_4 x_1 x_2$$


Protein transduction



$$S' = -\theta_1 S - \theta_2 SR + \theta_3 R_S, S'_d = \theta_1 S, R' = -\theta_2 SR + \theta_3 R_S + \theta_5 \frac{R_{pp}}{\theta_6 + R_{pp}}$$

$$R'_S = \theta_2 SR - \theta_3 R_S - \theta_4 R_S, R'_{pp} = \theta_4 R_S - \theta_5 \frac{R_{pp}}{\theta_6 + R_{pp}}$$


Free runs: the data, ProBMoT and our two best methods; every run's error right of its panel
data
ProBMoT
integral matching, cumulative
collocation
multiple shooting
best in the panel (error in bold)
Lake Zurich train 2000
test 2001-2002
phyto.conc
0.326
0.359
0.290
0.726
0.427
0.434
Lake Kasumigaura train 1990
test 1991-1992
0.420
0.413
29.190
16.069
Lake Bled train 1996
test 1997
0.521
0.198
0.350
1.154
1.363
1.217



Errors: RMSE of phyto.conc in free runs (lower is better); every method's structure is the one with its lowest training error. ProBMoT: its task's settings (DE, CVODE at 1e-3), simulated here by PyBM.
Zurich: one free run over the training years and one over the test years, each from the data on its first day; RMSE on the measured days (12 a year). Collocation: weekly seeds, the ODE as the week's integral.
Bled: the seasons are separate (no data over the winters): every season is a run from the data on its first day. Collocation: daily seeds, no ODE across a winter.
ProBMoT on Bled: only on collocation's structure; it fits one initial concentration to all four seasons.

Research directions

- small, domain-specific benchmarks, just integration methods
- 2026: 1100 synthetich benchmark problems - no methods
- **no good benchmark**
- collocation seems to join different approaches together $\rightarrow$ better method?