

Networks and Causal Inference Short Course: Part 3

TingFang Lee, Ashley Buchanan, URI Avenir Team

2026-04-30

Using Data from the Transmission Reduction Intervention Project in Athens, Greece

Download the data and load it into R Studio

This is a simulated toy dataset made for this course. It is based on data collected from the Transmission Reduction Intervention Project in Athens Greece. Public data here: <https://www.icpsr.umich.edu/web/NAHDAP/studies/39059/versions/V2/staff>

Read more: <https://pubmed.ncbi.nlm.nih.gov/27917890/>

Load packages and function script...

```
# -----  
# 1. Read data and functions into R  
# -----  
  
# Set the working directory to the current file's folder  
# install.packages("rstudioapi")  
library(rstudioapi)  
setwd(dirname(rstudioapi::getActiveDocumentContext()$path))  
getwd() # verify the change  
  
## [1] "/Users/buchanan/Library/CloudStorage/OneDrive-UniversityofRhodeIsland/R01 MSM HIV Networks/Train  
library(lme4)  
  
## Warning: package 'lme4' was built under R version 4.4.3  
  
library(plyr)  
library(dplyr)  
library(igraph)  
library(numDeriv)  
library(gtools)  
library(doParallel)  
library(foreach)  
library(knitr)  
  
## Warning: package 'knitr' was built under R version 4.4.3  
  
library(kableExtra)  
library(ggplot2)  
library(forcats)  
rm(list = ls())  
  
no_cores <- detectCores() - 1  
registerDoParallel(cores=no_cores)
```

```
#Can source GitHub page
#source("https://github.com/uri-ncipher/Nearest-Neighbor-estimators/blob/main/functions.R?raw=TRUE")
source("IPW_functions.R")
source("gcomp_dr_v2.R") #Ting-Fang removed warnings for bootstrap
```

Data Preparation

Read in the synthetic nodes and edges data sets for creating the simulated network.

```
# -----
# 2. Data Preparation
# -----


nodes <- read.csv("../TRIP_network_simulation/TRIPsim_nodes.csv")
edges <- read.csv("../TRIP_network_simulation/TRIPsim_edges.csv")

net0=graph_from_data_frame(d=edges, vertices = nodes, directed=F) # create network based on the nodes
```

Network visualization

```
# -----
# 3. Network Visualizaiton
# -----

# plot the network generated above
plot(net0, vertex.size=1, vertex.label=NA, vertex.color="cadetblue3", vertex.frame.color="cadetblue3")
```



Prepare the data for modeling

```
# -----
# 3. Data Preparation for Modeling
# -----

# Save the number of individuals (nodes) and number of components
n=length(V(net0)) # number of individuals
m=components(net0)$no # number of components

# generate a dataset with three columns, the first column is participant id (node id),
```

```

# the second column is number of nearest neighbors for each participant (is also node degree),
# the third column indicate which component the participant is in.
df=data.frame(id=1:n, na=unlist(lapply(1:n, num_neighbors, net=net0)),
              component=components(net0)$membership)

# assign treatment, outcome, and baseline covariates to data
df$treatment=nodes$treatment
df$outcome=nodes$outcome
df$age=nodes$age
df$age10=nodes$age/10 #age per 10 years
df$agebin=ifelse(nodes$age>35,1,0) #age >35 years old
df$posneg=nodes$posneg
df$date=nodes$date
df$share=nodes$share
df$education=nodes$education
df$employment=nodes$employment
df$na_a= unlist(lapply(1:n, trt_neighbors, net=net0))
df$notna_a=df$na-df$na_a

# six covariates, including age
base_covariate=c("age10", "posneg", "date", "share", "education", "employment")

# averaging baseline covariates (average of nearest neighbors' baseline covariate values)
# Note: show code for averaging "age10" and "agebin" as examples. Average of other neighbor covariates
#       Example code: df$avg_var1=unlist(lapply(1:n, avg_neighbors, net=net0, variable="var1")) # "var1"
df$avg_agebin=unlist(lapply(1:n, avg_neighbors, net=net0, variable="agebin"))
df$avg_age10 =unlist(lapply(1:n, avg_neighbors, net=net0, variable="age10"))

df$avg_posneg = nodes$avg_posneg
df$avg_date = nodes$avg_date
df$avg_share = nodes$avg_share
df$avg_education = nodes$avg_education
df$avg_employment = nodes$avg_employment

avg_covariate=c("avg_age10", "avg_posneg", "avg_date", "avg_share", "avg_education", "avg_employment")

```

Modeling

In this section, we will apply both IPW1 and IPW2 estimators for the average potential outcomes and corresponding causal effects. An individual's exposure/treatment and allocation strategy α jointly determine the average potential outcome (allocation strategy represents the probability that individuals in nearest neighbors set receiving the exposure/treatment in the counterfactual scenario, so it is a numeric value between 0 and 1). For each estimator, the R programs will output the **point estimation and the estimated variance of average potential outcomes** $\hat{Y}(1, \alpha)$, $\hat{Y}(0, \alpha)$, $\hat{Y}(\alpha)$ under three different allocation strategies α (i.e., 0.25, 0.50, and 0.75), respectively. Also, the R program will output the **point estimation and estimated variance of four causal effects: Direct (DE), Indirect (IE), Total (TE), and Overall effect (OE)**.

Equations for calculating the four causal effects are:

- $\widehat{DE} = \hat{Y}(1, \alpha) - \hat{Y}(0, \alpha)$
- $\widehat{IE} = \hat{Y}(0, \alpha_0) - \hat{Y}(0, \alpha_1)$
- $\widehat{TE} = \hat{Y}(1, \alpha_0) - \hat{Y}(0, \alpha_1)$
- $\widehat{OE} = \hat{Y}(\alpha_0) - \hat{Y}(\alpha_1)$,

where α_0 , α_1 both represents allocation strategies, and $\alpha_0 \neq \alpha_1$ (Note: The associated paper compared the estimated average potential outcomes with α_1 to α_0 for the indirect, total, and overall effects. The code here compared the estimated average potential outcomes with α_0 to α_1 for the indirect, total, and overall effects). Users can set any values between 0 and 1 for α_0 and α_1 . If given α is a vector, then the causal contrasts will produce pairwise comparisons in the sequential order of the values in α . For example, if $\alpha = c(0.75, 0.25, 0.50)$, the contrasts for spillover effects will compare

- (i) $\alpha_0 = 0.75$ versus $\alpha_1 = 0.25$;
- (ii) $\alpha_0 = 0.75$ versus $\alpha_1 = 0.50$;
- (iii) $\alpha_0 = 0.25$ versus $\alpha_1 = 0.50$.

IPW1

Using IPW1 to estimate the average potential outcomes and causal effects under allocation strategies α .

```
# -----
# 4a. IPW1 Estimator
# -----

alpha=c(0.5, 0.4, 0.3, 0.2) # set allocation strategies

base_covariate=c("agebin", "posneg", "date", "share", "education", "employment")
avg_covariate=c("avg_agebin", "avg_posneg", "avg_date", "avg_share", "avg_education", "avg_employment")
#Note: Age variable continuous removed due to convergence issue, used binary for now

IPW1 <- IPW_1_model(df, base_covariate, alpha)
IPW1
```

```
## [[1]]
##      a=1      a=0      margin alpha      type
## 1 0.3092160 0.4335645 0.3713902    0.5 point estimate
## 2 0.4320560 0.4732245 0.4567571    0.4 point estimate
## 3 0.5791977 0.5026645 0.5256245    0.3 point estimate
## 4 0.7290222 0.5168437 0.5592794    0.2 point estimate
## 5 1.1738709 2.0311950 1.5666401    0.5      variance
## 6 2.4318229 1.9349669 2.1197851    0.4      variance
## 7 4.3265120 1.7668522 2.4098753    0.3      variance
## 8 6.3788055 1.4558084 2.1576224    0.2      variance
##
## [[2]]
##      estimation alpha0 alpha1      type
## 1 -0.124348490    0.5    0.5 Direct
## 2 -0.041168492    0.4    0.4 Direct
## 3  0.076533148    0.3    0.3 Direct
## 4  0.212178426    0.2    0.2 Direct
## 5  0.143571364    0.5    0.5 Var DE
## 6  0.058017587    0.4    0.4 Var DE
## 7  0.594642103    0.3    0.3 Var DE
## 8  1.767408985    0.2    0.2 Var DE
## 9 -0.039659982    0.5    0.4 Indirect
## 10 -0.069100040    0.5    0.3 Indirect
## 11 -0.083279242    0.5    0.2 Indirect
## 12 -0.029440057    0.4    0.3 Indirect
## 13 -0.043619259    0.4    0.2 Indirect
## 14 -0.014179202    0.3    0.2 Indirect
## 15  0.001798721    0.5    0.4 Var IE
```

```
## 16 0.011661857 0.5 0.3 Var IE
## 17 0.053205013 0.5 0.2 Var IE
## 18 0.004448133 0.4 0.3 Var IE
## 19 0.036588249 0.4 0.2 Var IE
## 20 0.015745311 0.3 0.2 Var IE
## 21 -0.164008472 0.5 0.4 Total
## 22 -0.193448530 0.5 0.3 Total
## 23 -0.207627732 0.5 0.2 Total
## 24 -0.070608549 0.4 0.3 Total
## 25 -0.084787751 0.4 0.2 Total
## 26 0.062353946 0.3 0.2 Total
## 27 0.117491953 0.5 0.4 Var TE
## 28 0.079671521 0.5 0.3 Var TE
## 29 0.031114722 0.5 0.2 Var TE
## 30 0.077840048 0.4 0.3 Var TE
## 31 0.145135878 0.4 0.2 Var TE
## 32 0.788662594 0.3 0.2 Var TE
## 33 -0.085366830 0.5 0.4 Overall
## 34 -0.154234229 0.5 0.3 Overall
## 35 -0.187889172 0.5 0.2 Overall
## 36 -0.068867399 0.4 0.3 Overall
## 37 -0.102522341 0.4 0.2 Overall
## 38 -0.033654943 0.3 0.2 Overall
## 39 0.042070257 0.5 0.4 Var OE
## 40 0.091552822 0.5 0.3 Var OE
## 41 0.049549859 0.5 0.2 Var OE
## 42 0.009578877 0.4 0.3 Var OE
## 43 0.001469209 0.4 0.2 Var OE
## 44 0.007435416 0.3 0.2 Var OE
```

In the output above,

- The **section** `[[1]]` displays the point estimates (type = “point estimate” in the output) and estimated variances (type = “variance” in the output) for the average potential outcomes under three different allocation strategies (i.e., $\alpha = 0.25, 0.50, 0.75$) and each individual exposure ($a = 0, a = 1$, and margin). “Margin” is the average potential outcomes for a particular allocation strategy, regardless of individual exposure status.
- The **section** `[[2]]` displays the point estimates (type = “Direct”, “Indirect”, “Total”, “Overall” in the output) and estimated variances (type = “Var DE”, “Var IE”, “Var TE”, “Var OE” in the output) of four causal effects: direct, indirect, total and overall effects, corresponding to particular allocation strategies (α_0 and α_1). The estimated values are shown in “estimation” column in the output above.

IPW2

Using IPW2 to estimate the average potential outcomes and causal effects under allocation strategies α .

```
# -----
# 4b. IPW2 Estimator
# -----
#change back to age per 10 year increase
base_covariate=c("age10", "posneg", "date", "share", "education", "employment")
avg_covariate=c("avg_age10", "avg_posneg", "avg_date", "avg_share", "avg_education", "avg_employment")

alpha=c(0.5, 0.4, 0.3, 0.2) # set allocation strategies

formula_1=paste("cbind(na_a, notna_a)", "~", "treatment", "+",
```

```

paste(base_covariate, collapse = "+"), "+",
paste(avg_covariate, collapse = "+"))
formula_2=paste("treatment", "~", paste(base_covariate, collapse = "+"))
M1=glm(formula_1, family = binomial(link = "logit"), data=df)
M2=glm(formula_2, family = binomial(link = "logit"), data=df)

IPW2 <- IPW_2_model(df, M1, M2, alpha)
IPW2

```

```

## [[1]]
##           a=1           a=0      margin alpha           type
## 1 0.220810727 0.59176096 0.40628585 0.5 point estimate
## 2 0.292392238 0.59042302 0.47121071 0.4 point estimate
## 3 0.387385956 0.57233698 0.51685167 0.3 point estimate
## 4 0.505408711 0.54206916 0.53473707 0.2 point estimate
## 5 0.006943618 0.09001969 0.03029339 0.5      variance
## 6 0.012269497 0.05617945 0.02906814 0.4      variance
## 7 0.023480049 0.02942577 0.02347725 0.3      variance
## 8 0.044905869 0.01507811 0.01736360 0.2      variance
##
## [[2]]
##      estimation alpha0 alpha1      type
## 1  -0.3709502369    0.5    0.5 Direct
## 2  -0.2980307830    0.4    0.4 Direct
## 3  -0.1849510226    0.3    0.3 Direct
## 4  -0.0366604489    0.2    0.2 Direct
## 5   0.0727530662    0.5    0.5 Var DE
## 6   0.0397805488    0.4    0.4 Var DE
## 7   0.0198324068    0.3    0.3 Var DE
## 8   0.0230003806    0.2    0.2 Var DE
## 9   0.0013379431    0.5    0.4 Indirect
## 10  0.0194239855    0.5    0.3 Indirect
## 11  0.0496918036    0.5    0.2 Indirect
## 12  0.0180860424    0.4    0.3 Indirect
## 13  0.0483538604    0.4    0.2 Indirect
## 14  0.0302678181    0.3    0.2 Indirect
## 15  0.0050022015    0.5    0.4 Var IE
## 16  0.0222549084    0.5    0.3 Var IE
## 17  0.0485650418    0.5    0.2 Var IE
## 18  0.0061643281    0.4    0.3 Var IE
## 19  0.0224483697    0.4    0.2 Var IE
## 20  0.0050978758    0.3    0.2 Var IE
## 21 -0.3696122938    0.5    0.4 Total
## 22 -0.3515262514    0.5    0.3 Total
## 23 -0.3212584334    0.5    0.2 Total
## 24 -0.2799447407    0.4    0.3 Total
## 25 -0.2496769226    0.4    0.2 Total
## 26 -0.1546832045    0.3    0.2 Total
## 27  0.0412503517    0.5    0.4 Var TE
## 28  0.0175815581    0.5    0.3 Var TE
## 29  0.0064830895    0.5    0.2 Var TE
## 30  0.0170154604    0.4    0.3 Var TE
## 31  0.0069144403    0.4    0.2 Var TE
## 32  0.0110807476    0.3    0.2 Var TE

```

```
## 33 -0.0649248621    0.5    0.4 Overall
## 34 -0.1105658262    0.5    0.3 Overall
## 35 -0.1284512251    0.5    0.2 Overall
## 36 -0.0456409641    0.4    0.3 Overall
## 37 -0.0635263630    0.4    0.2 Overall
## 38 -0.0178853989    0.3    0.2 Overall
## 39  0.0004946305    0.5    0.4 Var OE
## 40  0.0032369653    0.5    0.3 Var OE
## 41  0.0100291441    0.5    0.2 Var OE
## 42  0.0013422311    0.4    0.3 Var OE
## 43  0.0067075875    0.4    0.2 Var OE
## 44  0.0021150165    0.3    0.2 Var OE
```

In the output above,

- The **section** `[[1]]` displays the point estimates (type = “point estimate” in the output) and estimated variances (type = “variance” in the output) for the average potential outcomes under three different allocation strategies (i.e., $\alpha = 0.75, 0.50, 0.25$) and each individual exposure ($a = 0, a = 1$, and margin). “Margin” is the average potential outcomes for a particular allocation strategy, regardless of individual exposure status.
- The **section** `[[2]]` displays the point estimates (type = “Direct”, “Indirect”, “Total”, “Overall” in the output) and estimated variances (type = “Var DE”, “Var IE”, “Var TE”, “Var OE” in the output) of four causal effects: direct, indirect, total and overall effects, corresponding to particular allocation strategies (α_0 and α_1). The estimated values are shown in “estimation” column in the output above.

Now, we provide example code for an outcome-model based approach, g-computation. We use assumptions similar to IPW2 regarding the covariates for confounding from an individual’s contacts in the network. We obtain 95% confidence intervals using a bootstrap on each individual and the summary information for their contacts’ exposures and covariates.

```
# -----
# 4c. G-computation Estimator (similar assumptions to IPW2)
# -----

#Obtain G-computation estimates with bootstrap CIs
#Uses similar assumptions for interference as IPW2
#Bootstrap unit is each individual and the information for their contacts

alpha <- c(0.5, 0.4, 0.3, 0.2)

res_gcomp <- gcomp_with_bootstrap(
  data = df,
  alpha = alpha,
  z_covariates = base_covariate,
  zn_covariates = avg_covariate,
  B = 1000,
  seed = 2026
)

res_gcomp$results
```

```
##      estimation alpha0 alpha1    type      lower      upper
## 1  -0.2942459106    0.5    0.5 Direct -0.50761492 0.06533357
## 2  -0.2293979865    0.4    0.4 Direct -0.42669257 0.06419693
## 3  -0.1598010505    0.3    0.3 Direct -0.33798759 0.07663089
## 4  -0.0854203130    0.2    0.2 Direct -0.25944479 0.12368184
```

## 5	0.0216511692	0.5	0.5	Var DE	NA	NA
## 6	0.0164000766	0.4	0.4	Var DE	NA	NA
## 7	0.0120227666	0.3	0.3	Var DE	NA	NA
## 8	0.0091832561	0.2	0.2	Var DE	NA	NA
## 9	0.0200839175	0.5	0.4	Indirect	-0.01693391	0.04428758
## 10	0.0403768693	0.5	0.3	Indirect	-0.03420301	0.09193725
## 11	0.0608319406	0.5	0.2	Indirect	-0.05179040	0.14283959
## 12	0.0202929518	0.4	0.3	Indirect	-0.01726860	0.04778418
## 13	0.0407480231	0.4	0.2	Indirect	-0.03485546	0.09824659
## 14	0.0204550713	0.3	0.2	Indirect	-0.01758550	0.05084486
## 15	0.0002468110	0.5	0.4	Var IE	NA	NA
## 16	0.0010415511	0.5	0.3	Var IE	NA	NA
## 17	0.0024635162	0.5	0.2	Var IE	NA	NA
## 18	0.0002745770	0.4	0.3	Var IE	NA	NA
## 19	0.0011522778	0.4	0.2	Var IE	NA	NA
## 20	0.0003021185	0.3	0.2	Var IE	NA	NA
## 21	-0.2741619931	0.5	0.4	Total	-0.47240345	0.07597257
## 22	-0.2538690413	0.5	0.3	Total	-0.43353718	0.09322211
## 23	-0.2334139700	0.5	0.2	Total	-0.40302065	0.10170925
## 24	-0.2091050347	0.4	0.3	Total	-0.39125631	0.07023090
## 25	-0.1886499634	0.4	0.2	Total	-0.36128077	0.09155945
## 26	-0.1393459792	0.3	0.2	Total	-0.30901130	0.08943311
## 27	0.0196262256	0.5	0.4	Var TE	NA	NA
## 28	0.0180032470	0.5	0.3	Var TE	NA	NA
## 29	0.0168711890	0.5	0.2	Var TE	NA	NA
## 30	0.0148275764	0.4	0.3	Var TE	NA	NA
## 31	0.0137482572	0.4	0.2	Var TE	NA	NA
## 32	0.0110057702	0.3	0.2	Var TE	NA	NA
## 33	-0.0352798432	0.5	0.4	Overall	-0.05516482	0.02138685
## 34	-0.0588057709	0.5	0.3	Overall	-0.10258781	0.04539049
## 35	-0.0692069521	0.5	0.2	Overall	-0.13731253	0.07315086
## 36	-0.0235259276	0.4	0.3	Overall	-0.04687556	0.02419022
## 37	-0.0339271089	0.4	0.2	Overall	-0.08552364	0.05206213
## 38	-0.0104011812	0.3	0.2	Overall	-0.03868068	0.02949115
## 39	0.0003810760	0.5	0.4	Var OE	NA	NA
## 40	0.0013757670	0.5	0.3	Var OE	NA	NA
## 41	0.0027839896	0.5	0.2	Var OE	NA	NA
## 42	0.0003201982	0.4	0.3	Var OE	NA	NA
## 43	0.0011822972	0.4	0.2	Var OE	NA	NA
## 44	0.0002889667	0.3	0.2	Var OE	NA	NA

Now, we provide example code for an doubly-robust approach, augmented IPW. We use assumptions similar to IPW2 regarding the covariates for confounding from an individual's contacts in the network. We obtain 95% confidence intervals using a bootstrap on each individual and the summary information for their contacts' exposures and covariates.

```
# -----
# 4d. Augmented IPW Estimator (doubly robust (DR1))
# -----

#Obtain DR1 Estimates with Bootstrap CIs
#Uses similar assumptions for interference as IPW2
#Bootstrap unit is each individual and the information for their contacts
alpha=c(0.5, 0.4, 0.3, 0.2) # set allocation strategies
```

```

res_dr <- dr_with_bootstrap(
  data = df,
  alpha = alpha,
  z_covariates = base_covariate,
  zn_covariates = avg_covariate,
  B = 1000, #how many bootstrap samples do we need? Usually 1000 for CIs, but can have less for demonstr
  seed = 2026
)
res_dr$results

```

##	estimation	alpha0	alpha1	type	lower	upper
## 1	-0.4455634514	0.5	0.5	Direct	-0.93715545	-0.016765493
## 2	-0.3577497959	0.4	0.4	Direct	-0.76750642	0.030082246
## 3	-0.2539181376	0.3	0.3	Direct	-0.56140257	0.094975729
## 4	-0.1342450916	0.2	0.2	Direct	-0.39851105	0.232588637
## 5	0.0531417912	0.5	0.5	Var DE	NA	NA
## 6	0.0414580541	0.4	0.4	Var DE	NA	NA
## 7	0.0390018854	0.3	0.3	Var DE	NA	NA
## 8	0.0526416964	0.2	0.2	Var DE	NA	NA
## 9	0.0449502665	0.5	0.4	Indirect	-0.01084133	0.149703682
## 10	0.0918239271	0.5	0.3	Indirect	-0.02200590	0.315064980
## 11	0.1374273586	0.5	0.2	Indirect	-0.03276185	0.478209199
## 12	0.0468736607	0.4	0.3	Indirect	-0.01165771	0.167767222
## 13	0.0924770921	0.4	0.2	Indirect	-0.02306165	0.330362955
## 14	0.0456034314	0.3	0.2	Indirect	-0.01098028	0.160935258
## 15	0.0016549408	0.5	0.4	Var IE	NA	NA
## 16	0.0074018887	0.5	0.3	Var IE	NA	NA
## 17	0.0165648912	0.5	0.2	Var IE	NA	NA
## 18	0.0020647643	0.4	0.3	Var IE	NA	NA
## 19	0.0077881332	0.4	0.2	Var IE	NA	NA
## 20	0.0018424493	0.3	0.2	Var IE	NA	NA
## 21	-0.4006131849	0.5	0.4	Total	-0.80526016	-0.008135616
## 22	-0.3537395242	0.5	0.3	Total	-0.66760483	0.031608331
## 23	-0.3081360928	0.5	0.2	Total	-0.55378513	0.071303381
## 24	-0.3108761352	0.4	0.3	Total	-0.61707076	0.047007159
## 25	-0.2652727037	0.4	0.2	Total	-0.49385115	0.083106573
## 26	-0.2083147061	0.3	0.2	Total	-0.44164396	0.123325407
## 27	0.0404582776	0.5	0.4	Var TE	NA	NA
## 28	0.0301274437	0.5	0.3	Var TE	NA	NA
## 29	0.0240662094	0.5	0.2	Var TE	NA	NA
## 30	0.0309960585	0.4	0.3	Var TE	NA	NA
## 31	0.0248090126	0.4	0.2	Var TE	NA	NA
## 32	0.0326468813	0.3	0.2	Var TE	NA	NA
## 33	-0.0347315409	0.5	0.4	Overall	-0.06821944	0.023101619
## 34	-0.0547823573	0.5	0.3	Overall	-0.12702281	0.066721805
## 35	-0.0585053488	0.5	0.2	Overall	-0.16705565	0.146756561
## 36	-0.0200508164	0.4	0.3	Overall	-0.05813752	0.051277125
## 37	-0.0237738079	0.4	0.2	Overall	-0.09998771	0.114006996
## 38	-0.0037229915	0.3	0.2	Overall	-0.04554477	0.070645016
## 39	0.0006677682	0.5	0.4	Var OE	NA	NA
## 40	0.0026659983	0.5	0.3	Var OE	NA	NA
## 41	0.0059769886	0.5	0.2	Var OE	NA	NA
## 42	0.0007509683	0.4	0.3	Var OE	NA	NA
## 43	0.0030976513	0.4	0.2	Var OE	NA	NA

```
## 44 0.0008663912 0.3 0.2 Var OE NA NA
```

Lastly, we perform assessment of the propensity score in IPW2 in the presence of interference.

```
# -----
# 5. Assessing the fit of the generalized propensity scores
# -----

### Check covariate balance for generalized propensity score: Fit a model on each covariate, then include

# IPW2 was fitted using "age10", so we check balance using "age10" (continuous covariate), not "agebin"
base_covariate=c("age10", "posneg", "date", "share", "education", "employment")
avg_covariate=c("avg_age10", "avg_posneg", "avg_date", "avg_share", "avg_education", "avg_employment")

##### check propensity score balance for IPW2
mat_1 = as.matrix(cbind(1, df[, row.names(coef(summary(M1)))[-1]])) # neighbors' treatment
mat_2 = as.matrix(cbind(1, df[, row.names(coef(summary(M2)))[-1]])) # Individual treatment

group_ps <- plogis(mat_1 %*% coef(M1))
ind_ps <- plogis(mat_2 %*% coef(M2))
df$group_ps_ipw2 <- group_ps
df$ind_ps_ipw2 <- ind_ps #Ke, should this be 1-ps for those not exposed?

### Step 1: check individual-level propensity score balance
# Note: Compare two models w/ and w/o treatment:
# (1) ind_covariate ~ ind_treatment + ind_ps_ipw2;
# (2) ind_covariate ~ ind_ps_ipw2
ipw2_balance <- data.frame()
for (i in 1:length(base_covariate)) {
  f1 <- paste0(base_covariate[i], " ~ ind_ps_ipw2")
  f2 <- paste0(base_covariate[i], " ~ treatment + ind_ps_ipw2")

  if (base_covariate[i] == "age10"){
    model_reduced <- glm(f1, data = df, family = gaussian)
    model_full <- glm(f2, data = df, family = gaussian("identity"))
  } else {
    model_reduced <- glm(f1, data = df, family = binomial("logit"))
    model_full <- glm(f2, data = df, family = binomial("logit"))
  }
  res_temp <- lmtest::lrtest(model_reduced, model_full)

  ipw2_balance <- rbind(ipw2_balance,
    c(f1, f2, round(res_temp$Chisq[2], 4), round(res_temp$`Pr(>Chisq)`[2], 4))
  )
}

### Step 2: check group-level propensity score balance
# Note: Compare two models w/ and w/o treatment:
# (1) group_covariate ~ group_treatment + group_ps;
# (2) group_covariate ~ group_ps.

for (i in 1:length(avg_covariate)) {
  f1 <- paste0(avg_covariate[i], " ~ group_ps_ipw2")
```

```

f2 <- paste0(avg_covariate[i], " ~ cbind(na_a, notna_a) + group_ps_ipw2")

model_reduced <- glm(f1, data = df)
model_full <- glm(f2, data = df)

res_temp <- lmtest::lrtest(model_reduced, model_full)

ipw2_balance <- rbind(ipw2_balance,
                      c(f1, f2, round(res_temp$Chisq[2], 4), round(res_temp$`Pr(>Chisq)`[2], 4))
)
}
colnames(ipw2_balance) <- c("Reduced model", "Full model", "Chisq", "Pr(>Chisq)")
ipw2_balance

##               Reduced model
## 1          age10 ~ ind_ps_ipw2
## 2          posneg ~ ind_ps_ipw2
## 3           date ~ ind_ps_ipw2
## 4           share ~ ind_ps_ipw2
## 5      education ~ ind_ps_ipw2
## 6      employment ~ ind_ps_ipw2
## 7      avg_age10 ~ group_ps_ipw2
## 8      avg_posneg ~ group_ps_ipw2
## 9       avg_date ~ group_ps_ipw2
## 10     avg_share ~ group_ps_ipw2
## 11 avg_education ~ group_ps_ipw2
## 12 avg_employment ~ group_ps_ipw2
##               Full model  Chisq Pr(>Chisq)
## 1          age10 ~ treatment + ind_ps_ipw2 0.0141    0.9053
## 2          posneg ~ treatment + ind_ps_ipw2 5e-04    0.9815
## 3           date ~ treatment + ind_ps_ipw2 3e-04    0.9873
## 4           share ~ treatment + ind_ps_ipw2 0.0314    0.8593
## 5      education ~ treatment + ind_ps_ipw2 0.0015    0.9687
## 6      employment ~ treatment + ind_ps_ipw2 0.0055    0.941
## 7      avg_age10 ~ cbind(na_a, notna_a) + group_ps_ipw2 0.8063    0.6682
## 8      avg_posneg ~ cbind(na_a, notna_a) + group_ps_ipw2 0.5856    0.7462
## 9       avg_date ~ cbind(na_a, notna_a) + group_ps_ipw2 1.3213    0.5165
## 10     avg_share ~ cbind(na_a, notna_a) + group_ps_ipw2 5.956    0.0509
## 11 avg_education ~ cbind(na_a, notna_a) + group_ps_ipw2 0.3799    0.827
## 12 avg_employment ~ cbind(na_a, notna_a) + group_ps_ipw2 2.3496    0.3089

#Optional: Format Latex Table for output of each estimation approach
#Create forest plot
library(dplyr)
library(forcats)
library(ggplot2)
library(knitr)
library(kableExtra)

z <- qnorm(0.975)

#####
# 1. Result object helper
#####

```

```

#library(conflicted)
#conflicts_prefer(dplyr::filter) # filter will now always use dplyr, even if MASS is loaded
#conflicts_prefer(dplyr::count)

make_result_object <- function(x) {
  if (is.list(x) && !is.data.frame(x)) {
    df_idx <- which(sapply(x, function(y) {
      is.data.frame(y) &&
      all(c("estimation", "alpha0", "alpha1", "type") %in% names(y))
    }))

    if (length(df_idx) == 0) {
      stop("No data frame with columns estimation, alpha0, alpha1, and type was found.")
    }

    x <- x[[df_idx[1]]]
  }

  if (!all(c("estimation", "alpha0", "alpha1", "type") %in% names(x))) {
    stop("Input must contain columns: estimation, alpha0, alpha1, type.")
  }

  est_rows <- x %>%
    filter(!grepl("^Var", type)) %>%
    mutate(
      effect_key = case_when(
        type == "Direct" ~ "DE",
        type == "Indirect" ~ "IE",
        type == "Total" ~ "TE",
        type == "Overall" ~ "OE",
        TRUE ~ type
      )
    )

  var_rows <- x %>%
    filter(grepl("^Var", type)) %>%
    mutate(
      effect_key = gsub("^Var\\s+", "", type),
      variance = estimation
    ) %>%
    select(alpha0, alpha1, effect_key, variance)

  results <- est_rows %>%
    left_join(
      var_rows,
      by = c("alpha0", "alpha1", "effect_key")
    ) %>%
    mutate(
      se = sqrt(variance),
      lower = estimation - z * se,
      upper = estimation + z * se
    ) %>%
    select(estimation, alpha0, alpha1, type, lower, upper)

```

```

    list(results = results)
  }

#####
# 2. Standardize alpha display by estimator/effect
#####

prep_effect_results <- function(results, estimator_name) {
  out <- results %>%
    filter(!grepl("^Var", type)) %>%
    mutate(
      estimator = estimator_name,
      effect = case_when(
        type == "Direct" ~ "Direct",
        type == "Indirect" ~ "Indirect",
        type == "Total" ~ "Total",
        type == "Overall" ~ "Overall",
        TRUE ~ type
      )
    )

  # G-comp and DR store coverage columns reversed relative to display.
  if (estimator_name %in% c("G-comp", "DR")) {
    out <- out %>%
      mutate(
        raw_alpha1 = alpha0,
        raw_alpha0 = alpha1
      )
  } else {
    out <- out %>%
      mutate(
        raw_alpha1 = alpha1,
        raw_alpha0 = alpha0
      )
  }

  out %>%
    mutate(
      display_alpha1 = pmax(raw_alpha1, raw_alpha0),
      display_alpha0 = pmin(raw_alpha1, raw_alpha0),
      contrast = paste0("(", display_alpha1, ", ", display_alpha0, ")")
    ) %>%
    filter(
      case_when(
        effect == "Direct" ~ display_alpha1 == display_alpha0,
        effect %in% c("Indirect", "Total") ~ display_alpha1 > display_alpha0,
        effect == "Overall" ~ TRUE,
        TRUE ~ TRUE
      )
    )
}

#####

```

```

# 3. LaTeX table helper
#####

make_latex_effect_table <- function(results,
                                     estimator_name,
                                     caption = "Estimated causal effects",
                                     digits = 3) {
  table_df <- prep_effect_results(results, estimator_name) %>%
    mutate(
      effect = factor(effect, levels = c("Direct", "Indirect", "Total", "Overall")),
      estimate = round(estimation, digits),
      ci = ifelse(
        is.na(lower) | is.na(upper),
        "",
        paste0(
          "(", round(lower, digits), ", ",
          round(upper, digits), ")"
        )
      )
    ) %>%
    arrange(effect, desc(display_alpha1), desc(display_alpha0)) %>%
    select(
      Effect = effect,
      `$(\\alpha_1, \\alpha_0)$` = contrast,
      `Point estimate` = estimate,
      `95\\% CI` = ci
    )

  direct_n <- sum(table_df$Effect == "Direct")
  indirect_n <- sum(table_df$Effect == "Indirect")
  total_n <- sum(table_df$Effect == "Total")
  overall_n <- sum(table_df$Effect == "Overall")

  tab <- table_df %>%
    kable(
      format = "latex",
      booktabs = TRUE,
      escape = FALSE,
      caption = caption,
      align = c("l", "c", "c", "c")
    ) %>%
    kable_styling(latex_options = c("hold_position"))

  start <- 1

  if (direct_n > 0) {
    tab <- tab %>% pack_rows("Direct effects", start, start + direct_n - 1, italic = TRUE)
    start <- start + direct_n
  }

  if (indirect_n > 0) {
    tab <- tab %>% pack_rows("Indirect effects", start, start + indirect_n - 1, italic = TRUE)
    start <- start + indirect_n
  }

```

```

}

if (total_n > 0) {
  tab <- tab %>% pack_rows("Total effects", start, start + total_n - 1, italic = TRUE)
  start <- start + total_n
}

if (overall_n > 0) {
  tab <- tab %>% pack_rows("Overall effects", start, start + overall_n - 1, italic = TRUE)
}

tab
}

#####
# 4. Create result objects
#####

res_ipw1 <- make_result_object(IPW1)
res_ipw2 <- make_result_object(IPW2)

res_gcomp <- if (exists("res_gcomp") && "results" %in% names(res_gcomp)) {
  res_gcomp
} else {
  make_result_object(gcomp_table)
}

res_dr <- if (exists("res_dr") && "results" %in% names(res_dr)) {
  res_dr
} else {
  make_result_object(dr_table)
}

#####
# 5. Create LaTeX tables
#####

ipw1_tab <- make_latex_effect_table(
  res_ipw1$results,
  estimator_name = "IPW1",
  caption = "IPW1 estimates of causal effects"
)

ipw2_tab <- make_latex_effect_table(
  res_ipw2$results,
  estimator_name = "IPW2",
  caption = "IPW2 estimates of causal effects"
)

gcomp_tab <- make_latex_effect_table(
  res_gcomp$results,
  estimator_name = "G-comp",
  caption = "G-computation estimates of causal effects"
)

```

```

)

dr_tab <- make_latex_effect_table(
  res_dr$results,
  estimator_name = "DR",
  caption = "Doubly robust estimates of causal effects"
)

cat(ipw1_tab, file = "ipw1_effects_table.tex")
cat(ipw2_tab, file = "ipw2_effects_table.tex")
cat(gcomp_tab, file = "gcomp_effects_table.tex")
cat(dr_tab, file = "dr_effects_table.tex")

#####
# 6. Forest plot data
#####

estimator_levels <- c("IPW1", "IPW2", "G-comp", "DR")

df <- bind_rows(
  prep_effect_results(res_ipw1$results, "IPW1"),
  prep_effect_results(res_ipw2$results, "IPW2"),
  prep_effect_results(res_gcomp$results, "G-comp"),
  prep_effect_results(res_dr$results, "DR")
) %>%
mutate(
  estimator = factor(estimator, levels = estimator_levels),
  effect = factor(effect, levels = c("Direct", "Indirect", "Total", "Overall"))
)

# Optional check: verify all estimator/effect/contrast combinations are present.
df %>%
  count(estimator, effect, contrast) %>%
  arrange(estimator, effect, contrast)

```

```

##   estimator   effect   contrast n
## 1      IPW1   Direct (0.2, 0.2) 1
## 2      IPW1   Direct (0.3, 0.3) 1
## 3      IPW1   Direct (0.4, 0.4) 1
## 4      IPW1   Direct (0.5, 0.5) 1
## 5      IPW1 Indirect (0.3, 0.2) 1
## 6      IPW1 Indirect (0.4, 0.2) 1
## 7      IPW1 Indirect (0.4, 0.3) 1
## 8      IPW1 Indirect (0.5, 0.2) 1
## 9      IPW1 Indirect (0.5, 0.3) 1
## 10     IPW1 Indirect (0.5, 0.4) 1
## 11     IPW1    Total (0.3, 0.2) 1
## 12     IPW1    Total (0.4, 0.2) 1
## 13     IPW1    Total (0.4, 0.3) 1
## 14     IPW1    Total (0.5, 0.2) 1
## 15     IPW1    Total (0.5, 0.3) 1
## 16     IPW1    Total (0.5, 0.4) 1
## 17     IPW1 Overall (0.3, 0.2) 1
## 18     IPW1 Overall (0.4, 0.2) 1

```

```

## 19      IPW1 Overall (0.4, 0.3) 1
## 20      IPW1 Overall (0.5, 0.2) 1
## 21      IPW1 Overall (0.5, 0.3) 1
## 22      IPW1 Overall (0.5, 0.4) 1
## 23      IPW2 Direct (0.2, 0.2) 1
## 24      IPW2 Direct (0.3, 0.3) 1
## 25      IPW2 Direct (0.4, 0.4) 1
## 26      IPW2 Direct (0.5, 0.5) 1
## 27      IPW2 Indirect (0.3, 0.2) 1
## 28      IPW2 Indirect (0.4, 0.2) 1
## 29      IPW2 Indirect (0.4, 0.3) 1
## 30      IPW2 Indirect (0.5, 0.2) 1
## 31      IPW2 Indirect (0.5, 0.3) 1
## 32      IPW2 Indirect (0.5, 0.4) 1
## 33      IPW2 Total (0.3, 0.2) 1
## 34      IPW2 Total (0.4, 0.2) 1
## 35      IPW2 Total (0.4, 0.3) 1
## 36      IPW2 Total (0.5, 0.2) 1
## 37      IPW2 Total (0.5, 0.3) 1
## 38      IPW2 Total (0.5, 0.4) 1
## 39      IPW2 Overall (0.3, 0.2) 1
## 40      IPW2 Overall (0.4, 0.2) 1
## 41      IPW2 Overall (0.4, 0.3) 1
## 42      IPW2 Overall (0.5, 0.2) 1
## 43      IPW2 Overall (0.5, 0.3) 1
## 44      IPW2 Overall (0.5, 0.4) 1
## 45      G-comp Direct (0.2, 0.2) 1
## 46      G-comp Direct (0.3, 0.3) 1
## 47      G-comp Direct (0.4, 0.4) 1
## 48      G-comp Direct (0.5, 0.5) 1
## 49      G-comp Indirect (0.3, 0.2) 1
## 50      G-comp Indirect (0.4, 0.2) 1
## 51      G-comp Indirect (0.4, 0.3) 1
## 52      G-comp Indirect (0.5, 0.2) 1
## 53      G-comp Indirect (0.5, 0.3) 1
## 54      G-comp Indirect (0.5, 0.4) 1
## 55      G-comp Total (0.3, 0.2) 1
## 56      G-comp Total (0.4, 0.2) 1
## 57      G-comp Total (0.4, 0.3) 1
## 58      G-comp Total (0.5, 0.2) 1
## 59      G-comp Total (0.5, 0.3) 1
## 60      G-comp Total (0.5, 0.4) 1
## 61      G-comp Overall (0.3, 0.2) 1
## 62      G-comp Overall (0.4, 0.2) 1
## 63      G-comp Overall (0.4, 0.3) 1
## 64      G-comp Overall (0.5, 0.2) 1
## 65      G-comp Overall (0.5, 0.3) 1
## 66      G-comp Overall (0.5, 0.4) 1
## 67      DR Direct (0.2, 0.2) 1
## 68      DR Direct (0.3, 0.3) 1
## 69      DR Direct (0.4, 0.4) 1
## 70      DR Direct (0.5, 0.5) 1
## 71      DR Indirect (0.3, 0.2) 1
## 72      DR Indirect (0.4, 0.2) 1

```

```
## 73      DR Indirect (0.4, 0.3) 1
## 74      DR Indirect (0.5, 0.2) 1
## 75      DR Indirect (0.5, 0.3) 1
## 76      DR Indirect (0.5, 0.4) 1
## 77      DR      Total (0.3, 0.2) 1
## 78      DR      Total (0.4, 0.2) 1
## 79      DR      Total (0.4, 0.3) 1
## 80      DR      Total (0.5, 0.2) 1
## 81      DR      Total (0.5, 0.3) 1
## 82      DR      Total (0.5, 0.4) 1
## 83      DR Overall (0.3, 0.2) 1
## 84      DR Overall (0.4, 0.2) 1
## 85      DR Overall (0.4, 0.3) 1
## 86      DR Overall (0.5, 0.2) 1
## 87      DR Overall (0.5, 0.3) 1
## 88      DR Overall (0.5, 0.4) 1
```

```
#####
# 7. Forest plot helper
#####
```

```
estimator_colors <- c(
  "IPW1" = "#009E73",
  "IPW2" = "#0072B2",
  "G-comp" = "#56B4E9",
  "DR" = "#E69F00"
)

estimator_shapes <- c(
  "IPW1" = 15,
  "IPW2" = 16,
  "G-comp" = 17,
  "DR" = 18
)

estimator_offsets <- c(
  "IPW1" = 0.27,
  "IPW2" = 0.09,
  "G-comp" = -0.09,
  "DR" = -0.27
)

make_effect_forest_plot <- function(plot_data, effect_name) {
  plot_data <- plot_data %>%
    filter(effect == effect_name)

  contrast_map <- plot_data %>%
    distinct(contrast, display_alpha1, display_alpha0) %>%
    arrange(desc(display_alpha1), desc(display_alpha0)) %>%
    mutate(contrast_id = row_number())

  plot_data <- plot_data %>%
    left_join(
      contrast_map,
```

```

    by = c("contrast", "display_alpha1", "display_alpha0")
  ) %>%
  mutate(
    y_pos = contrast_id + estimator_offsets[as.character(estimator)]
  )

ggplot(
  plot_data,
  aes(color = estimator, shape = estimator)
) +
  geom_vline(
    xintercept = 0,
    linetype = "dashed",
    linewidth = 0.6,
    color = "gray30"
  ) +
  geom_segment(
    aes(x = lower, xend = upper, y = y_pos, yend = y_pos),
    linewidth = 0.8
  ) +
  geom_point(
    aes(x = estimation, y = y_pos),
    size = 2.2
  ) +
  scale_y_continuous(
    breaks = contrast_map$contrast_id,
    labels = contrast_map$contrast
  ) +
  scale_color_manual(values = estimator_colors, breaks = estimator_levels) +
  scale_shape_manual(values = estimator_shapes, breaks = estimator_levels) +
  labs(
    title = paste(effect_name, "Effects"),
    x = "Estimate (95% CI)",
    y = expression(paste("Allocation (", alpha[1], ", ", alpha[0], ")")),
    color = "Estimator",
    shape = "Estimator"
  ) +
  theme_minimal(base_size = 16) +
  theme(
    legend.position = "top",
    plot.title = element_text(face = "bold", hjust = 0),
    axis.text.y = element_text(size = 12),
    panel.grid.minor = element_blank(),
    panel.grid.major.y = element_blank()
  )
}

#####
# 8. Create four forest plots
#####

p_direct <- make_effect_forest_plot(df, "Direct")
p_indirect <- make_effect_forest_plot(df, "Indirect")

```

```
p_total <- make_effect_forest_plot(df, "Total")
p_overall <- make_effect_forest_plot(df, "Overall")

ggsave("spillover_forest_direct.pdf", p_direct, width = 10, height = 4.5)
ggsave("spillover_forest_indirect.pdf", p_indirect, width = 10, height = 5.5)
ggsave("spillover_forest_total.pdf", p_total, width = 10, height = 5.5)
ggsave("spillover_forest_overall.pdf", p_overall, width = 10, height = 5.5)
```