Classical training of conditional instantaneous quantum polynomial-time Born machines

Oriol Balló-Gimbernat,[1,2,3,*] Emiliano Tolotti,[4] Laia Domingo,[2] Adan Garriga,[1] and Fernando Vilariño[2,3]

[1] *Eurecat, Centre Tecnològic de Catalunya, Barcelona, Spain*
[2] *Centre de Visió per Computador (CVC), Barcelona, Spain*
[3] *Universitat Autònoma de Barcelona (UAB), Barcelona, Spain*
[4] *Department of Information Engineering and Computer Science, University of Trento, Via Sommarive 9, 38123 Trento, Italy*

(Dated: October 9, 2026)

Instantaneous quantum polynomial-time (IQP) Born machines admit classical estimation of training observables for suitable input states, allowing model optimization without quantum circuit sampling. However, their standard fixed-input formulation models a single distribution. In this work, we introduce a conditional framework that encodes conditions into input states before applying a learned IQP unitary shared across conditions. The input preparation need not have strict IQP form, provided its reference state supports efficient classical sampling and amplitude-ratio evaluation. These operations enable unbiased classical estimation of Pauli-Z moments and their gradients. Experiments on sixteen-qubit discrete Gaussian families and the Curie–Weiss model demonstrate conditional generation. A correlated Gaussian encoder supports two-dimensional conditioning and generalization to mean–width combinations absent from fitting and development. For Curie–Weiss, the shared model achieves lower mean full-distribution total variation distance than both independent baseline families at two of three held-out temperatures, although the baselines are fitted directly at those temperatures and each family uses three times the total parameters and optimizer updates. Additional runs demonstrate the computational feasibility of classical conditional training from 64 to 2048 qubits. Furthermore, we show how input-state encoding can impose exact output symmetries in both conditional and unconditional IQP Born machines.

I. INTRODUCTION

Conditional generative models approximate a family of target distributions $p(\cdot \mid c)$ with a model $q_{\boldsymbol{\theta}}(\cdot \mid c)$, where c denotes the condition and $\boldsymbol{\theta}$ contains learned parameters shared across conditions. Classical examples include conditional generative adversarial networks [1–3], conditional variational autoencoders [4–6], and conditional diffusion models [7–9]. In the quantum domain, researchers have also adapted quantum circuit Born machines (QCBMs) [10, 11] to conditional tasks [12]. Researchers can introduce conditioning through input-state preparation or dedicated condition registers before applying a shared parameterized circuit [13–16]. Alternatively, postselection on a learned joint Born distribution can also yield conditional samples [17]. Beyond QCBMs, quantum diffusion models have explored conditional generation of both classical data and quantum states [18–20].

Existing complexity-theoretic results support the conjecture that classical algorithms cannot efficiently sample from certain output families of instantaneous quantum polynomial-time (IQP) Born machines under standard assumptions [21–25]. Yet, for maximum mean discrepancy (MMD) training with a Gaussian kernel [26], as commonly used for QCBMs [10, 27], classical algorithms can efficiently estimate the required Pauli-Z expectation values and their parameter gradients [28]. These estimators build on Van den Nest's techniques for computationally tractable input states [29]. However, the standard IQP formulation models a single target distribution per circuit. Extending IQP Born machines to conditional generation requires a conditioning mechanism that preserves classical access to the training observables and their gradients.

In this work, we develop a classically trainable framework for conditional IQP Born machines. We apply one learned IQP unitary $U_{\boldsymbol{\theta}}$ to condition-dependent input states $|\phi(c)\rangle$, giving $q_{\boldsymbol{\theta}}(x \mid c) = |\langle x|U_{\boldsymbol{\theta}}|\phi(c)\rangle|^2$. We establish sufficient conditions on the encoder for efficient classical estimation of the conditional training observables and their gradients, and construct encoders satisfying these conditions. Specifically, for the reference amplitudes $\psi_c(z) = \langle z|H^{\otimes n}|\phi(c)\rangle$, we require efficient sampling from $|\psi_c|^2$ and evaluation of amplitude ratios.

Building on sparse-observable methods [29, 30] and IQP training methods [28], we derive unbiased estimators of conditional Pauli-Z moments and their derivatives with respect to the learned phases. We bound the second moments of the moment and derivative estimators by one and four, respectively. These bounds imply that $O(\epsilon^{-2})$ reference samples suffice to estimate each specified moment or derivative to additive error ϵ at fixed confidence. We combine these estimators to obtain unbiased finite-sample estimates of the conditional MMD^2 objective and its gradients, enabling classical optimization of a single IQP Born machine across conditions. Figure 1 summarizes the framework.

We evaluate the framework on discrete Gaussian families and Curie–Weiss distributions at sixteen qubits. A

* oriol.ballo@eurecat.org




FIG. 1. Proposed framework for classical training and quantum sampling of conditional instantaneous quantum polynomial-time (IQP) Born machines. An encoder maps each condition c_i to an input state $|\phi(c_i)\rangle$. During classical training, samples and amplitude ratios from the reference state $H^{\otimes n}|\phi(c_i)\rangle$, together with phase differences induced by the IQP layer, yield estimates of conditional Pauli-Z moments and their gradients. We use these estimates to optimize one shared parameter vector $\boldsymbol{\theta}$ with a squared maximum mean discrepancy (MMD) objective averaged across training conditions. During quantum sampling, a chosen condition c_i determines the input state. Applying the trained IQP unitary $U_{\boldsymbol{\theta}}$ and measuring in the computational basis produces samples from the learned conditional distribution $q_{\boldsymbol{\theta}}(\cdot \mid c_i)$.

product-state encoder first illustrates conditional translation of Gaussian profiles. We then encode both mean and width in a correlated input and train a shared model with sixteen local rotations. Training the two coordinates separately tests generalization to unseen joint combinations, including pairs outside the joint training hull but within both marginal ranges.

For the Curie–Weiss model, we train a single model at four inverse temperatures. The model captures the change from unimodal to bimodal magnetization profiles, including the emergence of bimodality at the held-out inverse temperature $\beta = 1.0$. The encoder represents temperature through input phases while maintaining uniform computational-basis probabilities. The learned circuit converts this phase dependence into temperature-dependent output distributions. We compare this model with conditional and unconditional baseline families. Each family contains three independent circuits that we fit directly at the evaluation temperatures and uses three times the total parameters and optimizer updates of the shared model. The shared model achieves lower mean full-distribution total variation distance (TVD) than both baseline families at two of the three held-out temperatures, including $\beta = 1.6$, beyond the training range.

We also assess computational feasibility through optimization runs from 64 to 2048 qubits, tracking sampled MMD^2 at held-out temperatures throughout training.

Input-state design also allows exact output symmetries without restricting the learned phases. We illustrate this capability with a fixed input that enforces symmetry under flipping a selected subset of qubits while preserving classical trainability. Appendix A 3 c extends the construction to temperature-dependent Curie–Weiss inputs and reports a matched encoder comparison.

The remainder of this paper is organized as follows. In Section II, we introduce the conditional IQP model and its classical estimators. In Section III, we develop the conditional MMD training protocol. In Section IV, we describe the numerical experiments and report their results. In Section V, we show how input-state preparation can enforce output symmetries. In Section VI, we discuss the implications and limitations of our findings, and in Section VII, we summarize the contributions.

II. CONDITIONAL IQP MODEL

We separate condition encoding from the learned unitary transformation. An encoder maps each condition $c \in \mathcal{C}$ to an input state $|\phi(c)\rangle$, and we apply the same parameterized IQP unitary $U_{\boldsymbol{\theta}}$ to every encoded state. For a target family $\{p(\cdot \mid c) : c \in \mathcal{C}\}$ over n-bit strings, we define the model distribution as

$$q_{\boldsymbol{\theta}}(x \mid c) = \left|\langle x| U_{\boldsymbol{\theta}} |\phi(c)\rangle\right|^2, \qquad x \in \{0,1\}^n. \tag{1}$$

Throughout this work, we use "IQP unitary" to denote only the learned block $U_{\boldsymbol{\theta}}$. The encoder need not have IQP form and may include non-diagonal operations, so the complete conditional circuit need not belong to the strict IQP circuit class. Our conditions constrain classical access to the reference state rather than the encoder's gate structure: the reference state must support efficient sampling and amplitude-ratio evaluation.

The encoder also constrains how the model's output probabilities depend on the condition c. For rotation encodings with angles linear in c, the encoding generators determine the accessible Fourier frequencies, while the learned parameters control their coefficients within the constraints of the circuit architecture [31]. Multidimensional Fourier analyses further describe how the encoding and circuit architecture constrain the model's expressive capacity [32]. Caro et al. also derive encoding-dependent generalization bounds for parameterized quantum circuits [33]. We therefore distinguish encoder expressivity and generalization from the requirements for efficient classical estimation.

We parameterize the shared IQP unitary by an undirected graph $G = (V, E)$ with $n = |V|$ vertices. Each vertex $i \in V$ contributes a one-body generator Z_i, and each edge $\{i, j\} \in E$ contributes a two-body generator $Z_i Z_j$. We write the unitary as

$$U_{\boldsymbol{\theta}} = H^{\otimes n} D_G(\boldsymbol{\theta}) H^{\otimes n}, \tag{2}$$

where

$$D_G(\boldsymbol{\theta}) = \exp\left(i \sum_{i \in V} \theta_i Z_i + i \sum_{\{i,j\} \in E} \theta_{ij} Z_i Z_j \right). \tag{3}$$

All generators in D_G are diagonal in the computational basis and commute. In the numerical experiments, we use only one- and two-body generators. However, this formulation extends naturally to k-body interactions by adding the corresponding Pauli-Z products to the exponent.

We train the model using samples and amplitude ratios from the reference state $|\psi_c\rangle$ immediately before the diagonal IQP layer, without sampling the circuit's output distribution. We define its computational-basis amplitudes as

$$\psi_c(z) = \langle z | H^{\otimes n} | \phi(c) \rangle, \tag{4}$$

The squared amplitudes $|\psi_c(z)|^2$ give the reference sampling distribution for condition c. We require encoders that support two efficient classical operations for the relevant conditions c and bit masks a:

1. Sample $z \sim |\psi_c(z)|^2$.
2. Evaluate the amplitude ratio

$$R_c(z, a) = \frac{\psi_c(z \oplus a)}{\psi_c(z)} \tag{5}$$

for sampled z, where $\oplus$ denotes bitwise addition modulo two.

We call these two operations the sampling-and-ratio interface.

We estimate Pauli-Z moments by combining reference amplitude ratios with phase factors from the IQP layer. For each sampled string z, the ratio $R_c(z, a)$ compares the reference amplitudes of z and the paired string $z \oplus a$. The IQP layer contributes a complex phase factor determined by the phase difference between these strings. We multiply the amplitude ratio by this phase factor and average the real part over reference samples to estimate the corresponding Pauli-Z moment [29].

We evaluate amplitude ratios only on the support of $|\psi_c|^2$, because reference sampling never selects strings with $\psi_c(z) = 0$. Computationally tractable reference states in the sense of Van den Nest admit efficient computational-basis sampling and amplitude evaluation [29]. These states provide a sufficient realization of the sampling-and-ratio interface when amplitude evaluation supplies the precision needed to compute the required ratios efficiently.

The simplest case is a product-state encoder $|\phi(c)\rangle = \bigotimes_{i=1}^{n} |\phi_i(c)\rangle$. Its reference amplitudes factorize as $\psi_c(z) = \prod_i \psi_{c,i}(z_i)$, where $\psi_{c,i}(b) = \langle b | H | \phi_i(c) \rangle$. We can therefore generate reference samples by drawing each bit independently, and the amplitude ratio is

$$R_c(z, a) = \prod_{i : a_i = 1} \frac{\psi_{c,i}(1 - z_i)}{\psi_{c,i}(z_i)}. \tag{6}$$

When the local amplitudes have constant arithmetic evaluation cost, both operations require at most $O(n)$ local operations.

Efficient classical estimation of the observables used for training does not imply efficient classical sampling from $q_{\boldsymbol{\theta}}(\cdot \mid c)$. Existing IQP sampling-hardness results apply to specific circuit families and do not establish hardness for arbitrary condition-dependent input states or trained parameter values [22, 23]. To generate conditional samples on a quantum computer, we also need efficient circuits that prepare $|\phi(c)\rangle$ and implement $U_{\boldsymbol{\theta}}$. The classical sampling-and-ratio interface alone does not guarantee such circuits.

A. Conditional Pauli estimator and gradients

We express the conditional MMD objective in Section III in terms of Pauli-Z moments. For a bit mask $a \in \{0, 1\}^n$, we define $Z_a = \bigotimes_{i=1}^{n} Z_i^{a_i}$ and denote its conditional model expectation by $\mu_q(a \mid c)$. We use the sampling-and-ratio interface to derive estimators for this moment and its derivatives with respect to the learned phases.

We denote the diagonal IQP layer by $D_{\boldsymbol{\theta}}$ and write its action as

$$D_{\boldsymbol{\theta}} |z\rangle = e^{i f_{\boldsymbol{\theta}}(z)} |z\rangle, \tag{7}$$

with

$$f_{\boldsymbol{\theta}}(z) = \sum_{j=1}^{P} \theta_j \chi_{g_j}(z), \qquad \chi_{g_j}(z) = (-1)^{g_j \cdot z}, \tag{8}$$

where P is the number of generators and $g_j \in \{0,1\}^n$ specifies the support of the jth Pauli-Z generator. We evaluate the dot product $g_j \cdot z$ modulo two. We define the phase difference associated with the mask a as

$$\Delta_a f_{\boldsymbol{\theta}}(z) = f_{\boldsymbol{\theta}}(z \oplus a) - f_{\boldsymbol{\theta}}(z). \tag{9}$$

For a reference sample $z \sim |\psi_c|^2$, we define

$$\begin{aligned} W_{c,a}(z;\boldsymbol{\theta}) &= R_c(z,a) e^{i\Delta_a f_{\boldsymbol{\theta}}(z)}, \\ Y_{c,a}(z;\boldsymbol{\theta}) &= \mathrm{Re}\, W_{c,a}(z;\boldsymbol{\theta}). \end{aligned} \tag{10}$$

We define the derivative of the phase difference with respect to θ_j as

$$\begin{aligned} d_{j,a}(z) &= \partial_{\theta_j} \Delta_a f_{\boldsymbol{\theta}}(z) \\ &= \chi_{g_j}(z \oplus a) - \chi_{g_j}(z) \in \{-2, 0, 2\}. \end{aligned} \tag{11}$$

The following proposition establishes unbiased estimators for conditional Pauli-Z moments and their phase derivatives, and bounds their sampling error. We obtain these estimators by adapting amplitude-ratio methods for sparse observables [30]. For computationally tractable reference states, efficient estimation also follows from Van den Nest's sparse-operator theorem [29].

Proposition 1 (Classical estimation from reference-state access)**.** *Fix a condition c, a bit mask a, and a phase function with polynomially many diagonal Pauli-Z terms, as in Eq. (8). We assume that the reference state is normalized and independent of $\boldsymbol{\theta}$. We also assume that we can efficiently draw independent samples from $|\psi_c|^2$ and evaluate $R_c(z,a)$ for each sampled z. For a reference sample $z \sim |\psi_c|^2$, we define the moment and derivative estimators as follows:*

$$\begin{aligned} Y &= \mathrm{Re}\, W_{c,a}(z;\boldsymbol{\theta}), \\ Y'_j &= \mathrm{Re}[i\, d_{j,a}(z) W_{c,a}(z;\boldsymbol{\theta})] \end{aligned} \tag{12}$$

With exact sampling and arithmetic, these estimators have the following expectations and second-moment bounds:

$$\begin{aligned} \mathbb{E}[Y] &= \mu_q(a \mid c), & \mathbb{E}[Y^2] &\le 1, \\ \mathbb{E}[Y'_j] &= \partial_{\theta_j} \mu_q(a \mid c), & \mathbb{E}[(Y'_j)^2] &\le 4. \end{aligned} \tag{13}$$

We obtain unbiased estimates of the moment and its phase derivative by averaging Y and Y'_j over S independent reference samples. Their mean-square errors are at most $1/S$ and $4/S$, respectively. We can therefore estimate a specified moment or phase derivative to additive error ϵ at fixed confidence using $S = O(\epsilon^{-2})$ reference samples. These guarantees hold even when some reference amplitudes vanish.

Proof. We define the support of the reference distribution as $S_c = \{z : \psi_c(z) \neq 0\}$. Using $HZH = X$, we conjugate the measured observable Z_a through the final Hadamard layer to obtain $X_a = \bigotimes_{i=1}^n X_i^{a_i}$. This operator flips the bits selected by a, so

$$\begin{aligned} \mu_q(a \mid c) &= \langle \psi_c |\, D_{\boldsymbol{\theta}}^\dagger X_a D_{\boldsymbol{\theta}}\, | \psi_c \rangle \\ &= \mathrm{Re} \sum_{z \in S_c} \psi_c(z)^* \psi_c(z \oplus a) e^{i\Delta_a f_{\boldsymbol{\theta}}(z)} \\ &= \mathbb{E}_{z \sim |\psi_c|^2}[Y]. \end{aligned} \tag{14}$$

The last equality rewrites the sum as an expectation under $|\psi_c|^2$, using the amplitude ratio and the definition of Y.

The reference state does not depend on $\boldsymbol{\theta}$, so its sampling distribution and amplitude ratios remain fixed. We therefore differentiate only the IQP phase factor in the finite sum to obtain

$$\begin{aligned} \partial_{\theta_j} \mu_q(a \mid c) &= \mathbb{E}_{z \sim |\psi_c|^2}[\mathrm{Re}\,(i\, d_{j,a}(z) W_{c,a}(z;\boldsymbol{\theta}))] \\ &= \mathbb{E}[Y'_j]. \end{aligned} \tag{15}$$

Thus Y'_j is an unbiased estimator of the phase derivative.

Although individual amplitude ratios can be large, normalization bounds their second moment. The phase factor has unit magnitude, and the sampling probability $|\psi_c(z)|^2$ cancels the denominator in $|R_c(z,a)|^2$ when we take the expectation. We therefore obtain

$$\mathbb{E}[|W_{c,a}|^2] = \sum_{z \in S_c} |\psi_c(z \oplus a)|^2 \le 1. \tag{16}$$

The final inequality follows because bit flipping maps S_c to a subset of all bit strings and the reference state is normalized. Since Y is the real part of $W_{c,a}$, we have $\mathbb{E}[Y^2] \le 1$. Combining $|d_{j,a}(z)| \le 2$ with the same bound gives $\mathbb{E}[(Y'_j)^2] \le 4$. Averaging Y and Y'_j over S independent reference samples therefore gives mean-square errors at most $1/S$ and $4/S$, respectively. Chebyshev's inequality then yields the stated fixed-confidence sample complexity. The argument allows vanishing reference amplitudes because we evaluate ratios only for sampled strings. □

In practice, we draw S independent reference samples $z_s \sim |\psi_c|^2$ and estimate the moment as

$$\widehat{\mu}_q(a \mid c) = \frac{1}{S} \sum_{s=1}^{S} Y_{c,a}(z_s;\boldsymbol{\theta}). \tag{17}$$

We estimate the phase derivative by averaging the corresponding Y'_j values over the same samples. For the standard IQP input $|0\rangle^{\otimes n}$, all reference amplitudes are equal, so $R_c(z,a) = 1$. The moment estimator then reduces to $Y = \cos[\Delta_a f_{\boldsymbol{\theta}}(z)]$, recovering the usual IQP cosine estimator [29, 34].

For a circuit with r ancillary qubits, we apply the same estimator to the joint reference state, provided it supports the sampling-and-ratio interface. If we discard the

ancillary measurement outcomes, we extend each visible-bit mask a to $(a, 0^r)$, where 0^r denotes r zeros. The zero entries ensure that the observable acts as the identity on the ancillary qubits.

III. CONDITIONAL IQP TRAINING

We now formulate the training protocol for conditional IQP Born machines. Throughout this work, we use *classically trainable* to mean that we can efficiently estimate the training objective and its phase gradients to a prescribed additive accuracy on a classical computer.

A. Condition-balanced MMD objective

We optimize the shared parameter vector $\boldsymbol{\theta}$ by minimizing the squared maximum mean discrepancy (MMD) across the training conditions. For distributions p and q on $\{0,1\}^n$ and a positive-definite kernel k, the population squared MMD is [26]

$$\begin{aligned}\mathrm{MMD}^2(p,q) = \mathbb{E}_{x,x'\sim p}[k(x,x')] - 2\mathbb{E}_{x\sim p,\, y\sim q}[k(x,y)] \\ + \mathbb{E}_{y,y'\sim q}[k(y,y')],\end{aligned} \tag{18}$$

where we draw the two samples in each expectation independently.

Throughout this work, we use the Gaussian kernel on binary strings,

$$k_\sigma(x,y) = \exp\left[-\frac{d_H(x,y)}{2\sigma^2}\right], \tag{19}$$

where $d_H(x,y)$ is the Hamming distance, which counts the positions at which x and y differ, and $\sigma > 0$ is the kernel bandwidth.

Let $\mathcal{C}_{\mathrm{train}}$ denote the set of training conditions and τ the set of kernel bandwidths. We train the shared model by minimizing the condition-balanced objective

$$\mathcal{L}(\boldsymbol{\theta}) = \frac{1}{|\mathcal{C}_{\mathrm{train}}|}\sum_{c\in\mathcal{C}_{\mathrm{train}}}\frac{1}{|\tau|}\sum_{\sigma\in\tau}\mathrm{MMD}^2_\sigma(p(\cdot\mid c), q_{\boldsymbol{\theta}}(\cdot\mid c))\,. \tag{20}$$

Here, MMD^2_σ denotes the squared MMD computed with the kernel k_σ. We weight all training conditions and bandwidths equally. At each optimizer update, we independently draw one condition uniformly from $\mathcal{C}_{\mathrm{train}}$ and one bandwidth uniformly from τ, giving a stochastic estimate of this average.

B. Character expansion

For binary strings, the Gaussian kernel admits an exact expansion in binary characters. We sample a visible-bit mask $a \in \{0,1\}^n$ by drawing its coordinates independently according to

$$a_i \sim \mathrm{Bernoulli}(p_\sigma), \qquad p_\sigma = \frac{1-e^{-1/(2\sigma^2)}}{2}, \tag{21}$$

The corresponding binary character is

$$\chi_a(x) = (-1)^{a\cdot x}, \tag{22}$$

which records the parity of the bits selected by a. Averaging the product of these characters over a gives

$$k_\sigma(x,y) = \mathbb{E}_a[\chi_a(x)\chi_a(y)]\,. \tag{23}$$

For a condition c, define the target and model character moments

$$\begin{aligned}\mu_p(a\mid c) &= \mathbb{E}_{x\sim p(\cdot|c)}[\chi_a(x)],\\ \mu_q(a\mid c) &= \mathbb{E}_{x\sim q_{\boldsymbol{\theta}}(\cdot|c)}[\chi_a(x)].\end{aligned} \tag{24}$$

Substituting Eq. (23) into Eq. (18) gives

$$\mathrm{MMD}^2_\sigma(p(\cdot\mid c), q_{\boldsymbol{\theta}}(\cdot\mid c)) = \mathbb{E}_a\Big[(\mu_p(a\mid c) - \mu_q(a\mid c))^2\Big]\,. \tag{25}$$

Thus, the squared MMD averages the squared differences between target and model character moments over the mask distribution.

For a Born machine, the visible Pauli operator

$$Z_a = \bigotimes_{i=1}^n Z_i^{a_i} \tag{26}$$

has eigenvalue $\chi_a(x)$ on the computational-basis state $|x\rangle$. Its model expectation value is therefore

$$\mu_q(a\mid c) = \langle Z_a\rangle_{q_{\boldsymbol{\theta}}(\cdot|c)}. \tag{27}$$

We can thus express the conditional squared MMD entirely in terms of visible Pauli-Z moments. We estimate the model moments classically using the reference-state estimator in Sec. II A.

The bandwidth σ determines which correlation orders the objective emphasizes. The mask's Hamming weight $K = |a|$ counts the bits it selects, so it gives the correlation order of Z_a. Because we sample the mask coordinates independently,

$$\begin{aligned}K &\sim \mathrm{Binomial}(n, p_\sigma),\\ \mathbb{E}[K] &= np_\sigma,\\ \mathrm{Var}(K) &= np_\sigma(1-p_\sigma).\end{aligned} \tag{28}$$

Each bandwidth therefore induces a distribution over correlation orders. Large bandwidths favor lower-order correlations, whereas decreasing σ shifts weight toward higher-order correlations, with $\mathbb{E}[K] \to n/2$ as $\sigma \to 0$.

The choice of bandwidth can also influence the model's trainability. Previous results demonstrate that cost functions consisting of global terms can induce barren

plateaus [35, 36], even in shallow quantum circuits [37]. This creates a trade-off between trainability and sensitivity to higher-order correlations. Improving trainability may require restricting the objective to low-body correlations, which limits its ability to distinguish distributions that differ in higher-order correlations [38]. Researchers have proposed several strategies to address these difficulties, including tailored generator sets and restricted initializations [39, 40], and adversarial kernel adaptation [41]. How best to balance trainability and sensitivity to higher-order correlations remains an open question beyond the scope of this work.

C. Unbiased finite-sample MMD and gradients

For a fixed condition c and visible mask a, we draw $B \geq 2$ independent target samples and compute

$$T_b = \chi_a(x_b), \qquad x_b \sim p(\cdot \mid c). \tag{29}$$

Independently of these target samples, we draw $S \geq 2$ independent reference samples and evaluate the reference-state estimator from Eq. (10),

$$Y_s = Y_{c,a}(z_s; \boldsymbol{\theta}), \qquad z_s \sim |\psi_c|^2. \tag{30}$$

We denote the corresponding sample means by

$$\overline{T} = \frac{1}{B}\sum_{b=1}^{B} T_b, \qquad \overline{Y} = \frac{1}{S}\sum_{s=1}^{S} Y_s. \tag{31}$$

The direct estimate $(\overline{Y}-\overline{T})^2$ overestimates the squared moment difference on average because it includes the sampling variances of both sample means. We remove this bias by excluding products that use the same draw twice:

$$\begin{aligned}\widehat{\Delta^2_c}(a) = &\frac{1}{S(S-1)}\sum_{s\neq t} Y_s Y_t - 2\overline{Y}\,\overline{T} \\ &+ \frac{1}{B(B-1)}\sum_{b\neq b'} T_b T_{b'}.\end{aligned} \tag{32}$$

Independence within each pair gives

$$\mathbb{E}\left[\widehat{\Delta^2_c}(a)\right] = \left(\mu_q(a \mid c) - \mu_p(a \mid c)\right)^2. \tag{33}$$

Thus, Eq. (32) provides an unbiased finite-sample estimator of the squared character-moment difference appearing in Eq. (25). An unbiased finite-sample estimate of MMD^2 may be negative.

We evaluate the pair sums using the identities

$$\sum_{s\neq t} Y_s Y_t = \left(\sum_s Y_s\right)^2 - \sum_s Y_s^2, \tag{34}$$

and, since $T_b^2 = 1$,

$$\sum_{b\neq b'} T_b T_{b'} = \left(\sum_b T_b\right)^2 - B. \tag{35}$$

Once we have computed the sample values, we can therefore evaluate the estimator in time linear in the numbers of target and reference samples.

The same construction gives an unbiased estimator of the phase gradients. For a phase parameter θ_j, let

$$Y'_s = \partial_{\theta_j} Y_{c,a}(z_s; \boldsymbol{\theta}). \tag{36}$$

We evaluate Y'_s using Eq. (15). Differentiating Eq. (32) gives

$$\partial_{\theta_j}\widehat{\Delta^2_c}(a) = \frac{2}{S(S-1)}\sum_{s\neq t} Y_s Y'_t - 2\overline{T}\,\overline{Y'}, \tag{37}$$

where

$$\overline{Y'} = \frac{1}{S}\sum_s Y'_s. \tag{38}$$

Taking the expectation yields

$$\mathbb{E}\left[\partial_{\theta_j}\widehat{\Delta^2_c}(a)\right] = 2\left(\mu_q(a \mid c) - \mu_p(a \mid c)\right)\partial_{\theta_j}\mu_q(a \mid c), \tag{39}$$

which is the gradient of the corresponding squared moment difference.

At a fixed parameter vector, the expectations above average over independent draws from the target distribution and the reference sampling law. During training, we sample target minibatches with replacement from fixed training pools; the stochastic gradient is therefore unbiased for the empirical objective associated with those pools.

We exclude the diagonal terms $s = t$ because Y_s and Y'_s can be correlated when we compute them from the same reference draw. The fixed encoder makes the reference sampling law independent of $\boldsymbol{\theta}$. We therefore hold the sampled reference strings fixed during automatic differentiation to evaluate the phase gradients without differentiating through the sampler.

D. Stochastic mask estimator

Equation (25) expresses the squared MMD as an expectation over the mask distribution in Eq. (21). Since there are 2^n possible masks, we estimate this expectation using a finite sample of masks.

The identity mask $a = 0$ satisfies

$$\mu_p(0 \mid c) = \mu_q(0 \mid c) = 1 \tag{40}$$

for every condition and therefore contributes zero to the squared MMD. We consequently sample only nonidentity masks from the conditional distribution

$$P_\sigma(a \mid a \neq 0). \tag{41}$$

Under the original mask distribution, nonidentity masks have total probability

$$Q_\sigma^+ = 1 - (1 - p_\sigma)^n. \tag{42}$$

We multiply the conditional expectation by Q_σ^+ to preserve the original Gaussian kernel objective.

We draw M nonidentity masks $a_1, \ldots, a_M$ independently from $P_\sigma(a \mid a \neq 0)$ and estimate the squared MMD at condition c as

$$\widehat{\mathrm{MMD}}_\sigma^2(c) = Q_\sigma^+ \frac{1}{M} \sum_{m=1}^{M} \widehat{\Delta}_c^2(a_m), \tag{43}$$

where $\widehat{\Delta}_c^2$ is the unbiased finite-sample estimator in Eq. (32). Averaging over the mask, target, and reference draws recovers the full kernel squared MMD.

We evaluate each distinct sampled mask only once. Let $\mathcal{U}$ denote the set of distinct masks and m_u the number of times mask u occurs. We rewrite Eq. (43) as

$$\widehat{\mathrm{MMD}}_\sigma^2(c) = Q_\sigma^+ \sum_{u \in \mathcal{U}} \frac{m_u}{M} \widehat{\Delta}_c^2(u). \tag{44}$$

Weighting each distinct mask by m_u/M preserves the sampled objective and its gradient while reducing the number of Pauli moments we evaluate.

IV. NUMERICAL EXPERIMENTS

We evaluate the proposed architecture on Gaussian families controlled by translation or by both mean and width, and on the Curie–Weiss model at sixteen qubits. We also assess computational feasibility through optimization runs from 64 to 2048 qubits. For the sixteen-qubit benchmarks, we use the exact full-distribution total variation distance as the primary accuracy metric,

$$\mathrm{TVD}(p, q) = \frac{1}{2} \sum_{x \in \{0,1\}^n} |p(x) - q(x)|. \tag{45}$$

We also report the exact TVD between Hamming-weight profiles as a diagnostic,

$$\mathrm{TVD}_K(p, q) = \frac{1}{2} \sum_{k=0}^{n} |\rho_p(k) - \rho_q(k)|, \tag{46}$$

where $\rho_p(k)$ and $\rho_q(k)$ give the probabilities of observing Hamming weight k under p and q, respectively. Grouping bitstrings by Hamming weight gives $\mathrm{TVD}_K(p, q) \leq \mathrm{TVD}(p, q)$. The targets assign equal probability to all bitstrings with the same Hamming weight, but the learned models need not preserve this property. Profile TVD therefore does not resolve errors within Hamming-weight shells. We compute both metrics using the same exact circuit probabilities.

We train the models by minimizing the squared-MMD objective. We select checkpoints for the one-dimensional Gaussian translation experiment using mean exact profile TVD over the development conditions. For the two-dimensional Gaussian and all trained sixteen-qubit Curie–Weiss models, we use exact full-distribution TVD for hyperparameter and checkpoint selection. Appendices A and B specify the training and evaluation protocols.

A. Discrete Gaussian translation

Our first experiment illustrates the conditioning mechanism with a translated discrete Gaussian Hamming-weight profile. For $n = 16$ bits, let $K = |x|$ denote the Hamming weight of bitstring x. The condition $c \in [0, 1]$ controls the nominal center $5 + 6c$ of the profile. The target distribution assigns equal probability to all bitstrings with the same Hamming weight.

We use a fixed product-state encoder that applies the same two rotations to every qubit:

$$|\phi(c)\rangle = \bigotimes_{i=1}^{16} R_Z\left(c - \frac{1}{2}\right) R_Y(1.5)\, |0\rangle_i \,. \tag{47}$$

Changing c modifies the input phases but leaves the encoder's computational-basis measurement distribution unchanged.

The shared unitary uses a 4×4 lattice with 16 one-body phase gates and 24 two-body phase gates between horizontal and vertical nearest neighbors, giving 40 trainable parameters.

We train at $c \in \{0, 0.25, 0.5, 0.75, 1\}$ and evaluate at 80 held-out conditions. The median across runs of the mean full-distribution TVD over these conditions is 0.0995, compared with 0.2922 for the encoder alone (Table I). The corresponding profile TVD is 0.0464. The higher full-distribution TVD reveals discrepancies within Hamming-weight shells that the profile metric does not resolve. Figure 2 shows the translated profiles and conditional response. Appendix A 2 gives the training and evaluation protocol.

TABLE I. Exact full-distribution and profile TVDs for the Gaussian benchmark. Each entry reports the median across five runs of the mean error over 80 held-out conditions. Bold entries mark the lowest error in each column.

Model	Full TVD ↓	Profile TVD ↓
Conditional IQP	**0.0995**	**0.0464**
Encoder only	0.2922	0.2922




FIG. 2. Conditional translation of discrete Gaussian Hamming-weight profiles at sixteen qubits. (a) Solid colored curves show exact model profiles averaged across five runs at the development conditions $c \in \{0.125, 0.375, 0.625, 0.875\}$. We use these conditions for checkpoint selection and exclude them from fitting. (b) The solid black curve shows the median across runs of the model's mean output Hamming weight at each of 80 held-out conditions. Shading shows the interquartile range. Dashed curves show exact targets, dotted gray curves show the encoder alone, and gray circles mark training conditions on the target response. Table I reports exact full-distribution and profile errors.

B. Two-dimensional Gaussian conditioning and generalization

We next test generalization when two coordinates control the target distribution. For sixteen bits and Hamming weight $K = |x|$, we define

$$p(x \mid u, v) = \frac{\rho_{u,v}(K)}{\binom{16}{K}}, \tag{48}$$

$$\rho_{u,v}(k) \propto \exp\left[-\frac{(k-\mu(u))^2}{2\sigma_{\mathrm{G}}(v)^2}\right], \tag{49}$$

where $u, v \in [-1, 1]$, $\mu(u) = 8 + 3u$, and $\sigma_{\mathrm{G}}(v) = 2(1+0.2v)$. We normalize the profile over $k \in \{0, \ldots, 16\}$ and assign equal probability to bitstrings of the same weight. Thus, u controls the profile center and v controls its width. Their ranges correspond to centers between 5 and 11 and widths between 1.6 and 2.4. Discretization and finite support mean that these parameters need not equal the actual mean and standard deviation.

We encode width in the amplitudes of a correlated state and encode the mean coordinate through identical phase rotations:

$$|\chi(v)\rangle = \sum_{k=0}^{16} \sqrt{r_v(k)}\, |D_k^{(16)}\rangle\,, \tag{50}$$

$$|\phi(u,v)\rangle = R_Z(u/2)^{\otimes 16}\, |\chi(v)\rangle\,, \tag{51}$$

$$r_v(k) \propto \exp\left[-\frac{(k-8)^2}{2\tau(v)^2}\right], \qquad \tau(v) = \frac{2}{1+0.2v}. \tag{52}$$

Here $|D_k^{(16)}\rangle$ denotes the normalized uniform superposition of weight-k bitstrings. The width coordinate changes the centered input profile, whereas u changes phases without changing its computational-basis probabilities. This fixed encoder supplies a task-specific Gaussian prior; it does not prepare the requested target distribution.

We apply a shared learned layer containing only local rotations,

$$U_{\boldsymbol{\theta}} = \exp\left(i \sum_{j=1}^{16} \theta_j X_j\right) = \bigotimes_{j=1}^{16} R_X(-2\theta_j). \tag{53}$$

The sixteen angles remain fixed across conditions after training. Although this layer contains no learned entangling gates, the correlated input allows correlated outputs. Unequal angles can also break permutation symmetry, so we evaluate the full bitstring distribution. The reference state $H^{\otimes 16}\,|\phi(u,v)\rangle$ has one amplitude per Hamming-weight shell. This representation supplies the classical sampling and amplitude ratios required for training. Appendix B describes that access and the input-preparation resources.

We compare two training designs, each with nine fitting conditions and 1024 target samples per condition. In the *separate-variation* design, we vary u at $v = 0$ and v at $u = 0$. Neither fitting nor development uses a pair with both coordinates nonzero. In the *joint-variation* design, we fit the 3×3 grid $\{-1, 0, 1\}^2$. We select configurations and checkpoints using development full-distribution TVD and repeat the selected configuration in five independent fits. Appendix B gives the condition sets, optimization settings and selection protocol.

Separate variation supports generalization to combinations absent from fitting and development. Across sixteen mixed reporting pairs, the model achieves mean full-




FIG. 3. Generalization across Gaussian mean and width conditions with a correlated encoder and sixteen learned local rotations. Shading shows exact full-distribution TVD averaged over five fits at each point of a 41×41 grid. Crosses mark fitting conditions; dashed lines mark their convex hulls. (a) Training varies mean and width separately. Mixed conditions outside the diamond test joint extrapolation while remaining within each coordinate's training range. (b) Training varies both coordinates on a 3×3 grid, and the interior tests interpolation. Axes show the requested profile parameters. Both panels share a sequential color scale. The dense grid evaluates frozen models after selection; Table II includes the encoder-only baseline on a common withheld domain.

TABLE II. Mean full-distribution TVD on a common dense-grid domain. We exclude both designs' fitting and development pairs, leaving 1652 common pairs. The inside and outside groups use the separate-variation training hull, $|u| + |v| \leq 1$, for every row. Trained values are means and sample standard deviations of five per-fit condition averages; the encoder-only baseline is deterministic. This is a post-selection evaluation of frozen fits.

	All unseen pairs 1652 pairs	Inside hull 828 pairs	Outside hull 824 pairs
Encoder only	0.3124	0.2215	0.4038
Mean and width varied separately	0.0498 ± 0.0040	0.0357 ± 0.0029	0.0640 ± 0.0052
Mean and width varied jointly	0.0533 ± 0.0003	0.0379 ± 0.0004	0.0688 ± 0.0002

distribution TVD 0.0637 ± 0.0051. The four pairs inside the joint training hull give 0.0311 ± 0.0022, and the twelve outside give 0.0745 ± 0.0061. These outer pairs combine previously fitted coordinate values; they do not extend either marginal range. Joint variation gives 0.0646 ± 0.0002 on thirty-two withheld reporting pairs. We report means and sample standard deviations across five per-fit condition averages. These original reporting sets differ, so their averages do not directly compare the designs.

Figure 3 evaluates both designs on a common dense grid. Table II excludes every pair used for fitting or development by either design, leaving 1652 common pairs. Separate and joint variation achieve mean TVDs of 0.0498 ± 0.0040 and 0.0533 ± 0.0003, respectively, compared with 0.3124 for the encoder alone. Both designs therefore improve substantially on the untrained input across this domain. The dense grid provides a descriptive evaluation after selection, and earlier exploratory studies examined some reporting conditions. These results establish approximation of unseen joint combinations for the present fits, rather than an independent confirmatory comparison of training designs.

The conditional response remains imperfect. Freezing the width coordinate at zero increases separate-variation reporting TVD from 0.0637 to 0.0773; freezing the mean coordinate raises it to 0.3851. These diagnostics establish sensitivity to both inputs, but do not imply accurate calibration of the generated width. We also repeated selection and training with one angle shared across all sixteen rotations. That model achieves similar TVD but responds much less to the width coordinate. We retain sixteen independent angles to preserve the stronger two-coordinate response, and report the simplification and response diagnostics in Appendix B. The experiment demonstrates two-dimensional conditional generation with a local learned layer and a structured correlated input; it does not establish encoder necessity or quantum advantage.

C. Curie-Weiss spin model

We use the zero-field Curie–Weiss model [42] to test whether the architecture captures changes in distributional shape. The spins $s_i \in \{-1, +1\}$ interact with equal strength across all pairs, so the target assigns equal probability to bitstrings with the same Hamming weight. As the inverse temperature β increases, the finite-size Hamming-weight profile changes from a central peak to two symmetric modes.

We encode the inverse temperature using the fixed product-state encoder

$$|\phi(\beta)\rangle = \bigotimes_{i=1}^{16} R_Z(0.75\beta) R_Y\left(\frac{\pi}{2}\right) |0\rangle_i . \tag{54}$$

The R_Z rotations encode β in the input phases while leaving the computational-basis measurement distribution uniform. We parameterize the IQP unitary with all one- and two-body generators, giving 136 trainable parameters. We train at $\beta \in \{0.6, 0.8, 1.2, 1.4\}$ and evaluate at the held-out inverse temperatures $\beta \in \{0.4, 1.0, 1.6\}$.

We compare the shared conditional IQP model with two independently tuned baseline families. Each family comprises three circuits, which we fit separately at the three evaluation temperatures. The independent conditional IQPs retain the corresponding temperature encoder, whereas the independent unconditional IQPs use $|0\rangle^{\otimes 16}$ as their input state.

We use exact full-distribution TVD for hyperparameter optimization (HPO) and model selection. We tune the shared model on development temperatures and each independent family jointly across its fitted temperatures. Appendix A 3 a details the protocol.

Each independent baseline family uses three circuits and therefore three times the total parameters and optimizer updates of the shared model. The shared model uses more training-pool samples, with 4,096 entries per seed compared with 3,072 for each independent family. Appendix A 3 reports the detailed budgets.

The shared conditional model captures the change from unimodal to bimodal magnetization profiles, including bimodality at the held-out inverse temperature $\beta = 1.0$ (Figure 4). It achieves lower mean full-distribution TVD than both independent baseline families at $\beta = 1.0$ and 1.6, with mean errors of 0.2175 and 0.1709, respectively (Table III). The temperature $\beta = 1.6$ lies beyond the training range. At $\beta = 0.4$, the independent conditional family achieves lower mean TVD than the shared model (0.1240 versus 0.2240), while the uniform encoder-only baseline achieves the lowest error (0.1180). Together with the held-out results, this comparison suggests that learning across conditions may provide a useful inductive bias for generalization.

The profile diagnostic in Appendix A 3 (Table VII) gives a different ranking from full-distribution TVD. At $\beta = 1.0$, both independent baseline families achieve lower mean profile TVD than the shared model but higher mean full-distribution TVD. At $\beta = 0.4$, the shared model reduces mean profile TVD relative to the encoder while increasing mean full-distribution TVD. These differences show that agreement in Hamming-weight profiles does not ensure accurate bitstring probabilities.

We also evaluate physical observables to distinguish magnetization magnitude from energy fluctuations. The exact zero-field target has $\langle m \rangle = 0$ at finite size, so we report the mean absolute magnetization $\langle |m| \rangle$, with $m = n^{-1} \sum_i s_i$ and $n = 16$. For the Hamiltonian $H = -nm^2/2$, we define the per-spin heat-capacity fluctuation estimate

$$c_{\mathrm{fluc}}(\beta) = \frac{\beta^2}{n} \left(\langle H^2 \rangle - \langle H \rangle^2 \right). \tag{55}$$

This expression equals the per-spin equilibrium heat capacity for the Gibbs target. For a learned distribution, it measures energy fluctuations and need not equal the temperature derivative of the mean energy per spin. We compute both observables from exact probabilities for the same five selected confirmation circuits on a grid from $\beta = 0$ to 2 in steps of 0.02, without additional fitting or model selection. The sweep includes fitting and development temperatures as well as temperatures beyond the fitting range; it is not an entirely held-out evaluation. Appendix A 3 b specifies the calculation and aggregation.

The dense response reveals errors that the three-temperature distribution comparison does not fully describe (Figure 5). At $\beta = 1.0$, the shared model overestimates mean absolute magnetization (0.525 versus the target 0.451), while the independent fitted baselines are closer. At higher inverse temperatures, the shared response levels off and underestimates the target (0.855 versus 0.936 at $\beta = 2$). Energy fluctuations show a different discrepancy. The target's heat capacity reaches its maximum on the evaluated grid near $\beta = 1.52$ and then decreases, whereas the shared model's fluctuation estimate continues increasing through $\beta = 2$, reaching 1.299 versus the target 0.504. At $\beta = 1.6$, however, the shared estimate remains closer to the target than either independent baseline. Thus, capturing the change in magnetization magnitude does not ensure recovery of the target's energy fluctuations, and the relative accuracy depends on the observable and temperature.

D. Scaling

We assess the computational feasibility of classical training at $n \in \{64, 128, 256, 512, 1024, 2048\}$ visible qubits, without ancillas. We use the fixed product-state encoder $R_Z(0.75\beta) R_Y(\pi/2)$ on every qubit. The learned unitary uses independent one-body phase gates and two-body phase gates between horizontal and vertical nearest neighbors on an open rectangular lattice. For an $L_x \times L_y$ lattice with $n = L_x L_y$, the model has $3n - L_x - L_y$ trainable parameters, so the parameter count grows linearly




FIG. 4. Curie–Weiss magnetization profiles at sixteen qubits. We write the magnetization as $m = (2k - 16)/16$, where k is the Hamming weight. Panels show (a) encoder only, (b) shared conditional IQP, (c) independent conditional IQPs, and (d) independent unconditional IQPs. Colors distinguish $\beta = 0.4, 1.0, 1.6$, and dashed curves show exact targets. Solid curves show exact model profiles averaged over five confirmation runs used for model selection and reporting; the encoder-only profile is deterministic. We evaluate the shared model at temperatures excluded from fitting and current model selection, whereas we fit the independent circuits directly at each displayed temperature. Table III reports full-distribution TVD.

TABLE III. Exact full-distribution TVD for sixteen-qubit Curie–Weiss models. For trained models, we report means ± sample standard deviations across five confirmation runs used for model selection and reporting. The encoder-only baseline is deterministic. We evaluate the shared model at temperatures excluded from fitting and current model selection, whereas we fit the independent circuits directly at each evaluation temperature. Bold entries identify the lowest mean TVD in each column, including the encoder-only baseline.

Model	Evaluation	Full-distribution TVD ↓		
		$\beta = 0.4$	$\beta = 1.0$	$\beta = 1.6$
Encoder only	Baseline	**0.1180**	0.4406	0.8699
Shared conditional IQP	Held-out	0.2240 ± 0.0115	$\mathbf{0.2175 \pm 0.0136}$	$\mathbf{0.1709 \pm 0.0136}$
Independent conditional IQPs	Fitted	0.1240 ± 0.0083	0.2309 ± 0.0319	0.3948 ± 0.0003
Independent unconditional IQPs	Fitted	0.3842 ± 0.0017	0.3322 ± 0.0105	0.3299 ± 0.0119

with n. Appendix A 4 gives the lattice dimensions and optimization settings.

At each system size, we train at $\beta \in \{0.6, 0.8, 1.2, 1.4\}$ and track the mean sampled MMD^2 over the held-out temperatures throughout optimization (Figure 6). Appendix A 4 specifies the training and reporting protocol.

The scaling study demonstrates the computational feasibility of classical conditional training up to 2048 qubits (Figure 6). At 64 qubits, the median held-out sampled MMD^2 decreases from 0.0504 to 0.0350 after 5,000 updates; at 2048 qubits, it decreases from 0.0490 to 0.0417. These modest reductions suggest limited progress under the chosen training configuration and may reflect suboptimal hyperparameters. The runs use a sparse lattice




FIG. 5. Sixteen-qubit Curie–Weiss observables: (a) mean absolute magnetization and (b) per-spin heat-capacity fluctuation estimate, Eq. (55). Dashed and dotted curves show the exact target and uniform encoder reference. Conditional IQP curves and bands show mean and sample standard deviation across five frozen confirmation circuits at 101 temperatures. Independent markers use separately fitted circuits at $\beta = 0.4, 1.0, 1.6$, with the same summaries. We compute nonlinear observables within each run before aggregation. The sweep includes fitting, development and extrapolation conditions. For learned distributions, panel (b) measures energy fluctuations rather than a verified temperature response.

ansatz and optimizer settings that differ from the tuned sixteen-qubit comparison. Further tuning and benchmarking are needed for a systematic assessment of generative performance. Because the kernel bandwidths vary with system size, the absolute MMD^2 values do not directly compare distributional fidelity across sizes.




FIG. 6. Classical training of conditional IQP Born machines from 64 to 2048 qubits. At each plotted update, we average sampled MMD^2 over the held-out inverse temperatures $\beta \in \{0.4, 0.95, 1.0, 1.05, 1.6\}$. Curves and shaded bands show the median and interquartile range of these averages across three independent training runs. We fix the expected mask weights at $w \in \{2, 4\}$ for each system size, so the corresponding kernel bandwidths vary with n.

V. INPUT-STATE INDUCED SYMMETRIES IN IQP BORN MACHINES

Input-state encoding can also enforce exact output symmetries without restricting the learned phases. For a nonzero bit mask $s \in \{0,1\}^n$, the bit-flip operator $X_s = \bigotimes_{i=1}^n X_i^{s_i}$ commutes with the IQP unitary. If each encoded input is an eigenstate of X_s, the output state retains the same eigenvalue. Its computational-basis amplitudes at x and $x \oplus s$ therefore differ at most by a sign, giving equal probabilities for every condition and parameter vector. This applies the commuting-symmetry construction of Recio-Armengol *et al.* [28, Sec. 6] to conditional inputs. Such constraints provide inductive biases in variational quantum models [43].

A simple unconditional example uses the input

$$|\phi_s\rangle = \frac{|0^n\rangle + |s\rangle}{\sqrt{2}}. \tag{56}$$

This state satisfies $X_s |\phi_s\rangle = |\phi_s\rangle$ and therefore imposes

$$q_{\boldsymbol{\theta}}(x) = q_{\boldsymbol{\theta}}(x \oplus s) \qquad \text{for every } x \text{ and } \boldsymbol{\theta}. \tag{57}$$

The reference state $H^{\otimes n} |\phi_s\rangle$ has equal amplitudes on bitstrings satisfying $s \cdot z = 0$ modulo two and zero amplitudes elsewhere. To sample its measurement distribution, we choose a position with $s_i = 1$, draw the other bits uniformly, and set z_i to satisfy the parity constraint. For a sampled string z, the amplitude ratio $R_s(z, a)$ equals one when $s \cdot a = 0$ modulo two and zero otherwise. This input satisfies the sampling-and-ratio interface, so we can

estimate the training moments and their gradients efficiently on a classical computer.

For three qubits, we choose $s = 110$, giving $|\phi_s\rangle = (|000\rangle + |110\rangle)/\sqrt{2}$. This input enforces $q_{\boldsymbol{\theta}}(x) = q_{\boldsymbol{\theta}}(x \oplus 110)$ for every parameter vector. The ordinary $|000\rangle$ input does not enforce this symmetry: with only $\theta_1 = \pi/6$ nonzero, the model assigns $q(000) = 3/4$ and $q(110) = 0$. Figure 7 compares the two inputs at a separate parameter setting, using the same unitary for both. Appendix A 3 c gives a temperature-dependent encoder that enforces global spin-flip invariance for Curie–Weiss and reports its effect on distributional accuracy.




FIG. 7. Equal probabilities for paired outcomes under the encoded input. The circuit prepares $(|000\rangle + |110\rangle)/\sqrt{2}$ before applying $U_{\boldsymbol{\theta}}$. The plots show exact probabilities at one parameter setting for the encoded input (blue) and the ordinary $|000\rangle$ input (gray), using the same unitary in both cases. Adjacent outcomes differ by the bit flip 110. The encoded input guarantees equal probabilities within each pair for every choice of learned phases.

VI. DISCUSSION

Our framework establishes sufficient conditions for classical training of conditional IQP Born machines with input preparation beyond strict IQP form. Efficient sampling and amplitude-ratio evaluation of the reference state enable unbiased estimation of conditional training moments and their gradients, while one learned unitary shares parameters across conditions. The sixteen-qubit experiments demonstrate conditional translations and changes in distributional shape through input phases and correlated amplitudes. The two-dimensional Gaussian experiment also approximates mean–width combinations absent from fitting and development, including pairs outside the joint training hull of separately varied coordinates. For Curie–Weiss, the shared model achieves lower mean full-distribution TVD than both independent baseline families at $\beta = 1.0$ and 1.6, with the latter extending beyond the training range. Each baseline family fits these temperatures directly and uses three times the aggregate parameters and optimizer updates, whereas the shared model uses more training-pool samples. At $\beta = 0.4$, the uniform encoder-only distribution achieves the lowest error among the models in the primary comparison. Joint training may provide useful regularization, but comparisons with matched data and optimization budgets are needed to assess this explanation.

Input-state design can impose exact output symmetries while preserving classical trainability. The unconditional bit-flip input and conditional Curie–Weiss projection enforce their symmetries for every parameter vector. The encoder comparison in Appendix A 3 c shows temperature-dependent changes in full-distribution TVD, so exact symmetry does not guarantee improved accuracy. Spin-flip invariance also does not enforce uniformity within Hamming-weight shells. Classical output symmetrization is a relevant control because averaging a distribution with its bitwise complement cannot increase TVD to a spin-flip-invariant target. Coherent projection introduces interference and generally differs from this mixture. Comparisons that include symmetrization in fitting and selection would test whether projection improves accuracy beyond classical enforcement of the same symmetry.

The methodological limitations concern distributional evaluation and the scope of the scaling evidence. Efficient, unbiased MMD estimation does not ensure accurate recovery of every relevant correlation [44]. Although the Gaussian kernel includes all correlation orders, its bandwidth weights them unequally, and finite sampling and optimization may fail to resolve weakly weighted discrepancies. Agreement in Hamming-weight profiles can therefore coexist with errors in individual bitstring probabilities, making full-distribution diagnostics necessary whenever feasible. The observable sweep further shows that recovering magnetization trends does not ensure accurate energy fluctuations, especially beyond the fitting range. For Curie–Weiss, reporting reuses the confirmation runs used to select hyperparameters, so the reported spread does not independently assess model selection. The reporting temperatures are excluded from current fitting and selection but were examined in earlier experiments. Fresh seeds and previously unexamined conditions, evaluated with configurations fixed in advance, would strengthen the generalization evidence. The sparse-lattice runs establish computational feasibility up to 2048 qubits, with modest reductions in held-out sampled MMD^2. Their connectivity and optimizer settings differ from the sixteen-qubit comparison. Fixed expected mask weights emphasize low-order correlations as the system grows, while size-dependent bandwidths prevent direct comparisons of distributional accuracy across

sizes.

Future work should examine richer tractable encoders and optimization strategies that improve conditional accuracy. Broader families of correlated inputs and multidimensional encodings should be assessed alongside state-preparation and estimation costs, with particular attention to calibration of each conditional response. Conditional extensions of spectral Born machines would require corresponding sampling, amplitude-ratio and gradient estimators [45]. Generator selection, initialization and adaptive kernels merit investigation [39–41], including whether gradients from different conditions reinforce or cancel one another. Quantum deployment should assess how noise and circuit partitioning affect the conditional response and imposed symmetries [46, 47]. Practical quantum sampling advantage remains open: our Gaussian and Curie–Weiss targets admit efficient classical sampling. Demonstrations would require comparisons with strong classical generative models and sampling-hardness or verification arguments appropriate to the trained conditional circuits.

VII. CONCLUSIONS

We introduced a conditional framework for IQP Born machines that combines a shared learned unitary with encoders that need not have IQP form. Efficient reference-state sampling and amplitude-ratio evaluation enable unbiased classical estimation of conditional training observables and their gradients, allowing optimization without quantum circuit sampling. Input-state design also lets us impose exact output symmetries independently of the learned parameters.

Our sixteen-qubit experiments demonstrate conditional translations and changes in distributional shape through input phases and correlated amplitudes. The two-dimensional Gaussian model generalizes to joint mean–width combinations absent from fitting and development using sixteen learned local rotations. For the Curie–Weiss model, the shared model achieves lower mean full-distribution TVD than both independently fitted baseline families at two held-out temperatures, including one beyond the training range, with fewer aggregate parameters and optimizer updates. Additional runs establish the computational feasibility of classical conditional training up to 2048 qubits. Together, the theoretical constructions and numerical results establish conditional generation and symmetry control within a framework that supports classical training. Further work must assess distributional accuracy at larger scales and practical quantum advantage.

DATA AVAILABILITY

The code and data supporting this study are available on GitHub [48].

ACKNOWLEDGMENTS

OB is a fellow of Eurecat's "Vicente López" PhD grant program.

[1] M. Mirza and S. Osindero, Conditional generative adversarial nets (2014), arXiv:1411.1784 [cs.LG].
[2] P. Isola, J.-Y. Zhu, T. Zhou, and A. A. Efros, Image-to-image translation with conditional adversarial networks, in *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition* (2017) arXiv:1611.07004.
[3] T. Miyato and M. Koyama, cGANs with projection discriminator, in *International Conference on Learning Representations* (2018) arXiv:1802.05637.
[4] K. Sohn, H. Lee, and X. Yan, Learning structured output representation using deep conditional generative models, in *Advances in Neural Information Processing Systems*, Vol. 28 (2015).
[5] J. Walker, C. Doersch, A. Gupta, and M. Hebert, An uncertain future: Forecasting from static images using variational autoencoders, in *Computer Vision – ECCV 2016*, Lecture Notes in Computer Science, Vol. 9911 (2016) pp. 835–851, arXiv:1606.07873.
[6] X. Yan, J. Yang, K. Sohn, and H. Lee, Attribute2Image: Conditional image generation from visual attributes, in *Computer Vision – ECCV 2016*, Lecture Notes in Computer Science, Vol. 9908 (2016) pp. 776–791, arXiv:1512.00570.
[7] P. Dhariwal and A. Nichol, Diffusion models beat GANs on image synthesis, in *Advances in Neural Information Processing Systems*, Vol. 34 (2021) arXiv:2105.05233.
[8] J. Ho and T. Salimans, Classifier-free diffusion guidance (2022), arXiv:2207.12598 [cs.LG].
[9] R. Rombach, A. Blattmann, D. Lorenz, P. Esser, and B. Ommer, High-resolution image synthesis with latent diffusion models, in *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition* (2022) pp. 10684–10695, arXiv:2112.10752.
[10] J.-G. Liu and L. Wang, Differentiable learning of quantum circuit born machine, Physical Review A **98**, 062324 (2018).
[11] M. Benedetti, D. Garcia-Pintos, O. Perdomo, V. Leyton-Ortega, Y. Nam, and A. Perdomo-Ortiz, A generative modeling approach for benchmarking and training shallow quantum circuits, npj Quantum Information **5**, 45 (2019).
[12] Z. He, L. Li, S. Zheng, Z. Huang, and H. Situ, A conditional generative model based on quantum circuit and classical optimization, International Journal of Theoretical Physics **58**, 1138 (2019).
[13] M. Benedetti, B. Coyle, M. Fiorentini, M. Lubasch, and M. Rosenkranz, Variational inference with a quantum

computer, Physical Review Applied **16**, 044057 (2021), arXiv:2103.06720 [quant-ph].
[14] O. Kiss, M. Grossi, E. Kajomovitz, and S. Vallecorsa, Conditional born machine for monte carlo event generation, Physical Review A **106**, 022612 (2022).
[15] Q.-W. Zeng, H.-Y. Ge, C. Gong, and N.-R. Zhou, Conditional quantum circuit born machine based on a hybrid quantum–classical framework, Physica A: Statistical Mechanics and its Applications **618**, 128693 (2023).
[16] S. Certo, A. Pham, N. Robles, and A. Vlasic, Conditional generative models for learning stochastic processes, Quantum Machine Intelligence **5**, 42 (2023), arXiv:2304.10382 [quant-ph].
[17] J. Zeng, Y. Wu, J.-G. Liu, L. Wang, and J. Hu, Learning and inference on generative adversarial quantum circuits, Physical Review A **99**, 052306 (2019), arXiv:1808.03425 [quant-ph].
[18] A. Cacioppo, L. Colantonio, S. Bordoni, and S. Giagu, Quantum diffusion models (2023), arXiv:2311.15444 [quant-ph].
[19] C. Chen, Q. Zhao, M. Zhou, D. Niyato, Z. He, and H. Situ, Overcoming dimensional factorization limits in discrete diffusion models through quantum joint distribution learning, npj Quantum Information **12**, 49 (2026).
[20] D. Quinn, L. Buffoni, S. Gherardini, and G. De Chiara, Conditioning in generative quantum denoising diffusion models, Quantum Science and Technology **11**, 035047 (2026), arXiv:2509.17569 [quant-ph].
[21] D. Shepherd and M. J. Bremner, Instantaneous Quantum Computation, Proceedings of the Royal Society A: Mathematical, Physical and Engineering Sciences **465**, 1413 (2009), arXiv:0809.0847 [quant-ph].
[22] M. J. Bremner, R. Jozsa, and D. J. Shepherd, Classical simulation of commuting quantum computations implies collapse of the polynomial hierarchy, Proceedings of the Royal Society A: Mathematical, Physical and Engineering Sciences **467**, 459 (2011).
[23] M. J. Bremner, A. Montanaro, and D. J. Shepherd, Average-Case Complexity Versus Approximate Simulation of Commuting Quantum Computations, Physical Review Letters **117**, 080501 (2016).
[24] M. J. Bremner, A. Montanaro, and D. J. Shepherd, Achieving quantum supremacy with sparse and noisy commuting quantum computations, Quantum **1**, 8 (2017).
[25] S. C. Marshall, S. Aaronson, and V. Dunjko, Improved separation between quantum and classical computers for sampling and functional tasks, in *40th Computational Complexity Conference (CCC 2025)*, Leibniz International Proceedings in Informatics (LIPIcs), Vol. 339 (Schloss Dagstuhl – Leibniz-Zentrum für Informatik, 2025) pp. 5:1–5:14, arXiv:2410.20935 [quant-ph].
[26] A. Gretton, K. M. Borgwardt, M. J. Rasch, B. Schölkopf, and A. Smola, A kernel two-sample test, Journal of Machine Learning Research **13**, 723 (2012).
[27] B. Coyle, D. Mills, V. Danos, and E. Kashefi, The Born supremacy: Quantum advantage and training of an Ising Born machine, npj Quantum Information **6**, 60 (2020).
[28] E. Recio-Armengol, S. Ahmed, and J. Bowles, Train on classical, deploy on quantum: Scaling generative quantum machine learning to a thousand qubits (2026), arXiv:2503.02934v2 [quant-ph].
[29] M. Van den Nest, Simulating quantum computers with probabilistic methods, Quantum Information and Computation **11**, 784 (2011), arXiv:0911.1624 [quant-ph].
[30] V. Havlíček, Amplitude ratios and neural network quantum states, Quantum **7**, 938 (2023), arXiv:2201.09128 [quant-ph].
[31] M. Schuld, R. Sweke, and J. J. Meyer, The effect of data encoding on the expressive power of variational quantum-machine-learning models, Physical Review A **103**, 032430 (2021).
[32] B. Casas and A. Cervera-Lierta, Multidimensional fourier series with quantum circuits, Physical Review A **107**, 062612 (2023).
[33] M. C. Caro, E. Gil-Fuster, J. J. Meyer, J. Eisert, and R. Sweke, Encoding-dependent generalization bounds for parametrized quantum circuits, Quantum **5**, 582 (2021), arXiv:2106.03880 [quant-ph].
[34] E. Armengol and J. Bowles, IQPopt: Fast optimization of instantaneous quantum polynomial circuits in JAX (2026), arXiv:2501.04776v2 [quant-ph].
[35] J. R. McClean, S. Boixo, V. N. Smelyanskiy, R. Babbush, and H. Neven, Barren plateaus in quantum neural network training landscapes, Nature Communications **9**, 4812 (2018).
[36] M. Larocca, S. Thanasilp, S. Wang, K. Sharma, J. Biamonte, P. J. Coles, L. Cincio, J. R. McClean, Z. Holmes, and M. Cerezo, Barren plateaus in variational quantum computing, Nature Reviews Physics **7**, 174 (2025).
[37] M. Cerezo, A. Sone, T. Volkoff, L. Cincio, and P. J. Coles, Cost function dependent barren plateaus in shallow parametrized quantum circuits, Nature Communications **12**, 1791 (2021).
[38] M. S. Rudolph, S. Lerch, S. Thanasilp, O. Kiss, O. Shaya, S. Vallecorsa, M. Grossi, and Z. Holmes, Trainability barriers and opportunities in quantum generative modeling, npj Quantum Information **10**, 116 (2024).
[39] K. Shen, S. Pielawa, V. Dunjko, and H. Wang, Characterizing trainability of instantaneous quantum polynomial circuit born machines (2026), arXiv:2602.11042v2 [quant-ph].
[40] S. Lerch, J. Bowles, R. Puig, E. Armengol, Z. Holmes, and S. Thanasilp, IQP born machines under data-dependent and agnostic initialization strategies (2026), arXiv:2603.14576 [quant-ph].
[41] A. Kurkin, K. Shen, S. Pielawa, H. Wang, and V. Dunjko, Universality and kernel-adaptive training for classically trained, quantum-deployed generative models (2025), arXiv:2510.08476 [quant-ph].
[42] R. S. Ellis, *Entropy, Large Deviations, and Statistical Mechanics*, Classics in Mathematics (Springer, Berlin, Heidelberg, 2006).
[43] J. J. Meyer, M. Mularski, E. Gil-Fuster, A. A. Mele, F. Arzani, A. Wilms, and J. Eisert, Exploiting symmetry in variational quantum machine learning, PRX Quantum **4**, 010328 (2023).
[44] M. Herrero-Gonzalez, B. Coyle, K. McDowall, R. Grassie, S. Beentjes, A. Khamseh, and E. Kashefi, The born ultimatum: Conditions for classical surrogation of quantum generative models with correlators (2025), arXiv:2511.01845 [quant-ph].
[45] A. Huang, W. Maxwell, V. Belis, E. Peters, J. Pye, S. Jahangiri, and J. Bowles, Spectral born machines: Classically trainable quantum generative models for discrete data (2026), arXiv:2607.06675 [quant-ph].
[46] O. Balló-Gimbernat, M. Arroyo-Sánchez, P. García-Molina, A. Garriga, and F. Vilariño, Shallow instanta-

neous quantum polynomial-time circuits for generative modeling on noisy intermediate-scale quantum hardware, Physical Review A **113**, 042617 (2026).

[47] J.-Y. Ryu, W. Song, K. Bae, W. Lee, and I. Sohn, Deployment of large IQP circuit born machines on qubit-limited hardware using noise injection (2026), arXiv:2609.35163 [quant-ph].

[48] O. Balló-Gimbernat, Conditional generation with IQP circuits: Code and data (2026), gitHub repository.

[49] D. P. Kingma and J. Ba, Adam: A method for stochastic optimization, in *International Conference on Learning Representations* (2015) arXiv:1412.6980 [cs.LG].

[50] T. Akiba, S. Sano, T. Yanase, T. Ohta, and M. Koyama, Optuna: A next-generation hyperparameter optimization framework (2019), arXiv:1907.10902 [cs.LG].

[51] A. Defazio, X. A. Yang, H. Mehta, K. Mishchenko, A. Khaled, and A. Cutkosky, The road less scheduled (2024), arXiv:2405.15682 [cs.LG].

[52] J. Bergstra and Y. Bengio, Random search for hyper-parameter optimization, Journal of Machine Learning Research **13**, 281 (2012).

Appendix A: Hyperparameters and evaluation protocols

1. Common training settings

We train all models using the unbiased estimator of the squared-MMD objective. We keep the encoders fixed and initialize the circuit phases independently as $\theta_j \sim \mathcal{N}(0, s_\theta^2)$. At each update, we sample one fitting condition and one kernel bandwidth uniformly, then draw a target minibatch with replacement. We draw fresh nonidentity masks and apply the probability correction for excluding the identity mask. Mask budgets count draws, including repeated masks. We draw reference samples independently of the target minibatch and reuse them across masks. Table IV summarizes the translation, Curie–Weiss and scaling settings. Appendix B gives the separate two-dimensional Gaussian protocol.

For each initialization, we reset the optimizer and draw new circuit phases while reusing the target pools. For the experiments summarized in Table IV, each training seed includes all prescribed initializations, and we select the checkpoint with the lowest selection score across them. Reported uncertainty summarizes variation across independent training seeds.

We train the Gaussian and scaling models with `Adam` [49], using cosine learning-rate decay to one tenth of the initial rate. For the Curie–Weiss models, we use the optimizer selected by HPO and keep the learning rate constant. We set $b_1 = 0.9$, and use $b_2 = 0.999$ and $\epsilon = 10^{-8}$ for the `Adam` variants. We set weight decay to zero.

TABLE IV. Training settings and budgets per circuit. Mask and reference budgets give the number of draws per update. We select Curie–Weiss hyperparameters and checkpoints using full-distribution TVD. Table VI gives the search space for the optimizer, learning rate and initialization width. We report selected learning rates and initialization widths to three significant figures and display the expected mask weight 7.99 as 8. For Curie–Weiss, the update and initialization budgets apply to confirmation and evaluation; screening uses the smaller budgets specified in Sec. A 3 a.

Setting	Gaussian translation	Shared product input	Shared spin-flip input	Independent conditional	Independent unconditional	Scaling
Updates per initialization	1,024	2,000	2,000	2,000	2,000	5,000
Initializations per seed	1	3	3	3	3	3
Evaluation seeds	5	5	5	5	5	3
Training targets per condition	512	1,024	1,024	1,024	1,024	10,000
Target minibatch	128	256	256	256	256	450
Training mask draws	1,024	2,048	2,048	2,048	2,048	512
Training reference draws	1,024	2,048	2,048	2,048	2,048	1,024
Expected mask weights	$\{1\}$	$\{2, 4, 8\}$	$\{2, 4, 8\}$	$\{2, 4, 8\}$	$\{2, 4, 8\}$	$\{2, 4\}$
Checkpoint interval	32	100	100	100	100	25
Optimizer	`Adam`	`Adam`	`Adam`	`AdamW ScheduleFree`	`Adam`	`Adam`
Learning rate	0.005	0.0310	0.0100	0.0603	0.00844	0.01
Learning-rate schedule	Cosine	Constant	Constant	Constant	Constant	Cosine
Initialization width s_θ	0.25	0.696	0.500	0.119	0.117	0.1
Coefficient b_1	0.9	0.9	0.9	0.9	0.9	0.9

For an expected mask weight w, we set the Gaussian bandwidth to

$$\sigma(n, w) = \left[-2 \ln\left(1 - \frac{2w}{n}\right)\right]^{-1/2}, \qquad 0 < w < n/2, \tag{A1}$$

where n denotes the number of visible qubits and w is the expected mask weight before excluding the identity mask. We weight the bandwidths equally in the objective. For the sixteen-qubit Curie–Weiss models, we use $w \in \{2, 4, 7.99\}$ and display 7.99 as 8. Using 7.99 keeps $w < n/2$ and the bandwidth strictly positive.

We report rotation angles in radians and compute sixteen-qubit full and profile TVDs from exact circuit probabilities. Sampled-MMD diagnostics do not enter these calculations.

2. Discrete Gaussian translation

We use 16 visible qubits on an open 4×4 lattice. The learned unitary contains 16 one-body phase gates and 24 two-body phase gates between horizontal and vertical nearest neighbors. We prepare the input state with the fixed

product-state encoder

$$|\phi_{\mathrm{G}}(c)\rangle = \bigotimes_{i=1}^{16} R_Z(c-1/2)R_Y(1.5)\,|0\rangle_i\,. \tag{A2}$$

We choose the near-equatorial angle 1.5 radians empirically to avoid an input state whose output distribution the learned unitary cannot change. At $c = 0.5$, replacing this angle with $\pi/2$ would prepare $|+\rangle^{\otimes 16}$, a simultaneous eigenstate of every X-type generator in the IQP unitary. The learned parameters would then contribute only a global phase, leaving a uniform output distribution with a fixed binomial Hamming-weight profile. Using 1.5 removes this exact invariance and allows the learned parameters to modify the output distribution at $c = 0.5$.

We use the target Hamming-weight profile $\rho(k \mid c) \propto \exp[-(k-(5+6c))^2/8]$, where $k = |x|$. Within each Hamming-weight shell, we assign equal probability to all bitstrings. We train at $c \in \{0, 0.25, 0.5, 0.75, 1\}$, using 512 target samples per condition and 2560 per seed.

We evaluate the model at initialization and every 32 updates through update 1024, selecting the checkpoint with the lowest mean exact profile TVD over the development conditions $c \in \{0.125, 0.375, 0.625, 0.875\}$. We then evaluate the selected model at 80 held-out conditions, $c_j = (j + 1/3)/80$ for $j = 0, \ldots, 79$. We draw 1000 target samples per evaluation condition for auxiliary sampled-MMD diagnostics.

We compute full-distribution and profile TVDs from exact circuit probabilities. For each seed, we average each error over the evaluation conditions and report the median of these averages across five independent seeds. Figure 2 averages exact profiles across the five selected circuits at the development conditions and shows the median and interquartile range of their mean output Hamming weights at each held-out condition.

3. Curie–Weiss models

We use the sixteen-qubit target $p(x \mid \beta) \propto \exp[\beta(2|x| - 16)^2/32]$. For all trained sixteen-qubit Curie–Weiss models, we parameterize the learned unitary with 16 one-body phase gates and 120 two-body phase gates, without ancillas. For the shared product-input model, we prepare $R_Z(0.75\beta)R_Y(\pi/2)\,|0\rangle$ on every qubit. For the shared invariant model, we use the normalized projection of this product input onto the $+1$ eigenspace of the global spin-flip operator, as described in Sec. A 3 c.

We train both shared models at $\beta \in \{0.6, 0.8, 1.2, 1.4\}$, use $\beta \in \{0.5, 0.7, 1.3, 1.5\}$ for model selection, and report performance at $\beta \in \{0.4, 1.0, 1.6\}$. Each independent baseline family comprises three circuits that we fit directly at these reporting temperatures, using either the corresponding product input or $|0\rangle^{\otimes 16}$. For each baseline family, we select one optimizer, learning rate and initialization width jointly for its three circuits.

We train each circuit using 1024 target samples per fitting temperature and seed, minibatches of 256, and 2048 mask draws and 2048 reference draws per update. We store parameters and optimizer states in double precision and evaluate phase contractions in single precision. Table V summarizes the aggregate fitting resources.

For auxiliary sampled-MMD diagnostics, we use 2048 validation targets per fitting temperature and 2048 independently drawn test targets per reporting temperature. Each diagnostic uses 2048 mask draws per condition and bandwidth, and 2048 reference samples per condition shared across bandwidths. We do not use these diagnostics for model selection.

TABLE V. Curie–Weiss fitting budgets per seed for confirmation and evaluation. Training-target counts sum the pool entries over fitting temperatures and exclude repeated minibatch draws. Optimizer-update counts include all three initializations of every circuit. Each shared model fits one circuit, and each independent baseline family fits three.

Model	Trained circuits	Training targets	Optimizer updates
Shared product input	1	4,096	6,000
Shared spin-flip input	1	4,096	6,000
Independent conditional	3	3,072	18,000
Independent unconditional	3	3,072	18,000

a. *Hyperparameter optimization*

We run one Optuna study for each of the four model families, using a tree-structured Parzen estimator (TPE) [50]. Each study evaluates 60 configurations. We tune the optimizer choice among `Adam`, `AdamWScheduleFree` and

`SGDScheduleFree`, the constant learning rate, and the Gaussian initialization width [49, 51]. Table VI gives the search space. We assign each family the same number of trials, although each independent-family trial fits three circuits per seed.

We use random search as a reference for the trial budget [52]. For 60 independent configurations drawn from a fixed sampling distribution, the probability of sampling at least one configuration in its best-performing 5% is $1 - 0.95^{60} \approx 0.954$. This calculation motivates the budget but does not establish equivalent coverage for adaptive TPE proposals.

TABLE VI. Curie–Weiss hyperparameter search space. We treat optimizer choice as categorical and search learning rates and Gaussian initialization widths on a logarithmic scale.

Hyperparameter	Options or range
Optimizer	`Adam`, `AdamWScheduleFree`, `SGDScheduleFree`
Learning rate, `Adam` variants	$[3 \times 10^{-4}, 10^{-1}]$
Learning rate, `SGDScheduleFree`	$[10^{-3}, 1]$
Initialization width s_θ	$[0.01, 0.7]$ radians

We begin each study with 12 startup trials, including one reference configuration per optimizer. We set the reference learning rates to 0.01 for the `Adam` variants and 0.1 for `SGDScheduleFree`, with $s_\theta = 0.5$ for all reference configurations. We generate proposals in batches of two and update the sampler in proposal order. We do not prune trials.

We fix the optimizer coefficients as specified in the common training settings and use no warmup or gradient clipping. For schedule-free optimizers, we set the learning-rate weighting exponent to 2 and score checkpoints using the averaged parameters provided for evaluation.

For each screening trial, we train every circuit for 1000 updates on each of three seeds, using one initialization per seed. We compute exact TVD from the full distribution over the 2^{16} computational-basis states at initialization and every 100 updates. For each shared model, we select the checkpoint with the lowest mean TVD over the development temperatures. Within each independent baseline family, we select each circuit's checkpoint using TVD at its fitted temperature and average the three selected errors within each seed. We then take the median of the three seed scores as the trial score.

We confirm the three best distinct configurations from each study on five fresh seeds, training each circuit for 2000 updates from each of three initializations per seed. We select each circuit's checkpoint across its initializations using the same TVD criterion as in screening, then choose the configuration with the lowest median score across the five seeds.

We report performance using the five selected confirmation runs, without further fitting or checkpoint selection. Because these runs also inform hyperparameter selection, they do not provide an independent final evaluation. In the current protocol, we exclude the shared models' reporting temperatures from fitting and selection, although earlier experiments examined them. We fit the independent circuits directly at their reporting temperatures. For each temperature, we report the mean and sample standard deviation across the five seeds.

TABLE VII. Exact Hamming-weight profile TVD for sixteen-qubit Curie–Weiss models. We report means ± sample standard deviations across the five confirmation runs used for model selection and reporting. We select models using full-distribution TVD; encoder-only values are deterministic. We evaluate the shared model at temperatures excluded from fitting and current selection, and fit each independent circuit at its reporting temperature. Bold entries identify the lowest mean error at each temperature, including the encoder-only baseline.

Model	Evaluation	Hamming-weight profile TVD ↓		
		$\beta = 0.4$	$\beta = 1.0$	$\beta = 1.6$
Encoder only	Baseline	0.1180	0.4406	0.8699
Shared conditional IQP	Held-out	0.0976 ± 0.0269	0.1301 ± 0.0317	$\mathbf{0.0631 \pm 0.0135}$
Independent conditional IQPs	Fitted	$\mathbf{0.0939 \pm 0.0073}$	0.0885 ± 0.0116	0.3948 ± 0.0003
Independent unconditional IQPs	Fitted	0.1186 ± 0.0040	$\mathbf{0.0780 \pm 0.0320}$	0.3293 ± 0.0119

Table VII reports exact Hamming-weight profile errors for the primary Curie–Weiss comparison.

b. *Physical observables*

For a distribution q, let $\rho_q(k \mid \beta)$ denote its exact Hamming-weight profile and set $m_k = (2k-n)/n$ with $n = 16$. We compute its moments as $\langle m^r \rangle_q = \sum_{k=0}^{n} \rho_q(k \mid \beta) m_k^r$, and its mean absolute magnetization as $\sum_k \rho_q(k \mid \beta)|m_k|$. The target law corresponds to $H = -nm^2/2$ in units $J = k_B = 1$. Excluding self-interactions would add only a constant to H and would not change the energy variance. Equation (55) therefore becomes

$$c_{\mathrm{fluc},q}(\beta) = \frac{\beta^2 n}{4} \left(\langle m^4 \rangle_q - \langle m^2 \rangle_q^2 \right). \tag{A3}$$

The observables depend only on the shell profile and do not test uniformity within shells. For the Gibbs target, differentiating the mean energy per spin with respect to $T = \beta^{-1}$ gives this fluctuation expression. We do not assume that the learned family satisfies the same derivative identity.

We evaluate the shared product-input circuits selected by full-distribution TVD on 101 equally spaced inverse temperatures $\beta_j = 0.02j$, $j = 0, \ldots, 100$, using their frozen parameters and ordered generators. The grid includes the fitting temperatures $\{0.6, 0.8, 1.2, 1.4\}$ and development temperatures $\{0.5, 0.7, 1.3, 1.5\}$, as well as extrapolation below and above the fitting range. We reuse the five winning confirmation seeds 2026100610–2026100614; these are not an independent assessment of model selection. The selected checkpoint profiles and full-distribution TVDs at $\beta \in \{0.4, 1.0, 1.6\}$ reproduce the existing reporting records to numerical precision. We compute each observable separately within each seed before taking its mean and sample standard deviation, including the nonlinear heat-capacity estimate. The independent baselines appear only at their fitted temperatures, with the same within-seed calculation and aggregation. The uniform encoder reference has the binomial shell law $\rho_0(k) = 2^{-n}\binom{n}{k}$. These diagnostics do not change fitting, hyperparameter selection, or checkpoint selection.

c. *Spin-flip invariant temperature encoding*

The zero-field Curie–Weiss target satisfies $p(x \mid \beta) = p(\bar{x} \mid \beta)$, where $\bar{x}$ denotes the bitwise complement of x. We enforce this global spin-flip symmetry through the input state while retaining the temperature encoding and all 136 trainable circuit phases. With $n = 16$, $t = 0.75\beta$, and $F = X^{\otimes n}$, we project the product encoder onto the $+1$ eigenspace of F and normalize the resulting state:

$$|\phi_+(\beta)\rangle = \frac{(I + F)\,|\phi(\beta)\rangle}{\sqrt{2[1 + \cos^n(t)]}}. \tag{A4}$$

The identity $\langle \phi(\beta)|F|\phi(\beta)\rangle = \cos^n(t)$ gives the normalization factor. Because the IQP unitary commutes with F, it preserves the $+1$ eigenspace. The output therefore satisfies $q_{\boldsymbol{\theta},+}(x \mid \beta) = q_{\boldsymbol{\theta},+}(\bar{x} \mid \beta)$ for every parameter vector. We apply the symmetry construction of Recio-Armengol *et al.* [28, Sec. 6] to this conditional encoder following the criterion in Section V. The learned circuit can still break permutation symmetry, so this constraint does not guarantee equal probabilities within Hamming-weight shells.

The projected encoder preserves efficient classical access to the reference state $H^{\otimes n}\,|\phi_+(\beta)\rangle$. For a bitstring z with Hamming weight $k = |z|$, its amplitude is

$$\psi_{+,\beta}(z) = \frac{\mathbf{1}_{k \text{ even}} [\cos(t/2)]^{n-k} [-i \sin(t/2)]^k}{\sqrt{[1 + \cos^n(t)]/2}}. \tag{A5}$$

The indicator equals one for even k and zero otherwise, so the reference state has support only on bitstrings of even Hamming weight.

We draw k from a binomial distribution with n trials and success probability $\sin^2(t/2)$, conditioned on even k. We then choose a bitstring uniformly among those with Hamming weight k. For a sampled string z, the amplitude ratio is

$$R_{+,\beta}(z, a) = \begin{cases} [-i \tan(t/2)]^{|z \oplus a| - |z|}, & |a| \text{ even}, \\ 0, & |a| \text{ odd}. \end{cases} \tag{A6}$$

A mask with odd Hamming weight moves z outside the reference-state support, giving a zero amplitude ratio.

These sampling and amplitude-ratio calculations require polynomial resources, so the projected encoder supports the conditional estimators and MMD training objective developed above.

We can prepare the invariant input deterministically by tracking parity on the last qubit of the existing register. We initialize all n qubits in $|0\rangle$, set $t = 0.75\beta$, and write $Z_\ell^{(p)} = [1+(-1)^p \cos^\ell(t)]/2$ for the probability that ℓ independent reference bits have parity $p \in \{0,1\}$. At each step, p denotes the parity of the prepared prefix, and ℓ counts the remaining qubits, including the parity qubit. We apply a parity-controlled R_Y rotation to the next unprepared qubit, with angle

$$\alpha_p = 2\,\mathrm{atan2}\left(\sin(t/2)\sqrt{Z_{\ell-1}^{(p\oplus 1)}}, \cos(t/2)\sqrt{Z_{\ell-1}^{(p)}}\right). \tag{A7}$$

We then apply a controlled-NOT (CNOT) gate from the newly prepared qubit to the last qubit to update the parity. Repeating this procedure on the first $n-1$ qubits prepares the reference-state magnitudes conditioned on even parity. We apply a single-qubit phase gate that multiplies $|1\rangle$ by $-i$ on every qubit to obtain Eq. (A5), then apply Hadamards to all qubits to prepare Eq. (A4). The construction uses $O(n)$ gates without ancillas or postselection.

Because the IQP unitary commutes with the global spin-flip operator, we obtain

$$q_{\boldsymbol{\theta},+}(x \mid \beta) = \frac{|A_{\boldsymbol{\theta},\beta}(x) + A_{\boldsymbol{\theta},\beta}(\bar{x})|^2}{2[1+\cos^n(t)]}, \tag{A8}$$

where $A_{\boldsymbol{\theta},\beta}(x) = \langle x|U_{\boldsymbol{\theta}}|\phi(\beta)\rangle$. Interference between these amplitudes changes the model family, but does not guarantee a better fit.

We obtain the encoder-only distribution by setting the learned unitary to the identity: $q_{0,+}(x \mid \beta) = [1+\cos((2|x|-n)t)]/[2^n(1+\cos^n(t))]$. Because the Curie–Weiss target and both encoder-only distributions are uniform within each Hamming-weight shell, each encoder's full-distribution TVD equals its profile TVD.

We compare the shared product-input and spin-flip-invariant models using separate HPO studies with matched budgets and paired seeds. Both studies use the same fitting and development temperatures and the protocol in Section A 3 a. We use exact full-distribution TVD for model selection and reuse the selected confirmation runs for reporting (Table VIII).

Within each seed, we reuse the same target pools and Gaussian initialization directions and follow the same condition, minibatch, bandwidth and mask schedules. The tuned initialization widths may differ. For reference sampling, we reuse random numbers but sample from the distribution associated with each input. We retain odd-weight masks in the objective, although global spin-flip symmetry makes the corresponding moments of the projected model vanish.

We quantify deviations from global spin-flip symmetry using

$$D_{\mathrm{flip}}(q \mid \beta) = \frac{1}{2}\sum_x |q(x \mid \beta) - q(\bar{x} \mid \beta)|. \tag{A9}$$

The diagnostic vanishes exactly for spin-flip invariant distributions. For the trained product model, we obtain mean D_{flip} values of 0.4354, 0.1092, and 0.0087 at $\beta = 0.4, 1.0, 1.6$, respectively. The projected input enforces $D_{\mathrm{flip}} = 0$ at every temperature, independently of optimization. Numerical evaluation confirms this guarantee to machine precision.

TABLE VIII. Exact full-distribution TVD for the sixteen-qubit Curie–Weiss encoder comparison. We report means ± sample standard deviations across five paired confirmation runs used for model selection and reporting. Bold entries mark the lowest mean TVD at each temperature.

Model	$\beta = 0.4$	$\beta = 1.0$	$\beta = 1.6$
Product-state input	0.2240 ± 0.0115	0.2175 ± 0.0136	$\mathbf{0.1709 \pm 0.0136}$
Spin-flip invariant input	$\mathbf{0.0902 \pm 0.0184}$	$\mathbf{0.1889 \pm 0.0134}$	0.1805 ± 0.0276

Without the learned circuit, the product-state encoder has full-distribution TVDs of 0.1180, 0.4406, and 0.8699 at $\beta = 0.4, 1.0, 1.6$, respectively; the spin-flip invariant encoder gives 0.2561, 0.5536, and 0.9002. Input projection alone therefore does not improve the fit at these temperatures.

Table IX summarizes paired full-distribution TVD differences. We compute these differences within each seed before calculating their mean and sample standard deviation. The spin-flip-invariant model achieves lower full-distribution TVD than the product-input model in all five paired runs at $\beta = 0.4$ and 1.0, and in two of five at $\beta = 1.6$.

TABLE IX. Paired differences in exact full-distribution TVD for sixteen-qubit Curie–Weiss models. Within each seed, we subtract the product-input model's TVD from the spin-flip-invariant model's TVD. Negative values favor the invariant input. We report the mean and sample standard deviation (SD) of these differences across the five paired confirmation runs used for model selection and reporting.

Statistic	$\beta = 0.4$	$\beta = 1.0$	$\beta = 1.6$
Mean	−0.1338	−0.0287	0.0096
Sample SD	0.0199	0.0154	0.0218

4. Scaling

We use the product-state Curie–Weiss encoder on every qubit, with no ancillas, and adopt the open lattice architectures listed in Table X. At size n, the target distribution is $p(x \mid \beta) \propto \exp[\beta(2|x| - n)^2/(2n)]$.

We train at $\beta \in \{0.6, 0.8, 1.2, 1.4\}$, using 10,000 target samples per condition and 40,000 per seed. We evaluate at $\beta \in \{0.4, 0.95, 1.0, 1.05, 1.6\}$ and use three independent seeds at each size. We use the cosine-decay `Adam` settings in Table IV, with 5000 updates per initialization and three initializations per seed. These settings differ from the selected sixteen-qubit configurations. We have not tested the transfer of those configurations or retuned the scaling models.

TABLE X. Open rectangular lattice architectures for the scaling experiments. We assign one trainable phase to each qubit and one to each horizontal or vertical nearest-neighbor pair.

Visible qubits	Lattice	Trainable parameters
64	8×8	176
128	8×16	360
256	16×16	736
512	16×32	1,488
1,024	32×32	3,008
2,048	32×64	6,048

We select the checkpoint with the lowest mean sampled validation MMD^2 across training temperatures and bandwidths. We evaluate initialization and every 25 updates across three initializations. We exclude held-out temperatures from fitting and selection.

For each seed, we report the selected initialization at update 0 and every 500 updates through update 5000. At each reporting update, we average five independent MMD^2 estimates over the evaluation temperatures and bandwidths. Each estimate uses 2000 target draws per condition, 512 mask draws per condition and bandwidth, and 1024 reference draws per condition. We reuse reporting sample sets across updates and share reference samples across bandwidths. Figure 6 shows the median and interquartile range across the three seed averages. We retain negative unbiased MMD^2 estimates.

Appendix B: Two-dimensional Gaussian encoder and evaluation protocol

1. Fitting, development and reporting conditions

For joint-variation training, fitting conditions are $\{-1, 0, 1\}^2$ and development conditions are

$$\{-1, -0.5, 0, 0.5, 1\} \times \{-0.75, -0.25, 0.25, 0.75\}.$$

Reporting uses

$$u \in \{-1, -0.83, -0.37, 0.19, 0.61, 1\},$$
$$v \in \{-1, -0.79, -0.31, 0.23, 0.67, 1\}.$$

We omit the four fitted corners from the original reporting average, retaining thirty-two held-out pairs.

For separate-variation training, we fit $(u, 0)$ at $u \in \{-1, -0.37, 0, 0.37, 1\}$ and $(0, v)$ at $v \in \{-1, -0.31, 0.31, 1\}$. Development uses $(u, 0)$ at $u \in \{-0.73, -0.17, 0.17, 0.73\}$ and $(0, v)$ at $v \in \{-0.69, -0.13, 0.13, 0.69\}$. The sixteen

reporting pairs are

$$\{-1, -0.37, 0.37, 1\} \times \{-1, -0.31, 0.31, 1\}.$$

Every mixed reporting pair is absent from both fitting and development. The condition $|u| + |v| \leq 1$ identifies the four pairs inside the joint fitting hull; twelve pairs lie outside it. No coordinate exceeds its marginal fitting range. Some of these target conditions appeared in earlier exploratory studies; the reporting claim concerns pairs withheld from the present models' fitting and selection.

2. Sampled training and model selection

Each seed has a fixed pool of 1024 target bitstrings per fitting condition. Every update samples one condition and one kernel bandwidth uniformly, draws a target minibatch of 256 with replacement, and draws 1024 reference samples and 1024 nonidentity masks. We refresh masks and reference samples each update and retain the identity-mask probability correction. Conditional on the target pool, the sampled loss targets its empirical distribution. We use float64 estimator arithmetic with float32 phase-matrix contractions. Adam uses $b_1 = 0.9$, $b_2 = 0.999$, $\epsilon = 10^{-8}$ and zero weight decay. The learning rate follows cosine decay to one tenth of its initial value.

We independently screen eight predefined settings for each training design using 512 updates and checkpoints every 64 updates. The settings vary the initial learning rate, Gaussian phase-initialization scale and expected mask weights. We confirm the two candidates with lowest development full TVD using two new seeds and 2000 updates, selecting the candidate with lower mean development full TVD. Joint variation selects learning rate 0.01, initialization scale 0.25 and expected mask weights $\{1, 2, 4\}$. Separate variation selects learning rate 0.03, initialization scale 0.5 and expected mask weights $\{2, 4\}$. Confirmation and final fits evaluate checkpoints every 100 updates, including initialization and the last update. Checkpoints minimize mean exact development full TVD.

The eight settings are: learning rate 0.005, initialization scale 0.25, expected mask weight $\{1\}$; $(0.03, 0.5, \{2, 4\})$; $(0.003, 0.25, \{2, 4\})$; $(0.01, 0.25, \{2, 4\})$; $(0.03, 0.25, \{2, 4\})$; $(0.01, 0.1, \{2, 4\})$; $(0.01, 0.25, \{1, 2, 4\})$; and $(0.01, 0.25, \{2, 4, 6\})$. The mask law has the specified expected Hamming weight before conditioning on a nonidentity mask. Each target pool, parameter initialization, condition sequence, bandwidth sequence, masks and reference samples has its own reproducible RNG stream. The run receipts record the seed offsets, package versions and source hashes.

Screening uses seed 2026101901, confirmation uses seeds 2026101911 and 2026101912, and final fitting uses seeds 2026101921 through 2026101925. Within each stage, target pools and training random streams are matched across candidates of the same design. Both selected configurations become fixed before either reporting grid is evaluated. Final fits are independent of the seeds used for configuration selection. Figure shading uses the pointwise mean of five full-distribution TVDs. Table summaries first average over conditions within each fit, then compute the mean and sample standard deviation with divisor 4 across five fits. We do not evaluate the TVD of a mixture of fitted models.

3. Dense-grid evaluation and aggregation

After completing selection and the original reporting, we evaluate the frozen models on $u, v \in \{-1, -0.95, \ldots, 0.95, 1\}$. The heatmaps include all 1681 pairs and mark the fitting conditions. The common table domain removes any pair present in either design's fitting or development set, leaving 1652 pairs. Of these, 828 satisfy $|u| + |v| \leq 1$ and 824 lie outside that hull. This grouping is defined by the separate-variation design and applied identically to both models and the baseline. The denser grid is a descriptive post-selection evaluation; it does not supply an additional independent training replicate or a new confirmatory reporting set. Exact probability replay at all original reporting conditions verifies every dense evaluator against its stored checkpoint outputs. Heatmap cells show directly evaluated points without smoothing.

4. Simplification and conditional-response diagnostics

The simplicity study first compares a forty-phase lattice with reciprocal-squared width, a sixteen-phase local layer with that width, and a forty-phase lattice with reciprocal-first-power width. Each variant repeats eight screens, four confirmation fits and five final fits per design, giving 102 fits. We then repeat both designs for the sixteen-phase reciprocal-first-power candidate, giving 34 fits. A development-only exact capacity probe motivates a final 34-fit repetition with one shared phase. Adam differentiates through expansion of that scalar to sixteen physical phases.

The tied model retains sixteen physical rotations and the same correlated preparation. Its scalar initialization is the first draw from the same Gaussian law, so its effective initial state differs from the untied model. All candidates and unsuccessful fits remain in the result records.

Hyperparameter selection uses exact development full TVD, never reporting TVD or width-response diagnostics. Both design winners are frozen before final reporting. The comparison of architectures is adaptive and informed by earlier results; the reporting coordinates are not untouched confirmatory data. The final choice retains sixteen independent local phases because the shared-angle model weakens width sensitivity despite comparable full TVD. No post-hoc numerical calibration threshold is imposed. Width-response and input-clamp diagnostics accompany all final fits.

For the retained model, the endpoint width-response ratio is 0.405 after separate-variation training and 0.126 after joint-variation training. We compute the change in generated standard deviation between $v = -1$ and $v = 1$ at each fixed u in the original reporting grid, divide by the corresponding target change, and average over those u values and fits. This diagnostic uses the full original grid, including the fitted corners of the joint-variation grid that we exclude from its reporting TVD. A ratio of one would match the target change. The single-angle model gives ratios 0.073 and 0.083, respectively. Its original reporting TVD is 0.0665 ± 0.0001 for separate variation and 0.0633 ± 0.0002 for joint variation. For separate variation, freezing $v = 0$ increases the single-angle error to 0.0689, compared with 0.0773 for the retained model. We evaluate clamping on each original reporting set without retraining. These diagnostics measure the fitted model's sensitivity, rather than the optimum attainable by a condition-blind model. Local nonmonotonic width responses remain in one of five retained separate-variation fits and are more pronounced after joint variation.

5. Reference access and input-state preparation

We write the encoder's computational-basis amplitude at weight k as

$$a_{u,v}(k) = \sqrt{\frac{r_v(k)}{\binom{16}{k}}}\exp[-iu(16-2k)/4]. \tag{B1}$$

The Hadamard transform preserves permutation symmetry. For a reference bitstring of weight j, its amplitude is

$$\psi_{u,v}(j) = 2^{-8}\sum_{k=0}^{16} a_{u,v}(k)\mathcal{K}_k(j), \tag{B2}$$

$$\mathcal{K}_k(j) = \sum_{\ell=0}^{k}(-1)^\ell \binom{j}{\ell}\binom{16-j}{k-\ell}, \tag{B3}$$

with binomial coefficients outside their valid ranges equal to zero. We normalize and tabulate these seventeen amplitudes. Sampling first draws j with probability $\binom{16}{j}|\psi_{u,v}(j)|^2$, then draws a uniform weight-j bitstring. For a mask b and reference sample z, the estimator obtains its amplitude ratio from the entries at $|z|$ and $|z \oplus b|$. It only divides by amplitudes on the sampled support. For general n, the same construction uses a polynomial-size shell table and transform.

The correlated preparation precedes the local R_Z encoder and learned R_X rotations. It contributes to the physical resources even though it introduces no learned parameters. One preparation route maintains the Hamming weight of the prepared prefix in a clean counter. Define the per-string probability $g(k) = r_v(k)/\binom{n}{k}$, the suffix sum $F(n,k) = g(k)$, and the recursion

$$F(i,k) = F(i+1,k) + F(i+1,k+1). \tag{B4}$$

At prefix length i and prefix weight k, a counter-controlled R_Y rotation with angle

$$2\arcsin\sqrt{\frac{F(i+1,k+1)}{F(i,k)}} \tag{B5}$$

prepares the next conditional bit amplitude. We update the counter after each visible qubit and uncompute it after preparing all bits. At $n = 16$, this construction uses five clean workspace qubits, 136 counter-controlled rotations, 160 controlled counter-update operations and sixteen local R_Z rotations. These 312 high-level operations exclude the learned layer and do not specify elementary-gate depth. The campaign uses classical shell access and validates circuit probabilities through explicit state-vector preparation. It does not execute the counter circuit; earlier small-register checks used the reciprocal-squared profile. These results therefore establish reference access for training, without demonstrating hardware preparation.