Seq2Seq Modeling for RDF triples to Natural Text

Oral and Written Language Processing (GCED-UPC) Spring Semester


David Bergés, Roser Cantenys, Roger Creus, Oriol Domingo Professor: José Adrián Fonollosa

- 1) Problem
- 2) System Architecture
- **3)** Experiments
- 4) Results
- 5) Next Steps

Problem - Contextualization

- Knowledge Base (KB): large source of information represented in a structured way.
- Resources Description Frameworks (RDF): Base of the information structure which consists in 3 elements and establishes relations between them.
 - Predicate (relation), subject and object (entities)

Problem - Example



Triples

RDF

<Antoni Gaudí, design, Sagrada Família>
<Antoni Gaudí, birthPlace, Barcelona>
<Sagrada Família, location, Barcelona>

(b) Knowledge base and its RDF triples.

Natural Sentence

Antoni Gaudí was born in Barcelona, the city where he designed Sagrada Família.

(c) Corresponding natural language description.

Problem - Description

Two main tasks

- RDF to Text generation
- Text to RDF semantic parsing

Problem - Formal Definition

- Input: KB denoted as a set of RDFs, $\mathcal{K}:=\{r_1,\ldots,r_n\}$ and each RDF is defined as $\langle s_i,p_i,o_i\rangle$.
- **Output:** sequence of sentences \mathcal{S} , each sentence is a sequence of words $[w_1, \ldots, w_m]$ which should be grammatically correct and should also contain all the information present in \mathcal{K} .

Problem - Objectives

End-to-end Architectures

- Encoder-Decoder Convolutional
- Encoder-Decoder Transformer


Model Enhancement

- Byte-Pair Encoding
- Back Translation
- Embeddings

System Architecture - Approach

Natural Language Generation (NLG)

· Data to Text - RDF to Text



· Text to Text - MachineTranslation

System Architecture - Preprocessing


• **Delexicalisation:** Entity name to Entity type

(Rome, capital of, Italy) \rightarrow (CITY, CAPITALOF, COUNTRY)

- Moses Tokenization
- Byte-Pair Encoding (BPE)


System Architecture - Models

Transformer



Ashish Vaswani et al. : Attention Is All You Need

Convolutional



Angela Fan et al. : Hierarchical Neural Story Generation

System Architecture - Postprocessing

• Relexicalisation: Entity type to Entity name

CITY is the CAPITALOF COUNTRY \rightarrow Rome is the capital of Italy

- Moses Detokenization
- Byte-Pair Decoding

Experiments - Byte-Pair Encoding & Embeddings

Byte-Pair Encoding

Optimum subwords' number

Embeddings

- Learned embeddings
- Pretrained embeddings without BPE and delex.

Experiments - Back Translation

Back Translation Model

Predict using Monolingual

Text to RDF

BPE + Lexicalise


Transformer Model

Wikipedia Data Base

Preprocessing DB

Experiments - Back Translation

Back Translation Performance




Generated Data

Poor synthetic data

Remove BPE


Filter Monolingual text Pretrained embeddings

Results - Data



Results - Hyperparameter Tuning

- · Grid Search on Transformer > 100 models
- · Small Search on Convolutional 3 models



Results - System Prediction

Input

Arròs negre country Spain

Arròs negre mainIngredients
White rice, cuttlefish or
squid, cephalopod ink,
cubanelle peppers

Arròs negre region Catalonia

Arròs negre ingredient

Cuttlefish

Output

Arròs negre is a food found in Catalonia, Spain. The main ingredients of Arròs negre are White rice, cuttlefish or squid, cephalopod ink, cubanelle peppers

Next Steps - Short Term

Training Phase

- More solid results
- Use BT generated Data

Experiments

- Influence of BPE
- Comparative results of embeddings

Next Steps - Long Term

• Submit Results WebNLG Challenge 2020

Seq2Seq Modeling for RDF triples to Natural Text

Oral and Written Language Processing (GCED-UPC) Spring Semester

David Bergés, Roser Cantenys, Roger Creus, Oriol Domingo Professor: José Adrián Fonollosa