

Ferroelectric Recording For HDD Application

Jun Ohno

Western Digital Technologies, Fujisawa 252-0888, Japan, jun.ohno@wdc.com

Hard disk drives (HDDs) have achieved continuous areal density scaling through successive technological innovations. However, further progress is increasingly constrained by the fundamental limitations of magnetic recording. In this work, we explore ferroelectric recording as a potential alternative paradigm for HDD type storage, in which the control variable is shifted from magnetic field to electric field. Ferroelectric materials exhibit bistable polarization states suitable for nonvolatile data storage and offer the potential for sharp transitions due to weak domain interactions. We investigate the feasibility of HDD type recording on ferroelectric thin films. The results indicate that transition based recording and structured data storage are achievable, while challenges remain in readout, high speed operation, and interface reliability. These findings suggest that ferroelectric recording could provide a new pathway for extending HDD scaling beyond magnetic technologies.

Index Terms—Hard disk drives, areal density, ferroelectric recording.

I. INTRODUCTION

The continuous scaling of HDD areal density has been driven by a series of breakthroughs in media, head technologies, and signal processing. However, the rate of density increase has slowed in recent years as magnetic recording approaches its fundamental limits. This limitation is commonly described by the trade off among signal to noise ratio, thermal stability, and writability.

Advanced approaches such as heat assisted magnetic recording mitigate this constraint, but further scaling toward 10 terabit per square inch remains uncertain [1]. This motivates the exploration of alternative physical mechanisms that can complement or replace magnetization based recording.

In this work, we investigate ferroelectric recording as such an alternative. In this approach, information is stored in the polarization states of a ferroelectric material rather than magnetization. Similar to magnetic systems, ferroelectrics exhibit bistable states in the absence of an external field, enabling nonvolatile data storage. By leveraging electric field driven polarization switching, this approach introduces a fundamentally different physical mechanism for recording while preserving the concept of transition based data storage in an HDD type framework.

II. CONCEPT OF FERROELECTRIC RECORDING

Fig. 1 illustrates the conceptual correspondence between conventional magnetic recording and ferroelectric recording. In magnetic recording, information is stored in the direction of

magnetization in a ferromagnetic material, as represented by the hysteresis loop shown on the left side of the figure. Writing is achieved by applying a magnetic field generated from a current driven coil in the recording head.

In ferroelectric recording, information is stored in the polarization state of a ferroelectric material, as represented by the polarization electric field (P-E) hysteresis loop on the right side of the figure. Writing is performed by applying a voltage to an electrode, which generates an electric field across the recording layer and switches the polarization state.

The overall recording concept remains closely related between the two systems. In both cases, binary information is encoded in two stable states and written by an external field applied from a moving head. The essential difference lies in the physical quantity used for control. Magnetic recording relies on magnetic field and magnetization. Ferroelectric recording relies on electric field and polarization[2].

This shift in the control parameter enables the introduction of a new physical mechanism into an HDD type recording framework while preserving its basic architecture.

III. POTENTIAL ADVANTAGES FOR HIGH-DENSITY

In magnetic recording, strong exchange coupling requires granular or patterned structures to localize transitions. This leads to limitations associated with finite grain size and irregular transition boundaries.

In contrast, ferroelectric materials exhibit weaker interactions between domains, enabling sharp transitions even




Fig. 1 a. Ferromagnetic recording b. ferroelectric recording

in continuous films[3]. This property allows transitions to form without being constrained by predefined microstructures.

As a result, ferroelectric recording offers the potential for improved transition definition and higher achievable density, providing a fundamentally different scaling pathway from conventional magnetic recording.

IV. FEASIBILITY OF HDD-LIKE RECORDING ON FERROELECTRIC FILMS

To examine the feasibility of HDD type recording on ferroelectric materials, we first evaluate the formation of continuous transitions under dynamic writing conditions. A scanning probe platform is used to emulate the motion of a recording head while applying an alternating voltage to the probe during lateral scanning. This configuration enables the formation of periodic polarization transitions along the scan direction, providing a model system to assess spatial resolution and the basic behavior of transition based recording.

These results confirm that stable and repeatable transitions can be generated on ferroelectric thin films in a manner consistent with HDD type recording concepts. This establishes a basis for evaluating information storage beyond simple periodic signals.




Fig. 2 Company logo recorded in a single-crystal LiTaO₃ thin film

Fig. 2 shows an example of recording a structured pattern on a ferroelectric thin film. In this experiment, a voltage is applied to the probe while scanning laterally, and adjacent tracks are written with a controlled offset to build up a two dimensional pattern through successive overwriting. This process corresponds to a recording scheme analogous to that used in shingled recording.

The recorded image demonstrates that polarization domains can be organized into a recognizable pattern with clear contrast. This result indicates that ferroelectric recording is capable of supporting arbitrary data representation rather than being limited to periodic transitions.

Although these demonstrations are carried out using a model experimental platform, they provide direct evidence that both

transition based recording and structured information storage are feasible within an HDD type recording framework.

V. CONSIDERATIONS FOR PRACTICAL IMPLEMENTATION

Although the feasibility study indicates promising behavior, several key challenges must be addressed to enable practical HDD applications.

First, unlike magnetic systems, ferroelectric domains do not naturally produce detectable external fields due to charge screening effects. As a result, readout requires active probing techniques, such as nonlinear dielectric detection methods, which must be adapted to non-contact and high-speed operation.

Second, the head-media interface introduces new constraints. Polarization switching requires electric fields exceeding the coercive field, and the dielectric properties of ferroelectrics can concentrate the electric field within the head-media gap. This may lead to extremely high local fields, raising concerns about reliability and stability of the interface.

In addition, achieving data rates comparable to modern HDD systems remains a significant challenge, as both writing and readout mechanisms must operate in the GHz regime.

VI. SUMMARY

We have explored ferroelectric recording as an alternative approach for extending HDD scaling. By replacing magnetization with polarization, this method introduces a new physical mechanism while preserving the recording architecture.

Feasibility studies confirm that both transition based recording and structured information storage can be realized on ferroelectric thin films. At the same time, key challenges remain in readout speed, and interface stability.

Ferroelectric recording represents a promising direction for future storage technologies and warrants further study.

ACKNOWLEDGEMENT

The author would like to thank Prof. Yasuo Cho of Tohoku University for valuable discussions and prior work on ferroelectric recording. The author also acknowledges NGK for providing ferroelectric thin film samples used in this study.

REFERENCES

- [1] E. Roddick, M. Kief, A. Takeo, "A new Advanced Storage Research Consortium HDD Technology Roadmap", TMRC (2022)
- [2] Y. Hiranaga et al., "Nanodomain Formation on Ferroelectrics and Development of Hard-Disk-Drive-Type Ferroelectric Data Storage Devices," Jpn. J. Appl. Phys., vol. 48, 09KA18, 2009.
- [3] T. Aoki, Y. Hiranaga, and Y. Cho, "High-density ferroelectric recording using a hard disk drive-type data storage system", J. Appl. Phys. 119, 184101 (2016)