

SQL PRACTICE NOTES - ORDERS TABLE

2520030030

U.Rohit Sai

STEP 1: CREATE TABLE

MySQL Workbench

Local instance MySQL80 x

File Edit View Query Database Server Tools Scripting Help

Navigator: MANAGEMENT
Server Status
Client Connections
Users and Privileges
Status and System Variables
Data Export
Data Import/Restore
INSTANCE
Startup / Shutdown
Server Logs
Options File
PERFORMANCE
Dashboard
Performance Reports
Performance Schema Setup

Query 1 SQL File 4* Week-2* SQL File 5* SQL File 6* x

```
1 • USE aggregate_db;  
2 • CREATE TABLE orders (  
3     ord_no INT PRIMARY KEY,  
4     purch_amt DECIMAL(10,2),  
5     ord_date DATE,  
6     customer_id INT,  
7     salesman_id INT  
8 );
```

Output

#	Time	Action	Message
✓ 1	10:18:53	USE aggregate_db	0 row(s) affected
✓ 2	10:18:57	CREATE TABLE orders (ord_no INT PRIMARY KEY, purch_amt DECIMAL(10,2), ord_date DATE, cust...	0 row(s) affected

STEP 2: INSERT DATA

MySQL Workbench

Local instance MySQL80 x

File Edit View Query Database Server Tools Scripting Help

Navigator: MANAGEMENT
Server Status
Client Connections
Users and Privileges
Status and System Variables
Data Export
Data Import/Restore
INSTANCE
Startup / Shutdown
Server Logs
Options File
PERFORMANCE
Dashboard
Performance Reports
Performance Schema Setup

Query 1 SQL File 4* Week-2* SQL File 5* SQL File 6* x

```
1 • INSERT INTO orders VALUES  
2 (30030,150.50,'2012-10-05',3005,5002),  
3 (70009,270.65,'2012-09-10',3001,5005),  
4 (70002,65.26,'2012-10-05',3002,5001),  
5 (70004,110.50,'2012-08-17',3009,5003),  
6 (70007,948.50,'2012-09-10',3005,5002),  
7 (70005,2400.60,'2012-07-27',3007,5001),  
8 (70008,5760.00,'2012-09-10',3002,5001),  
9 (70010,1983.43,'2012-10-10',3004,5006),  
10 (70003,2480.40,'2012-10-10',3009,5003),
```

Output

#	Time	Action	Message
✓ 1	10:18:53	USE aggregate_db	0 row(s) affected
✓ 2	10:18:57	CREATE TABLE orders (ord_no INT PRIMARY KEY, purch_amt DECIMAL(10,2), ord_date DATE, cust...	0 row(s) affected
✓ 3	10:20:11	INSERT INTO orders VALUES (30030,150.50,'2012-10-05',3005,5002), (70009,270.65,'2012-09-10',3001,5005), (...	12 row(s) affected Records: 12 Duplicates: 0 Warnings: 0

1 - WHERE CLAUSE :

MySQL Workbench

Local instance MySQL80

File Edit View Query Database Server Tools Scripting Help

Navigator

MANAGEMENT

- Server Status
- Client Connections
- Users and Privileges
- Status and System Variables
- Data Export
- Data Import/Restore

INSTANCE

- Startup / Shutdown
- Server Logs
- Options File

PERFORMANCE

- Dashboard
- Performance Reports
- Performance Schema Setup

Administration Schemas

Query 1 SQL File 4* Week-2* SQL File 5* SQL File 6*

Limit to 1000 rows

```
1 SELECT *
2 FROM orders
3 WHERE purch_amt > 2000;
```

Result Grid

ord_no	purch_amt	ord_date	customer_id	salesman_id
70003	2480.40	2012-10-10	3009	5003
70005	2400.60	2012-07-27	3007	5001
70008	5760.00	2012-09-10	3002	5001
70013	3045.60	2012-04-25	3002	5001

Output

Action Output

#	Time	Action	Message
1	10:18:53	USE aggregate_db	0 row(s) affected
2	10:18:57	CREATE TABLE orders (ord_no INT PRIMARY KEY, purch_amt DECIMAL(10,2), ord_date DATE, cus...	0 row(s) affected
3	10:20:11	INSERT INTO orders VALUES (30030,150.50,2012-10-05,3005,5002), (70009,270.65,2012-09-10,3001,5005), ...	12 row(s) affected Records: 12 Duplicates: 0 Warnings: 0
4	10:21:01	SELECT * FROM orders WHERE purch_amt > 2000 LIMIT 0, 1000	4 row(s) returned

MySQL Workbench

Local instance MySQL80

File Edit View Query Database Server Tools Scripting Help

Navigator

MANAGEMENT

- Server Status
- Client Connections
- Users and Privileges
- Status and System Variables
- Data Export
- Data Import/Restore

INSTANCE

- Startup / Shutdown
- Server Logs
- Options File

PERFORMANCE

- Dashboard
- Performance Reports
- Performance Schema Setup

Administration Schemas

Query 1 SQL File 4* Week-2* SQL File 5* SQL File 6*

Limit to 1000 rows

```
1 SELECT *
2 FROM orders
3 WHERE ord_date='2012-09-10';
```

Result Grid

ord_no	purch_amt	ord_date	customer_id	salesman_id
70007	948.50	2012-09-10	3005	5002
70008	5760.00	2012-09-10	3002	5001
70009	270.65	2012-09-10	3001	5005

orders 2

Output

Action Output

#	Time	Action	Message
1	10:18:53	USE aggregate_db	0 row(s) affected
2	10:18:57	CREATE TABLE orders (ord_no INT PRIMARY KEY, purch_amt DECIMAL(10,2), ord_date DATE, cus...	0 row(s) affected
3	10:20:11	INSERT INTO orders VALUES (30030,150.50,2012-10-05,3005,5002), (70009,270.65,2012-09-10,3001,5005), ...	12 row(s) affected Records: 12 Duplicates: 0 Warnings: 0
4	10:21:01	SELECT * FROM orders WHERE purch_amt > 2000 LIMIT 0, 1000	4 row(s) returned
5	10:22:14	SELECT * FROM orders WHERE ord_date='2012-09-10' LIMIT 0, 1000	3 row(s) returned

MySQL Workbench

Local instance MySQL80 x

File Edit View Query Database Server Tools Scripting Help

Navigator

MANAGEMENT

- Server Status
- Client Connections
- Users and Privileges
- Status and System Variables
- Data Export
- Data Import/Restore

INSTANCE

- Startup / Shutdown
- Server Logs
- Options File

PERFORMANCE

- Dashboard
- Performance Reports
- Performance Schema Setup

Administration Schemas

Information

Query 1 SQL File 4* Week-2* SQL File 5* SQL File 6* x

Limit to 1000 rows

```

1 SELECT *
2 FROM orders
3 WHERE salesman_id=5001;

```

Result Grid

ord_no	purch_amt	ord_date	customer_id	salesman_id
70002	65.26	2012-10-05	3002	5001
70005	2400.60	2012-07-27	3007	5001
70008	5760.00	2012-09-10	3002	5001
70013	3045.60	2012-04-25	3002	5001

orders 3 x

Output

Action Output

#	Time	Action	Message
1	10:18:53	USE aggregate_db	0 row(s) affected
2	10:18:57	CREATE TABLE orders (ord_no INT PRIMARY KEY, purch_amt DECIMAL(10,2), ord_date DATE, cus...	0 row(s) affected
3	10:20:11	INSERT INTO orders VALUES (30030,150.50,'2012-10-05',3005,5002), (70009,270.65,'2012-09-10',3001,5005), ...	12 row(s) affected Records: 12 Duplicates: 0 Warnings: 0
4	10:21:01	SELECT * FROM orders WHERE purch_amt > 2000 LIMIT 0, 1000	4 row(s) returned
5	10:22:14	SELECT * FROM orders WHERE ord_date='2012-09-10' LIMIT 0, 1000	3 row(s) returned
6	10:23:15	SELECT * FROM orders WHERE salesman_id=5001 LIMIT 0, 1000	4 row(s) returned

4 - ORDER BY

MySQL Workbench

Local instance MySQL80 x

File Edit View Query Database Server Tools Scripting Help

Navigator

MANAGEMENT

- Server Status
- Client Connections
- Users and Privileges
- Status and System Variables
- Data Export
- Data Import/Restore

INSTANCE

- Startup / Shutdown
- Server Logs
- Options File

PERFORMANCE

- Dashboard
- Performance Reports
- Performance Schema Setup

Administration Schemas

Information

Query 1 SQL File 4* Week-2* SQL File 5* SQL File 6* x

Limit to 1000 rows

```

1 SELECT *
2 FROM orders
3 ORDER BY purch_amt DESC;
4

```

Result Grid

ord_no	purch_amt	ord_date	customer_id	salesman_id
70008	5760.00	2012-09-10	3002	5001
70013	3045.60	2012-04-25	3002	5001
70003	2480.40	2012-10-10	3009	5003
70005	2400.60	2012-07-27	3007	5001
70010	1983.43	2012-10-10	3004	5006
70007	948.50	2012-09-10	3005	5002
70009	270.65	2012-09-10	3001	5005
70012	250.45	2012-06-27	3008	5002
30030	150.50	2012-10-05	3005	5002
70004	110.50	2012-08-17	3009	5003
70011	75.29	2012-08-17	3003	5007
70002	65.26	2012-10-05	3002	5001

orders 4 x

Output

Action Output

#	Time	Action	Message
2	10:18:57	CREATE TABLE orders (ord_no INT PRIMARY KEY, purch_amt DECIMAL(10,2), ord_date DATE, c...	0 row(s) affected
3	10:20:11	INSERT INTO orders VALUES (30030,150.50,'2012-10-05',3005,5002), (70009,270.65,'2012-09-10',3001,5005)...	12 row(s) affected Records: 12 Duplicates: 0 Warnings: 0
4	10:21:01	SELECT * FROM orders WHERE purch_amt > 2000 LIMIT 0, 1000	4 row(s) returned
5	10:22:14	SELECT * FROM orders WHERE ord_date='2012-09-10' LIMIT 0, 1000	3 row(s) returned
6	10:23:15	SELECT * FROM orders WHERE salesman_id=5001 LIMIT 0, 1000	4 row(s) returned
7	10:23:56	SELECT * FROM orders ORDER BY purch_amt DESC LIMIT 0, 1000	12 row(s) returned

MySQL Workbench

Local instance MySQL80 x

File Edit View Query Database Server Tools Scripting Help

Navigator

MANAGEMENT

- Server Status
- Client Connections
- Users and Privileges
- Status and System Variables
- Data Export
- Data Import/Restore

INSTANCE

- Startup / Shutdown
- Server Logs
- Options File

PERFORMANCE

- Dashboard
- Performance Reports
- Performance Schema Setup

Administration Schemas

Information

No object selected

Query 1 SQL File 4* Week-2* SQL File 5* SQL File 6* x

Limit to 1000 rows

```

1 • SELECT *
2 FROM orders
3 ORDER BY ord_date;

```

Result Grid

ord_no	purch_amt	ord_date	customer_id	salesman_id
70013	3045.60	2012-04-25	3002	5001
70012	250.45	2012-06-27	3008	5002
70005	2400.60	2012-07-27	3007	5001
70004	110.50	2012-08-17	3009	5003
70011	75.29	2012-08-17	3003	5007
70007	948.50	2012-09-10	3005	5002
70008	5760.00	2012-09-10	3002	5001
70009	270.65	2012-09-10	3001	5005
30030	150.50	2012-10-05	3005	5002
70002	65.26	2012-10-05	3002	5001
70003	2480.40	2012-10-10	3009	5003
70010	1983.43	2012-10-10	3004	5006

orders 5 x

Output

Action Output

#	Time	Action	Message
3	10:20:11	INSERT INTO orders VALUES (30030,150.50,'2012-10-05',3005,5002), (70009,270.65,'2012-09-10',3001,5005), ...	12 row(s) affected Records: 12 Duplicates: 0 Warnings: 0
4	10:21:01	SELECT * FROM orders WHERE purch_amt > 2000 LIMIT 0, 1000	4 row(s) returned
5	10:22:14	SELECT * FROM orders WHERE ord_date='2012-09-10' LIMIT 0, 1000	3 row(s) returned
6	10:23:15	SELECT * FROM orders WHERE salesman_id=5001 LIMIT 0, 1000	4 row(s) returned
7	10:23:56	SELECT * FROM orders ORDER BY purch_amt DESC LIMIT 0, 1000	12 row(s) returned
8	10:24:56	SELECT * FROM orders ORDER BY ord_date LIMIT 0, 1000	12 row(s) returned

6 - SUM()

MySQL Workbench

Local instance MySQL80 x

File Edit View Query Database Server Tools Scripting Help

Navigator

MANAGEMENT

- Server Status
- Client Connections
- Users and Privileges
- Status and System Variables
- Data Export
- Data Import/Restore

INSTANCE

- Startup / Shutdown
- Server Logs
- Options File

PERFORMANCE

- Dashboard
- Performance Reports
- Performance Schema Setup

Administration Schemas

Information

Query 1 SQL File 4* Week-2* SQL File 5* SQL File 6* x

Limit to 1000 rows

```

1 • SELECT SUM(purch_amt) AS total_revenue
2 FROM orders;

```

Result Grid

total_revenue
17541.18

Output

Action Output

#	Time	Action	Message
1	10:18:53	USE aggregate_db	0 row(s) affected
2	10:18:57	CREATE TABLE orders (ord_no INT PRIMARY KEY, purch_amt DECIMAL(10,2), ord_date DATE, cus...	0 row(s) affected
3	10:20:11	INSERT INTO orders VALUES (30030,150.50,'2012-10-05',3005,5002), (70009,270.65,'2012-09-10',3001,5005), ...	12 row(s) affected Records: 12 Duplicates: 0 Warnings: 0
4	10:21:01	SELECT * FROM orders WHERE purch_amt > 2000 LIMIT 0, 1000	4 row(s) returned
5	10:22:14	SELECT * FROM orders WHERE ord_date='2012-09-10' LIMIT 0, 1000	3 row(s) returned
6	10:23:15	SELECT * FROM orders WHERE salesman_id=5001 LIMIT 0, 1000	4 row(s) returned
7	10:23:56	SELECT * FROM orders ORDER BY purch_amt DESC LIMIT 0, 1000	12 row(s) returned
8	10:24:56	SELECT * FROM orders ORDER BY ord_date LIMIT 0, 1000	12 row(s) returned
9	10:25:38	SELECT SUM(purch_amt) AS total_revenue FROM orders LIMIT 0, 1000	1 row(s) returned

7 - AVG()

MySQL Workbench

Local instance MySQL80 x

File Edit View Query Database Server Tools Scripting Help

Navigator

MANAGEMENT

- Server Status
- Client Connections
- Users and Privileges
- Status and System Variables
- Data Export
- Data Import/Restore

INSTANCE

- Startup / Shutdown
- Server Logs
- Options File

PERFORMANCE

- Dashboard
- Performance Reports
- Performance Schema Setup

Administration Schemas

Information

No object selected

Query 1 SQL File 4* Week-2* SQL File 5* SQL File 6* x

Limit to 1000 rows

```
1 • SELECT AVG(purch_amt) AS average_order
2 FROM orders;
```

Result Grid

	average_order
▶	1461.765000

Result 7 x

Output

Action Output

#	Time	Action	Message
✓	3 10:20:11	INSERT INTO orders VALUES (30030,150.50,'2012-10-05',3005.5002), (70009,270.65,'2012-09-10',3001.5005...	12 row(s) affected Records: 12 Duplicates: 0 Warnings: 0
✓	4 10:21:01	SELECT * FROM orders WHERE purch_amt > 2000 LIMIT 0, 1000	4 row(s) returned
✓	5 10:22:14	SELECT * FROM orders WHERE ord_date='2012-09-10' LIMIT 0, 1000	3 row(s) returned
✓	6 10:23:15	SELECT * FROM orders WHERE salesman_id=5001 LIMIT 0, 1000	4 row(s) returned
✓	7 10:23:56	SELECT * FROM orders ORDER BY purch_amt DESC LIMIT 0, 1000	12 row(s) returned
✓	8 10:24:56	SELECT * FROM orders ORDER BY ord_date LIMIT 0, 1000	12 row(s) returned
✓	9 10:25:38	SELECT SUM(purch_amt) AS total_revenue FROM orders LIMIT 0, 1000	1 row(s) returned
✓	10 10:26:15	SELECT AVG(purch_amt) AS average_order FROM orders LIMIT 0, 1000	1 row(s) returned

8 - MAX()

MySQL Workbench

Local instance MySQL80 x

File Edit View Query Database Server Tools Scripting Help

Navigator

MANAGEMENT

- Server Status
- Client Connections
- Users and Privileges
- Status and System Variables
- Data Export
- Data Import/Restore

INSTANCE

- Startup / Shutdown
- Server Logs
- Options File

PERFORMANCE

- Dashboard
- Performance Reports
- Performance Schema Setup

Administration Schemas

Information

No object selected

Query 1 SQL File 4* Week-2* SQL File 5* SQL File 6* x

Limit to 1000 rows

```
1 • SELECT MAX(purch_amt) AS highest_order
2 FROM orders;
```

Result Grid

	highest_order
▶	\$760.00

Output

Action Output

#	Time	Action	Message
✓	1 10:18:53	USE aggregate_db	0 row(s) affected
✓	2 10:18:57	CREATE TABLE orders (ord_no INT PRIMARY KEY, purch_amt DECIMAL(10,2), ord_date DATE, cus...	0 row(s) affected
✓	3 10:20:11	INSERT INTO orders VALUES (30030,150.50,'2012-10-05',3005.5002), (70009,270.65,'2012-09-10',3001.5005), ...	12 row(s) affected Records: 12 Duplicates: 0 Warnings: 0
✓	4 10:21:01	SELECT * FROM orders WHERE purch_amt > 2000 LIMIT 0, 1000	4 row(s) returned
✓	5 10:22:14	SELECT * FROM orders WHERE ord_date='2012-09-10' LIMIT 0, 1000	3 row(s) returned
✓	6 10:23:15	SELECT * FROM orders WHERE salesman_id=5001 LIMIT 0, 1000	4 row(s) returned
✓	7 10:23:56	SELECT * FROM orders ORDER BY purch_amt DESC LIMIT 0, 1000	12 row(s) returned
✓	8 10:24:56	SELECT * FROM orders ORDER BY ord_date LIMIT 0, 1000	12 row(s) returned
✓	9 10:25:38	SELECT SUM(purch_amt) AS total_revenue FROM orders LIMIT 0, 1000	1 row(s) returned
✓	10 10:26:15	SELECT AVG(purch_amt) AS average_order FROM orders LIMIT 0, 1000	1 row(s) returned
✓	11 10:27:27	SELECT MAX(purch_amt) AS highest_order FROM orders LIMIT 0, 1000	1 row(s) returned

9 - MIN() :

MySQL Workbench

Local instance MySQL80 x

File Edit View Query Database Server Tools Scripting Help

Navigator

MANAGEMENT

- Server Status
- Client Connections
- Users and Privileges
- Status and System Variables
- Data Export
- Data Import/Restore

INSTANCE

- Startup / Shutdown
- Server Logs
- Options File

PERFORMANCE

- Dashboard
- Performance Reports
- Performance Schema Setup

Administration Schemas

Information

No object selected

Object Info Session

Query 1 SQL File 4* Week-2* SQL File 5* SQL File 6*

Limit to 1000 rows

```
1 • SELECT MIN(purch_amt) AS lowest_order
2 FROM orders;
```

Result Grid

	lowest_order
▶	65.26

Result 9 x

Output

Action Output

#	Time	Action	Message
✓	1 10:18:53	USE aggregate_db	0 row(s) affected
✓	2 10:18:57	CREATE TABLE orders (ord_no INT PRIMARY KEY, purch_amt DECIMAL(10,2), ord_date DATE, cus...	0 row(s) affected
✓	3 10:20:11	INSERT INTO orders VALUES (30030,150.50,'2012-10-05',3005,5002), (70009,270.65,'2012-09-10',3001,5005), ...	12 row(s) affected Records: 12 Duplicates: 0 Warnings: 0
✓	4 10:21:01	SELECT * FROM orders WHERE purch_amt > 2000 LIMIT 0, 1000	4 row(s) returned
✓	5 10:22:14	SELECT * FROM orders WHERE ord_date='2012-09-10' LIMIT 0, 1000	3 row(s) returned
✓	6 10:23:15	SELECT * FROM orders WHERE salesman_id=5001 LIMIT 0, 1000	4 row(s) returned
✓	7 10:23:56	SELECT * FROM orders ORDER BY purch_amt DESC LIMIT 0, 1000	12 row(s) returned
✓	8 10:24:56	SELECT * FROM orders ORDER BY ord_date LIMIT 0, 1000	12 row(s) returned
✓	9 10:25:38	SELECT SUM(purch_amt) AS total_revenue FROM orders LIMIT 0, 1000	1 row(s) returned
✓	10 10:26:15	SELECT AVG(purch_amt) AS average_order FROM orders LIMIT 0, 1000	1 row(s) returned
✓	11 10:27:27	SELECT MAX(purch_amt) AS highest_order FROM orders LIMIT 0, 1000	1 row(s) returned
✓	12 10:28:17	SELECT MIN(purch_amt) AS lowest_order FROM orders LIMIT 0, 1000	1 row(s) returned

10 - COUNT()

MySQL Workbench

Local instance MySQL80 x

File Edit View Query Database Server Tools Scripting Help

Navigator

MANAGEMENT

- Server Status
- Client Connections
- Users and Privileges
- Status and System Variables
- Data Export
- Data Import/Restore

INSTANCE

- Startup / Shutdown
- Server Logs
- Options File

PERFORMANCE

- Dashboard
- Performance Reports
- Performance Schema Setup

Administration Schemas

Information

No object selected

Object Info Session

Query 1 SQL File 4* Week-2* SQL File 5* SQL File 6*

Limit to 1000 rows

```
1 • SELECT COUNT(*) AS total_orders
2 FROM orders;
```

Result Grid

	total_orders
▶	12

Result 10 x

Output

Action Output

#	Time	Action	Message
✓	2 10:18:57	CREATE TABLE orders (ord_no INT PRIMARY KEY, purch_amt DECIMAL(10,2), ord_date DATE, c...	0 row(s) affected
✓	3 10:20:11	INSERT INTO orders VALUES (30030,150.50,'2012-10-05',3005,5002), (70009,270.65,'2012-09-10',3001,5005), ...	12 row(s) affected Records: 12 Duplicates: 0 Warnings: 0
✓	4 10:21:01	SELECT * FROM orders WHERE purch_amt > 2000 LIMIT 0, 1000	4 row(s) returned
✓	5 10:22:14	SELECT * FROM orders WHERE ord_date='2012-09-10' LIMIT 0, 1000	3 row(s) returned
✓	6 10:23:15	SELECT * FROM orders WHERE salesman_id=5001 LIMIT 0, 1000	4 row(s) returned
✓	7 10:23:56	SELECT * FROM orders ORDER BY purch_amt DESC LIMIT 0, 1000	12 row(s) returned
✓	8 10:24:56	SELECT * FROM orders ORDER BY ord_date LIMIT 0, 1000	12 row(s) returned
✓	9 10:25:38	SELECT SUM(purch_amt) AS total_revenue FROM orders LIMIT 0, 1000	1 row(s) returned
✓	10 10:26:15	SELECT AVG(purch_amt) AS average_order FROM orders LIMIT 0, 1000	1 row(s) returned
✓	11 10:27:27	SELECT MAX(purch_amt) AS highest_order FROM orders LIMIT 0, 1000	1 row(s) returned
✓	12 10:28:17	SELECT MIN(purch_amt) AS lowest_order FROM orders LIMIT 0, 1000	1 row(s) returned
✓	13 10:29:04	SELECT COUNT(*) AS total_orders FROM orders LIMIT 0, 1000	1 row(s) returned

11 - GROUP BY

MySQL Workbench

Local instance MySQL80

File Edit View Query Database Server Tools Scripting Help

Navigator

MANAGEMENT

- Server Status
- Client Connections
- Users and Privileges
- Status and System Variables
- Data Export
- Data Import/Restore

INSTANCE

- Startup / Shutdown
- Server Logs
- Options File

PERFORMANCE

- Dashboard
- Performance Reports
- Performance Schema Setup

Administration Schemas

Information

No object selected

Query 1 SQL File 4* Week-2* SQL File 5* SQL File 6*

```
1 SELECT salesman_id,  
2 SUM(purch_amt) AS total_sales  
3 FROM orders  
4 GROUP BY salesman_id;
```

Result Grid

salesman_id	total_sales
5002	1349.45
5001	11271.46
5003	2590.90
5005	270.65
5006	1983.43
5007	75.29

Result 11

Output

Action Output

#	Time	Action	Message
3	10:20:11	INSERT INTO orders VALUES (30030,150.50,'2012-10-05',3005,5002),(70009,270.65,'2012-09-10',3001,5005...	12 row(s) affected Records: 12 Duplicates: 0 Warnings: 0
4	10:21:01	SELECT * FROM orders WHERE purch_amt > 2000 LIMIT 0, 1000	4 row(s) returned
5	10:22:14	SELECT * FROM orders WHERE ord_date='2012-09-10' LIMIT 0, 1000	3 row(s) returned
6	10:23:15	SELECT * FROM orders WHERE salesman_id=5001 LIMIT 0, 1000	4 row(s) returned
7	10:23:56	SELECT * FROM orders ORDER BY purch_amt DESC LIMIT 0, 1000	12 row(s) returned
8	10:24:56	SELECT * FROM orders ORDER BY ord_date LIMIT 0, 1000	12 row(s) returned
9	10:25:38	SELECT SUM(purch_amt) AS total_revenue FROM orders LIMIT 0, 1000	1 row(s) returned
10	10:26:15	SELECT AVG(purch_amt) AS average_order FROM orders LIMIT 0, 1000	1 row(s) returned
11	10:27:27	SELECT MAX(purch_amt) AS highest_order FROM orders LIMIT 0, 1000	1 row(s) returned
12	10:28:17	SELECT MIN(purch_amt) AS lowest_order FROM orders LIMIT 0, 1000	1 row(s) returned
13	10:29:04	SELECT COUNT(*) AS total_orders FROM orders LIMIT 0, 1000	1 row(s) returned
14	10:31:15	SELECT salesman_id, SUM(purch_amt) AS total_sales FROM orders GROUP BY salesman_id LIMIT 0, 1000	6 row(s) returned

MySQL Workbench

Local instance MySQL80

File Edit View Query Database Server Tools Scripting Help

Navigator

MANAGEMENT

- Server Status
- Client Connections
- Users and Privileges
- Status and System Variables
- Data Export
- Data Import/Restore

INSTANCE

- Startup / Shutdown
- Server Logs
- Options File

PERFORMANCE

- Dashboard
- Performance Reports
- Performance Schema Setup

Administration Schemas

Information

No object selected

Query 1 SQL File 4* Week-2* SQL File 5* SQL File 6*

```
1 SELECT customer_id,  
2 SUM(purch_amt) AS total_purchase  
3 FROM orders  
4 GROUP BY customer_id;
```

Result Grid

customer_id	total_purchase
3002	8870.86
3009	2590.90
3007	2400.60
3001	270.65
3004	1983.43
3003	75.29
3008	250.45

Result 12

Output

Action Output

#	Time	Action	Message
4	10:21:01	SELECT * FROM orders WHERE purch_amt > 2000 LIMIT 0, 1000	4 row(s) returned
5	10:22:14	SELECT * FROM orders WHERE ord_date='2012-09-10' LIMIT 0, 1000	3 row(s) returned
6	10:23:15	SELECT * FROM orders WHERE salesman_id=5001 LIMIT 0, 1000	4 row(s) returned
7	10:23:56	SELECT * FROM orders ORDER BY purch_amt DESC LIMIT 0, 1000	12 row(s) returned
8	10:24:56	SELECT * FROM orders ORDER BY ord_date LIMIT 0, 1000	12 row(s) returned
9	10:25:38	SELECT SUM(purch_amt) AS total_revenue FROM orders LIMIT 0, 1000	1 row(s) returned
10	10:26:15	SELECT AVG(purch_amt) AS average_order FROM orders LIMIT 0, 1000	1 row(s) returned
11	10:27:27	SELECT MAX(purch_amt) AS highest_order FROM orders LIMIT 0, 1000	1 row(s) returned
12	10:28:17	SELECT MIN(purch_amt) AS lowest_order FROM orders LIMIT 0, 1000	1 row(s) returned
13	10:29:04	SELECT COUNT(*) AS total_orders FROM orders LIMIT 0, 1000	1 row(s) returned
14	10:31:15	SELECT salesman_id, SUM(purch_amt) AS total_sales FROM orders GROUP BY salesman_id LIMIT 0, 1000	6 row(s) returned
15	10:32:04	SELECT customer_id, SUM(purch_amt) AS total_purchase FROM orders GROUP BY customer_id LIMIT 0, 1000	8 row(s) returned

13 - GROUP BY + MAX()

MySQL Workbench

Local instance MySQL80

File Edit View Query Database Server Tools Scripting Help

Navigator

MANAGEMENT

- Server Status
- Client Connections
- Users and Privileges
- Status and System Variables
- Data Export
- Data Import/Restore

INSTANCE

- Startup / Shutdown
- Server Logs
- Options File

PERFORMANCE

- Dashboard
- Performance Reports
- Performance Schema Setup

Administration Schemas

Information

No object selected

Query 1

```
1 SELECT customer_id,
2 MAX(purch_amt) AS highest_purchase
3 FROM orders
4 GROUP BY customer_id;
```

Result Grid

customer_id	highest_purchase
3005	948.50
3002	5760.00
3009	2480.40
3007	2400.60
3001	270.65
3004	1983.43
3003	75.29
3008	250.45

Result 13

Output

Action Output

#	Time	Action	Message
10	10:26:15	SELECT AVG(purch_amt) AS average_order FROM orders LIMIT 0, 1000	1 row(s) returned
11	10:27:27	SELECT MAX(purch_amt) AS highest_order FROM orders LIMIT 0, 1000	1 row(s) returned
12	10:28:17	SELECT MIN(purch_amt) AS lowest_order FROM orders LIMIT 0, 1000	1 row(s) returned
13	10:29:04	SELECT COUNT(*) AS total_orders FROM orders LIMIT 0, 1000	1 row(s) returned
14	10:31:15	SELECT salesman_id, SUM(purch_amt) AS total_sales FROM orders GROUP BY salesman_id LIMIT 0, 1000	6 row(s) returned
15	10:32:04	SELECT customer_id, SUM(purch_amt) AS total_purchase FROM orders GROUP BY customer_id LIMIT 0, 1000	8 row(s) returned
16	10:33:49	SELECT customer_id, MAX(purch_amt) AS highest_purchase FROM orders GROUP BY customer_id LIMIT 0, 1000	8 row(s) returned

14 - GROUP BY + HAVING

MySQL Workbench

Local instance MySQL80

File Edit View Query Database Server Tools Scripting Help

Navigator

MANAGEMENT

- Server Status
- Client Connections
- Users and Privileges
- Status and System Variables
- Data Export
- Data Import/Restore

INSTANCE

- Startup / Shutdown
- Server Logs
- Options File

PERFORMANCE

- Dashboard
- Performance Reports
- Performance Schema Setup

Administration Schemas

Information

No object selected

Query 1

```
1 SELECT salesman_id,
2 SUM(purch_amt) AS total_sales
3 FROM orders
4 GROUP BY salesman_id
5 HAVING SUM(purch_amt) > 3000;
```

Result Grid

salesman_id	total_sales
5001	11271.46

Result 14

Output

Action Output

#	Time	Action	Message
11	10:27:27	SELECT MAX(purch_amt) AS highest_order FROM orders LIMIT 0, 1000	1 row(s) returned
12	10:28:17	SELECT MIN(purch_amt) AS lowest_order FROM orders LIMIT 0, 1000	1 row(s) returned
13	10:29:04	SELECT COUNT(*) AS total_orders FROM orders LIMIT 0, 1000	1 row(s) returned
14	10:31:15	SELECT salesman_id, SUM(purch_amt) AS total_sales FROM orders GROUP BY salesman_id LIMIT 0, 1000	6 row(s) returned
15	10:32:04	SELECT customer_id, SUM(purch_amt) AS total_purchase FROM orders GROUP BY customer_id LIMIT 0, 1000	8 row(s) returned
16	10:33:49	SELECT customer_id, MAX(purch_amt) AS highest_purchase FROM orders GROUP BY customer_id LIMIT 0, 1000	8 row(s) returned
17	10:34:43	SELECT salesman_id, SUM(purch_amt) AS total_sales FROM orders GROUP BY salesman_id HAVING SUM(purch_amt) > 3000	1 row(s) returned

15 - GROUP BY + HAVING

MySQL Workbench

Local instance MySQL80 x

File Edit View Query Database Server Tools Scripting Help

Navigator

MANAGEMENT

- Server Status
- Client Connections
- Users and Privileges
- Status and System Variables
- Data Export
- Data Import/Restore

INSTANCE

- Startup / Shutdown
- Server Logs
- Options File

PERFORMANCE

- Dashboard
- Performance Reports
- Performance Schema Setup

Administration Schemas

Information

No object selected

Query 1 SQL File 4* Week-2* SQL File 5* SQL File 6* x

```
1 SELECT customer_id,
2 SUM(purch_amt) AS total_purchase
3 FROM orders
4 GROUP BY customer_id
5 HAVING SUM(purch_amt) > 2500;
```

Result Grid

customer_id	total_purchase
3002	8870.86
3009	2590.90

Result 15 x

Output

Action Output

#	Time	Action	Message
12	10:28:17	SELECT MIN(purch_amt) AS lowest_order FROM orders LIMIT 0, 1000	1 row(s) returned
13	10:29:04	SELECT COUNT(*) AS total_orders FROM orders LIMIT 0, 1000	1 row(s) returned
14	10:31:15	SELECT salesman_id, SUM(purch_amt) AS total_sales FROM orders GROUP BY salesman_id LIMIT 0, 1000	6 row(s) returned
15	10:32:04	SELECT customer_id, SUM(purch_amt) AS total_purchase FROM orders GROUP BY customer_id LIMIT 0, 1000	8 row(s) returned
16	10:33:49	SELECT customer_id, MAX(purch_amt) AS highest_purchase FROM orders GROUP BY customer_id LIMIT 0, 1...	8 row(s) returned
17	10:34:43	SELECT salesman_id, SUM(purch_amt) AS total_sales FROM orders GROUP BY salesman_id HAVING SUM(p...	1 row(s) returned
18	10:36:19	SELECT customer_id, SUM(purch_amt) AS total_purchase FROM orders GROUP BY customer_id HAVING SU...	2 row(s) returned

16 - GROUP BY + HAVING

MySQL Workbench

Local instance MySQL80 x

File Edit View Query Database Server Tools Scripting Help

Navigator

MANAGEMENT

- Server Status
- Client Connections
- Users and Privileges
- Status and System Variables
- Data Export
- Data Import/Restore

INSTANCE

- Startup / Shutdown
- Server Logs
- Options File

PERFORMANCE

- Dashboard
- Performance Reports
- Performance Schema Setup

Administration Schemas

Information

No object selected

Query 1 SQL File 4* Week-2* SQL File 5* SQL File 6* x

```
1 SELECT customer_id,
2 COUNT(*) AS total_orders
3 FROM orders
4 GROUP BY customer_id
5 HAVING COUNT(*) > 1;
```

Result Grid

customer_id	total_orders
3005	2
3002	3
3009	2

Result 16 x

Output

Action Output

#	Time	Action	Message
13	10:29:04	SELECT COUNT(*) AS total_orders FROM orders LIMIT 0, 1000	1 row(s) returned
14	10:31:15	SELECT salesman_id, SUM(purch_amt) AS total_sales FROM orders GROUP BY salesman_id LIMIT 0, 1000	6 row(s) returned
15	10:32:04	SELECT customer_id, SUM(purch_amt) AS total_purchase FROM orders GROUP BY customer_id LIMIT 0, 1000	8 row(s) returned
16	10:33:49	SELECT customer_id, MAX(purch_amt) AS highest_purchase FROM orders GROUP BY customer_id LIMIT 0, 1...	8 row(s) returned
17	10:34:43	SELECT salesman_id, SUM(purch_amt) AS total_sales FROM orders GROUP BY salesman_id HAVING SUM(p...	1 row(s) returned
18	10:36:19	SELECT customer_id, SUM(purch_amt) AS total_purchase FROM orders GROUP BY customer_id HAVING SU...	2 row(s) returned
19	10:36:59	SELECT customer_id, COUNT(*) AS total_orders FROM orders GROUP BY customer_id HAVING COUNT(*) > ...	3 row(s) returned

17 - GROUP BY + HAVING + ORDER BY

MySQL Workbench

Local instance MySQL80

File Edit View Query Database Server Tools Scripting Help

Navigator

MANAGEMENT

- Server Status
- Client Connections
- Users and Privileges
- Status and System Variables
- Data Export
- Data Import/Restore

INSTANCE

- Startup / Shutdown
- Server Logs
- Options File

PERFORMANCE

- Dashboard
- Performance Reports
- Performance Schema Setup

Administration Schemas

Information

No object selected

Query 1 SQL File 4* Week-2* SQL File 5* SQL File 6*

Limit to 1000 rows

```
1 SELECT customer_id,
2 SUM(purch_amt) AS total_purchase
3 FROM orders
4 GROUP BY customer_id
5 HAVING SUM(purch_amt) > 1000
6 ORDER BY total_purchase DESC;
```

Result Grid

customer_id	total_purchase
3002	8870.86
3009	2590.90
3007	2400.60
3004	1983.43
3005	1099.00

Result 17

Output

Action Output

#	Time	Action	Message
✓ 14	10:31:15	SELECT salesman_id, SUM(purch_amt) AS total_sales FROM orders GROUP BY salesman_id LIMIT 0, 1000	6 row(s) returned
✓ 15	10:32:04	SELECT customer_id, SUM(purch_amt) AS total_purchase FROM orders GROUP BY customer_id LIMIT 0, 1000	8 row(s) returned
✓ 16	10:33:49	SELECT customer_id, MAX(purch_amt) AS highest_purchase FROM orders GROUP BY customer_id LIMIT 0, 1...	8 row(s) returned
✓ 17	10:34:43	SELECT salesman_id, SUM(purch_amt) AS total_sales FROM orders GROUP BY salesman_id HAVING SUM(p...	1 row(s) returned
✓ 18	10:36:19	SELECT customer_id, SUM(purch_amt) AS total_purchase FROM orders GROUP BY customer_id HAVING SU...	2 row(s) returned
✓ 19	10:36:59	SELECT customer_id, COUNT(*) AS total_orders FROM orders GROUP BY customer_id HAVING COUNT(*) > ...	3 row(s) returned
✓ 20	10:37:40	SELECT customer_id, SUM(purch_amt) AS total_purchase FROM orders GROUP BY customer_id HAVING SU...	5 row(s) returned

18 - BETWEEN + HAVING

MySQL Workbench

Local instance MySQL80

File Edit View Query Database Server Tools Scripting Help

Navigator

MANAGEMENT

- Server Status
- Client Connections
- Users and Privileges
- Status and System Variables
- Data Export
- Data Import/Restore

INSTANCE

- Startup / Shutdown
- Server Logs
- Options File

PERFORMANCE

- Dashboard
- Performance Reports
- Performance Schema Setup

Administration Schemas

Information

No object selected

Query 1 SQL File 4* Week-2* SQL File 5* SQL File 6*

Limit to 1000 rows

```
1 SELECT customer_id,
2 MAX(purch_amt) AS max_purchase
3 FROM orders
4 GROUP BY customer_id
5 HAVING MAX(purch_amt) BETWEEN 2000 AND 6000;
```

Result Grid

customer_id	max_purchase
3002	5760.00
3009	2480.40
3007	2400.60

Result 18

Output

Action Output

#	Time	Action	Message
✓ 15	10:32:04	SELECT customer_id, SUM(purch_amt) AS total_purchase FROM orders GROUP BY customer_id LIMIT 0, 1000	8 row(s) returned
✓ 16	10:33:49	SELECT customer_id, MAX(purch_amt) AS highest_purchase FROM orders GROUP BY customer_id LIMIT 0, 1...	8 row(s) returned
✓ 17	10:34:43	SELECT salesman_id, SUM(purch_amt) AS total_sales FROM orders GROUP BY salesman_id HAVING SUM(p...	1 row(s) returned
✓ 18	10:36:19	SELECT customer_id, SUM(purch_amt) AS total_purchase FROM orders GROUP BY customer_id HAVING SU...	2 row(s) returned
✓ 19	10:36:59	SELECT customer_id, COUNT(*) AS total_orders FROM orders GROUP BY customer_id HAVING COUNT(*) > ...	3 row(s) returned
✓ 20	10:37:40	SELECT customer_id, SUM(purch_amt) AS total_purchase FROM orders GROUP BY customer_id HAVING SU...	5 row(s) returned
✓ 21	10:38:19	SELECT customer_id, MAX(purch_amt) AS max_purchase FROM orders GROUP BY customer_id HAVING MA...	3 row(s) returned

19 - COUNT + HAVING

MySQL Workbench

Local instance MySQL80 x

File Edit View Query Database Server Tools Scripting Help

Navigator: Query 1 SQL File 4* Week-2* SQL File 5* SQL File 6* x

MANAGEMENT

- Server Status
- Client Connections
- Users and Privileges
- Status and System Variables
- Data Export
- Data Import/Restore

INSTANCE

- Startup / Shutdown
- Server Logs
- Options File

PERFORMANCE

- Dashboard
- Performance Reports
- Performance Schema Setup

Administration Schemas

Information: No object selected

```
1 SELECT salesman_id,
2 COUNT(*) AS total_orders
3 FROM orders
4 GROUP BY salesman_id
5 HAVING COUNT(*) >= 2;
```

Result Grid

salesman_id	total_orders
5002	3
5001	4
5003	2

Result 19 x

Output

Action Output

#	Time	Action	Message
16	10:33:49	SELECT customer_id, MAX(purch_amt) AS highest_purchase FROM orders GROUP BY customer_id LIMIT 0, 1...	8 row(s) returned
17	10:34:43	SELECT salesman_id, SUM(purch_amt) AS total_sales FROM orders GROUP BY salesman_id HAVING SUM(p...	1 row(s) returned
18	10:36:19	SELECT customer_id, SUM(purch_amt) AS total_purchase FROM orders GROUP BY customer_id HAVING SU...	2 row(s) returned
19	10:36:59	SELECT customer_id, COUNT(*) AS total_orders FROM orders GROUP BY customer_id HAVING COUNT(*) > ...	3 row(s) returned
20	10:37:40	SELECT customer_id, SUM(purch_amt) AS total_purchase FROM orders GROUP BY customer_id HAVING SU...	5 row(s) returned
21	10:38:19	SELECT customer_id, MAX(purch_amt) AS max_purchase FROM orders GROUP BY customer_id HAVING MA...	3 row(s) returned
22	10:39:07	SELECT salesman_id, COUNT(*) AS total_orders FROM orders GROUP BY salesman_id HAVING COUNT(*) >=...	3 row(s) returned

20 - MAX + GROUP BY + HAVING

MySQL Workbench

Local instance MySQL80 x

File Edit View Query Database Server Tools Scripting Help

Navigator: Query 1 SQL File 4* Week-2* SQL File 5* SQL File 6* x

MANAGEMENT

- Server Status
- Client Connections
- Users and Privileges
- Status and System Variables
- Data Export
- Data Import/Restore

INSTANCE

- Startup / Shutdown
- Server Logs
- Options File

PERFORMANCE

- Dashboard
- Performance Reports
- Performance Schema Setup

Administration Schemas

Information: No object selected

```
1 SELECT ord_date,
2 MAX(purch_amt) AS highest_purchase
3 FROM orders
4 GROUP BY ord_date
5 HAVING MAX(purch_amt) > 2000;
6
```

Result Grid

ord_date	highest_purchase
2012-10-10	2480.40
2012-07-27	2400.60
2012-09-10	5760.00
2012-04-25	3045.60

Result 20 x

Output

Action Output

#	Time	Action	Message
17	10:34:43	SELECT salesman_id, SUM(purch_amt) AS total_sales FROM orders GROUP BY salesman_id HAVING SUM(p...	1 row(s) returned
18	10:36:19	SELECT customer_id, SUM(purch_amt) AS total_purchase FROM orders GROUP BY customer_id HAVING SU...	2 row(s) returned
19	10:36:59	SELECT customer_id, COUNT(*) AS total_orders FROM orders GROUP BY customer_id HAVING COUNT(*) > ...	3 row(s) returned
20	10:37:40	SELECT customer_id, SUM(purch_amt) AS total_purchase FROM orders GROUP BY customer_id HAVING SU...	5 row(s) returned
21	10:38:19	SELECT customer_id, MAX(purch_amt) AS max_purchase FROM orders GROUP BY customer_id HAVING MA...	3 row(s) returned
22	10:39:07	SELECT salesman_id, COUNT(*) AS total_orders FROM orders GROUP BY salesman_id HAVING COUNT(*) >=...	3 row(s) returned
23	10:39:48	SELECT ord_date, MAX(purch_amt) AS highest_purchase FROM orders GROUP BY ord_date HAVING MAX(p...	4 row(s) returned