

Sockets

2520030030

U.Rohit Sai

1.Server_side.c

Code:

```
rohitsai@MSI: ~/OS
GNU nano 8.7.1
#include <sys/un.h>
#include <string.h>

#define SOCKET_PATH "/tmp/my_socket"

int main()
{
    int server_fd, client_fd;
    struct sockaddr_un address;
    char buffer[100];
    server_fd = socket(AF_UNIX, SOCK_STREAM, 0);
    address.sun_family = AF_UNIX;
    strcpy(address.sun_path, SOCKET_PATH);
    unlink(SOCKET_PATH);
    bind(server_fd, (struct sockaddr *)&address, sizeof(address));
    listen(server_fd, 5);
    printf("Server waiting...\n");
    client_fd = accept(server_fd, NULL, NULL);
    read(client_fd, buffer, sizeof(buffer));
    printf("Message from client: %s\n", buffer);
    close(client_fd);
    close(server_fd);
    unlink(SOCKET_PATH);
    return 0;
}
```

2.Client_side.c

```
rohitsai@MSI: ~/OS
GNU nano 8.7.1
#include <stdio.h>
#include <unistd.h>
#include <sys/socket.h>
#include <sys/un.h>
#include <string.h>

#define SOCKET_PATH "/tmp/my_socket"

int main()
{
    int client_fd;
    struct sockaddr_un address;

    client_fd = socket(AF_UNIX, SOCK_STREAM, 0);

    address.sun_family = AF_UNIX;
    strcpy(address.sun_path, SOCKET_PATH);

    connect(client_fd,
            (struct sockaddr *)&address,
            sizeof(address));

    write(client_fd, "Hello Server", 12);

    printf("Message sent to server.\n");

    close(client_fd);

    return 0;
}
```

Output :

```
rohitsai@MSI:~/OS$ cd OS
rohitsai@MSI:~/OS$ nano Server_side.c
rohitsai@MSI:~/OS$ gcc Server_side.c -o Server_side
rohitsai@MSI:~/OS$ ./Server_side
Server waiting...
Message from client: Hello Server
rohitsai@MSI:~/OS$

rohitsai@MSI:~/OS$ gcc Client_side.c -o Client_side
rohitsai@MSI:~/OS$ ./Client_side
Message sent to server.
rohitsai@MSI:~/OS$
```