

Skill-3

2520030030

U.Rohit Sai

Programm - 1

Code:

```
rohitsai@MSI: ~/Skill
GNU nano 8.7.1
#include <stdio.h>
#include <stdlib.h>
#include <string.h>

#define MAX 10
int main()
{
    char *history[MAX];
    char command[100];
    int count = 0;
    while (1)
    {
        printf("2520030030_shell> ");
        fgets(command, sizeof(command), stdin);
        command[strcspn(command, "\n")] = '\0';
        if (strcmp(command, "exit") == 0)
            break;
        if (strcmp(command, "history") == 0)
        {
            for (int i = 0; i < count; i++)
                printf("%d: %s\n", i + 1, history[i]);
            continue;
        }
        if (count < MAX)
        {
            history[count] = malloc(strlen(command) + 1);
            strcpy(history[count], command);
            count++;
        }
    }
    for (int i = 0; i < count; i++)
        free(history[i]);
    return 0;
}
```

Output :

```
rohitsai@MSI: ~/Skill
rohitsai@MSI:~$ cd Skill
rohitsai@MSI:~/Skill$ nano Skill-3.c
rohitsai@MSI:~/Skill$ gcc Skill-3.c -o Skill-3
rohitsai@MSI:~/Skill$ ./Skill-3
2520030030_shell> ls
2520030030_shell> pwd
2520030030_shell> history
1: ls
2: pwd
2520030030_shell> whoami
2520030030_shell> history
1: ls
2: pwd
3: whoami
2520030030_shell> exit
rohitsai@MSI:~/Skill$ |
```

Programm - 2

Code:

```
GNU nano 8.7.1
#include <stdio.h>
#include <string.h>

int main()
{
    char input[100];
    char *token;

    printf("Enter command: ");
    fgets(input, sizeof(input), stdin);

    input[strcspn(input, "\n")] = '\0';

    if (strlen(input) == 0)
    {
        printf("Empty command\n");
        return 0;
    }

    token = strtok(input, " ");

    while (token != NULL)
    {
        printf("Token: %s\n", token);
        token = strtok(NULL, " ");
    }

    return 0;
}|
```

Output :

```
rohitsai@MSI:~/Skill$ nano Skill-3b.c
rohitsai@MSI:~/Skill$ gcc Skill-3b.c -o Skill-3b
rohitsai@MSI:~/Skill$ ./Skill-3b
Enter command: ls 5
Token: ls
Token: 5
```