

Block 4 — Giving Claude Hands: MCP + GitHub

Goal

Connect Claude to an extra tool (the filesystem MCP server) and then have Claude open a GitHub pull request for you — entirely through plain-English instructions. You will never type a git command yourself.

Type this

Part A — add the MCP server.

1. In your terminal (outside the Claude chat, so press `Ctrl+C` or open a second terminal tab), run: `claude mcp add filesystem -- npx -y @modelcontextprotocol/server-filesystem .`
2. Confirm it was added: `claude mcp list` You should see `filesystem` in the list.
3. Start Claude again: `claude`
4. Inside the chat, check that MCP is active: `/mcp`

Part B — push to GitHub.

5. Ask Claude to create a repository and push the report script (paste as-is): Create a new GitHub repository called `adriatica-sales-report` and push our report script to it.
6. Once Claude confirms the repo exists, ask it to open a pull request: Open a pull request that adds a short README describing the monthly report.

You should see

- `claude mcp list` showing `filesystem` with its status.
- Claude calling the `gh` CLI (GitHub's command-line tool) and the MCP server to create the repo, push the file, and open the PR.
- A GitHub repository URL and a pull request URL printed in the chat.

If it looks wrong

- "Not signed in to GitHub" or `gh: command not found`: Help me sign in to GitHub first, then try again.
- The MCP server fails to start or `npx` is not found: ask the facilitator — Node.js may need to be installed.
- Claude creates the repo but can't open the PR: make sure you approved each step; if it is still stuck, say Try the pull request step again.
- If GitHub is unavailable on your network today, use the fallback example at `fallbacks/b4-pr-example.md` — it shows what a successful run looks like so you can follow along.