

















GW5A-EV25MG196S



Notes:

1. F_CLK signal is an external input clock signal.
- It is recommended that F_CLK signal be provided through an active oscillator crystal.
2. External Flash memory is used to store downloaded programs.
- For details about SPI Flash model selection, see "Chapter 4.5 SPI Flash Selection" in UG714, Arara V 25K FPGA Products Programming and Configuration Guide .
3. It is recommended that add an ESD protection chip to the JTAG download circuit.
4. VCC core voltage requires a large current, so it is recommended to supply power separately.
5. The MODE pin is the GowinCONFIG configuration mode selection signal.
- For details about how to select the Mode signal, see "Chapter 3.1 Configuration Modes" in UG714, Arara V 25K FPGA Products Programming and Configuration Guide.


GW5A-EV25PG256C



Notes:

- 1.F.CLK signal is an external input clock signal. It is recommended that F.CLK signal be provided through an active oscillator crystal.
- 2.External Flash memory is used to store downloaded programs. For details about SPI Flash model selection, see "Chapter 4.5 SPI Flash Selection" in UG714, Arora V 25K FPGA Products Programming and Configuration Guide .
- 3.It is recommended that add an ESD protection chip to the JTAG download circuit.
- 4.VCC core voltage requires a large current, so it is recommended to supply power separately.
- 5.The MODE pin is the GowinCONFIG configuration mode selection signal. For details about how to select the Mode signal, see "Chapter 3.1 Configuration Modes" in UG714, Arora V 25K FPGA Products Programming and Configuration Guide.





GW5A-EV25PG256S



Notes:

- 1.F CLK signal is an external input clock signal.
- It is recommended that F CLK signal be provided through an active oscillator crystal.
- 2.External Flash memory is used to store downloaded programs.
- For details about SPI Flash model selection, see "Chapter 4.5 SPI Flash Selection" in UG714, Arora V 25K FPGA Products Programming and Configuration Guide
- 3.It is recommended that add an ESD protection chip to the JTAG download circuit.
- 4.VCC core voltage requires a large current, so it is recommended to supply power separately.
- 5.The MODE pin is the GowinCONFIG configuration mode selection signal.
- For details about how to select the Mode signal, see "Chapter 3.1 Configuration Modes" in UG714, Arora V 25K FPGA Products Programming and Configuration Guide.


Title			
GOWIN Minimum System Diagram			
Size	Document Number		Rev
C	GW5A-EV25PG256S		2.3
Date:	Tuesday, May 07, 2024	Sheet	4 of 15



Notes:

- 1.F.CLK signal is an external input clock signal. It is recommended that F.CLK signal be provided through an active oscillator crystal.
- 2.External Flash memory is used to store downloaded programs. For details about SPI Flash model selection, see "Chapter 4.5 SPI Flash Selection" in UG714, Arora V 25K FPGA Products Programming and Configuration Guide.
- 3.It is recommended that add an ESD protection chip to the JTAG download circuit.
- 4.VCC core voltage requires a large current, so it is recommended to supply power separately.
- 5.The MODE pin is the GowinCONFIG configuration mode selection signal. For details about how to select the Mode signal, see "Chapter 3.1 Configuration Modes" in UG714, Arora V 25K FPGA Products Programming and Configuration Guide.

GW5A-EV25UG256C























Notes:

1. F_CLK signal is an external input clock signal.
- It is recommended that F_CLK signal be provided through an active oscillator crystal.
2. External Flash memory is used to store downloaded programs.
- For details about SPI Flash model selection, see "Chapter 4.5 SPI Flash Selection" in UG714, Arora V 25K FPGA Products Programming and Configuration Guide.
3. It is recommended that add an ESD protection chip to the JTAG download circuit.
4. VCC core voltage requires a large current, so it is recommended to supply power separately.
5. The MODE pin is the GowinCONFIG configuration mode selection signal.
- For details about how to select the Mode signal, see "Chapter 3.1 Configuration Modes" in UG714, Arora V 25K FPGA Products Programming and Configuration Guide.

Title			
GOWIN Minimum System Diagram			
Size C	Document Number GW5A-EV25UG256C		Rev 2.3
Date:	Tuesday, May 07, 2024	Sheet	6 of 15







GW5A-EV25UG324S



Notes:

- 1.F CLK signal is an external input clock signal.
- It is recommended that F CLK signal be provided through an active oscillator crystal.
- 2.External Flash memory is used to store downloaded programs.
- For details about SPI Flash model selection, see "Chapter 4.5 SPI Flash Selection" in UG714, Arora V 25K FPGA Products Programming and Configuration Guide
- 3.It is recommended that add an ESD protection chip to the JTAG download circuit.
- 4.VCC core voltage requires a large current, so it is recommended to supply power separately.
- 5.The MODE pin is the GowinCONFIG configuration mode selection signal.
- For details about how to select the Mode signal, see "Chapter 3.1 Configuration Modes" in UG714, Arora V 25K FPGA Products Programming and Configuration Guide.

GW5A-LV25LQ100












Notes:

- 1.F.CLK signal is an external input clock signal.
- It is recommended that F.CLK signal be provided through an active oscillator crystal.
- External Flash memory Is used to store downloaded programs.
- For details about SPI Flash model selection, see "Chapter 4.5 SPI Flash Selection" in UG714, Arora V 25K FPGA Products Programming and Configuration Guide .
- It is recommended that add an ESD protection chip to the JTAG download circuit.
- VCC core voltage requires a large current, so it is recommended to supply power separately.
- The MODE pin is the GowinCONFIG configuration mode selection signal.
- For details about how to select the Mode signal, see "Chapter 3.1 Configuration Modes" in UG714, Arora V 25K FPGA Products Programming and Configuration Guide.

Title		
GOWIN Minimum System Diagram		
Size	Document Number	Rev
C	GW5A-LV25LQ100	2.3
Date:	Tuesday, May 07, 2024	Sheet 8 of 15


GW5A-LV25LQ144




Notes:

1. F_CLK signal is an external input clock signal.
It is recommended that F_CLK signal be provided through an active oscillator crystal.
2. External Flash memory is used to store downloaded programs.
For details about how to select mode selection, see "Chapter 3.1 SPI Flash Selection" in UG714, Arvix V 25K FPGAs Products Programming and Configuration Guide
3. It is recommended that add an ESD protection chip to the JTAG download circuit.
4. VCC core voltage requires a large current, so it is recommended to supply power separately.
5. The MODE pin is the GowinCONFIG configurator mode selection signal.
For details about how to select the Mode pins, see "Chapter 3.1 Configuration Modes" in UG714, Arvix V 25K FPGAs Products Programming and Configuration Guide.


GW5A-LV25MG121N




GW5A-LV25K-MG121N




GW5A-I V25K-MG121N




GW5A-I V25K-MG121N







GW5A-I V25K-MG121N





GW5A-I V25K-MG121N



GW5A-I V25K-MG121N






GW5A-J V25K-MG121N



Notes:


- 1.F CLK signal is an external input clock signal.
It is recommended that F CLK signal be provided through an active oscillator crystal.
- 2.External Flash memory is used to store downloaded programs.
For details about SPI Flash model selection, see "Chapter 4.5 SPI Flash Selection" in UG714, Arora V 25K FPGA Products Programming and Configuration Guide .
- 3.It is recommended that add an ESD protection chip to the JTAG download circuit.
- 4.VCC core voltage requires a large current, so it is recommended to supply power separately.
- 5.The MODE pin is the GowinCONFIG configuration mode selection signal.
For details about how to select the Mode signal, see "Chapter 3.1 Configuration Modes" in UG714, Arora V 25K FPGA Products Programming and Configuration Guide.

GW5A-LV25MG196S



Notes:
1.F CLK signal is an external input clock signal.
It is recommended that F.CLK signal be provided through an active oscillator crystal.
2.External Flash memory is used to store downloaded programs.
For details about SPI Flash model selection, see "Chapter 4.5 SPI Flash Selection" in UG714,
Arora V 25K FPGA Products Programming and Configuration Guide .
3.It is recommended that add an ESD protection chip to the JTAG download circuit.
4.VCC core voltage requires a large current, so it is recommended to supply power separately.
5.The MODE pin is the GowinCONFIG configuration mode selection signal.
For details about how to select the Mode signal, see "Chapter 3.1 Configuration Modes" in UG714,
Arora V 25K FPGA Products Programming and Configuration Guide.




GW5A-LV25PG196S










Notes:

- 1.F CLK signal is an external input clock signal.
It is recommended that F CLK signal be provided through an active oscillator crystal.
- 2.External Flash memory is used to store downloaded programs.
For details about SPI Flash model selection, see "Chapter 4.5 SPI Flash Selection" in UG714, Arora V 25K FPGA Products Programming and Configuration Guide .
- 3.It is recommended that add an ESD protection chip to the JTAG download circuit.
- 4.VCC core voltage requires a large current, so it is recommended to supply power separately.
- 5.The MODE pin is the GowinCONFIG configuration mode selection signal.
For details about how to select the Mode signal, see "Chapter 3.1 Configuration Modes" in UG714, Arora V 25K FPGA Products Programming and Configuration Guide.


GW5A-LV25PG256S



Notes:
1.F CLK signal is an external input clock signal.
It is recommended that F_CLK signal be provided through an active oscillator crystal.
2.External Flash memory is used to store downloaded programs.
For details about SPI Flash model selection, see "Chapter 4.5 SPI Flash Selection" in UG714, Arora V 25K FPGA Products Programming and Configuration Guide .
3.It is recommended that add an ESD protection chip to the JTAG download circuit.
4.VCC core voltage requires a large current, so it is recommended to supply power separately.
5.The MODE pin is the GowinCONFIG configuration mode selection signal.
For details about how to select the Mode signal, see "Chapter 3.1 Configuration Modes" in UG714, Arora V 25K FPGA Products Programming and Configuration Guide.



GW5A-LV25UG324




Notes:


1. F_CLK signal is an external input clock signal.
- It is recommended that F_CLK signal be provided through an active oscillator crystal.
2. External Flash memory is used to store downloaded programs.
- For details about SPI Flash model selection, see "Chapter 4.5 SPI Flash Selection" in UG714, Arora V 25K FPGA Products Programming and Configuration Guide .
3. It is recommended that add an ESD protection chip to the JTAG download circuit.
4. VCC core voltage requires a large current, so it is recommended to supply power separately.
5. The MODE pin is the GowinCONFIG configuration mode selection signal.
- For details about how to select the Mode signal, see "Chapter 3.1 Configuration Modes" in UG714, Arora V 25K FPGA Products Programming and Configuration Guide.

Title				
GOWIN Minimum System Diagram				
Size C	Document Number GW5A-LV25UG324			Rev 2
Date:	Tuesday, May 07, 2024	Sheet	14	of 14


1




GW5A-LV25UG3249



GW5A-LV25UG32



*Configurable GPIO mode section



*JTAG download section

Title			
GOWIN Minimum System Diagram			
Size C	Document Number GW5A-LV25UG324S		Rev 2.3
Date:	Tuesday, May 07, 2024	Sheet	15 of 15