

# Bug fix in pixelqualityLM

- Bad: tag\_pixelqualitylm\_datav6.3=2025V0
  - ▷ link error rates from MIDAS meta data file not correctly incorporated
- Good: tag\_pixelqualitylm\_datav6.5=2025V0
- Cross-check comparison link error rate in raw JSON file and payload
  - ▷ use most conspicuous runs when comparing old and new versions
  - ▷ Table contains link counts JSON/Payload

Run	(M)asked	(S)tatus4	Diagnostic
3509	99/98	225/210	M: 102C, S: 102AB, (195,1316)ABC, 1286B top/bottom, (1281-1158)ABC deadChip
4576	99/96	62/59	M: 102C, 1126AC contaminated S: 1251ABC top/bottom
4602	99/98	0/0	M: 102C
4608	99/95	50/50	M: 102C, 1123A contamination, 1126B contamination
4725	99/98	0/0	M: 102C
4748	99/96	21/21	M: 1123B contamination, 102X, 165A contamination
5656	99/97	13/12	M: 102C S: 102X
5850	99/98	3/3	M: 102C
6157	96/95	228/220	M: 102C declBad, S: 102AB, (1158,1281)ABC empty
6158	96/95	228/220	ditto
6164	96/95	228/199	M: 102C, S: 102AB, (1158,1281,1284-6,1316-8)ABC empty
6213	96/95	1/1	M: 102C, S: confirmed same chip+link
6261	96/95	228/220	M: 102C, S: 102AB, (1158,1281)ABC empty
6263	96/95	2/2	M: 102C, S: confirmed same chips+links
6270	96/94	17/17	M: 102C, 165C contaminated

⇒ "Successful" manual validation of (a selection of) payloads

# Preparation for v6.5

---

- mu3eUtil branch **CDB-v6.5pre**
  - This must go into v6.5!
- Request to eliminate compiler warnings
  - API change (removal of GT in cdb\* instantiation)
- Can replace any tag contained in GT with another tag
  - ▷ e.g. switch easily the "alignment" or "efficiency" for studies (not yet via command line)
- Can query iov runnumber
  - ▷ to check whether it's for the current one (not yet pushed)

calEventStuff  
first valid TS  
last valid TS

iov\_5432

analyze run 5433

# Preparation for v6.5 (II)

---

- Scaling of file number for JSON backend
  - ▷ "payloads" directory with new subdirectories
    - tag
    - iov files arranged in blocks of maximum 1000 files  
(problem: pixelqualitylm and eventstuffv1 have  $\mathcal{O}(n_{\text{runs}})$  iovs)
  - ▷ "runrecords" directories with subdirectories
    - runrecord files arranged in blocks of maximum 1000 runs
- code backward compatible (but old code cannot read new structure)
- no more hesitations to add new tag versions

# Global tags for v6.5

---

- 2025 Data GT `datav6.5=2025V0`
  - ▷ not there, yet (to be sync'ed with v6.5!)
  - ▷ current test GT: `datav6.5=2025V1test`
- New `mcidealv6.5` GT
  - ▷ now includes all tags for perfect setup (except `calPixelTimCalibration`)
  - ▷ for boot-strap "install" CDB (not for real analysis)
- Waiting for realization that we need `mcrealistic` GT
  - ▷ how else would you have the same code for analysis of data and MC?
- Need a better scheme/setup for GT/tag documentation!
  - ▷ `current bitbucket doc`

# pixelqualityLM algorithm I

---

- Status enum

- ▷ -1=ChipNotFound, 0=Good, 1=Noisy, 2=Suspect, 3=DeclaredBad
- ▷ 4=LVDSErrorLink, 5=LVDSErrorOtherLink, 6=LVDSErrorTopBottomEdge
- ▷ 7=DeadChip, 8=NoHits, 9=Masked
- ▷ M-link=nhit/ovfl (derived from DQM hitmap)

⇒ Not all applicable on all levels, e.g. DeadChip not on pixel level

- Chips

- ▷ DeclaredBad: hand-curated list (102)
- ▷ Masked (chip/link): (all 3 links/1 link) masked
- ▷ DeadChip: all 3 links have no hits

- Links

- ▷ LVDSErrorTopBottomEdge: mean row  $< 10$  or  $> 245$ , if not masked
- ▷ LVDSErrorLink: unmasked link error rate  $> 10$  Hz (midas meta data)
- ▷ LVDSErrorOtherLink: if other unmasked link error rate  $> 10$  Hz
- ▷ NoHits: no hits on link
- ▷ M-Link:  $(\text{uint32})\text{nhits}/\text{nOverflow}$  (1 if  $\text{nOverflow} > \text{nhits}$ )

# pixelqualityLM algorithm II

---

- Columns
  - ▷ Dead: no hits (IFF mean column hit = 10)
  - ▷ Suspect: more than 40 noisy pixels (see below)
- Pixels (only counting pixels with hits)
  - ▷ Noisy: pixel hit count  $> 10\sigma$  above mean pixel hit count