

easy & medium
hard

new feedback
+ given by instructors
+ lesson content
+ easy + classic questions

ing use

Paymon

Techniques to arrange data in the form
key value pairs

Hash Table

by count

10¹, 2
20¹, 2
60¹, 20

cazius

Recursion
+
loops

```

graph TD
    10((10)) --> 20((20))
    10 --> 30((30))
    20 --> 40((40))
    20 --> 50((50))
    40 --> 60((60))
    40 --> 70((70))
    60 --> 80((80))
    60 --> 90((90))
    80 --> 100((100))
  
```

Level 1 → 10

Level 2 → 20

Level 3 → 40

- ↳ class (array)
- ↳ heap (linked list)

$[10, 15, 30, 40, \text{null}, 100, 30, 60, \text{null}]$

Free

```

graph TD
    10((10)) --> 15((15))
    10 --> 30((30))
    15 --> 40((40))
    40 --> 60((60))
    30 --> 100((100))
    30 --> 50((50))
  
```

[10, 15, 25, 121, 5]

② 25, 15, 10, 8]

- ↳ Two sum
- ↳ k the largest value
- ↳ group anagrams together
- ↳ last stone weight.
- ↳ frequent elements

$$[10,5, 1,5, 2,8]$$

Min-heap

```

graph TD
    15((15)) --> 5((5))
    15((15)) --> 10((10))
    5((5)) --> 8((8))
    8((8)) --> 10((10))
  
```