

Information presented in this document is the property of Control Solutions LLC is considered proprietary and confidential and not to be reproduced or distributed without the specific written permission of Controls Solutions LLC.

Title: **3.3V, 5V, and 15V Power Supplies**

Document Number: **008324B**


Size: **B** Engineer: **C. Ray** Rev **B**

Date: **4/28/2020** Time: **15:09:49** Sheet **2** of **14**

File: **Page-2.SchDoc**









**CONTROL SOLUTIONS LLC™**  
2520 Diehl Road, Aurora, Illinois 60502  
Tel: 630.806.7062 Fax: 630.806.7065  
www.controls.com





MCP2562 ESD protection on CANH & CANL meeting IEC61000-4-2 to 8KV.

|                      |                                 |                       |       |     |    |
|----------------------|---------------------------------|-----------------------|-------|-----|----|
| $C_{i/o-GND}$        | Capacitance between I/O and GND | $V_R = 1.65\text{ V}$ | 2.5   | 3.5 | pF |
| $\Delta C_{i/o-GND}$ |                                 |                       | 0.015 |     |    |
| $C_{i/o-i/o}$        | Capacitance between I/O         | $V_R = 1.65\text{ V}$ | 1.2   | 1.7 | pF |
| $\Delta C_{i/o-i/o}$ |                                 |                       | 0.04  |     |    |
| $C_{i/o-GND}$        | Capacitance between I/O and GND | $V_R = 1.65\text{ V}$ | 2.5   | 3.5 | pF |
| $\Delta C_{i/o-GND}$ |                                 |                       | 0.015 |     |    |
| $C_{i/o-i/o}$        | Capacitance between I/O         | $V_R = 1.65\text{ V}$ | 1.2   | 1.7 | pF |
| $\Delta C_{i/o-i/o}$ |                                 |                       | 0.04  |     |    |



CG 6

Changes / Notes : Changed TX1030 to 74LV4T125




|   |   |   |   |   |   |
|---|---|---|---|---|---|
| 1 | 2 | 3 | 4 | 5 | 6 |
| A |   |   |   |   | A |
| B |   |   |   |   | B |
| C |   |   |   |   | C |
| D |   |   |   |   | D |

Page 6 is blank. The USB interface was removed.

Information presented in this document is the property of Control Solutions LLC is considered proprietary and confidential and not to be reproduced or distributed without the specific written permission of Controls Solutions LLC.


**CONTROL SOLUTIONS LLC™**  
2520 Diehl Road, Aurora, Illinois 60502  
Tel: 630.806.7062 Fax: 630.806.7065  
[www.controls.com](http://www.controls.com)







Since the PIC Voh(MIN) is only specified at 2.4V, while the bridge driver Vih(Max) is specified as 2.7V over the -40C to +125C temp. range.




Changes / Notes :

R55 changed to 0.02 ohms making the current sensing range approximately 0A-3.3A.

U12 Vout:  $V_{out} = 1V / 1A$   
 $V_{out} = I \times R \times G$   
 $V_{out} = 1A \times 0.02 \times 50V/V$

Ref. Brake I Sense.asc simulation.  
Manufacturer Papice model indicates 20mV out when  
the current through the sense resistor is 0.  
Ref. also ina181a2 Symbol Test1.asc  
Better than single-supply R2R in/out ISL28130 in  
diff-amp config.



Information presented in this document is the property of Control Solutions LLC is considered proprietary and confidential and not to be reproduced or distributed without the specific written permission of Controls Solutions LLC.

Title: **Brake Drive & Brake Current Sense**  
Document Number: **008324B**  
Size: **B** Engineer: C. Ray Rev **B**  
Date: 4/28/2020 Time: 15:09:50 Sheet 11 of 14  
File: Page-11.SchDoc



**CONTROL SOLUTIONS LLC™**  
2520 Diehl Road, Aurora, Illinois 60502  
Tel: 630.806.7062 Fax: 630.806.7065  
www.controls.com

