

VALUE ADDED COATING SOLUTION PVT. LTD.

Head Office : 515, Devika Tower, Chandra Nagar, Ghaziabad, U.P.

Works : K-288, Site-V, Kasna Industrial Area, Noida(U.P.)

Website : www.coating-solution.com,

E-mail : info@coating-solution.com,

M/S. RELIANT ALUMINIUM PVT LTD

Howrah(West Bengal)

Subject: **Quotation for Automatic Booth with Cyclone & Dust collector.**

Dear Sir ,

This has reference to our discussion regarding the Powder spray manual booth for Mild steel components. We are offering you the Booth with Mono- Cyclone & Dust collector for the same purpose.

The complete details are as below as per discussion:

1.Recovery Booth with dust collector

Powder Coating Mono-Cyclonic Recovery Spray Booth with dust collector

Mono- Cyclonic Recovery System is a revolutionary new concept becoming popular in Indian powder coating market. Mono- cyclonic systems gives excellent 98% over sprayed powder. Mono- cyclonic systems are widely used at the places where we require large volumes and high powder coating recovery efficiency for application.

Mono-Cyclonic Recovery Systems four major parts:

1. BOOTH: The enclosed zone in which gun operator applies virgin powder film through electrostatic charging is called booth, this is the effective volume in which powder coating process takes place.
2. MONO-CYCLONE: IN Mono-Cyclonic Recovery System one cyclone of large diameter introduce, depending upon the effective working volume to enhance the suction power. Since powder enters from the top of clone through the stabilizing chamber, access to clone for cleaning is extremely easy. .

3. BLOWER: This is mounted at the top of the dust collector to suck out the air from the booth through Cyclone along with over sprayed powder particles. Over sprayed usable powder particles get settled due to gravitational force in the collector bin at the conical end of cyclone.
4. DUCTS: Ducts connects booth to mono-cyclone & mono-cyclone to dust collector.
5. DUST COLLECTOR- Dust collector is the device in which fine powders separate from the air through the cartridge filters & collects in the bin. The motor & blower are placed in this machine. The cartridge filters clean automatically through reverse jet pulsing system.

Technical Specifications

Booth Size(LXDXH in mm)- 5000 (L)X1200(D)X3050(H)

MOC of Booth-SS-304(1.2mm & 1.5mm)

Dimensions of Dust collector(LXWXH in mm)-1600X1600X4000

Dimensions of Mono-Cyclone(LXWXH in mm)-1150X1150X4000

MOC of Cyclone & Dust Collector- 1.5mm(CRC) & 2.0mm(HRC)

Number of Filters- 9 Nos

Number of valve- 9 Nos

Cleaning of Filters- Reverse Jet Type

Recovery System- Mono- Cyclone

Suction Motor Rating: 20 H.P. X1 unit(2800rpm)

Collection of Recycled: Positive powder collector box

Connection: Ducts

Control Panel- Automatic

COMMERCIAL OFFER

Spraying Booth- 1 Nos

Mono-cyclone-1 Nos

Dust Collector- 1 Nos

Connecting Ducts- As required

Rs. 20,00,000(Rupees Twenty Lakh Only.)

Terms & conditions

Price: The above prices are ex-works Noida.

Payments: 50% against formal purchase order
, 50% prior to dispatch.

Taxes & Duties : **GST @18% further added on to it.**

Freight : To pay basis.

Warranty : One Year Against any manufacturing
Defect except equipment purchased by third party
such as Motor etc.

Delivery : Within 30-45 days from the date of
formal purchase order along with
advance.

Civil Work : Any Civil work if required will be at
your side.

We are sure that you will find our commercial offer in line with your
acceptation and will place your valuable order with us.

For Value Added Coating Solution Pvt.Ltd.,

Harish Sharma (+919811846214)
(Director)

06 February 2025