

300 kg/hr Bobble Line.
Centre filled

BOOKLET FOR COMPLETE PRODUCT LINES



Starmers
Engineering Works

300 kg/hr

STANDARD

CENTRE-FILLED BUBBLE LINE SLOW SPEED COMPLETE LINE

1. SUGER GRINDER SEW-701 ✓
2. HEATING CABINET SEW-702 ✗
3. BUBBLE GUM MIXER SEW-112 ✓
4. REST TABLE SEW-804 ✓
5. Trolly SEW – 815 ✓
6. BUBBLE GUM EXTRUDER SEW-113 ✓
7. LIQUID FILLING PUMP SEW-110 ✓
8. ROPE SIZER 5 STAGES SEW-212 ✓
9. REST CONVEYOR SEW-808 ✓
10. UNIPLAST SEW-116 ✓
11. ROTARY DIE WITH CUTTING RINGS SEW-117 ✓
12. DIE STAND SEW-118 ✓
13. COOLING TUNNEL 3 STAGES SEW-121 ✓
14. AC UNIT SEW- ✓
15. WRAPPING MACHINE SEW-120 ✓

1. SUGAR GRINDER SEW-701

Trait:

A sugar grinder converts crystal sugar into fine uniform powder to ensure smooth dough formation, efficient blending with gum base and consistent product texture in bubble gum production.

Specification:

- Storage Capacity: 500 kg
- Grinder 45 Number
- Motor Power 15 hp
- Inner Box SS 303
- Outer Box M.S
- Dimensions 4 w x 6 l

Dimension: 4 w x 6 l

Weight:

Power Load: 15hp

2. HEATING CABINET SEW-702

Trait:

A heating cabinet maintains controlled temperature to pre-soften and condition the gum mass, ensuring smooth shaping, uniform elasticity, and stable processing in the bubble gum line.

Specification:

- 5 trays
- Outer sheets in M.S
- Inner sheets SS 304
- Double jacketed with glass wool
- Heaters and blower total load 10 hp

Dimension: 3'x3'x 6'

Weight:

Power Load: 10hp

3. BUBBLE GUM MIXER SEW-112

Traits:

The bubble gum mixer is used to blend all the raw ingredients into a homogeneous gum base mass suitable for further processing (like extrusion and shaping).

Specification:

1. Capacity: 100 kg in 20 min ✓
2. Pan: In S.S 304 ✓
3. Double jacketed ✓
4. Double jacketed with S.S 304 ✓
5. Z-arm: S.S 304 ✓
6. Pan cover: In S.S 304 ✓
7. Gear motor main drive: 20 hp ✓
8. Heavy duty: M.S structure ✓
9. Electric heaters ✓
10. Electric panel with all new features ✓
11. Weight: 2 ton approx ✓
12. ~~Side sheets: S.S~~ ✓
13. Tilting system ~~gear motor~~ 2hp ✓

Electric heater 3000 watt x 2 = 6000 watt

Dimension: (6' x 8' x 8')

Weight:

Power Load: 61hp

4. REST TABLE SEW-804

Trait:

- For a temporary rest of the gum box batch coming from the mixer.

Specifications:

- Base Plate thickness 10mm in S.S 304
- Legs 4 Nos in S.S 201

Dimension: 3ft*6ft

Weight:

Power load: 0hp

5. Trolly SEW-815

Trait:

It is used to safely transfer the hot, viscous gum base mass from the mixer to the extruder, ensuring continuous material flow and preventing contamination or handling delays in the bubble production line.

Specifications:

For moving the gum base mass from mixer to extruder

3ft length

3ft width

Pan in S.S 304

Trolly stand M.S

Dimension:

Weight:

Power Load: 0hp

6. BUBBLE GUM EXTRUDER SEW-113

Traits:

The bubble gum extruder shapes the mixed gum mass into a continuous rope or sheet with uniform thickness, texture, and density—making it suitable for further forming (cutting, rolling, or shaping).

It essentially transforms the soft, irregular gum from the mixer into a consistent product form for downstream processing.

Specifications:

1. 1 rope ✓
2. 2 Worms ✓
3. 7.5 hp gear motor drive ✓
4. 10 hp inverter ✓
5. M.S structure ✓
6. keef in S.S *304* ✓
7. Electric heaters *6000 watt* ✓
8. Electric panel with all new features ✓
9. Helping roller system in keef ✓

Dimension:

Weight:

Power Load: 14hp ✓

7. LIQUID FILLING PUMP SEW-110

Trait:

The center filling pump is a precision dosing system designed to inject liquid filling (such as fruit syrup, chocolate, cream, or jam) into the core of the candy rope during the forming process. It ensures consistent filling quantity and uniform distribution across all candies.

Specifications:

- Filling chocolate and liquid ✓
- keef in S.S 304 ✓
- keef double-jacketed ✓
- ~~Rod in S.S with Teflon covering food-grade heat proof material~~
- Pipe flexible food grade ✓
- Electric panel with new feature ✓
- Gear motor 2 hp main drive ✓
- Stand in M.S ✓
- Electric heater to moderate temperature 1000 watt 1 NOS ✓
- Electric inverter 2HP to increase or decrease filling in product ✓
- Overflow system to recycle liquid/Chocolate ✓

Dimension:

Weight:

Power Load: 3.3hp ✓

8. ROPE SIZER 5 STAGES SEW-212

Traits:

The rope sizer is a precision machine used to accurately reduce & calibrate the diameter of the candy and toffee rope produced by the batch roller. It ensures a uniform rope thickness suitable for feeding into the forming or cutting machine, maintaining consistent candy size and weight throughout production.

Specifications:

- * Horizontal model
 - * 5 stages (4 stages horizontal & 1 vertical)
 - * 1st pair in S.S 304 37mm
 - * 2nd pair in S.S 304 32mm
 - * 3rd pair in S.S 304 27mm
 - * 4th pair in S.S 304 22mm
 - * 5th pair in S.S 304 17mm
 - * Electric panel in S.S 201
 - * Sizer plates in S.S 304
 - * Side Sheets S.S 201
 - * Rope guide in brass
 - * Electric inverter new brand INVENT company 3HP
 - * Gear motors are of SEW brand Germany 3hp
 - * Heat controllers 2 NOS
 - * Emergency break to stop equipment
 - * Emergency switch to off equipment
 - * Electric breakers
 - * Electric components brand new
 - * Electric heaters 500 x 4 = 2KW
- Dimension:** (H x W x L) 4'6" x 3' x 5'6"
- Power Load:** 5.68hp

9. REST CONVEYOR SEW-808

Trait:

The rest conveyer provides a controlled resting time for the center-filled bubble so the filled material settles evenly, internal pressure stabilizes and the seal strength develops properly. This helps to prevent leakage, deformation or bursting of the bubble.

Specifications

- Dimension: 3 ft width x 20 ft length ✓
- Single Belt ✓
- Belt food-grade material ✓
- Gear motor main driver 2hp ✓
- ~~Double jacketed duct on top of conveyor~~ ✓
- ~~Insulated with thermopore~~ ✓
- Variable inverter for speed control ✓
- Frame in M.S ✓

• Top Cover S.S 304 ✓

• Fans for Cooling 3 Nos ✓

Dimension: 3 ft width x 20 ft length ✓

Weight:

Power Load:

10. UNIPLAST SEW-116

Trait:

- The SEW-4 has been designed for the continuous production of seamless sweets with or without center filling using a standard die arrangement.
- The machine can be used as a part of a complete production plant supplied by Starmer Engineering Works, or integrated into an existing line.
- Suitable for forming hard boiled candies, center liquid filled candies, center powder filled candies, toffees, chewy-toffee, chewy candies, chewing-gum & bubble gum products. It forms seamless sweets with high depth thickness.

Specifications:

- 5 hp motor for main drive ✓
- 5 hp inverter new brand (INVENT Company) ✓
- ~~Up to 450kg/hr~~ ^{upto 300kg/hr} ✓
- Electric panel with all new features ✓
- CAMS used in this machine in bearing steel grade ✓
- Reverse Cams in S.G iron ✓
- Gears used in this machine are of high carbon steel forged material ✓
- ~~2500 to 3500 pieces/min depending upon size of product.~~ ^{upto 2200 p/min} ✓
- Filling % of the candy upto 12 % ✓

Dimension: 6.5ftx4.5ftx3.5ft ✓

Weight:

Power Load: 5hp

11. ROTARY DIE WITH CUTTING RINGS SEW-117

Trait:

The heart of any candy production line is the rotary dies in the forming machine. They literally shape the product and add to its face value. The forming dies are used for the production of hard-boiled candies, Toffees, Eclairs, Powder-filled candies, liquid-filled candies, and more. Starmer Forming dies are recognized in the confectionery industry for their precision-based performance, safety, and functional efficiency.

Starmer machines are built for generational use, we offer a supply of spare parts and die-heads for models that may have been discontinued for decades. As the leading confectionery machinery manufacturer, Starmer aims to be your reliable long-term business partner, and offers the following benefits:

Accuracy:

- Perfectly formed, seamless candies
- Nearly any shape of candy can be made
- To ensure accuracy, we provide drawings, and product samples on request to help you visualize the sense of the product

Quality:

- The finest quality raw material used

Durability:

- Our 55+ years of experience have garnered the forming dies into a piece of perfection, even with continuous production, the die-set does not damage easily

Material specification:

- Cutting Ring: Cutting Ring in grade Forged M.S. This grade provides cutter pitch (teeth) of 2-3 mm.
- Punch: Punch in grade 1045, Hardness upto 45 Hrc
- Block: High Quality
- M.S. Guide Pins: Guide pins in grade Carbon Steel.
- Die Parts: Casting in grade Cast Iron.
- Outer Ring: Outer Ring in Brass Casting. For the improvement of rope cutting.

Dimension: 1ftx1ftx1'5"

Weight:

Power Load: 0

12. DIE STAND SEW-118

Trait:

It's main purpose is to make die changing and fitting easier and more efficient.

Specification:

- Main Frame in M.S ✓
- Wheels for movement ✓
- Die Caplene in casting Material ✓
- Screw for die up/down ✓

Dimension: 5.5ftx5ft ✓

Weight:

Power Load: 0

13. COOLING TUNNEL 3 STAGES SEW-121

Trait:

Its main purpose is to rapidly and uniformly reduce the temperature of freshly formed candy, ensuring dimensional stability, proper hardness, and surface quality before cutting, wrapping or packaging.

Specifications:

- 16ft long ✓
- 3ft width ✓
- ~~With 5 ton AC~~ ✓
- 3 stages ✓
- 1st step mesh wire in S.S 304 grade ✓
- 2nd step mesh wire in S.S 304 grade ✓
- 3rd step mesh wire in S.S 304 grade ✓
- outer and inner Side sheets in S.S 201 ✓
- Electric panel with all new features ✓
- Inverter new brand ✓
- All covers in ~~S.S 201~~ S.S 304 ✓
- Double jacketed insulates with thermopore ✓
- Rods are in S.S 304 5mm thickness ✓
- Chain in M.S 40 no ✓
- Gear motor 3hp (1hp each 3 nos) SEW brand ✓
- Variable speed inverter ✓
- Electric inverter for controlling speed (5hp) ✓

Dimension: x3ftx16ft

Weight:

Power Load:

10 Ton

14. AC UNIT 5 TON

Description:

Indoor Unit capacity 5 Ton (6.5 HP) floor standing type for cooling conveyor Accessories

- 1: evaporator brand new copper tube size 3/8 gage 22 distributor size 1/2 section header 7/8.
- 2: aluminum fins thickness. 0.150mm company Breez.
- 3: High-velocity air blower With 1 HP motor 3 phase 440/v Hz 50.
- 4: expansion valve company Emerson model TCLE 6.5 HP.
- 5: Base frame angle iron sizes are on customer demand.
- 6: Indoor frame cover sheet GI colored 22 gage.
- 7: indoor frame cover sheet insulation with insulated material.
- 8: Indoor copper pipe fitting 18 gauge length tube.,

6.5 HP OUTDOOR Company Bitzer with all his ACCESSORIES:

- 1: condensing unit Company Bitzer with high-density condensing coil.
- 2: High static air flow fan 3phase 440/v Hz50.
- 3: compressor Copeland scroll capacity 6.5 HP 3 phase 440/v H250.
- 4: Liquid receiver capacity 5 liter.
- 5: Oil spreader in/out pipe size 7/8.
- 6: Hand valve 1/2.
- 7: Filter 1/2.
- 8: Copper length 1/2 and 5/8.
- 9: section accumulator 7/8
- 10: Copper long bend 5/8 and 7/8 and 3/8 elbow.
- 11: dual high low-pressure safety switch company Danfoss with high-pressure leads.
- 12: Outdoor base frame channel and angle iron.
- 13: refrigerant R-22 company (Honeywell USA).

ELECTRIC PANEL equipment:

- 1: 7.5 KVA inverter company (INVT).
- 2: magnetic contactor 30A amperes for compressor
- 3: Holding contactor
- 4: blower contactor.
- Sastermostat
- 6: fan contactor.
- 7: connection strip
- 8: push button
- 9: Electric panel box size 12" x 24".

15. WRAPPING MACHINE SEW-123

Trait:

is high performance pillow pack wrapping machine for filled or un-filled candies, bubblegums and other similar items incorporating latest and precision components the machine is capable of achieving speed upto 800 pieces per minute. Fin seal and end seal are of high quality ensuring long shelf life of the product. Large size feed disc and brushes enable positive transfer of candies to the carrier chain

SPECIFICATIONS:

OUTPUT:

Upto 800 Pcs/min on candy i Upto ~~500~~ Pcs/min on bubble ✓

ELECTRIC MOTORS:

* (1) 2H.P./3-Phase ✓

* (2) ½ H.P. ✓

ELECTRIC HEATERS: 3.2 ✓

STANDARD EQUIPMENT: Photo Electric Eye & Invertet ✓

DIMENSIONS (L x WxH): 2,335 x 900 x 1,715 mm ~ ✓

WEIGHT: 750 Kg ✓

REEL (Maximum Outer Dia / Core Dia): 280 / 70mm ✓

Power Load:

~~Same as dynamic~~ ?