

Pop bubble Complete line

BOOKLET FOR COMPLETE PRODUCT LINES



Starmers
Engineering Works

Double Twist Bubble Production Line

1. Sugar Grinder
2. Heating Cabinet
3. Bubble Gum Mixer
4. Rest table
5. Trolley
6. Bubble Gum Extruder
7. Single step Cooling Conveyor
8. Cut & [REDACTED] Wrapping Machine
Double Twist

1.Sugar Grinder SEW-701

Trait:

A sugar grinder converts crystal sugar into fine uniform powder to ensure smooth dough formation, efficient blending with gum base and consistent product texture in bubble gum production.

Specification:

- Storage Capacity: 500 kg
- Grinder 45 Number
- Motor Power 15 hp
- Inner Box SS 303
- Outer Box M.S
- Dimensions 4 w x 6 l Dimension: 4 w x 6 l

Power Load: 15 hp

Weight:

2.Heating Cabinet

Trait:

A heating cabinet maintains controlled temperature to pre-soften and condition the gum mass, ensuring smooth shaping, uniform elasticity, and stable processing in the bubble gum line.

Specification:

- 5 trays
- Outer sheets in M.S
- Inner sheets SS 304
- Double jacketed with glass wool
- Heaters and blower total load 10 hp

Dimension: 3'x3'x 6' Weight:

Power Load: 10hp

3. BUBBLE GUM MIXER

Traits:

The bubble gum mixer is used to blend all the raw ingredients into a homogeneous gum base mass suitable for further processing (like extrusion and shaping).

Specification:

1. Capacity: 100 kg in 20 min
 2. Pan: In S.S 304
 3. Double jacketed
 4. Double jacketed with: S.S 304
 5. Z-arm: S.S 304
 6. Pan cover: In S.S 304
 7. Gear motor main drive: 20 hp
 8. Heavy duty: M.S structure
 9. Electric heaters: 6000 watt
 10. Electric panel: With all new features
 11. Side sheets: S.S 201
 12. Tilting system: Gear motor 2 Hp
- Dimensions (H $\times$ W $\times$ L): 6'x8'x8'
 - Power Load: 28 hp

4.Rest table

Trait:

- For a temporary rest of the gum base batch coming from the mixer.

Specifications:

- Base Plate thickness 10mm in S.S 304
- Legs 4 Nos in S.S 201

Dimension: 3ft*6ft

Weight:

Power load: 0hp

5.Trolley

Trait:

It is used to safely transfer the hot, viscous gum base mass from the mixer to the extruder, ensuring continuous material flow and preventing contamination or handling delays in the bubble production line.

Specifications:

- For moving the gum base mass from mixer to extruder
- 3ft length
- 3ft width
- Pan in S.S 304
- Trolley stand M.S

Dimension:

Weight:

Power Load: 0hp

6. Bubble Gum Extruder

Traits

The bubble gum extruder shapes the mixed gum mass into a continuous rope or sheet with uniform thickness, texture, and density—making it suitable for further forming (cutting, rolling, or shaping).

It essentially transforms the soft, irregular gum from the mixer into a consistent product form for downstream processing.

Specifications

1. 1 rope
2. 2 Worms
3. 7.5 hp gear motor drive
4. 10 hp inverter
5. M.S structure
6. keef in S.S 304
7. Electric heaters: 6000 watt
8. Electric panel with all new features
9. Helping roller system in keef

• **Dimension:**

• **Power Load: 18 hp**

7.Single step Cooling Conveyor

Trait:

The cooling conveyors are designed for high-performance precision cooling of a wide range of ball and ac cylindrical pieces, while retaining the original pieces, shape and quality.

Specifications:

- Conveyor: 3ft x 20ft
- Function: All types of Bubble Gum
- Belt Size: W 2.5ft x length 20ft
- Belt Type: White Food Grade
- Motor Power: 2hp
- Invertor: 2hp
- Structure: Ms Heavy Pipe 14g
- Control Panel: with all New Features
- Double Jacketed duct on top of Conveyor
- Insulated with thermopore

Dimension: 3ft x 20ft

Weight:

Power Load:

Dimension:

Weight:

Power Load:

9.CUT & DOUBLE TWIST :

Trait:

A cut and double twist wrapping machine is used to wrap individual candies quickly and neatly. Its purpose is to take a piece of wrapper, place the candy inside, cut the wrapper to the right size, and then twist both ends.

Specifications:

- Speed: 350 piece per minute (depending upon size of product)
- Double Reel: Inner & Outer
- Bearing in gears: NTN Japan
- Inverter to control speed: 2 HP INVENT BRAND
- Gear motor: 2hp, 3 phase
- Motor brand: New HECO
- Photocell: Photocell Eye
- Paper: Continues Paper

Weight: 1100 kg

Dimensions: L 1500mm x W 1500mm x H 2100mm