


Chain Die Toffee 400 kg/hr.

BOOKLET FOR COMPLETE PRODUCT LINES



Starm
Engineering Works

CHAIN DIE TOFFEE (400 KG/HOUR)

- 1: Glucose Tank ✓
- 2: Steam Generator (600 kg) ✓
- 3: Steam Headler ✓
- 4: Toffee Cooker (150 kg) ✓
- 5: Cooling Table ✓
- 6: Pulling Machine ✓
- 7: Liquid Filling Pump ✓
- 8: Batch Roller (75kg) ✓
- 9: Rope Sizer (5 stages) ✓
- 10: Chain Die *forming plants with die* ✓
- 11: Cooling Tunnel 3 Stages ✓
- 12: Ac Unit ✓
- 13: Wrapping Machine ✓
- 14: Chain die Stand with reference molder ✗


11/2/26
Approved by
Arslan Shahid

1. Glucose Tank SEW-101

Trait:

Glucose storage tanks are engineered with specific traits to ensure hygienic, stable and crystal free storage of liquid glucose and Syrups for industrial applications. ✓

Specifications:

- * Grade: S.S 304 ✓
- * Sheet thickness: 5 mm upper and lower sheet ✓
- * Outer dia sheet thickness: 3 mm ✓
- * Design Type: Vertical ✓
- * Heating System: Coil on the base of tank for Steam Circulation ✓
- * Ladder: Outside the tank ✓
- * Capacity: 20 ton Glucose ✓
- * Dimension: 16ft height x 7ft diameter ✓
- * Power load: 0 ✓

Approved by
Aselan Shohid
11/2/26

2. Steam Generator SEW-102

Trait:

Steam generator heats water to produce high Pressure steam for heating, cleaning or industrial processes.

Detail of Mechanical Parts:

1. Gauge Glass: 01 ✓
2. Stop Valve diameter 1": 01 ✓
3. Safety Valve diameter 1": 01 ✓
4. NRV diameter 1": 01 ✓
5. Blow down diameter 1": 01 ✓
6. Air Vent diameter globe Valve = 1/2": 01 ✓
7. Feed Water Pump 01 Multistage (Grundfos): 01 ✓
8. Electric panel Box with complete auto controlled system: 01 ✓
9. Stack diameter 8" height 15ft. thick 2.5 mm: 01 ✓

Detail of Electric Parts:

1. Burner with gas assembly and diesel pump ✓
2. Panel Box 16" x 30" x 8" thick 18g ✓
3. Overload company Schneider: 02 ✓
4. Pressure switch 10 kg imported: 02 ✓
5. Electric Contactor: 02 ✓
6. Power relay company (Finder): 04 ✓ 7. Push button company (Telemechanic): 03 ✓

Specifications:

- * Type of passes: 3 pass ✓
- * Test pressure: 225 psi ✓
- * Working pressure: 150 psi ✓
- * Tube Dia: 2" or 2 1/2" ✓
- * Pressure Shell thickness: 1/2" ✓
- * Tube sheet thick: 1/2" ✓

11/2/26
Approved by Anselon Shahid

* Rock wool thickness: 2" ✓

* Isolation sheet thickness: 24 GAUGE ✓

* Burner Motor: 2hp ✓

* Feed water motor: 3hp ✓

General Details:

* Capacity: 600 kg/hr ✓

* Electric Load: 5 hp ✓

* Dimension: 8' x 3'5" x 3'5" ✓

11/2/26
Approved by
Arsalon Shuhid
[Signature]

3. Steam Header SEW-103

Trait:

Steam headers are design to collect steam from a boiler or steam generator and distribute highquality, dry steam to various user points while performing several critical functions. ✓

Specifications:

- * Material of header: M.S ✓
- * Diameter: 1 ft ✓
- * Branch pipes: 1", 2", 3", 4" depend on system needs ✓
- * Design: Cushioned Cylinder ✓
- * Connection: 5 ✓
- * Dimension: Dia 1ft x Length 3ft ✓
- * Power load: 0 ✓

11/2/26
Approved by Arsalan Shohid

4: Toffee Cooker (150 Kg)

Trait:

The purpose of a toffee cooker is to heat and cook sugar based mixtures to a controlled temperature so the toffee reaches the correct thickness, texture, and moisture level. It provides uniform heating and precise temperature control to prevent burning, ensure consistent quality, and achieve the required hardness or chewiness of the final toffee product. ✓

Specifications:

Toffee cooker ✓

* Capacity: 150kg per batch after 20 to 25 mins ✓

* Stirrer: S.S 304 ✓

* Pan material: S.S 304 ✓

* Pan double jacketed with S.S 304 ✓

* Frame in: M.S ✓

* Electric pannel with all new features ✓

* 3 hp gear motor drive ✓

* Safety valve ✓

* Cover of pan in S.S 304 ✓

Approved by Anshu Sharma
11/2/24

Dimension: (H \ W \ L)

Power Load: 3hp ✓

5. Cooling Table SEW-108

Trait:

The cooling table is a crucial post-cooking unit used for rapid cooling and conditioning of the cooked sugar mass before further processing such as mixing, flavoring, coloring, or forming. It ensures uniform texture and workability of the batch. ✓

Specifications

- * Base plate thickness: 10mm in S.S 304 ✓
- * Material of plate: Boundary wall S.S 304 ✓
- * Cooling medium water: Cooling system A frame work for moving water Inlet and outlet Valve. * Legs: 4 Nos in S.S 201 grade ✓

Dimension: 3ft x 6ft x 2'6" (W x L x H) ✓

Power Load: 0

Handwritten:
~~Not~~
Approved

6: Pulling Machine

Trait:

The purpose of a pulling machine is to stretch and fold cooked candy or toffee in a controlled way to improve its texture and structure. By continuously pulling the mass, the machine incorporates air, evens out temperature, and develops the desired smoothness, shine, and chew of the final product. ✓ ✓ ✓

Specifications:

- * Capacity: 100kg ✓
- * Main drive motor: 10hp ✓
- * Arms: Hard chromed ✓
- * Arms for continuous pulling: 3 arms ✓
- * Side sheets: In S.S ²⁰¹ ✓
- * Electric pannel for control ✓

Approved

Dimension: (H \ W \ L)

Power Load: 10hp ✓

7: Liquid Filling Pump

Trait:

The center filling pump is a precision dosing system designed to inject liquid filling (such as fruit syrup, chocolate, cream, or jam) into the core of the candy rope during the forming process. It ensures consistent filling quantity and uniform distribution across all candies. ✓

Specifications:

- * Filling chocolate and liquid ✓
- * keef in S.S 304 ✓
- * keef double-jacketed ✓
- * Rod in S.S with Teflon covering food-grade heat proof material ✓
- * Pipe flexible food grade ✓
- * Electric panel with new feature ✓
- * Gear motor 2 hp main drive ✓
- * Stand in M.S ✓
- * Electric heater to moderate temperature 1000 watt 1 NOS ✓
- * Electric inverter 2HP to increase or decrease filling in product ✓
- * Overflow system to recycle liquid/Chocolate ✓

Dimension: (H \ W \ L)

Power Load: 3.34 hp

Approved

8: Batch Roller (75kg)

Trait:

The batch roller is a key intermediate machine in the candy, lollipop, toffee, and fudge production line. It is designed to continuously roll, shape, and form the cooked mass into a uniform cylindrical rope. It ensures consistent rope size and proper distribution of center filling, flavor, and color before feeding into the rope sizer or forming machine. ✓

Specifications:

- * Frame work horizontal ✓
- * Rollers Quantity 4 ✓
- * Rollers material in S.S 304 food grade ✓
- * Upper body in S.S 304 food grade ✓
- * Bearing in gears ✓
- * Gear motor main drive 1hp ✓
- * Up and down drive 1hp ✓
- * Electric heaters to maintain temperature 1000 watt (2 NOS) ✓
- * Capacity 75 kg ✓
- * Length 6.5 ft ✓
- * Gear motor SEW brand Germany ✓ ~~Regulated~~
- * Roller caplene in casting material ✓
- * Additional tray for removal of wastage ✓

Approved

Dimensions (H x W x L): 4'6" x 2'2" x 7' ✓

Power Load: 4.68 hp ✓

9: ROPE SIZER SEW-212

Traits:

The rope sizer is a precision machine used to accurately reduce & calibrate the diameter of the candy and toffee rope produced by the batch roller. It ensures a uniform rope thickness suitable for feeding into the forming or cutting machine, maintaining consistent candy size and weight throughout production.

Specifications:

- * Horizontal model
- * 5 stages (4 stages horizontal & 1 vertical) ✓
- * 1st pair in S.S 304 37mm ✓
- * 2nd pair in S.S 304 32mm ✓
- * 3rd pair in S.S 304 27mm ✓
- * 4th pair in S.S 304 22mm ✓
- * 5th pair in S.S 304 17mm ✓
- * Electric panel in S.S 201 ✓
- * Sizer plates in S.S 304 ✓
- * Side Sheets S.S 201 ✓
- * Rope guide in brass ✓
- * Electric inverter new brand INVENT company 3HP ✓
- * Gear motors are of SEW brand Germany 3hp ✓
- * Heat controllers 2 NOS ✓
- * Emergency break to stop equipment ✓
- * Emergency switch to off equipment ✓
- * Electric breakers *brand new* ✓
- * Electric components brand new ✓
- * Electric heaters 500 x 4 = 2KW ✓

Dimension: (H x W x L) 4'6" x 3' x 5'6" ✓

Power Load: 5.68hp ✓

*11/4/18
Approved*

10.CHAIN DIE FORMING PLANT

Trait:

Chain Die Forming Plant with Die is a continuous forming system used in confectionery manufacturing to shape candy ropes into uniform pieces. It synchronizes a metering/sizing unit and a die-chain assembly to compress & cut the candy/toffee into precise shapes. The system also supports high-filling products, ensuring stable encapsulation of powder, liquid, cream fillings without leakage while maintaining accurate weight and dimensions. ✓

Specifications:

Speed 2000 to 3500 (pieces per minute depend upon the size & shape of product) ✓

* Up-to 20% filling of product ✓

* Sizer Set in M.S. ✓

* Top Cover in M.S. ✓

* Gear Motor 1 hp for Sizer box drive ✓

* Gear Motor 3 Hp for main drive. ✓

* Gear Motor 0.5 hp for belt drive. ✓

* Gear Motor 0.5 hp for spreader movement ✓

* Inverter 3 hp for speed control ✓ of die

* Inverter 1 hp for speed control ✓ of Sizer Box

~~* Inverter 0.2 hp for speed control~~

Inverter 1 hp for speed control of spreader Belt

* Production upto 450 kg/hr ✓ 400 kg/hr

Dimension:

Weight:

HxWxL

Power Load: 5 hp ✓

~~Not~~
Approved

CHAIN DIE

Trait:

- A Chain Die facilitates high precision formation of Candy Ropes by guiding and shaping the material through calibrated die channels, ensuring uniform size and continuous flow in the production line.

Specification

Material Specification:

- Frame of die : Aluminium Alloy.
- Cutter Blades : D2
- Punches : D2
- U Clamps : Case hardened M.S
- Sprockets : Forged Carbon Steel
- Bushes, Bolts, Pipes, Bearing Conus : EN19
- Connecting Rods (Upper + Lower) ^{high speed} Carbon Steel

Approved

11: Cooling Tunnel 3 Stages

Trait:

Its main purpose is to rapidly and uniformly reduce the temperature of freshly formed candy, ensuring dimensional stability, proper hardness, and surface quality before cutting, wrapping or packaging. ✓

Specifications:

- * 16ft long ✓
- * 3ft width ✓
- * ~~With 5 ton AC~~ With 12 ton AC ✓
- * 3 stages ✓
- * 1st step mesh wire in S.S 304 grade ✓
- * 2nd step mesh wire in S.S 304 grade ✓
- * 3rd step mesh wire in S.S 304 grade ✓
- * Outer and inner Side sheets in S.S 201 ✓
- * Electric panel with all new features ✓
- * Inverter new brand (~~Invent 5hp~~) (INVENT 5hp) ✓
- * All covers in S.S 201 ✓
- * Double jacketed insulates with thermopore ✓
- * Rods are in S.S 304 5mm thickness ✓
- * Chain in M.S 40 no ✓
- * Gear motor 3hp (1hp each 3 nos) SEW brand ✓

Dimension: {H \ W \ L} (3ftx16ft)

Power Load: 3hp

Approved

13: 12 Ton AC UNIT

Description

Indoor Unit capacity 6 Ton (7.5 HP) x 2 roof type for cooling conveyor

Accessories Indoor:

1. evaporator brand new copper tube: size 3/8 gage 22 distributor size 1/2 section header 7/8.
2. aluminum fins thickness: 0.150mm company Breez.
3. high velocity Air blower: With 1 HP motor 3 phase 440/v Hz 50.
4. expansion valve: company Emerson model TCLE 7.5 HP.
5. Base frame angle iron sizes: are on customer demand.
6. Indoor frame cover sheet: GI colored 22 gage.
7. Indoor frame cover sheet insulation: with insulated material.
8. Indoor copper pipe fitting: 18 gage length tube.

6 Ton (7.5 HP) x 2 OUTDOOR with all his ACCESSORIES:

1. condensing unit box type.
2. compressor: Copeland scroll capacity 6 Ton 3 phase 440/v Hz 50.
3. Liquid receiver capacity: 5 liter.
4. Oil spreader: in/out pipe size 7/8.
5. Hand valve: 1/2.
6. Filter: 1/2.
7. section accumulator: 7/8.
8. dual high low pressure safety switch: company Danfoss with high pressure leads.
9. Outdoor base frame: channel and angle iron.
10. refrigerant: R-22.

ELECTRIC PANEL equipment's.

1. Magnetic contactor: 30 A for compressor.
2. Holding contactor.
3. Blower contactor.

4. Digital thermostat.
5. Fan contactor.
6. Connection strip.
7. Push button.
8. Electric panel box: 12" x 24".

13: Wrapping Machine:

Trait:

This double twist wrapping machine is built to wrap individual candies quickly, evenly, and without waste. Its main purpose is to take loose candies, feed them one by one, and wrap each piece tightly using single or double paper, keeping the product clean and well protected. The machine also aims to keep production steady and reliable by controlling paper feed, speed, and alignment automatically, so every wrapped candy looks the same and no empty or missing wraps are produced.

MACHINE FEATURES:

1. MACHINE WITH CANDY-SETTLING PLATE, FEEDING CANDY AUTOMATICALLY.
2. SINGLE AND DOUBLE LAYERS OF WRAPPING PAPER ARE USED.
3. 100% PACKING RATE. NO EMPTY PACKAGE. NO CANDY NO PAPER SENDING.
4. SERVO MOTOR CONTROL PAPER SENDING SYSTEM.
5. AUTOMATICALLY FOLLOWED BY PHOTO ELECTRICITY OF COMPUTER.
6. THE SPEED IS ADJUSTED BY FREQUENCY-CHANGING DEVICE.
7. HAS TOUCH SCREEN AND EASY OPERATION.

Specifications :

- * CAPACITY: 450PCS/ MIN.
- * PACKING MATERIAL: CELLOPHANE, PVC, POLYPROPYLENE, STENCIL, COMPOSITE MATERIAL, ETC.
- * POWER: 2.5 KW
- * ELECTRICAL SOURCE: 380V 50HZ
- * WEIGHT OF MACHINE: 1083 KG
- * SPECIFICATION OF FOOD:
- * LENGTH: 11-35MM
- * WIDTH: 11-26MM
- * THICKNESS: 5-20MM
- * DIMENSION: 1900*1100*1480MM

Must Approved

Chain Die Stand (Reference Mold)

- Frame in M.S

- Wheels for Movement (4 NOS)


Approved

11/2/26