


BOOKLET FOR COMPLETE PRODUCT LINES

Zimbabwe Lines



Starmers
Engineering Works

Zombie Complete Line:

1. Glucose Tank ✓
2. Steam Generator ✓
3. Steam Headler ✓
4. Toffee Cooker ✓
5. Cooling Table ✓
6. Pulling Machine ✓
7. Batch Roller 75 kg ✓
8. Rope Sizer 5 stages ✓
9. Cut & Pillow Pack Zombie Machine ✓

1.GLUCOSE TANK:

Trait:

Glucose storage tanks are engineered with specific traits to ensure hygienic, stable and crystal free storage of liquid glucose and Syrups for industrial applications.

Specifications:

- * Grade: S.S 304
- * Sheet thickness: 5 mm upper and lower sheet
- * Outer dia sheet thickness: 3 mm
- * Design Type: Vertical
- * Heating System: Coil on the base of tank for Steam Circulation
- * Ladder: Outside the tank
- * Capacity: 20 ton Glucose

- * Dimension: 16ft height x 7ft diameter
- * Power load: 0

2. STEAM GENERATOR:

Trait:

Steam generator heats water to produce high Pressure steam for heating, cleaning or industrial

processes.

Detail of Mechanical Parts:

1. Gauge Glass:01
2. Stop Valve diameter 1": 01
3. Safety Valve diameter 1": 01
4. NRV diameter 1": 01
5. Blow down diameter 1": 01
6. Air Vent diameter globe Valve : 1/2"
7. Feed Water Pump 01 Multistage (Grundfos): 01
8. Electric panel Box with complete auto controlled system: 01
9. Stack diameter 8" height 15 ft thick 2.5 mm: 01

Detail of Electric Parts:

1. Burner with gas assembly and diesel pump
2. Panel Box 16" x 30" x 8" thick 18 guage
3. Overload company Schneider: 02
4. Pressure switch 10 kg imported: 02
5. Electric Contactor: 02
6. Power relay company (Finder): 04
7. Push button company (Telemechanic): 03

Specifications:

- * Type of passes: 3 pass
- * Test pressure: 225 psi

- * Working pressure: 150 psi
- * Tube Dia: 2" or 2 1/2"
- * Pressure Shell thickness: 1/2"
- * Tube sheet thick: 1/2"
- * Rock wool thickness: 1/2"
- * Insolation sheet thickness: 24 GUAGE
- * Burner Motor: 2hp
- * Feed water motor: 3hp

General Details:

- * Capacity: 600 kg/hr
- * Electric Load: 5 hp
- * Dimension: 8'x3'5"x3'5"

3.STEAM HEADLER:

Trait:

Steam headers are design to collect steam from a boiler or steam generator and distribute highquality, dry steam to various user points while performing several critical functions.

Specifications:

- * Material of header: M.S
- * Diameter: 1 ft
- * Branch pipes: 1", 2", 3", 4" depend on system needs
- * Design: Cushioned Cylinder
- * Connection: 5
- * Dimension: Dia 1ft x Length 3ft
- * Power load: 0

4. Toffee Cooker [150 Kg]

Trait:

The purpose of a toffee cooker is to heat and cook sugar-based mixtures to a controlled temperature so the toffee reaches the correct thickness, texture, and moisture level. It provides uniform heating and precise temperature control to prevent burning, ensure consistent quality, and achieve the required hardness or chewiness of the final toffee product.

Specifications:

- * Capacity: 150kg per batch after 20 to 25 mins
- * Stirrer: S.S 304
- * Pan material: S.S 304
- * Pan double jacketed with S.S 304 [M.S optional]
- * Frame in: M.S [S.S 201 optional]
- * Electric panel with all new features
- * 3 hp gear motor drive
- * Safety valve
- * Cover of pan in S.S 304

Dimensions (H x W x L):

Power Load: [3 hp]

5.Cooling Table SEW-108:

Trait:

The cooling table is a crucial post-cooking unit used for rapid cooling and conditioning of the cooked sugar mass before further processing such as mixing, flavoring, coloring, or forming. It ensures uniform texture and workability of the batch.

Specifications

- * Base plate thickness: 10mm in S.S 304
- * Material of plate: Boundary wall S.S 304
- * Cooling medium water: Cooling system A frame work for moving water Inlet and outlet Valve.
- * Legs: 4 Nos in S.S 201 grade

Dimension: 3ft x 6ft x 2'6"

Power Load: 0

6. Pulling Machine:

Trait:

The purpose of a pulling machine is to stretch and fold cooked candy or toffee in a controlled way to improve its texture and structure. By continuously pulling the mass, the machine incorporates air, evens out temperature, and develops the desired smoothness, shine, and chew of the final product.

Specifications:

- * Capacity: 100kg
- * Main drive motor: 10hp
- * Arms: Hard chromed
- * Arms for continuous pulling: 3 arms
- * Side sheets: In S.S
- * Electric pannel for control

Dimension:

Power Load: 10 hp

7.BATCH ROLLER 75KG:

Trait:

The batch roller is a key intermediate machine in the candy, lollipop, toffee, and fudge production line. It is designed to continuously roll, shape, and form the cooked mass into a uniform cylindrical rope. It ensures consistent rope size and proper distribution of center filling, flavor, and color before feeding into the rope sizer or forming machine.

Specifications:

- * Frame work horizontal
- * Rollers Quantity 4
- * Rollers material in S.S 304 food grade
- * Upper body in S.S 304 food grade
- * Bearing in gears
- * Gear motor main drive 1hp
- * Up and down drive 1hp
- * Electric heaters to maintain temperature 1000 watt (2 NOS)
- * Capacity 75 kg
- * Length 6.5 ft
- * Gear motor SEW brand Germany
- * Roller caplene in casting material
- * Additional tray for removal of wastage

Dimensions (H x W x L): 4'6" x 2'2" x 7'

Power Load: 4.68hp

8. ROPE SIZER 5 STAGES:

Traits:

The rope sizer is a precision machine used to accurately reduce & calibrate the diameter of the candy and toffee rope produced by the batch roller. It ensures a uniform rope thickness suitable for feeding into the forming or cutting machine, maintaining consistent candy size and weight throughout production.

Specifications:

- * Horizontal model
- * 5 stages (4 Stages horizontal & 1 vertical)
- * 1st pair in S.S 304 37mm
- * 2nd pair in S.S 304 32mm
- * 3rd pair in S.S 304 27mm
- * 4th pair in S.S 304 22mm
- * 5th pair in S.S 304 17mm
- * Electric panel in S.S 201
- * Side sheets in S.S 201
- * Sizer plates in S.S 304
- * Rope guide in brass
- * Electric inverter new brand INVENT company =3hp
- * Gear motors are of SEW brand Germany
- * Heat controllers Digital 2 NOS
- * Emergency break to stop equipment
- * Emergency switch to off equipment
- * Electric breakers
- * Electric components brand new
- * Electric Heaters 500x4 =2 KW

Dimension:HxWxL:4'6" x 3'x 5'6"

Weight:

Power Load: 5•68 hp

9 • CUT AND PILLOW PACK ZOMBIE MACHINE :

Trait:

This machine is a horizontal flow wrapping machine used to pack products quickly and efficiently in a production line. It feeds items along a conveyor, wraps them in a continuous plastic film, then seals and cuts the film to form individual packets. The process uses heat sealing to ensure each pack is closed properly.

Specifications:

- Size of Pack (Length x Width x Height): 80 - 200 x 05 - 10 x 22 - 35 mm
- OUTPUT: Upto 250 Packs Per Minute
- ELECTRIC MOTORS: (1) 2 H.P. (2) ½ H.P.
- HEATERS: 2.6 Kw
- STANDARD EQUIPMENT: Photo Electric Eye & Inverter
- DIMENSIONS OF MACHINE (Length x Width x Height): 4,590 x 1,820 x 1,000 mm
- WEIGHT: 1050 Kg.
- REEL (Maximum Outer Dia / Core Dia): 300 / 75 mm.
- DATE CODER: Optional
- STAINLESS STEEL VERSION**: Optional