

BOOKLET FOR COMPLETE PRODUCT LINES

New



Starmers
Engineering Works

CHAIN DIE COMPLETE LINE 450 KG/HR

1. Glucose Tank SEW-101 ✓
2. Steam Generator SEW-102 ✓
3. Steam Headler SEW-103 ✓
4. Dissolving Tank SEW-106 ✓
5. Storage Tank SEW-107 ✓
6. Candy Continuous cooker SEW-104 ✓
7. Vacuum Pump SEW-105 ✓
8. Cooling Table SEW-108 ✓
9. Kneading Machine SEW-109 ✓
10. Center Filling Liquid Pump SEW-110 ✓
11. Center Filling Powder pump SEW-111 ✓
12. Batch Roller SEW-114 ✓
13. Rope Sizer SEW-115 ✓
14. Chain DIE Forming plants with Die SEW- ✓
15. Cooling Conveyer close Body SEW-121 ✓
16. AC Unit SEW-122 ✓
17. Vibrator SEW-120 ✓
18. Pillow Pack Wrapping Machine SEW-123 ✓
19. Chain Die stand (Reference Mold) SEW- ✓

1. Glucose Tank SEW-101

Trait:

Glucose storage tanks are engineered with specific traits to ensure hygienic, Stable and crystal free storage of liquid glucose and Syrups for Industrial applications.

Specifications:

~~Size:~~

~~14 ft height x 7.6 ft diameter (approximate).~~

Grade:

S.S 304

Sheet thickness:

5 mm upper and lower sheet

Outer dia sheet thickness:

3 mm

Design Type:

Vertical

Heating System:

Coil on the base of tank

Ladder:

Outside the tank

Capacity:

20 ton glucose

For steam circulation.

Dimension: 16ft height x 7ft diameter

Weight:

Power load: 0

Capacity : 20 ton Glucose

Approved by Anshu Patel
4/12/23

2. Steam Generator SEW-102

Trait:

Steam generator heats water to produce high Pressure steam for heating, cleaning or industrial processes.

Detail of Mechanical Parts:

- | | |
|--|------|
| 1. Gauge Glass like a new = ✓ | 01 ✓ |
| 2. Stop Valve diameter 1-1/2" = ✓ | 01 ✓ |
| 3. Safety Valve diameter 1 1/2" = ✓ | 01 ✓ |
| 4. NRV diameter 1" like a new = ✓ | 01 ✓ |
| 5. Blow down diameter 1" = 1" ✓ | 01 ✓ |
| 6. Air Vent diameter 1" globe Valve = ✓ | 01 ✓ |
| 7. Feed Water Pump 01 Multistage (Grundfos)= ✓ | 01 ✓ |
| 8. Electric panel Box with complete auto controlled system = ✓ | 01 ✓ |
| 9. Stack diameter 15" height 20 ft. thick 2.5 mm = ✓ | 01 ✓ |

Detail of Electric Parts:

- | | |
|--|--------|
| 1. Burner with gas assembly and or. diesel pump ✓ | |
| 2. Panel Box 18" x 30" x 8" thick 18 gauge ✓ | |
| 3. Overload company Schneider Schneider ✓ | = 02 ✓ |
| 4. Pressure switch 10 kg imported ✓ | = 02 ✓ |
| 5. Load and unloading Responsibility of Client | |
| 6. Electric Contactor ✓ | = 02 ✓ |
| 7. Power relay company (Finder) ✓ | = 04 ✓ |
| 8. Push button company (Telemecanic) ✓ | = 03 ✓ |

Approved by Arslan Ishaq
4/12/24

Specifications:

Type of passes: ✓	3 pass ✓
Test pressure: ✓	225 psi ✓
Working pressure: ✓	150 psi ✓
Tube Dia: ✓	2" or 2 1/2" ✓
Pressure Shell thickness: ✓	1/2" ✓
Tube sheet thick: ✓	1/2" ✓
Rock wool thickness ✓	2" 2 1/2" ✓
Insulation sheet thickness: ✓	24 GAUGE ✓
Burner Motor: ✓	2hp ✓
Feedwater motor ✓	3hp ✓

Capacity: ^{1500kg/hr} ~~1200kg/hr~~ ✓

Electric Load: ^{5hp} ~~6hp~~ ✓

Dimension: 8'x3'5"x3'5" ✓

~~Weight:~~

~~Sound level:~~

Approved by ^[Signature] ~~Arshad Shaid~~
4/12/25

3. Steam Header SEW-103 ✓

Trait: ✓

Steam headers are design to collect steam from a boiler or steam generator and distribute high-quality, dry steam to various user points while performing several critical functions.

Specifications:

- Material of header = M.S ✓
- Diameter = 1 ft ✓
- Branch pipes = 1", 2", 3", 4 "depend on system needs ✓
- Design = Cushioned Cylinder ✓
- *Connection* = 5 ✓

Dimension: Dia length
1ft x 3ft

~~Weight:~~

Power load: 0

Approved by  Anslam Sheikh
4/12/25

4. Dissolving Tank SEW-106

Trait:

The dissolving tank is an essential unit in the candy manufacturing process designed for the controlled dissolution of sugar, glucose syrup, and other ingredients in water to form a homogeneous sugar solution or slurry. ✓

Specifications:

- 400kg capacity ✓
- Double jacketed with MS ✓
- Body in S.S 304 ✓
- Legs in M.S ✓
- Stirrer in S.S 304 ✓
- Gear motor main drive 2hp ✓
- Steam guage ✓
- safety valve ✓
- Seat valve ✓

Dimension: ^H 5'6" x ^w 3'5" x ^L 3'5"

~~Weight.~~

Power Load: 2hp

Approved by 
9/12/25

5. Storage Tank SEW-107 ✓

Trait:

The storage tank is designed to hold and maintain cooked sugar mass or syrup at a controlled temperature before feeding it into the forming or depositing section of the candy line. ✓

Specifications:

- 400kg capacity ✓
- single jacketed ✓
- Body in S.S 304 ✓
- Legs in M.S ✓
- Stirrer in S.S 304 ✓
- Gear motor main drive 1hp ✓

Dimension: ^{H x W x L} 6'x3'6"x3'6" ✓

~~Weight:~~

Power Load: 1 hp ✓

Approved by ^{###} Andon Shuhid
4/12/25

6. Candy Continuous cooker SEW-104

Trait:

The candy continuous vacuum cooker automatically produces hard-boiled candies and milk caramels with high clarity and smooth texture. It minimizes sugar loss and maintains consistent quality, even with moisture levels below 1%.

Operating parameters such as output vacuum, temperature, cooking time, and batch weight are adjustable. Once set, the system runs automatically and continuously with low operating cost.

Specifications:

- Electric Pannel ✓
- 450 kg per hour ✓
- Pans in S.S 304 ✓
- Body in S.S 304 ✓
- Electric panel with all new features ✓
- Body Double jacketed (S.S 304) ✓
- Output 450 kg/hr ✓
- Dozing pump 3 hp (imported used) ✓
- For sugar pump 2 hp 1450 rpm ✓
- Pan 2 nos in S.S 304 food grade ✓
- Batch Auto control ✓
- Steam guage ✓
- Safety valve ✓
- seat valve ✓

Dimension:

H x W x L

8.5ft x 6ft x 7ft

Power Load:

4hp

~~5hp~~

Approved by 
4/12/25

7. Vacuum Pump SEW-105

Trait:

The vacuum pump is used to rapidly remove moisture (Water vapor) from the cooked candy mass under reduced pressure, which allows lower temperature boiling and prevents caramelization or burning of sugars.

Specification:

For vacuum pump 7.5 hp=1450 rpm

Frame = M.S

Dimension:

H x L x W
2ft x 4ft x 1ft

~~Weight:~~

Power Load:

10hp

~~7.5hp~~

Approved by  Anson Shaid
9/12/25

8. Cooling Table SEW-108

Trait:

The cooling table is a crucial post-cooking unit used for rapid cooling and conditioning of the cooked sugar mass before further processing such as mixing, flavoring, coloring, or forming. It ensures uniform texture and workability of the batch.

Specifications

- Base plate thickness: 10mm in S.S 304 ✓
- Material of plate: Boundry wall S.S 304 ✓
- Cooling medium water: Cooling system A frame work for moving water Inlet and outlet ✓
Valve 6 - Legs 4 Nos in S.S 201 grade ✓
- legs 4Nos in SS 201 grade.

W x L x H
Dimension: 3ft x 6ft x 2'6" ✓

Weight:

Power Load: 0

Approved by Aslam Shahid
4/12/25

9. Kneading Machine SEW-109

Trait:

The rotary kneading machine (SEW-109) is a specialized piece of confectionery equipment perfectly suited for the uniform mixing and kneading of the cooked sugar mass used in producing hard-boiled candy. ✓

Its primary function is to guarantee the uniform distribution of essential ingredients, including solids, acids, and any other additives, ensuring a consistent and high-quality final product. ✓

To maintain food safety standards, the machine operates in a hygienic way, utilizing stainless steel for all contact parts, which are also efficiently water-cooled to manage the high temperatures of the candy mass during the kneading process. ✓

This machine eliminates the need for tiresome and exhausting manual mixing and saves on the labor costs. ✓

Specifications:

- Roller ⁱⁿ S.S 304 ✓
- Main drive 5hp ✓
- Steel plate 4ft ✓
- Switch on / off ✓
- Side sheets in S.S 201 ✓
- Main plate in S.S 304 ✓

Dimension: ^{H x W x L} 5'x5'6"x5'6" ✓

~~Weight:~~

Power Load: 5hp

Approved by ^{7/1/1} Anabel Shahid
9/12/25

10. Center Filling Liquid Pump SEW-110

Trait:

The center filling pump is a precision dosing system designed to inject liquid filling (such as fruit syrup, chocolate, cream, or jam) into the core of the candy rope during the forming process. It ensures consistent filling quantity and uniform distribution across all candies.

Specifications:

- Filling chocolate and liquid ✓
- keef in S.S 304 ✓
- keef double-jacketed ✓
- Rod in S.S with Teflon covering food-grade heat proof material ✓
- Pipe flexible food grade ✓
- Electric panel with new feature ✓
- Gear motor 2 hp main drive ✓
- Stand in M.S ✓
- Electric heater to moderate temperature 1000 watt 1 NOS ✓
- Electric inverter 2HP to increase or decrease filling in product ✓
- Overflow system to recycle liquid/Chocolate ✓

Dimension:

H x W x L

~~W x H x L~~

Power Load: 3.34 hp

Approved by  Amr Shalid
4/22/25

11. Center Filling Powder pump SEW-111

Trait:

The center filling powder pump is a precision feeding and dosing unit designed to inject or deliver dry or semi-dry powdered filling materials (such as milk powder, cocoa powder, fruit powder, or malt-based mixtures) into the center of a candy rope during forming. It ensures consistent and uniform distribution of powder filling across all pieces. ✓

Specifications:

- Centre Filing Powder ✓
- -Keef in S.S 304 grade ✓
- ~~Electric panel~~ ✓
- Electric panel ✓
- Gear motor 2hp ✓
- Variable Inverter 2hp for speed control ✓
- Stand in M.S ✓
- Rod With Teflon covering with S.S worm inside ✓

Dimension:

HxWxL

~~Weight:~~

Power Load:

2hp

9/12/21
Approved by Anshu Sharma
H.S.

12. Batch Roller SEW-114

Trait:

The batch roller is a key intermediate machine in the candy, lollipop, toffe, fudge production line designed to continuously roll, shape, and form the cooked mass into a uniform cylindrical rope. It ensures consistent rope size and proper distribution of center filling, flavour, and color before feeding into the rope sizer or forming machine.

Specifications:

- Frame work horizontal ✓
- Rollers Quantity 4 ✓
- Rollers material in S.S 304 food grade ✓
- Upper body in S.S 304 food grade ✓
- Bearing in gears ✓
- Gear motor main drive 1hp ✓
- Up and down drive 1hp ✓
- ~~drive 2 hp~~
- ~~Electric panel for control~~
- Electric heaters to maintain temperature 1000 watt (2 NOS) ✓
- Capacity 75 kg ✓
- Length 6.5 ft ✓
- Gear motor SEW brand Germany ✓
- Roller caplene in casting material ✓
- Additional tray for removal of wastage ✓

Dimension: ^{H x W x L} 4'6"x2'2"x7' ✓

Weight:

Power Load: 4.68 hp

4/12/25
Approved by Anshu Ghelid
12/4

13. Rope Sizer SEW-115

Traits:

The rope sizer is a precision machine used to accurately reduce & calibrate the diameter of the candy and toffe rope produced by the batch roller. It ensures a uniform rope thickness suitable for feeding into the forming or cutting machine, maintaining consistent candy size and weight throughout production. ✓ ✓ ✓

Specifications:

- Horizontal model ✓
- 4 stages ✓
- 1st pair in S.S 304 32mm ✓
- 2nd pair in S.S 304 27mm ✓
- 3rd pair in S.S 304 22mm ✓
- 4th pair in S.S 304 17mm ✓
- Electric panel in S.S 201 ✓
- Side sheets in S.S 201 ✓
- Sizer plates in S.S 304 ✓
- Rope guide in brass ✓
- Electric inverter new brand INVENT company = ~~3HP~~ 2HP ✓
- Gear motors are of SEW brand Germany ✓
- Heat controllers Digital 2 NOS ✓
- Emergency break to stop equipment ✓
- Emergency switch to off equipment ✓
- Electric breakers ✓
- Bearings are used instead of bushes to reduce maintenance of equipment ✓
- Main Drive Gear Motor = 2HP ✓
- Heaters 500 Watt (4 NOS) = ~~4kw~~ 2kw ✓

Dimension:

Weight:

Power Load: 4.68hp

H x W x L
4.3ft x 2.5ft x 6ft

Approved by ~~W. H. H.~~
4/12/25

14. Chain DIE Forming plants with Die SEW

Trait:

Chain Die Forming Plant with Die is a continuous forming system used in confectionery manufacturing to shape candy ropes into uniform pieces. It synchronizes a metering/sizing unit and a die-chain assembly to compress & cut the candy/toffee into precise shapes. The system also supports high-filling products, ensuring stable encapsulation of powder, liquid, cream fillings without leakage while maintaining accurate weight and dimensions.

Specifications:

Speed 2000 to 3500 (pieces per minute depend upon the size & shape of product)

- Up-to 20% filling of product
- Sizer Set in M.S.
- Top Cover in M.S.
- Gear Motor 1 hp for Sizer box drive
- Gear Motor 3 Hp for main drive.
- Gear Motor 0.5 hp for belt drive.
- Gear Motor 0.5 hp for spreader movement
- Inverter 5 hp for speed control
- Inverter 5 hp for speed control
- Inverter 0.1 hp for speed control
- Production upto 450 kg/hr

Dimension:

Weight:

Power Load: 5 hp

HxWxL

Approved by Arslan Shaid
4/12/25

CHAIN DIE SEW

Trait:

A chain die facilitates high-precision formation of candy ropes by guiding & shaping the material through calibrated die channels, ensuring uniform size & continuous flow in the production line.

Specification:

~~By 1/1/2025~~

✓ Material specification

- ✓ • Frame of Die: Aluminium Alloy
- ✓ • Cutter Blocks: D-2
- ✓ • Punches: D-2
- ✓ • U-clamps: Case Hardened M.S
- ✓ • Sprockets: Forged Carbon Steel
- ✓ • Bushes, Bolts, Pipes, Bearing Cones: EN19
- ✓ • Connecting Rods (Upper + Lower): High Speed Carbon Steel

Approved by ^{Hu}Arslan Shukid
4/12/25

15. Cooling Conveyer close Body SEW-121

Trait:

Its main purpose is to rapidly and uniformly reduce the temperature of freshly formed candy, ensuring dimensional stability, proper hardness, and surface quality before cutting, wrapping or packaging.

Specifications:

- 16ft long ✓
- 3ft width ✓
- With 5 ton AC ✓
- 3 stages ✓
- 1st step mesh wire in S.S 304 grade ✓
- 2nd step mesh wire in S.S 304 grade ✓
- 3rd step mesh wire in S.S 304 grade ✓
- outer and inner Side sheets in S.S 201 ✓
- Electric panel with all new features ✓
- Inverter new brand **INVENT (5hp)** ✓
- All covers in S.S 201 ✓
- Double jacketed insulates with thermopore ✓
- Rods are in S.S 304 5mm thickness ✓
- Chain in M.S 40 no ✓
- Gear motor 3hp (1hp each 3 nos) SEW brand ✓
- ~~Variable speed inverter (2hp each)~~
- ~~Electric inverter for controlling speed (5hp)~~

Dimension: ^{H x W x L} x3ftx16ft

Weight:

Power Load: **3hp**

7/12/25
Approved by Anshu Shukla
[Signature]

16. AC Unit SEW-122

Description: ✓

Indoor Unit capacity 5 Ton (6.5 HP) floor standing type for cooling conveyor Accessories ✓
indoor: ✓

- 1: evaporator brand new copper tube size 3/8 gage 22 distributor size 1/2 section ✓
header 7/8. ✓
- 2: aluminum fins thickness. 0.150mm company Breez. ✓
- 3: High-velocity air blower With 1 HP motor 3 phase 440/v Hz 50. ✓
- 4: expansion valve company Emerson model TCLE 6.5 HP. ✓
- 5: Base frame angle iron sizes are on customer demand. ✓
- 6: Indoor frame cover sheet GI colored 22 gage. ✓
- 7: indoor frame cover sheet insulation with insulated material. ✓
- 8: Indoor copper pipe fitting 18 gauge length tube. ✓

6.5 HP OUTDOOR Company Bitzer with all his ACCESSORIES: ✓

- 1: condensing unit Company Bitzer with high-density condensing coil. ✓
- 2: High static air flow fan 3phase 440/v Hz50. ✓
- 3: compressor Copeland scroll capacity 6.5 HP 3 phase 440/v Hz50. ✓
- 4: Liquid receiver capacity 5 liter. ✓
- 5: Oil spreader in/out pipe size 7/8. ✓
- 6: Hand valve 1/2. ✓
- 7: Filter 1/2. ✓
- 8: Copper length 1/2 and 5/8. ✓
- 9: section accumulator 7/8 ✓
- 10: Copper long bend 5/8 and 7/8 and 3/8 elbow. ✓
- 11: dual high low-pressure safety switch company Danfoss with high-pressure leads. ✓
- 12: Outdoor base frame channel and angle iron. ✓
- 13: refrigerant R-22 company (Honeywell USA). ✓

Approved by  Arsalan Shahid
4/12/25

ELECTRIC PANEL equipment: ✓

- 1: 7.5 ~~KVA~~^{HP} inverter company (INVT). ✓
- 2: magnetic contactor 30A amperes for compressor ✓
- 3: Holding contactor. ✓
- 4: blower contactor. ✓
- 5: digital thermostat ✓
- 6: fan contactor. ✓
- 7: connection strip ✓
- 8: push button. ✓
- 9: Electric panel box size 12" x 24". ✓

Indoor and outdoor manufacturing with all his accessories testing installation complete material and labor charges capacity (6.5 HP) brand new total cost.

Dimension:

H x W x L

~~Weight:~~

Power Load: ~~6.5hp~~

~~6.5hp~~

✓ 6.5hp

Approved by  Arslan Sheikh
4/12/25

17. Vibrator SEW-120

Trait:

The vibrator helps smoothly transport candies from the cooling and forming sections to packaging, preventing dumping or sticking. ✓

Specifications:

- Frame in M.S ✓
- Main sheet in S.S 304 ✓ 18 Gauge
- Fan 2 nos ✓
- Gear motor ~~0.5~~ 1hp ✓
- Trays in S.S 304 for removal of wastage 2 nos ✓ 20 Gauge

Dimension:

4ft width
8ft length

H x W x L

3.5ft x 4.5ft x 8ft

Weight:

Power Load: 1hp

Approved by  Aisalam Shehid
4/12/25

18. Pillow Pack Wrapping Machine SEW-123

Trait:

Is high performance pillow pack wrapping machine for filled or un-filled candies, bubblegums and other similar items incorporating latest and precision components the machine is capable of achieving speed upto 800 pieces per minute. Fin seal and end seal are of high quality ensuring long shelf life of the product. Large size feed disc and brushes enable positive transfer of candies to the carrier chain

SPECIFICATIONS:

- OUTPUT:
- Upto 800 Pcs/min on candy ✓
- Upto 500 Pcs/min on bubble ✓
- ELECTRIC MOTORS:
- (1) 2 H.P./3-Phase ✓
- (2) ½ H.P. *Brushes*
- ELECTRIC HEATERS: 3.2 Kw ✓
- STANDARD EQUIPMENT: Photo Electric Eye & Inverter ✓
- DIMENSIONS (L x W x H): 2,335 x 900 x 1,715 mm ✓
- WEIGHT: 750 Kg
- REEL (Maximum Outer Dia / Core Dia): 280 / 70 mm ✓

Dimension:

Same as dynamic
H x W x L
1,715 x 900 x 2,335

~~Weight:~~

Same as dynamic

Power Load:

~~Same as dynamic~~
Mohib

4/12
Approved by Arslan Shuhid
[Signature]

19. Chain Die stand (Reference Mold) SEW-

- Frame in M.S
- Wheels for movement 4 NOS

Dimension:

~~Weight:~~

~~Power Loads~~